deConfUSIon User Manual

Practical installation and analysis guide

Soner Caner Cagun
MPI for Biological Cybernetics
29 October 2026

Single 2D slices | 2D probe with step motor | Volumetric 3D probe

A practical route from the original recording through quality control and processing to reviewed visualization, regions, connectivity and groups.

Contents

1 Install and start 5
Prepare the toolbox 5
Check the active version 5
Operating systems and native exports 5
2 Choose the acquisition route 6
Keep these records 6
3 Load data into Studio 7
Loading from a server 8
4 A first single-slice 2D analysis 9
Compare branches fairly 9
5 Reconstruct a step-motor recording 10
Register and analyze source planes 10
6 Prepare a volumetric 3D recording 11
Use physical units consistently 11
7 Review quality control 12
8 Frame rejection and interpolation 13
9 Choose preprocessing deliberately 14
Chop and temporal reduction 14
Imregdemons 15
Temporal filters and drift 15
10 Review PCA ICA and regressors 16
Regressor analysis 17
11 Set baseline and signal windows 18
12 Use SCM GUI and fixed ROIs 19
Underlay and atlas context 20
13 Draw automatic SCM search masks 21
Read the painted support 22
Review candidates and export 22
Rank complete atlas regions across slices 22

14 Prepare masks and atlas registration 24
Mask Editor 24
Geometric masks for volumetric probe data 24
Register one 2D source plane 25
LightSuite guided atlas registration 26
15 Inspect movies and the 3D model 33
Time Course Viewer and Video GUI 33
Volumetric display 34
16 Compute functional connectivity 36
17 Import ROI results into Group Analysis 38
Choose a metric and biological unit 38
Assign concentrations and display titrations 38
Select dose comparisons and statistical tests 39
Preview publication figures before exporting 39
18 Use Standardized Analysis 41
Review the current automated presets 41
19 Save export and reproduce 42
Final review checklist 42
20 Troubleshoot common problems 43
21 Essential terms and further reading 44
Acknowledgments 44
Acknowledgments and responsibility 45

Practical guide to installation and everyday analysis

Reference edition 29 October 2026

Translations of this handbook and the practical manual were produced using a large language model (LLM). Language and technical translation errors are possible. Check the English reference and MATLAB source when uncertain. MATLAB control labels, code identifiers, equations and original source excerpts are retained where necessary for exact matching. Translation does not independently validate an analysis.

deConfUSIon addresses a practical need in fUSI research: examining recordings and comparing analysis choices without requiring programming experience. Its MATLAB interface connects quality control, preprocessing, anatomical context and regional analysis through visible intermediate results. This supports exploratory work and helps researchers review how each choice affects the data. Scientific interpretation and quality review remain the researcher's responsibility.

This guide takes a new user from a reconstructed functional ultrasound movie to inspected images, region time courses, connectivity and group summaries. It covers single 2D slices, sequential step-motor recordings and volumetric 3D probe data. Use the full handbook for mathematical derivations, all QC figures and the script reference.

Functional ultrasound imaging measures blood-related ultrasound fluctuations. A percentage signal change or correlation is an analysis result whose meaning depends on acquisition, timing, artifacts and the chosen spatial support. Keep the original scan and event log alongside every derived result.

The GUI examples illustrate controls and typical views. Their masks, time windows and display settings are examples, not a reviewed experimental protocol. Adapt every analysis choice to the acquisition, scientific question and independent quality review.

1 Install and start

Prepare the toolbox

1. Download the complete repository from GitHub, or clone it with Git. Keep the folder structure intact.
2. Place it on a local drive. Keep the root scripts, `lib`, `atlas_tools`, `acquisition` and `theme_icons` together. `lib` contains runtime functions and is essential.
3. Start MATLAB. The illustrated reference installation uses MATLAB R2023b on Windows. Functions such as image registration need their corresponding MATLAB toolbox; a missing-function error identifies a dependency to check.
4. Change MATLAB's current folder to the extracted `deConfUSIon` folder and run the following commands.

```
deConfUSIon_setup
deConfUSIon
```

Setup adds the supported runtime folders. Avoid adding the entire repository and backup folders with `genpath`: competing versions can make MATLAB call an older function. Keep backups outside the active MATLAB path.

Check the active version

Run `which deConfUSIon -all` if MATLAB opens an unexpected version. The first result should belong to your intended checkout. After replacing source files, reopen affected GUIs to load their updated callbacks.

Checkpoint: Studio opens, the intended toolbox path is active, and the complete runtime folders are present.

Operating systems and native exports

Windows with MATLAB R2023b remains the reference installation. Native MATLAB on Linux and macOS is supported by the source; end-to-end validation on those platforms is pending. Use the actual mounted data path rather than Windows drive letters. Linux movie exports use Motion JPEG AVI; Windows and macOS use MP4. On macOS and Linux, PPTX requires MATLAB Report Generator, and XLSX export does not use Excel COM styling. Live acquisition remains subject to scanner and hardware-driver support.

2 Choose the acquisition route

Table 1. 2 Choose the acquisition route

Acquisition	Expected movie layout	First action
Single 2D plane	Y by X by time	Load and verify the final time dimension
2D probe with step motor	Continuous stream or split files, then Y by X by Z by time	Reconstruct planes using motor timing
Volumetric 3D probe	Y by X by Z by time	Verify axis order, spacing and slice coverage


Y means rows, X means columns and the final dimension is time. A three-dimensional MATLAB array can be a 2D movie over time. It does not automatically represent a 3D anatomy volume. The repetition time, or TR, is the interval between analyzed samples. Changing TR changes time windows and filter frequencies.

Keep these records

Record the original file, animal/session identity, acquisition type, timing, event log, physical voxel spacing and chosen output folder. Save the processing sequence and its parameters. Preserve saved atlas packages and ROI sidecars together.

3 Load data into Studio

Figure 1. Studio workflow overview



1. Click **Load fUSI Data** and choose the original acquisition or a saved deConfUSIon result.
2. Review the load options. Confirm dimensions, volume/frame count, TR and any warning about irregular timestamps.
3. Confirm the analysis output folder. A local output folder helps separate processing time from server write time.
4. Check the active dataset label before opening a viewer or applying a processing step.
5. Open Time-Course Viewer and inspect early, middle and late frames before correcting anything.

Loading from a server

A large network MAT file may first be copied into a local read cache. This is a disk copy that can be reused by another MATLAB session when the source still matches. The first transfer remains limited by the network; local parsing follows it. A different network drive letter does not by itself provide a faster connection.

Distinguish the stages shown in progress messages: source transfer, MAT reading, array preparation and GUI initialization. A copy reaching 100 percent is not the end of every later phase. Keep enough local disk space for the cache and saved derived results.

Checkpoint: You can identify the active dataset and its analyzed TR, and the raw movie has usable contrast and plausible orientation.

4 A first single-slice 2D analysis

1. Load the original 2D movie and confirm a Y by X by time layout.
2. Inspect the raw movie for displacement, jumps, saturation, dropouts and slow drift.
3. Run QC and review the frames that produced warnings.
4. Make a separate derived branch for one justified correction. Compare it with the raw recording using the same ROI and time interval.
5. Set baseline and signal windows from the event log, then open SCM GUI.
6. Prepare an inclusion mask and, if anatomical ROIs are required, register the slice to the atlas.
7. Review fixed or automatic ROIs and their traces before exporting.
8. Continue to FC or Group Analysis with the matching anatomy, timing and export files.

Compare branches fairly

Use the same anatomical support and baseline when comparing processing choices. Check response amplitude, latency, mean anatomy and motion. A smoother trace or lower variance alone does not show that the processing is better.

For a long pharmacological recording, first compare modest temporal reduction and correction of observed motion. For a short stimulation recording, retain enough samples across onset and recovery, and treat isolated artifacts selectively. Review component removal against independent evidence in either case.

5 Reconstruct a step-motor recording

A 2D probe with a motor acquires different planes at different times. Stacking them does not make them simultaneous. Use the original motor log and acquisition naming to establish plane order, dwell time and movement frames.

1. In Studio choose **Motor**, or the corresponding Standardized Analysis preset.
2. Select the continuous-stream or split-file route that matches the acquisition.
3. Enter the source slice count and frame/dwell information from the recording protocol.
4. Review the reconstructed dimensions and retained time indices.
5. Inspect the beginning and end of every reconstructed plane for a plane offset or movement contamination.
6. Save the reconstruction and its metadata before further processing.

Register and analyze source planes

Use the 2D coronal registration route for each acquired source plane. Keep source-slice indices separate from atlas-slice indices. Save the combined session with its transforms and underlays; keep relative subfolders together. A single-plane registration cannot label all source planes by stretching it along Z.

Inspect each plane in SCM/Video before searching a slice range. Correlation across sequentially acquired planes requires a justified time-alignment strategy.

6 Prepare a volumetric 3D recording

1. Load the matrix-probe movie and confirm Y, X, Z and time.
2. Check physical spacing, axis permutation and displayed laterality against acquisition records.
3. Inspect several nonempty planes at early, middle and late times. Empty boundary planes may reflect missing acquired coverage.
4. Run QC. Review component spatial patterns and time courses before selecting PCA/ICA removal.
5. Compare the corrected mean anatomy and raw time course with the input.
6. If using Imregdemons, choose the dimensional mode that matches the data; true 3D requires consistent geometry.
7. Recheck TR after temporal reduction, then choose valid filters and event windows.
8. Register the atlas and inspect multiple anatomical cuts before extracting labels or FC.


Use physical units consistently

Column spacing controls horizontal width; row spacing controls vertical height. A footprint of five columns by five rows need not be physically square. Confirm spacing before requesting an ROI in micrometres, a physical scale bar or a model slab thickness.

Checkpoint: The movie has the expected acquired slice support, correct analyzed timing and a consistent native-to-atlas geometry.

7 Review quality control

Figure 2. Frame rejection quality control



Run **Full QC** before selecting corrections. Start with global intensity over time, motion-related views, spatial stability and sample coverage. Review the raw movie around any flagged event. Irregular timestamps must be investigated before treating an FFT or FC interval as uniformly sampled.

Table 2. 7 Review quality control

Finding	Inspect next	Possible action to compare
One or a few global intensity jumps	Original frames and trigger/event log	Targeted frame rejection/interpolation
Sparse voxel spikes	Local traces and affected frames	Despike with reviewed settings
Anatomy changes position	Early/late images and landmarks	Appropriate motion correction
Slow trend	Warm-up, physiology, event timing and controls	Drift model or filter only if response remains identifiable
Missing region samples	Mask, acquired coverage and atlas alignment	Correct support or retain the result as missing

QC thresholds are screening rules. A flagged frame is not automatically invalid, and a smooth-looking trace is not automatically physiological. Save QC outputs and record accepted exclusions or corrections.

8 Frame rejection and interpolation

1. Open the frame-rejection/QC view for the selected dataset.
2. Review the threshold, flagged indices and the original movie around each event.
3. Decide which events are artifacts using acquisition and experimental evidence.
4. Apply the chosen correction to a derived dataset and save its record.
5. Compare original and corrected traces, including the time around each gap.

Interpolation estimates missing values from surrounding samples. It does not recover the original measurement or create independent information. Long gaps, rapid responses and nonstationary changes deserve special review. Keep the original usable-sample information with later analyses.

The line-outlier correction in Full QC is a separate screening/correction path. Do not assume every QC option means global frame rejection, and avoid applying the same correction twice without checking its record.

9 Choose preprocessing deliberately

Table 3. 9 Choose preprocessing deliberately

Step	Use when justified	Review afterward
Chop	Remove a known unusable beginning/end	Updated time origin and event coordinates
Temporal smoothing or block means	Reduce noise or very long movies	New TR and retained event bandwidth
Imregdemons	Correct observed spatial displacement	Landmarks, deformation and response preservation
Temporal filter	Retain a specified temporal band	Actual response, endpoints and mean handling
Despike	Treat sparse abnormal local samples	Preserved physiological peaks and local traces
PCA or ICA	Review structured components	Removed patterns, mean anatomy and retained response
Drift or regressor analysis	Model identified confounds or experimental predictors	Units, timing, collinearity and residuals

Apply one justified change at a time on a comparison branch. Save its settings and evaluate the same independently defined ROI before adding another step.

Chop and temporal reduction

Chopping the beginning shifts the time origin. Update event windows and document the removed duration. Averaging blocks of n input frames changes TR to n times the input TR. With a 0.32 s input, blocks of five produce 1.6 s samples; blocks of fifty produce 16 s samples and can hide short events. Choose the factor from the fastest event you need to resolve. Block averaging has limited anti-alias rejection.

Imregdemons

Choose 2D, per-slice or true 3D operation to match the acquisition. Review reference-frame choice, temporal reduction and deformation behavior. Compare reduced unregistered images with registered images so averaging is not mistaken for improved alignment. A cleaner alignment does not establish that a vascular response was preserved.

Temporal filters and drift

Enter cutoffs using the analyzed TR. A valid cutoff must lie below the Nyquist frequency, 1 divided by twice TR. Review the filter-response preview and endpoint behavior. High-pass filtering can remove a slow pharmacological response; low-pass filtering can blur stimulation onset. Restoring the mean does not restore dynamics removed by the filter. Treat temperature, physiology or instrument drift as hypotheses that need supporting records.

10 Review PCA ICA and regressors

Figure 3. PCA component review



PCA finds orthogonal variance patterns. A component combines a spatial pattern and a temporal profile; its rank describes explained variance, not biological identity. PC1 is not automatically an artifact. ICA seeks statistically independent patterns and has its own convergence and interpretation checks.

1. Confirm the spatial scope and estimation method in the component GUI.
2. Inspect the component time course and available spatial information.
3. Compare timing with motion, acquisition events, physiology and stimulation.
4. Select only components supported by a clear rationale, then apply removal.
5. Let computation and saving finish. Compare the derived mean image, representative raw traces and the expected response with the original.

Component removal subtracts that pattern from all included samples according to its spatial weights. If the pattern contains response information, that response will also be altered. Preserve the original branch so the decision remains reviewable.

Regressor analysis

Match each regressor to the analyzed time axis and units. Review whether a predictor is experimental, physiological or a nuisance signal. Check lag/convolution settings when offered, the model rank and correlations between predictors. Two nearly identical response and drift regressors cannot be separated reliably by giving them different names. Inspect residuals and use independent controls before interpreting a fitted coefficient.

11 Set baseline and signal windows

Percentage signal change compares a time course with its chosen reference intensity. Choose a stable baseline with enough valid acquired samples and a meaningful denominator. Keep it consistent for comparisons unless the experimental design requires otherwise.

Table 4. 11 Set baseline and signal windows

Field or view	Timing convention to check
SCM baseline and signal controls	Seconds in the ordinary time view; verify any frame/volume mode
Automatic SCM search and plateau	Minutes within each selected scan
Group Analysis metric windows	Minutes in the displayed controls
Filters	Frequency in Hz based on analyzed TR

Review the active baseline source when using another scan or shared baseline. The reference changes amplitudes; it does not align anatomy or make sequential recordings simultaneous. Keep external baseline files and exported shared-baseline sidecars with the analysis.

12 Use SCM GUI and fixed ROIs

Figure 4. SCM ROI and time course



1. Open **SCM GUI** from the intended active dataset.
2. Confirm the displayed slice, baseline and signal windows.
3. Set the sign policy and a sensible percentage color range. Lower overlay opacity when anatomy is hidden.
4. Enter the ROI size and center, then use **ADD ROI**.
5. Inspect its outline and populated time course, including baseline and signal bands.
6. Save or export the intended ROI trace and its settings.


An ROI fixed independently of the response is different from an automatic maximum search. Choose the method before interpreting the endpoint. Reuse the same spatial support when comparing raw and processed branches.

Underlay and atlas context

Open **Underlay** to choose a saved atlas display mode or use **Load new underlay** and **Load atlas**. Inspect Histology, Vascular and Regions from the matching registration. A sharp underlay can remain attractive even when the functional movie was overprocessed; inspect the active raw array and trace separately. Reset to native before reusing native ROI coordinates.

13 Draw automatic SCM search masks

Figure 5. Target and Control painting



1. Open **Automatic analysis**, then **Find and review ROI**.
2. Choose square pixels, physical X/Y size or whole atlas region. Whole-region mode requires named atlas labels.
3. Enter search start/end and plateau duration in minutes per scan. A duration of zero uses the whole interval; a positive duration searches complete windows within it.
4. Choose Target, Control or both, and confirm image-side assignment and the split column.
5. Choose atlas region(s), coverage, rectangle and slice range as required.
6. Paint the intended restriction, review it, then click **GO / Start analysis**.

Read the painted support

Left-drag adds and right-drag erases. The first add starts empty; the first erase starts full. **Clear painted area** selects none; **Fill painted area** removes the paint restriction. Orange Target and cyan Control fills, with solid bright edges, show selected support. Dashed boundaries show broader eligibility. White role labels remain above the dark exclusion shade.

The same XY painting and rectangle apply across the searched slices. Review other planes before GO. Paint remains active when the brush is switched off. In atlas searches, the uploaded SCM display mask is ignored, but atlas tissue, paint, side, rectangle, valid samples and coverage still constrain the search. Without atlas labels the uploaded mask remains part of eligibility.

Review candidates and export

Click a candidate row to inspect its outline and time course. Checkboxes select export membership; they do not themselves request a new trace. Keep maxima exploratory unless selection was independent of the measured response. Export the intended per-role bundle, add a note and keep its parameter/audit files and sidecars together. Whole-region mode still honors restrictive paint and bounds.

Rank complete atlas regions across slices

In SCM GUI > Automatic analysis, choose Atlas: rank whole regions across slices. Set the signal interval, acquired slice range and number of top Target and Control regions; 0 includes all regions. This mode uses registered integer region labels from a standard or LightSuite atlas, even when histology or vascular anatomy is displayed.

Choose separate image sides and the Target side, or combine the sides. Draw midline defines a straight or slanted dividing line across the searched slices; Remove / combine sides removes that

boundary. These controls describe displayed image sides, not automatically inferred anatomical laterality. ROI-size, brush and rectangular search restrictions do not apply to this whole-region mode.

Rank by the interval mean or by the peak of each regional mean curve, selecting increases, decreases or absolute change. Each regional trace averages one fixed set of eligible voxels across the selected slices. Voxels require a valid baseline and finite samples throughout the signal interval. Minimum usable coverage defaults to 75% and can be set from 75% to 100%; it refers to labelled voxels in the acquired slices, not the complete reference atlas.

The review table reports region names, signed signal change, rank, voxel counts, slice span and usable coverage. Click a row to preview its slice, atlas-shaped outline and trace. Mark / export boxes initially remain unchecked. Dashed outlines are temporary previews; solid outlines identify checked regions. Edit Role to reassign Target or Control, and use Clear selection to unmark results.

Pair same region on opposite side previews the matching atlas region using the same scan, signal and baseline windows, and slice range. Checking a Target retains its matching Control; unchecking releases that automatic selection unless the Control was selected independently. Missing coverage is reported rather than replaced with an unrelated region. Matching Controls remain available below the Control top-N cutoff. This display and selection pairing does not choose a statistical test.

Export tables + curves saves CSV summaries and time courses plus a MAT audit with settings, atlas/source provenance, omitted regions and fixed voxel indices. Standard checked-ROI TXT and bundle exports retain selected regions and edited roles. Attached scans are ranked separately using scan-relative times; short scans are reported without shortening the requested interval. Ranking is exploratory and does not establish statistical significance.

14 Prepare masks and atlas registration

Mask Editor


Select the intended mask target before drawing: the anatomy/brain target and functional overlay target can serve different purposes. Confirm include/exclude convention, inspect the kept/excluded preview and save the required mask objects. A display mask and atlas search membership are not interchangeable.

Geometric masks for volumetric probe data

In Mask Editor, Auto: Rectangular (3D probe) proposes straight-edged coverage; Auto: Ellipse (rounded) proposes an oval, and Anatomical (intensity) follows the Doppler envelope. Review and resize the preview before applying it. Overlay masks default to Follow slice size, fitting each slice separately; turn this off for one fixed box. Underlay masks default to fixed geometry. Smooth: All slices processes each plane independently, whereas Current slice limits the operation. Empty slices remain empty and an existing brain mask restricts overlay smoothing. Apply mask updates the editor; SAVE UNDERLAY / OVERLAY / BOTH saves the result.

Register one 2D source plane

Figure 6. Coronal registration controls



1. Open the 2D coronal registration route for the chosen source slice.
2. Confirm displayed orientation and laterality from acquisition records.
3. Select the matching atlas plane and adjust alignment using several landmarks.
4. Inspect boundaries and vascular/anatomical correspondence across the field.
5. Save explicitly. Keep the dated Slice folder, transform and underlay files together.
6. Reopen that package with **Load atlas** in SCM or Video and review the result.

For a motor stack repeat the source-plane mapping and preserve the combined session. For a true 3D probe use the 3D registration route and inspect coronal, sagittal and axial cuts. Verify spacing, permutation and acquired coverage before accepting it. A visually plausible slice is insufficient evidence of a correct whole-volume transform.

LightSuite guided atlas registration


Open Registration to Atlas > LightSuite (beta), or run deConfUSIon_LightSuite. This optional route registers volumetric Doppler anatomy to a vascular reference. Check dependencies, the animal and scan, and measured voxel spacing in millimetres before starting.

Follow the guided workflow

Continue automatically between steps is enabled by default. Preparation opens orientation confirmation, then landmark editing. Save pairs (S) keeps editing; the green Save + continue to fit button finishes editing and starts fitting. Accept + save all outputs maps anatomy and exports the atlas package. Disable automatic continuation to run individual steps.

1. 1 Prepare + start: build a median anatomy from the current Doppler recording, using its original geometry. Do not prepare registration from a percentage-change movie.
2. 2 Confirm orientation: compare sample and vascular atlas; confirm AP, DV, ML and laterality. Closing leaves this step unconfirmed.
3. 3 Edit landmarks: distribute reliable matching features throughout the acquired volume; complete or cancel every pending pair before saving.
4. 4 Fit registration: affine and B-spline fitting report stage and iteration progress. fUS defaults are a 1.6 mm B-spline grid and landmark weight 0.1.
5. 5 Review + accept: compare vessels, boundaries and coverage on several coronal, horizontal and sagittal slices. Rejecting or closing does not export.
6. 6 Save all outputs: acceptance automatically saves mapped anatomy, native region labels, available vascular/histology backgrounds and editable tissue masks. SAVED identifies the output folder.

Guided LightSuite workspace



Actual guided workspace with anonymized example identifiers. Coloured numbered buttons perform analysis; the current step is emphasized. Green controls save results and blue Help controls open instructions. This is an interface example, not an accepted registration.

Check dependencies and recording geometry

Use Dependencies > Install / complete setup to install the supported Windows open-source dependencies outside the toolbox in deConfUSIon_ExternalTools. The installer preserves upstream licenses and does not install licensed MATLAB products or change the global MATLAB path. LightSuite requires MATLAB R2022b or newer and its reported toolboxes; the documented deConfUSIon reference remains R2023b. CZI import additionally requires BioformatsImage and OME Bio-Formats; TIFF does not. Cortical flatmaps are not enabled by this adapter.

The Recording field can use the active Studio dataset, including its current in-memory processing result. Check that the input is Doppler anatomy rather than a percentage-change movie. Spacing is read from supported metadata and verified beamformer profiles; the status identifies its source. Unsupported headers require measured millimetres along the original array dimensions. Numerical magnitude alone never defines units. Confirm the signed orientation onto AP, DV and ML; closing orientation confirmation cancels that step.

Load edited underlay... opens the recording's Visualization folder and accepts a Mask Editor MAT bundle on the same native grid. It changes the anatomy shown for landmark placement; fitting retains the original anatomical template and native coordinates. Mask Editor standard is the default landmark contrast. Sample contrast, atlas contrast and atlas opacity affect only the display. Complete or cancel pending point pairs before saving.

Choose and edit reliable landmarks

Prefer distinctive vessel bifurcations and junctions identifiable in both sample and vascular atlas. Clear midline, ventricle boundaries and characteristic brain contours may help. Check features in multiple views; distribute pairs across AP, DV, ML and both imaged hemispheres. Do not force matches outside acquired coverage.


The paper reports a median of 219 user landmarks per mouse, not a required threshold. Five noncoplanar pairs are only the numerical minimum. Add confident, distributed matches in rounds and check unused anatomical features after fitting. Neither point count nor a low fitting residual establishes anatomical accuracy.

In Mark matching points mode, right-click an image to undo the last click. Undoing an atlas point keeps its sample pending for correction; another right-click cancels that sample. Delete selected pair removes both points. Zoom and pan retain their normal mouse controls.

BUSY identifies the operation; READY means the editor accepts input. UNSAVED CHANGES and PENDING POINT differ from SAVED with a timestamp. Important Command Window messages have

bold stage labels, time, animal, scan and file path. Marker edits do not recalculate image enhancement.

Landmark editor with save and activity indicators



Actual paired editor with acquired Doppler anatomy and the published vascular reference. Identifiers are anonymized; no matched points or registration acceptance are implied. The header, save badge, activity line and green Save + continue button identify the current task.

Load saved outputs

In SCM or Video choose Underlay > LOAD ATLAS > LightSuite folder and select the project. Normal folder loads standard registrations; Single file remains available. Atlas underlay offers Vascular, Histology and Regions when installed and exported, preserving native functional data and anatomical region context.

Keep LightSuite_Native_Regions.mat and LightSuite_Native_Backgrounds.mat together. Regions includes IDs, names and hemisphere masks. LightSuite_Native_Mask.mat supplies anatomy and an editable tissue mask to Mask Editor. anatomy_in_atlas.mat is mapped anatomy for QC, not a functional movie. Retain the complete session and transform chain.

Older labels-only projects generate missing backgrounds once from their accepted saved fit when the complete project and dependencies are available, without refitting. A standalone old region file cannot recreate images. Histology needs the Allen CCF2020 average template; install with -IncludeHistology and export again if absent.

Re-register and load the exact saved version

Use Open existing project > Re-register (new version) to save another fit in a timestamped Registration_yyyyMMdd_HHmmss_SSS subfolder while preserving the previous fit. Edit copied landmarks retains editable pairs; Recheck orientation starts orientation confirmation without carrying pairs into a changed coordinate system. Fitted projects open read-only. Review and accept the new fit, then load that exact revision in SCM. Selecting a parent with multiple complete revisions opens a version chooser; an incomplete revision is not offered.

Inspect affine and nonlinear overlays in coronal, horizontal and sagittal views, including unused anatomy, acquired boundaries and laterality. Review saved landmark residuals and the AP/DV/ML span of the point set. A small inverse round-trip error or many landmarks does not prove anatomical accuracy. If numerical acceptance fails, Rebuild inverse + recheck prepares a separate candidate; it replaces the existing inverse only if the unchanged checks pass.

SCM starts with Show atlas outside acquired field unchecked. Enable it to inspect the full reference; the dashed box separates acquired tissue from reference-only anatomy. Recorded anatomy is available when the native mask bundle includes the original template. Changing the background, affine/nonlinear stage or display extent does not create functional coverage or change native ROI coordinates. Keep the full registration package and use matching grids when loading regions into SCM, Video, Mask Editor or the volume viewer.

Method scope and interpretation

Native outputs require the original recording grid. Cropping, resampling, reorientation or another scan requires an appropriate registration. Use versioned re-registration to revise a fit without overwriting it. Numerical inverse checks complement, rather than replace, anatomical review.

The preprint constructs a within-mouse anatomy from aligned repeated sessions before atlas registration. This workspace prepares a median template from the selected recording and does not automatically reproduce that multi-session construction. Expression mapping and implant tracing require suitable histology or fluorescence data.

LightSuite citation and acknowledgment

We acknowledge Dimokratis Karamanlis and all LightSuite coauthors for the original framework, methods and resources. Cite their preprint alongside deConfUSIon and the relevant atlas references. It was posted on 14 October 2026 and had not been peer reviewed. These integration screenshots do not reproduce paper figures.

Karamanlis D, Xie Y, Foucher CG, Alappat M, Masood A, Dimitropoulou I, Pivron LAF, Martínez de Paz JM, Macé E, Gaspari S, El-Boustani S. LightSuite: scalable atlas registration and cell detection across the central nervous system. bioRxiv (2026). doi:10.64898/2026.10.13.757638.

Brunner et al. (2021). Whole-brain functional ultrasound imaging in awake head-fixed mice. Nature Protocols 16, 3547-3571. doi:10.1038/s41596-021-00548-8. LightSuite resources: Zenodo 21338217 (CC BY 4.0).

LightSuite | LightSuite fUS

15 Inspect movies and the 3D model


Time Course Viewer and Video GUI

The Time-Course Viewer helps inspect the active movie and ROI traces. Start raw intensity display with neutral contrast and inspect representative frames. Video GUI combines the functional movie/PSC view with underlay and atlas context. Set frame/time, sign, percentage range and opacity deliberately.

1. Open Video from the intended result and choose a representative frame.
2. Open **Underlay** to load a replacement background or matching atlas package.
3. Check alignment and native/atlas coordinates before placing ROIs.
4. Use consistent display settings when comparing recordings.
5. Export a short movie first and review the result before a long export.

Volumetric display

Figure 9. Complete reference atlas views




Use the 3D companion from Video for acquired-field volume, surface or coronal-stack displays. Confirm spacing and choose a backend appropriate to the data. Disable the PSC overlay to review anatomy alone; adjust the Doppler cutoff carefully so faint acquired support is not mistaken for absent tissue. Surfaces and gap/stagger/depth settings are presentation choices.

These views show the complete Allen reference atlas from three orientations. This is reference anatomy, not evidence of full coverage in an acquired scan. Use the acquired-data view to inspect the actual recording support. Blender is an optional external presentation tool; the current toolbox does not provide a native Blender scene/mesh exporter.

16 Compute functional connectivity

Figure 10. Region connectivity matrix



1. Open **Functional Connectivity** with the intended processed movie.
2. Load matching integer atlas regions or supported segmentation output. A colored histology picture alone does not define ROI membership.
3. Inspect label alignment, acquired coverage and voxel counts.
4. Choose merged **Parent** regions for a shorter regional list, or detailed labels when justified. Parent grouping and left/right hemisphere combination are separate settings.
5. Select the scan, period and local time interval. Verify TR and usable duration.
6. Press **ROI current** to recompute the selected region analysis, or the corresponding all-period action.
7. Review traces, matrix values, missing regions and graph settings before exporting.

Recompute after changing labels, period, TR or support. A valid nonconstant trace normally has self-correlation one; missing/constant regions should remain identifiable. Correlation reflects association and can change with motion, global component removal, filtering and task timing. A graph display threshold is not automatically a corrected significance test.

For scan comparisons, confirm period timing within each scan. For group FC, use independent animal-level results and inspect finite counts, correction settings and retained regions.

17 Import ROI results into Group Analysis

1. Open **Group Analysis** and choose the ROI/time-course route.
2. Click **Add ROI / DATA** and select one intended ensemble representation per recording/role. Do not import both equivalent mean and allROIs summaries as separate observations.
3. Verify animal, group, condition, role and PairID against the experimental record. Resolve unassigned rows.
4. Choose the metric and interval, then inspect the time-course preview.
5. Switch to **Statistics** and select a test matching the actual design and independent sample count.
6. Review counts, exclusions and multiplicity settings, then export tables and figures with their parameter record.

Choose a metric and biological unit

A fixed-interval mean describes a prespecified interval. A maximum-plateau endpoint searches complete windows for the largest mean and should be treated as exploratory unless prespecified independently. Keep search width and duration consistent across comparisons.

Several ROIs from one animal do not become several independent animals. A paired test needs verified matching identities. Use **Test = None** for a descriptive one-recording example. Display interpolation or smoothing does not create original measurements or independent sample size. Preserve baseline MAT sidecars with ROI TXT exports.

Assign concentrations and display titrations

In Group Analysis > ROI Preview, choose Titration in the Bottom dropdown, then Assign doses.... Select the animal/scan rows for a dose, choose a concentration from the fixed 1/2/5 series between 1 pM and 10 µM, and click Assign selected. Individual Concentration cells also use dropdowns. Custom typed doses are unavailable; legacy off-list assignments remain visible until replaced or cleared.

Choose the source Group for aCSF; Auto recognizes aCSF, Vehicle and Control. Control rows do not need a dose. Source Group and Condition labels remain unchanged, while the plotted control category is aCSF. If the control Group has several Conditions, select one explicitly. The plot places aCSF first, followed by ascending doses with equal spacing by default; log spacing is optional. Unassigned treatment rows are reported and omitted.

Each titration dot is the animal mean of unique source scans within that category, and group means weight animals equally. Selected aCSF scans are pooled within animal irrespective of any older concentration assignment. Treatment Group and Condition combinations stay separate. Several

ROIs or repeated scans do not become independent animals. Titration mode does not fit a dose-response model or run the generic pooled ROI test and Group-by-Condition outlier screening.

Error bars default to None; choose SEM or SD in Assign doses... when needed. The Legend checkbox shows or hides the live legend in the upper-right corner. Point edges match their fill colors. Save List / Load List retains assignments, selected comparisons and display choices. Correct Animal ID values before connecting repeated animals; connecting lines change the display and do not select paired statistics.

Select dose comparisons and statistical tests

Comparisons... supports dose-versus-aCSF tests, adjacent doses and any pair of displayed categories. On first use, all dose-versus-aCSF comparisons are selected. The default is an unpaired, equal-variance Student t-test with the one-tailed alternative dose > aCSF. Student vs aCSF restores those defaults for an older list. Test and Tail update checked rows; individual comparisons can instead use Welch, paired or two-sided tests.

Tests use the animal means shown by the dots. Paired tests run only when explicitly selected and match Animal IDs. Independent tests retain their independence assumption and report overlapping animal IDs rather than silently changing the test. Review sample counts, unavailable results and the experimental design. Saved selections are retained, including intentionally clearing every comparison.

Annotations show stars and rounded p-values together by default; for example, 0.00776 appears as ** p = 0.008. Calculations and result tables retain full precision. Star thresholds use the unrounded p-value: *** for $p \leq 0.001$, ** for $p \leq 0.01$ and * for $p \leq 0.05$. Extra digits near these thresholds prevent inconsistent labels. Stars-only display is available. Unadjusted p-values are the default; Holm and Bonferroni apply to the selected comparison family and adjusted values are labelled p_adj. Hiding annotations does not change that family.

Preview publication figures before exporting

Export Top..., Export Bottom... and Export Both... open publication previews for time courses, ordinary group comparisons and titrations. Compare Compact (85 × 75 mm), Square (90 × 90 mm) and Wide (140 × 90 mm) layouts. Choose Light or Dark; the initial scheme follows the visible ROI Preview. Axis labels, tick labels and p-values share the publication font size, and axis strokes use a consistent thickness. Marker sizes are scaled for the physical figure dimensions.

Click and drag a p-value label or bracket to move them together before saving. Reset p-value positions restores automatic placement. Positions are retained when switching layouts and used in

the exported figure. The manually selected y minimum and maximum remain exact; comparison brackets have a separate annotation area above the data.

Show legend toggles the export legend, and Legend position places it above the plot or in an inside corner. The default export position is above the plot. Corner placement may overlap data, so inspect the preview after moving it. Preview and saved output use the same rendering path, including the chosen theme and legend settings.

Choose PNG at 600 dpi, vector PDF, or both, then continue to the export folder. Excel export includes source assignments, animal means, dose summaries, selected comparisons, raw and adjusted p-values, and included animal IDs. Reported confidence intervals are pointwise, not simultaneous intervals for the whole family. Retain the saved list and parameter record with the figures.

18 Use Standardized Analysis

1. Open **Standardized Analysis** in Studio and choose a preset matching acquisition and experimental state.
2. Review every checked step, its order and parameters. Click a row to edit its values; use the Run checkbox to include/exclude it.
3. Set baseline/signal windows, reduction factors and filter cutoffs for the actual recording.
4. Run the workflow and complete its interactive review stages. Some steps wait for a viewer to close.
5. Review final QC and outputs, and save the actual settings before processing more animals.

Presets are editable starting points. In particular, the current awake 3D preset E requests automated PC1 removal and substantial block reduction, with nsub 50. Inspect those choices and their effect on temporal resolution before using it. A preset name does not establish suitability for your experiment.

A fixed ROI protocol should contain independently chosen coordinates, dimensions and windows matching the current native or atlas grid. Changing a label does not transform its coordinates. Validate it on a known scan before repeated use.

Review the current automated presets

H | Awake fast injections runs Frame Rejection at 3 sigma with interpolation on the original time grid, automatic PC1 removal across slices with voxel means restored, median blocks of 50 followed by Imregdemons, and SCM GUI. SCM starts positive-only at 0–50%, alpha modulation 5–10%, baseline 30–60 s and signal 700–900 s. Frame QC is saved without opening preview windows.

I | Low-pass / Reject / Imreg50 runs a 0.01 Hz, order-2, zero-phase Butterworth low-pass filter with voxel means preserved, Frame Rejection at 3 sigma with interpolation, then median blocks of 50 and Imregdemons. It does not automatically open SCM. J | Reject / PC1-5 / Imreg50 / SCM uses the H sequence but removes PCs 1–5 and opens SCM with a 7–14 min signal interval.

These presets automatically choose the registration mode for 2D, step-motor or 3D inputs. Median blocks of 50 multiply analyzed TR by 50. A timing check precedes processing; review every step, filter cutoff, component choice and event window for the current acquisition. Defaults are editable starting points and do not establish biological suitability. Reopen Standardized Analysis after replacing source files.

19 Save export and reproduce

Keep the original acquisition and event log, derived datasets, processing parameters, analyzed TR/time origin, masks, atlas registration package and ROI definitions. Preserve export notes, audit text and shared-baseline MAT sidecars together. Copy complete folders when sharing an ROI bundle or registration session.

Large saves can include writing and verification phases after numerical processing. Review the final path and completion message. A network write may take longer than a local write of the same result. Keep enough disk space for temporary and complete files, and reopen a saved result before discarding an original working copy.

Final review checklist

1. Active dataset and original provenance are correct.
2. Timing, TR, event windows and physical geometry are documented.
3. QC decisions and component/filter choices have supporting evidence.
4. Baseline, mask, registration and ROI support match the endpoint.
5. Independent animal count, pairing and test match the study design.
6. Saved files, notes and sidecars can be reopened by another user.

20 Troubleshoot common problems

Table 5. 20 Troubleshoot common problems

Symptom	First checks
Loading takes minutes	Current transfer/read phase, network throughput, cache state and expanded data size
GUI changed after an update	Close/reopen it; check the active toolbox with `which` and remove competing backup paths
Raw movie looks flat after processing	Active array, display limits, mean-restoration choice and excessive component/filter removal
Painted mask seems ignored	Orange/cyan selected support, side, slice range, rectangle, atlas membership and footprint size
Whole atlas region is unavailable	Load named saved integer region labels and select a region
No ROI candidate fits	Paint/coverage intersections, ROI size, valid samples and selected time interval
FC has missing regions	Label alignment, acquired support, selected window and zero-variance traces
Group results have too many observations	Duplicate ensemble representations or ROIs counted as independent animals
Workflow appears paused	Interactive review window, save/verification phase and last status message

Record the active script path, source file, dimensions, TR, exact action and complete MATLAB error when reporting a problem. A screen image is useful together with those details. Reproduce on a preserved original before changing several options at once.

21 Essential terms and further reading

Table 6. 21 Essential terms and further reading

Term	Meaning
fUSI	Functional ultrasound imaging of blood-related signal fluctuations
TR	Time interval between analyzed frames or volumes
QC	Quality control and artifact screening
PSC	Percentage signal change relative to a chosen baseline
SCM	Signal-change map and its associated viewer
ROI	Region of interest with defined spatial membership
PCA	Principal component analysis of variance patterns
ICA	Independent component analysis
FC	Functional connectivity, here primarily correlation of time courses
SEM	Standard error of the mean across independent included observations
FDR	False discovery rate correction for the specified comparison family

For mathematical definitions, every QC output, detailed GUI controls and the complete script/function reference, open the **deConfUSIon User Handbook** supplied beside this guide. The handbook also contains the literature list and interpretation limits. A foundational fUSI reference is Macé et al., *Functional ultrasound imaging of the brain*, Nature Methods, 2011, DOI 10.1038/nmeth.1641.

Acknowledgments

deConfUSIon is developed by Soner Caner Cagun, MPI for Biological Cybernetics. ChatGPT/Codex assisted with documentation drafting, organization, figure annotation and software troubleshooting; the developer remains responsible for reviewing the software and scientific interpretation.

Acknowledgments and responsibility

We acknowledge Dimokratis Karamanlis and all LightSuite coauthors for the original framework, methods and resources. Cite their preprint alongside deConfUSIon and the relevant atlas references. It was posted on 14 October 2026 and had not been peer reviewed. These integration screenshots do not reproduce paper figures.

Karamanlis D, Xie Y, Foucher CG, Alappat M, Masood A, Dimitropoulou I, Pivron LAF, Martínez de Paz JM, Macé E, Gaspari S, El-Boustani S. LightSuite: scalable atlas registration and cell detection across the central nervous system. bioRxiv (2026). doi:10.64898/2026.10.13.757638. https://doi.org/10.64898/2026.10.13.757638

ConfUSIus provides a complementary Python-based approach to fUSI analysis. deConfUSIon emphasizes a connected MATLAB GUI workflow for researchers who do not write code. Thanks are due to ConfUSIus developers Samuel Le Meur-Diebolt and Felipe Cybis Pereira, and José María Martínez de Paz from Émilie Macé's laboratory, for discussions. The projects are independently developed.

Beta research software. No guarantee is given for the correctness of a particular analysis; no liability for incorrect data analysis to the extent permitted by law. Mandatory statutory liability is unaffected.