ServletContext

- ServletContext is an interface in the javax.servlet package, automatically created by the server when a web application is deployed.
- It represents the entire web application and is used to share information across servlets within the same application.
- It provides information about the server and web application

```
ServletContext context = req.getServletContext();
```

- We can initialize parameters for ServletContext using the <context-param> tag in the web.xml file.

```
<web-app>
   <context-param>
      <param-name>name</param-name>
      <param-value>value</param-value>
   </context-param>
   <!-- Additional context-param tags can be added as needed -->
</web-app>
```

- Inorder to access the initialized parameter values in the servlet, we need to use getInitParameter() method on the ServletContext object.

Method Syntax:

```
public abstract String getInitParameter(java.lang.String name)
```

Example:

```
String value = context.getInitParameter("name");
```

Kishan

- ServletContext is shared across the entire web application, meaning all servlets in the application can access the same ServletContext object.

ServletConfig

- ServletConfig is an interface in the javax.servlet package. It is automatically created when a servlet is loaded for execution.
- It provides configuration information specific to a single servlet.
- The ServletConfig object includes the servlet's name and other initialization parameters set in web.xml.

```
ServletConfig config = this.getServletConfig();
```

- Parameters specific to a servlet can be set using the <init-param> tag inside the <servlet> tag in the web.xml file

Kishan

Syntax in web.xml

```
<web-app>
  ...
  <servlet>
    <servlet-name>name</servlet-name>
    <servlet-class>class</servlet-class>
    <init-param>
      <param-name>name</param-name>
      <param-value>value</param-value>
    </init-param>
  </servlet>
  <servlet-mapping>
    <servlet-name>name</servlet-name>
    <url-pattern>/url</url-pattern>
  </servlet-mapping>
  ...
</web-app>
```

Kishan

- Inorder to access the initialized parameter values in the servlet, we need to use getInitParameter() method on the ServletConfig object.

Method Syntax:

```
public abstract String getInitParameter(java.lang.String name)
```

Example:

```
String value = config.getInitParameter("name");
```

- ServletConfig is unique to each servlet, meaning each servlet has its own ServletConfig object. getInitParameter() retrieves values for parameters defined for that specific servlet in web.xml.

Kishan