

```
// 1. Type Conversion.
```

// Write a function called `convertToNumber` that takes a string as an argument and returns the equivalent number. If the string cannot be converted to a number, the function should return the string "Invalid number". Use error handling in javascript to achieve this output.

```
function convertToNumber(str) {  
  try {  
    const num = Number(str);  
    if (Number.isNaN(num)) {  
      throw new Error("Invalid number");  
    }  
    return num;  
  } catch (error) {  
    return error.message;  
  }  
}  
  
console.log(convertToNumber("123"));  
console.log(convertToNumber("abc"));
```

// 2. Building Robust Functions in JavaScript

// Create a function called `getPerson` that takes an object as a parameter representing a person's name and age. The function should return the person's name and age as a string in the format "Name: <name>, Age: <age>". However, if the parameter is not a valid object with the properties "name" and "age", the function should throw an error with the message "Invalid parameter type". Use try-catch to handle this error and return the error message if it occurs.

```
function getPerson(person) {  
  try {  
    if (typeof person !== "object" || !person.name || !person.age) {  
      throw new Error("Invalid parameter type");  
    }  
    return `Name: ${person.name}, Age: ${person.age}`;  
  } catch (error) {  
    return error.message;  
  }  
}
```

// Expected Output

```
console.log(getPerson({ name: "Mithun", age: 20 })); // Name: Mithun,  
Age: 20  
console.log(getPerson({ name: "Mithun" })); // Invalid parameter type  
console.log(getPerson(["name", "Mithun"])); // Invalid parameter type
```

```
// 3. Car Description Class.
```

```
// Create a class called Car with three properties: company,
model, and year. The class should have a method called
getDescription that returns a string in the format "This is a
<year> <company> <model>". Instantiate an instance of the Car
class and call the getDescription method.
```

```
// Expected Output
```

```
// console.log(myCar.getDescription());
// Output: This is a 2022 Skoda Rapid.
```

```
class Car {
  constructor(company, model, year) {
    this.company = company;
    this.model = model;
    this.year = year;
  }

  getDescription() {
    return `This is a ${this.year} ${this.company}
    ${this.model}.`;
  }
}
```

```
const myCar = new Car("Skoda", "Rapid", 2022);
```

```
console.log(myCar.getDescription()); // Output: This is a 2022
Skoda Rapid.
```

```
/*
```

4. Employee Class Challenge.

Create a class called Employee with three properties: name, position, and salary. The class should have a method called getSalary that returns the employee's salary. Instantiate an instance of the Employee class and call the getSalary method.

Expected Output:

```
console.log(employee1.getSalary()); // Output: 80000
```

```
*/
```

```
class Employee {  
  constructor(name, position, salary) {  
    this.name = name;  
    this.position = position;  
    this.salary = salary;  
  }  
  
  getSalary() {  
    return this.salary;  
  }  
}  
  
const employee1 = new Employee("Prabir Kumar", "Software  
Engineer", 80000);  
  
// Expected Output  
console.log(employee1.getSalary()); // Output: 80000
```

```
/*
```

5. Implementing a Person Class with Default Values

Create a class called Person with two properties: name and age. The class should have a method called getDetails that returns a string in the format "Name: <name>, Age: <age>". Use default parameters in the constructor to set the values of name and age to "Unknown" and 0 if they are not provided.

Expected Output

```
const person1 = new Person("Mithun", 20);
console.log(person1.getDetails()); // Output: "Name: Mithun, Age: 20"
```

```
const person2 = new Person();
console.log(person2.getDetails()); // Output: "Name: Unknown, Age: 0"
```

```
*/
```

```
class Person {
  constructor(name = "Unknown", age = 0) {
    this.name = name;
    this.age = age;
  }

  getDetails() {
    return `Name: ${this.name}, Age: ${this.age}`;
  }
}
```

```
}
```

```
// Expected Output
```

```
const person1 = new Person("Mithun", 20);  
console.log(person1.getDetails()); // Output: "Name: Mithun, Age:  
20"
```

```
const person2 = new Person();  
console.log(person2.getDetails()); // Output: "Name: Unknown, Age:  
0"
```

```
/*
```

6. Using Static Method to Add Two Numbers with Calculator Class

Create a class called Calculator with a static method called add. The add method should take two numbers as arguments and return their sum. Instantiate the Calculator class and call the add method.

Expected Output:

```
console.log(result); // Output: 15
```

```
*/
```

```
class Calculator {  
  static add(num1, num2) {  
    return num1 + num2;  
  }  
}  
  
const result = Calculator.add(5, 10);
```

```
// Expected Output:
```

```
console.log(result); // Output: 15
```

```
/*
```

7. Password Checker.

Create a class called User with properties username and password. Implement a getter method for password that returns the password with all characters replaced by asterisks. Implement a setter method for password that checks if the new password is at least 8 characters long and contains at least one number and one uppercase letter. If the password is valid, set the new password. If not, log an error message.

Expected output:

```
const user = new User("johndoe", "Password123");  
console.log(user.getPassword()); // *****
```

```
user.setPassword("myPassword"); // Error: Password must be at  
least 8 characters long and contain at least one number and one  
uppercase letter.
```

```
user.setPassword("MyPassword"); // Error: Password must be at  
least 8 characters long and contain at least one number and one
```

uppercase letter.

```
user.setPassword("Mypassword123");  
console.log(user.getPassword()); // *****
```

```
*/
```

```
class User {  
  constructor(username, password) {  
    this.username = username;  
    this.password = password;  
  }  
  
  getPassword() {  
    return this.password.replace(/./g, "*");  
  }  
  
  setPassword(newPassword) {  
    let containsNumber = false;  
    let containsUppercase = false;  
    for (let i = 0; i < newPassword.length; i++) {  
      const char = newPassword.charAt(i);  
      if (!isNaN(char)) {  
        containsNumber = true;  
      } else if (char === char.toUpperCase()) {
```



```

        containsUppercase = true;
    }
}
if (newPassword.length >= 8 && containsNumber &&
containsUppercase) {
    this.password = newPassword;
} else {
    console.log(
        "Error: Password must be at least 8 characters long and
contain at least one number and one uppercase letter."
    );
}
}
}
}

```

// Expected output:

```

const user = new User("johndoe", "Password123");
console.log(user.getPassword()); // *****

```

```

user.setPassword("myPassword"); // Error: Password must be at
least 8 characters long and contain at least one number and one
uppercase letter.

```

```

user.setPassword("MyPassword"); // Error: Password must be at
least 8 characters long and contain at least one number and one
uppercase letter.

```

```

user.setPassword("Mypassword123");
console.log(user.getPassword()); // *****

```

// 8. Adding a Method to a Prototype.

// Create a prototype object called Student with a property name. Add a method called printDetails to the prototype that logs the string "Hello, my name is {name}" to the console. Instantiate a Student object with the name "Mithun" and call the printDetails method.

// Expected Output

```

// const student = new Student("Mithun");
// student.printDetails(); // "Hello, the student is Mithun"

```

```
function Student(name) {
  this.name = name;
}

Student.prototype.printDetails = function () {
  console.log(`Hello, my name is ${this.name}`);
};

// Expected Output

const student = new Student("Mithun");
student.printDetails(); // "Hello, the student is Mithun"
```

```
/*
```

9. Check the presence using closures.

Create a numberChecker function that takes an array of numbers as an argument and returns a function. The returned function should take another number as an argument and return true if the number is in the array, and false otherwise.

```
*/
```

```
function numberChecker(numbers) {  
  return function (num) {  
    return numbers.includes(num);  
  };  
}  
  
// Expected Result:  
const arr = [1, 2, 3, 4, 5];  
const checkNum = numberChecker(arr);  
  
console.log(checkNum(3)); // true  
console.log(checkNum(6)); // false
```

```
/*
```

10. Filter by Category.

Write a function that takes an array of products and returns a function that filters the array by a given product category. The function must filter an eCommerce products array by a specific category. The closure filters products using the `filter()` method. Finally, it returns a new array containing only the products with the same category as the input.

```
*/
```

```
function filterByCategory(products) {  
  return function (category) {  
    return products.filter(function (product) {  
      return product.category === category;  
    });  
  };  
}
```

```
// Expected Output
```

```
var products = [  
  { name: "Shirt", category: "Clothing" },  
  { name: "Pants", category: "Clothing" },  
  { name: "Hat", category: "Accessories" },  
  { name: "Sunglasses", category: "Accessories" },  
];
```

```
var clothingProducts = filterByCategory(products)("Clothing");
```

```
console.log(clothingProducts);
```

```
// Output: [{name: "Shirt", category: "Clothing"}, {name: "Pants",  
category: "Clothing"}]
```