

ECON567B: R session

Soo Jeong Lee

Remember, never ever ever use `install.packages` in a code chunk.

```
install.packages("wooldridge")
library(wooldridge)
install.packages("knitr")
install.packages("tinytex")
tinytex::install_tinytex(bundle = "TinyTeX")
```

<— As you can see, paragraphs in R Markdown are separated by a blank line.
To start a new paragraph, you need to hit Enter twice.

```
knitr::opts_chunk$set(echo = TRUE)
```

Here, `knitr::` refers directly to the knitr package, so we do not need to call `library(knitr)` first.

`echo = TRUE`, means that the R code itself will be shown in the output document.

Here, `knitr::` refers directly to the knitr package, so we do not need to call `library(knitr)` first. `echo = TRUE`, means that the R code itself will be shown in the output document.

The same setting could also be written as:

```
library(knitr)
opts_chunk$set(echo = TRUE)
```

Here, `eval = FALSE` means that this example code is displayed in the document but is not executed.

EC567B

Hello, This file provides guidance for our R session.

[1] Online version of Rstudio (<https://rstudio.cloud>) - You could download local ver. of Rstudio (from official website - for free).

[2] How to generate your submission file by using RMarkdown”

Now, let’s get started!

```
# four panes (Console, R script, Environment-, Packages-)
# Setting the Working Directory
getwd()
```

```
## [1] "C:/Users/SIU856615949/Downloads"
```

```
#or setwd("/cloud/project/ECON567")
```

```
## Keyboard Shortcuts
```

```
# Run the current line or selected lines:
```

```
# Windows: Ctrl + Enter
```

```
# Mac: Command+Return/Enter (on a Mac)
```

```
# Cntl+L ; Screen (console) should be refreshed/cleared
```

```
#Creating a code chunk
```

```
# Windows: Ctrl+Alt+I
```

```
# Mac: Command+Option+I
```

```
# R as a calculator
```

```
1+1
```

```
## [1] 2
```

```
sqrt(5)
```

```
## [1] 2.236068
```

```
5*(4-1)^2
```

```
## [1] 45
```

```
x<- 3
```

```
y <- c(1, 2, 3, 4, 5, 6, 7, 8)
```

```
mean(y)
```

```
## [1] 4.5
```

```
x*y
```

```
## [1] 3 6 9 12 15 18 21 24
```

```
pnorm(-5)
```

```
## [1] 2.866516e-07
```

```
pnorm(1, mean=4, sd=0.6)
```

```
## [1] 2.866516e-07
```

```
# accessing the help files/ get particular function
```

```
# ?mean
```

```
# ?median
```

From here, I create a code chunk

```
z <-8  
(k <-4)
```

```
## [1] 4
```

```
z+k
```

```
## [1] 12
```

```
wage2=wooldridge::wage2  
mean(wage2$wage)
```

```
## [1] 957.9455
```

```
summary(wage2$wage)
```

```
##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.  
##    115.0   669.0   905.0   957.9  1160.0  3078.0
```

Comparing this PDF file with its R Markdown file would be helpful.

I'll also provide the problem set and detailed code in class!