Solving Proximity Constraints

Sophie Hofmanninger   Jan-Michael Holzinger

26.06.2019

Johannes Kepler University, A-4040 Linz, Austria

Theory
0000

System Model
○

Workflow
○

JYU
JOHANNES KEPLER
UNIVERSITÄT LINZ

Theory
●○○○

System Model
○

Workflow
○

J⊻U
JOHANNES KEPLER
UNIVERSITÄT LINZ

Introduction

4 sets:

- P: unification problem to be solved
- C: neighborhood constraint
- σ: set of pre-unifier
- ψ: name-class mapping

Pre-Unification rules

(Tri) Trivial: . . .
(Dec) Decomposition: . . .
. . .

Theory
○○○●○

System Model
○

Workflow
○

JOHANNES KEPLER
UNIVERSITÄT LINZ

Rules for Neigborhood Constraints

(FFS) Function Symbols: ...
(NFS) Name vs Function Symbol: ...
...

Theory
○○○●

System Model
○

Workflow
○

JYU
JOHANNES KEPLER
UNIVERSITÄT LINZ

Simple example

Problem to solve: $p(x, y) =? q(f(a), g(b))$
Solution: . . .

Theory
oooo

System Model
o

Workflow
o

JYU
JOHANNES KEPLER
UNIVERSITÄT LINZ

Steps Pre-Unification

. . .

Steps Constraint-Simplification

. . .

Theory
oooo

System Model
o

Workflow
o

JYU
JOHANNES KEPLER
UNIVERSITÄT LINZ

System Model

. . .

Theory
○○○○

System Model
○

Workflow
○

JYU
JOHANNES KEPLER
UNIVERSITÄT LINZ

1 Theory

2 System Model

3 Workflow

Workflow

. . .