

R Installation and Administration - with modifications

R Version 2.15.0 (2012-03-30), pqR version 2.15.0 (2013-06-28)

R Development Core Team, pqR modifications by Radford Neal

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation approved by the R Development Core Team.

Copyright © 2001–2012 R Development Core Team

ISBN 3-900051-09-7

Modifications for pqR copyright © 2013 Radford M. Neal

Table of Contents

1	Obtaining pqR and R	1
1.1	Getting and unpacking the sources	1
1.2	Getting patched and development versions	1
1.2.1	Using Subversion and rsync	2
2	Installing R under Unix-alikes	3
2.1	Simple compilation	3
2.2	Help options	5
2.3	Making the manuals	5
2.4	Installation	6
2.5	Uninstallation	8
2.6	Sub-architectures	8
2.6.1	Multilib	9
2.7	Other Options	10
2.7.1	Inter-Procedure Optimization	10
2.8	Testing an Installation	11
3	Installing R under Windows	12
3.1	Building from source	12
3.1.1	Getting the tools	12
3.1.2	Getting the source files	12
3.1.3	Building the core files	14
3.1.4	Building the bitmap files	14
3.1.5	Building the cairo devices	14
3.1.6	Checking the build	15
3.1.7	Building the manuals	15
3.1.8	Building the Inno Setup installer	15
3.1.9	Building the MSI installer	16
3.1.10	Cross-building on Linux	17
3.1.11	64-bit Windows builds	17
3.2	Testing an Installation	17
4	Installing R under (Mac) OS X	19
4.1	Building from source on (Mac) OS X	19
5	Running R	20

6	Add-on packages	21
6.1	Default packages	21
6.2	Managing libraries	21
6.3	Installing packages	22
6.3.1	Windows	23
6.3.2	OS X	24
6.3.3	Customizing package compilation	24
6.3.4	Multiple sub-architectures	24
6.3.5	Byte-compilation	25
6.4	Updating packages	25
6.5	Removing packages	25
6.6	Setting up a package repository	26
6.7	Checking installed source packages	26
7	Internationalization and Localization	28
7.1	Locales	28
7.1.1	Locales under Linux	29
7.1.2	Locales under Windows	29
7.1.3	Locales under OS X	29
7.2	Localization of messages	29
8	Choosing between 32- and 64-bit builds	31
9	The standalone Rmath library	33
9.1	Unix-alikes	33
9.2	Windows	34
Appendix A Essential and useful other programs		
under a Unix-alike		36
A.1	Essential programs and libraries	36
A.2	Useful libraries and programs	37
A.2.1	Tcl/Tk	39
A.2.2	Java support	39
A.3	Linear algebra	40
A.3.1	BLAS	40
A.3.1.1	ATLAS	41
A.3.1.2	ACML	41
A.3.1.3	Goto BLAS	41
A.3.1.4	Intel MKL	42
A.3.1.5	Shared BLAS	43
A.3.2	LAPACK	43
A.3.3	Caveats	44

Appendix B Configuration on a Unix-alike ... 45

B.1	Configuration options	45
B.2	Helper threads	46
B.3	Internationalization support	46
B.4	Configuration variables	46
B.4.1	Setting paper size	47
B.4.2	Setting the browsers	47
B.4.3	Compilation flags	47
B.4.4	Making manuals	47
B.5	Setting the shell	47
B.6	Using make	48
B.7	Using FORTRAN	48
B.7.1	Using gfortran	49
B.8	Compile and load flags	49

Appendix C Platform notes 51

C.1	X11 issues	51
C.2	Linux	52
C.2.1	Clang	53
C.2.2	Intel compilers	53
C.2.3	Oracle Solaris Studio compilers	54
C.3	FreeBSD	55
C.4	(Mac) OS X	55
C.4.1	64-bit builds	56
C.4.2	Snow Leopard	56
C.4.3	Lion	56
C.5	Solaris	57
C.5.1	Using gcc	59
C.6	AIX	60
C.7	Cygwin	62
C.8	New platforms	62

Appendix D The Windows toolset 64

D.1	L ^A T _E X	65
D.2	The Inno Setup installer	65
D.3	The command line tools	65
D.4	The MinGW-w64 toolchain	66
D.5	Useful additional programs	66

Function and variable index 67

Concept index 68

Environment variable index 69

1 Obtaining pqR and R

Sources, binaries, and documentation for pqR can be obtained from <http://github.com/radfordneal/pqR/>. The remainder of this section documents how to obtain versions of R produced by the R Core Team.

Sources, binaries and documentation for R can be obtained via CRAN, the “Comprehensive R Archive Network” whose current members are listed at <http://cran.r-project.org/mirrors.html>.

1.1 Getting and unpacking the sources

The simplest way is to download the most recent ‘R-x.y.z.tar.gz’ file, and unpack it with

```
tar -xf R-x.y.z.tar.gz
```

on systems that have a suitable¹ `tar` installed. On other systems you need to have the `gzip` program installed, when you can use

```
gzip -dc R-x.y.z.tar.gz | tar -xf -
```

The pathname of the directory into which the sources are unpacked should not contain spaces, as most `make` programs (and specifically GNU `make`) do not expect spaces.

If you want the build to be usable by a group of users, set `umask` before unpacking so that the files will be readable by the target group (e.g., `umask 022` to be usable by all users). Keep this setting of `umask` whilst building and installing.

If you use a recent GNU version of `tar` and do this as a root account (which on Windows includes accounts with administrator privileges) you may see many warnings about changing ownership. In which case you can use

```
tar --no-same-owner -xf R-x.y.z.tar.gz
```

and perhaps also include the option ‘`--no-same-permissions`’. (These options can also be set in the `TAR_OPTIONS` environment variable: if more than one option is included they should be separated by spaces.)

1.2 Getting patched and development versions

A patched version of the current release, ‘`r-patched`’, and the current development version, ‘`r-devel`’, are available as daily tarballs and via access to the R Subversion repository. (For the two weeks prior to the release of a minor (2.x.0) version, ‘`r-patched`’ tarballs may refer to beta/release candidates of the upcoming release, the patched version of the current release being available via Subversion.)

The tarballs are available from <ftp://ftp.stat.math.ethz.ch/pub/Software/R/>. Download ‘`R-patched.tar.gz`’ or ‘`R-devel.tar.gz`’ (or the ‘`.tar.bz2`’ versions) and unpack as described in the previous section. They are built in exactly the same way as distributions of R releases.

¹ e.g. GNU `tar` version 1.15 or later, or that from the ‘`libarchive`’ (as used on OS 10.[67]) or ‘Heirloom Toolchest’ distributions.

1.2.1 Using Subversion and rsync

Sources are also available via <https://svn.R-project.org/R/>, the R Subversion repository. If you have a Subversion client (see <http://subversion.apache.org/>), you can check out and update the current ‘r-devel’ from <https://svn.r-project.org/R/trunk/> and the current ‘r-patched’ from ‘<https://svn.r-project.org/R/branches/R-x-y-branch/>’ (where x and y are the major and minor number of the current released version of R). E.g., use

```
svn checkout https://svn.r-project.org/R/trunk/ path
```

to check out ‘r-devel’ into directory *path* (which will be created if necessary). The alpha, beta and RC versions of an upcoming x.y.0 release are available from ‘<https://svn.r-project.org/R/branches/R-x-y-branch/>’ in the four-week period prior to the release.

Note that ‘https:’ is required², and that the SSL certificate for the Subversion server of the R project should be recognized as from a trusted source.

Note that retrieving the sources by e.g. `wget -r` or `svn export` from that URL will not work: the Subversion information is needed to build R.

The Subversion repository does not contain the current sources for the recommended packages, which can be obtained by `rsync` or downloaded from CRAN. To use `rsync` to install the appropriate sources for the recommended packages, run `./tools/rsync-recommended` from the top-level of the R sources.

If downloading manually from CRAN, do ensure that you have the correct versions of the recommended packages: if the number in the file ‘VERSION’ is ‘x.y.z’ you need to download the contents of ‘<http://CRAN.R-project.org/src/contrib/dir>’, where *dir* is ‘x.y.z/Recommended’ for r-devel or ‘x.y-patched/Recommended’ for r-patched, respectively, to directory ‘src/library/Recommended’ in the sources you have unpacked. After downloading manually you need to execute `tools/link-recommended` from the top level of the sources to make the requisite links in ‘src/library/Recommended’. A suitable incantation from the top level of the R sources using `wget` might be (for the correct value of ‘*dir*’)

```
wget -r -ll --no-parent -A\*.gz -nd -P src/library/Recommended \
  http://CRAN.R-project.org/src/contrib/dir
./tools/link-recommended
```

² for some Subversion clients ‘http:’ may appear to work, but requires continual redirection.

2 Installing R under Unix-alikes

pqR will configure and build under most common Unix and Unix-alike platforms, in the same way as R-2.15.0, on which pqR is based. Except as noted, the remainder of this section applies equally to R-2.15.0 and pqR.

R-2.15.0 will configure and build on most common Unix and Unix-alike platforms including ‘cpu-*-linux-gnu’ for the ‘alpha’, ‘arm’, ‘hppa’, ‘ix86’, ‘ia64’, ‘m68k’, ‘mips’, ‘mipsel’, ‘powerpc’, ‘s390’, ‘sparc’, and ‘x86_64’ CPUs, ‘i386-apple-darwin’, ‘x86_64-apple-darwin’, ‘i386-sun-solaris’, ‘sparc-sun-solaris’, ‘x86_64-*-freebsd’, and ‘powerpc-ibm-aix6*’ as well as perhaps (it is tested less frequently on these platforms) ‘powerpc-apple-darwin’, ‘i386-*-freebsd’, ‘i386-*-netbsd’ and ‘i386-*-openbsd’.

No binary distributions of pqR are available yet. Versions of R distributed by the R Core Team are available as binary distributions for some common Linux distributions and for OS X (formerly Mac OS). See the FAQ for current details. These are installed in platform-specific ways, so for the rest of this chapter we consider only building from the sources.

2.1 Simple compilation

First review the essential and useful tools and libraries in [Appendix A \[Essential and useful other programs under a Unix-alike\]](#), page 36, and install those you want or need. Ensure that the environment variable TMPDIR is either unset (and ‘/tmp’ exists and can be written in and scripts can be executed from) or points to a valid temporary directory (one from which execution of scripts is allowed).

Choose a place to install the R tree (R is not just a binary, but has additional data sets, help files, font metrics etc). Let us call this place *R_HOME*. Untar the source code. This should create directories ‘src’, ‘doc’, and several more under a top-level directory: change to that top-level directory. Issue the following commands:

```
./configure
make
```

(See [Section B.6 \[Using make\]](#), page 48 if your make is not called ‘make’.) Users of Debian-based 64-bit systems¹ may need

```
./configure LIBnn=lib
make
```

Other options to ‘./configure’ may also be useful (see [Appendix B \[Configuration on a Unix-alike\]](#), page 45). In particular, North American users should consult [Section B.4.1 \[Setting paper size\]](#), page 47.

Once make has finished, you should check that the built system works correctly by

```
make check
```

Failures are not necessarily problems as they might be caused by missing functionality,² but you should look carefully at any reported discrepancies. (Some non-fatal errors are expected in locales that do not support Latin-1, in particular in true C locales and non-UTF-8 non-Western-European locales.) A failure in ‘tests/ok-errors.R’ may indicate inadequate resource limits (see [Chapter 5 \[Running R\]](#), page 20).

¹ which use ‘lib’ rather than ‘lib64’ for their primary 64-bit library directories.

² for example, if you configured R with ‘--without-recommended’.

More comprehensive testing can be done by

```
make check-devel
```

or

```
make check-all
```

see file ‘tests/README’.

If the command `configure` and `make` commands execute successfully, a shell-script front-end called ‘R’ will be created and copied to ‘*R_HOME*/bin’. You can copy this script to a place where users can invoke it, for example to ‘*/usr/local/bin/R*’. You could also copy the man page ‘R.1’ to a place where your `man` reader finds it, such as ‘*/usr/local/man/man1*’. If you want to install the complete R tree to, e.g., ‘*/usr/local/lib/R*’, see [Section 2.4 \[Installation\]](#), page 6. Note: you do not *need* to install R: you can run it from where it was built.

You do not necessarily have to build R in the top-level source directory (say, ‘*TOP_SRCDIR*’). To build in ‘*BUILDDIR*’, run

```
cd BUILDDIR
TOP_SRCDIR/configure
make
```

and so on, as described further below. This has the advantage of always keeping your source tree clean and is particularly recommended when you work with a version of R from Subversion. (You may need GNU `make` to allow this, and you will need no spaces in the path to the build directory.)

Now `rehash` if necessary, type `R`, and read the R manuals and the R FAQ (files ‘FAQ’ or ‘doc/manual/R-FAQ.html’, or <http://CRAN.R-project.org/doc/FAQ/R-FAQ.html> which always has the version for the latest release of R).

Most of the files in the source directory are human-created, but a few are created automatically from other files. One example is ‘NEWS’, supplied with the source directory, but also re-created from ‘doc/NEWS.Rd’, as part of the normal build process. Other such files do not normally need to be re-created. In particular, you will not usually need to re-create ‘configure’, which is derived from ‘configure.ac’, ‘VERSION’, and the macro definitions in the ‘m4’ directory. If you do want to re-create this or other other automatically built files (such as ‘src/main/gram.c’ from ‘src/main/gram.y’), you will need to run ‘./configure’ with the `--enable-maintainer-mode` option, which creates a ‘Makefile’ with the appropriate rules. Note that these files are always recreated in the source directory, even if you are using a separate build directory. (When re-creating ‘configure’, you should not use a separate build directory, since this has the effect of stripping comments from ‘configure’.)

There is a possible logical flaw with the concept of re-creating ‘configure’ using a ‘Makefile’ that can be created only if you have a working ‘configure’ script — if necessary, you can re-create ‘configure’ as follows, when in the main source directory:

```
cat m4/R.m4 m4/bigendian.m4 m4/cairo.m4 m4/clibs.m4 \
    m4/codeset.m4 m4/gettext.m4 m4/gettext-lib.m4 \
    m4/java.m4 m4/libtool.m4 m4/ltoptions.m4 m4/ltversion.m4 \
    m4/ltsugar.m4 m4/lt~obsolete.m4 m4/stat-time.m4 > acinclude.m4
aclocal --output=aclocal.m4 -I .
autoconf -B .
```

2.2 Help options

By default HTML help pages are created when needed rather than being built at install time.

If you need to disable the server and want HTML help, there is the option to build HTML pages when packages are installed (including those installed with R). This is enabled by the `configure` option ‘`--enable-prebuilt-html`’. Whether `R CMD INSTALL` (and hence `install.packages`) pre-builds HTML pages is determined by looking at the R installation and is reported by `R CMD INSTALL --help`: it can be overridden by specifying one of the `INSTALL` options ‘`--html`’ or ‘`--no-html`’.

The server is disabled by setting the environment variable `R_DISABLE_HTTPD` to a non-empty value, either before R is started or within the R session before HTML help (including `help.start`) is used. It is also possible that system security measures will prevent the server from being started, for example if the loopback interface has been disabled. See `?tools::startDynamicHelp` for more details.

2.3 Making the manuals

There is a set of manuals that can be built from the sources,

‘`refman`’ Printed versions of the help pages for the base packages.

‘`fullrefman`’
 Printed versions of all the help pages for base and recommended packages (over 3200 pages).

‘`R-FAQ`’ R FAQ

‘`R-intro`’ “An Introduction to R”.

‘`R-data`’ “R Data Import/Export”.

‘`R-admin`’ “R Installation and Administration”, this manual.

‘`R-exts`’ “Writing R Extensions”.

‘`R-lang`’ “The R Language Definition”.

To make these (except ‘`fullrefman`’), use

```
make pdf      to create PDF versions
make info     to create info files (not ‘refman’).
```

You will not be able to build any of these unless you have `makeinfo` version 4.7 or later installed, and for PDF you must have `texi2dvi` and ‘`texinfo.tex`’ installed (which are part of the GNU `texinfo` distribution but are, especially ‘`texinfo.tex`’, often made part of the `TeX` package in re-distributions).

The PDF versions can be viewed using any recent PDF viewer: they have hyperlinks that can be followed. The info files are suitable for reading online with Emacs or the standalone GNU `info` program. The PDF versions will be created using the paper size selected at configuration (default ISO a4): this can be overridden by setting `R_PAPERSIZE` on the `make` command line, or setting `R_PAPERSIZE` in the environment and using `make -e`. (If re-making the manuals for a different paper size, you should first delete the file ‘`doc/manual/version.texi`’.)

There are some issues with making the PDF reference manual, ‘`refman.pdf`’. The help files contain both ISO Latin1 characters (e.g. in ‘`text.Rd`’) and upright quotes, neither of which are contained in the standard L^AT_EX Computer Modern fonts. We have provided four alternatives:

- times** (The default.) Using standard PostScript fonts, Times Roman, Helvetica and Courier. This works well both for on-screen viewing and for printing. One disadvantage is that the Usage and Examples sections may come out rather wide: this can be overcome by using *in addition* either of the options **beramono** or **inconsolata** (which is part of the current default), which replace the Courier monospaced font by Bera Sans mono or Inconsolata respectively. (You will need the appropriate L^AT_EX package **bera** or **inconsolata** installed.³)
 Note that in most L^AT_EX installations this will not actually use the standard fonts for PDF, but rather embed the URW clones NimbusRom, NimbusSans and (for Courier, if used) NimbusMon.
- lm** Using the *Latin Modern* fonts. These are not often installed as part of a T_EX distribution, but can be obtained from <http://www.ctan.org/tex-archive/fonts/ps-type1/lm/> and mirrors. This uses fonts rather similar to Computer Modern, but is not so good on-screen as **times**.
- cm-super** Using type-1 versions of the Computer Modern fonts by Vladimir Volovich. This is a large installation, obtainable from <http://www.ctan.org/tex-archive/fonts/ps-type1/cm-super/> and its mirrors. These type-1 fonts have poor hinting and so are nowhere near so readable on-screen as the other three options.
- ae** A package to use composites of Computer Modern fonts. This works well most of the time, and its PDF is more readable on-screen than the previous two options. There are three fonts for which it will need to use bitmapped fonts, ‘`tctt0900.600pk`’, ‘`tctt1000.600pk`’ and ‘`tcrm1000.600pk`’. Unfortunately, if those files are not available, Acrobat Reader will substitute completely incorrect glyphs so you need to examine the logs carefully.

The default can be overridden by setting the environment variable `R_RD4PDF`. (On Unix-alikes, this will be picked up at install time and stored in ‘`etc/Renviron`’, but can still be overridden when the manuals are built.) The default value for `R_RD4PDF` is ‘`times,inconsolata,hyper`’: omit ‘`hyper`’ if you do not want hyperlinks (e.g. for printing the manual) or do not have L^AT_EX package **hyperref**, and omit ‘`inconsolata`’ if you do not have L^AT_EX package **inconsolata** installed.

2.4 Installation

To ensure that the installed tree is usable by the right group of users, set `umask` appropriately (perhaps to ‘022’) before unpacking the sources and throughout the build process.

```
After
    ./configure
    make
```

³ Debian/Ubuntu use a rather old version of TeXLive and so need Debian package ‘`texlive-fonts-extra`’ installed.

```
make check
```

(or, when building outside the source, `TOP_SRCDIR/configure`, etc) have been completed successfully, you can install the complete R tree to your system by typing

```
make install
```

A parallel make can be used (but run `make all` first).

This will install to the following directories:

`'prefix/bin'` or `'bindir'`

the front-end shell script and other scripts and executables

`'prefix/man/man1'` or `'mandir/man1'`

the man page

`'prefix/LIBnn/R'` or `'libdir/R'`

all the rest (libraries, on-line help system, ...). Here *LIBnn* is usually `'lib'`, but may be `'lib64'` on some 64-bit Linux systems. This is known as the R home directory.

where *prefix* is determined during configuration (typically `'/usr/local'`) and can be set by running `configure` with the option `'--prefix'`, as in

```
./configure --prefix=/where/you/want/R/to/go
```

This causes `make install` to install the R script to `'/where/you/want/R/to/go/bin'`, and so on. The prefix of the installation directories can be seen in the status message that is displayed at the end of `configure`. You can install into another directory tree by using

```
make prefix=/path/to/here install
```

at least with GNU `make` (and current Solaris and FreeBSD `make`, but not some older Unix makes).

More precise control is available at configure time via options: see `configure --help` for details. (However, most of the 'Fine tuning of the installation directories' options are not used by R.)

Configure options `'--bindir'` and `'--mandir'` are supported and govern where a copy of the R script and the man page are installed.

The configure option `'--libdir'` controls where the main R files are installed: the default is `'eprefix/LIBnn'`, where *eprefix* is the prefix used for installing architecture-dependent files, defaults to *prefix*, and can be set via the configure option `'--exec-prefix'`.

Each of `bindir`, `mandir` and `libdir` can also be specified on the `make install` command line (at least for GNU `make`).

The `configure` or `make` variables `rdocdir` and `rsharedir` can be used to install the system-independent `'doc'` and `'share'` directories to somewhere other than `libdir`. The C header files can be installed to the value of `rincludedir`: note that as the headers are not installed into a subdirectory you probably want something like `rincludedir=/usr/local/include/R-2.15.0`.

If you want the R home to be something other than `'libdir/R'`, use `'rhome'`: for example

```
make install rhome=/usr/local/lib64/R-2.15.0
```

will use a version-specific R home on a Linux 64-bit system.

If you have made R as a shared/dynamic library you can install it in your system's library directory by

```
make prefix=/path/to/here install-libR
```

where `prefix` is optional, and `libdir` will give more precise control.

```
make install-strip
```

will install stripped executables, and on platforms where this is supported, stripped libraries in directories 'lib' and 'modules' and in the standard packages.

Note that installing R into a directory whose path contains spaces is not supported, and at least some aspects (such as installing source packages) will not work.

To install info and PDF versions of the manuals, use one or more of

```
make install-info
```

```
make install-pdf
```

Once again, it is optional to specify `prefix`, `libdir` or `rhome` (the PDF manuals are installed under the R home directory). (`make install-info` needs Perl installed if there is no command `install-info` on the system.)

More precise control is possible. For info, the setting used is that of `infodir` (default '`prefix/info`', set by configure option '`--infodir`'). The PDF files are installed into the R 'doc' tree, set by the `make` variable `rdocdir`.

A staged installation is possible, that it is installing R into a temporary directory in order to move the installed tree to its final destination. In this case `prefix` (and so on) should reflect the final destination, and `DESTDIR` should be used: see http://www.gnu.org/prep/standards/html_node/DESTDIR.html.

You can optionally install the run-time tests that are part of `make check-all` by

```
make install-tests
```

which populates a 'tests' directory in the installation.

2.5 Uninstallation

You can uninstall R by

```
make uninstall
```

optionally specifying `prefix` etc in the same way as specified for installation.

This will also uninstall any installed manuals. There are specific targets to uninstall info and PDF manuals in file '`doc/manual/Makefile`'.

Target `uninstall-tests` will uninstall any installed tests, as well as removing the directory 'tests' containing the test results.

2.6 Sub-architectures

Some platforms can support closely related builds of R which can share all but the executables and dynamic objects. Examples include builds under Solaris for different chips (in particular, 32- and 64-bit builds), 64- and 32- bit builds on 'x86_64' Linux and different CPUs (e.g. 'ppc', 'i386' and 'x86_64') under (Mac) OS X >= 10.4.

R supports the idea of architecture-specific builds, specified by adding `'r_arch=name'` to the `configure` line. Here *name* can be anything non-empty, and is used to name subdirectories of `'lib'`, `'etc'`, `'include'` and the package `'libs'` subdirectories. Example names from other systems are the use of `'sparcv9'` on Sparc Solaris and `'32'` by `gcc` on `'x86_64'` Linux.

If you have two or more such builds you can install them over each other (and for 32/64-bit builds on one architecture, one build can be done without `'r_arch'`). The space savings can be considerable: on `'x86_64'` Linux a basic install (without debugging symbols) took 63Mb, and adding a 32-bit build added 6Mb. If you have installed multiple builds you can select which build to run by

```
R --arch=name
```

and just running `'R'` will run the last build that was installed.

R CMD INSTALL will detect if more than one build is installed and try to install packages with the appropriate library objects for each. This will not be done if the package has an executable `configure` script or a `'src/Makefile'` file. In such cases you can install for extra builds by

```
R --arch=name CMD INSTALL --libs-only pkg1 pkg2 ...
```

If you want to mix sub-architectures compiled on different platforms (for example `'x86_64'` Linux and `'i686'` Linux), it is wise to use explicit names for each, and you may also need to set `'libdir'` to ensure that they install into the same place.

When sub-architectures are used the version of `Rscript` in e.g. `'/usr/bin'` will be the last installed, but architecture-specific versions will be available in e.g. `'/usr/lib64/R/bin/exec${R_ARCH}'`. Normally all installed architectures will run on the platform so the architecture of `Rscript` itself does not matter. The executable `Rscript` will run the R script, and at that time the setting of the `R_ARCH` environment variable determines the architecture which is run.

When running post-install tests with sub-architectures, use

```
R --arch=name CMD make check[-devel|all]
```

to select a sub-architecture to check.

Sub-architectures are also used on Windows, but by selecting executables within the appropriate `'bin'` directory, `'R_HOME/bin/i386'` or `'R_HOME/bin/x64'`. For backwards compatibility with R < 2.12.0, there are executables `'R_HOME/bin/R.exe'` or `'R_HOME/bin/Rscript.exe'`: these will run an executable from one of the subdirectories, which one being taken first from the `R_ARCH` environment variable, then from the `'--arch'` command-line option⁴ and finally from the installation default (which is 32-bit for a combined 32/64 bit R installation).

2.6.1 Multilib

On Linux⁵, there is an alternative mechanism for mixing 32-bit and 64-bit libraries known as *multilib*. If a Linux distribution supports multilib, then parallel builds of R may be installed in the sub-directories `'lib'` (32-bit) and `'lib64'` (64-bit). The build to be run may then be chosen using the `setarch` command. For example, a 32-bit build may be chosen by

⁴ with possible values `'i386'`, `'x64'`, `'32'` and `'64'`.

⁵ mainly on RedHat and Fedora, whose layout is described here.

```
setarch i686 R
```

The `setarch` command is only operational if both 32-bit and 64-bit builds are installed. If there is only one installation of R, then this will always be run regardless of the architecture specified by the `setarch` command.

There can be problems with installing packages on the non-native architecture. It is a good idea to run e.g. `setarch i686 R` for sessions in which packages are to be installed, even if that is the only version of R installed (since this tells the package installation code the architecture needed).

At present there is a potential problem with packages using Java, as the post-install for a ‘i386’ RPM on ‘x86_64’ Linux reconfigures Java and will find the ‘x86_64’ Java. If you know where a 32-bit Java is installed you may be able to run (as root)

```
export JAVA_HOME=<path to jre directory of 32-bit Java>
setarch i686 R CMD javareconf
```

to get a suitable setting.

When this mechanism is used, the version of `Rscript` in e.g. ‘`/usr/bin`’ will be the last installed, but an architecture-specific version will be available in e.g. ‘`/usr/lib64/R/bin`’. Normally all installed architectures will run on the platform so the architecture of `Rscript` does not matter.

2.7 Other Options

There are many other installation options, most of which are listed by `configure --help`. Almost all of those not listed elsewhere in this manual are either standard `autoconf` options not relevant to R or intended for specialist uses by the R developers.

One that may be useful when working on R itself is the option ‘`--disable-byte-compiled-packages`’, which ensures that the base and recommended packages are lazyloaded but not byte-compiled. (Alternatively the (make or environment) variable `R_NO_BASE_COMPILE` can be set to a non-empty value for the duration of the build.)

2.7.1 Inter-Procedure Optimization

In a conventional build system each C/Fortran source file is compiled and optimized separately. A trend in modern compilers is to carry optimization across source files: this has been done in commercial compilers for some time.

GCC introduced a version of inter-procedure optimization in version 4.5.0, which it calls *link-time optimization*. This writes an intermediate representation in the ‘.o’ file, and then the linker combines those intermediate representations and re-compiles with optimization the combined representation. Support for LTO is still evolving: it is available for ELF-based systems and more recently for PE_COFF (Windows): only on some platforms⁶ can objects in static libraries be included in the link-time optimization.

Link-time optimization roughly doubles the compilation time and increases the size of the ‘.o’ files (but not the installed ‘.so’ and executable files).

Link-time optimization can be enabled by the `configure` option ‘`--enable-lto`’: no check is made that the compiler/linker support it. In experiments with `gcc` 4.5.x on Linux

⁶ For those using GNU `binutils`, where `gold` is used as the linker: this might be enabled when `gcc` was built or selected *via* the `alternatives` mechanism.

the performance gain was very small (mainly seen with ‘`--enable-R-shlib`’), but this may not be so with later compilers or other platforms.

Setting ‘`--enable-lto=R`’ enables LTO for building R itself but not for extension packages (including the recommended packages).

2.8 Testing an Installation

Full testing is possible only if the test files have been installed with

```
make install-tests
```

which populates a ‘`tests`’ directory in the installation.

If this has been done, two testing routes are available. The first is to move to the home directory of the R installation (as given by `R.home()`) and run

```
cd tests
## followed by one of
../bin/R CMD make check
../bin/R CMD make check-devel
../bin/R CMD make check-all
```

and other useful targets are `test-BasePackages` and `test-Recommended` to the run tests of the standard and recommended packages (if installed) respectively.

This re-runs all the tests relevant to the installed R (including for example code in the package vignettes), but not for example the ones checking the example code in the manuals nor making the standalone Rmath library. This can occasionally be useful when the operating environment has been changed, for example by OS updates or by substituting the BLAS (see [Section A.3.1.5 \[Shared BLAS\]](#), page 43).

Alternatively, the installed R can be run, preferably with ‘`--vanilla`’. Then

```
library("tools")
testInstalledBasic("both")
testInstalledPackages(scope = "base")
testInstalledPackages(scope = "recommended")
```

runs the basic tests and then all the tests on the standard and recommended packages. These tests can be run from anywhere: the basic tests write their results in the ‘`tests`’ folder of the R home directory and run slightly fewer tests than the first approach: in particular they do not test Internet access.

These tests work best if `diff` (in ‘`Rtools*.exe`’ for Windows users) is in the path, and on some systems need the collation locale set manually (the R code tries to do so but it may not be possible to reset it): so if needed try setting the environment variable `LC_COLLATE` to ‘`C`’ before starting R.

It is possible to test the installed packages (but not the package-specific tests) by `testInstalledPackages` even if `make install-tests` was not run.

Note that the results may depend on the language set for times and messages: for maximal similarity to reference results you may want to try setting

```
LANGUAGE=en LC_TIME=C
```


3 Installing R under Windows

The current version of pqR has not been tested under Windows. There is no known reason why it shouldn't work, but there has likely been some change that will cause problems. This section is retained for future reference once this has been remedied. It applies at present only to R-2.15.0, not to pqR.

The `'bin/windows'` directory of a CRAN site contains binaries for a base distribution and a large number of add-on packages from CRAN to run on Windows XP or later on ix86 CPUs (including AMD64/Intel64¹ chips and Windows x64).

Your file system must allow long file names (as is likely except perhaps for some network-mounted systems).

Installation is *via* the installer `'R-2.15.0-win.exe'`. Just double-click on the icon and follow the instructions. When installing on a 64-bit version of Windows the options will include 32- or 64-bit versions of R (and the default is to install both). You can uninstall R from the Control Panel.

Note that you will be asked to choose a language for installation, and that choice applies to both installation and un-installation but not to running R itself.

See the [R Windows FAQ](#) for more details on the binary installer.

3.1 Building from source

R can be built as either a 32-bit or 64-bit application on Windows: to build the 64-bit application you need a 64-bit edition of Windows: such an OS can also be used to build 32-bit R.

The standard installer combines 32-bit and 64-bit builds into a single executable which can then be installed into the same location and share all the files except the `'.exe'` and `'.dll'` files and some configuration files in the `'etc'` directory.

3.1.1 Getting the tools

If you want to build R from the sources, you will first need to collect, install and test an extensive set of tools. See [Appendix D \[The Windows toolset\]](#), [page 64](#) (and perhaps updates in <http://cran.r-project.org/bin/windows/Rtools/>) for details.

The `'Rtools*.exe'` executable installer described in [Appendix D \[The Windows toolset\]](#), [page 64](#) also includes some source files in addition to the R source as noted below. You should run it first, to obtain a working `tar` and other necessities. Choose a “Full installation”, and install the extra files into your intended R source directory, e.g. `'C:/R'`. The directory name *should not contain spaces*. We will call this directory `'R_HOME'` below.

The toolchain used as from R 2.14.2 differs from from that used for R 2.12.0 to R 2.14.1.

3.1.2 Getting the source files

You need to collect the following sets of files:

- Get the R source code tarball `'R-2.15.0.tar.gz'` from CRAN. Open a command window (or another shell) at directory `R_HOME`, and run

¹ formerly known as EM64T.

```
tar -xf R-2.15.0.tar.gz
```

to create the source tree in *R_HOME*. **Beware:** do use `tar` to extract the sources rather than tools such as WinZip that do not understand symbolic links. If you are using an account with administrative privileges you may get a lot of messages which can be suppressed by

```
tar --no-same-owner -xf R-2.15.0.tar.gz
```

or perhaps better, set the environment variable `TAR_OPTIONS` to the value `'--no-same-owner --no-same-permissions'`.

It is also possible to obtain the source code using Subversion; see [Chapter 1 \[Obtaining pqR and R\], page 1](#) for details.

- If you are not using a tarball you need to obtain copies of the recommended packages from CRAN. Put the `.tar.gz` files in `'R_HOME/src/library/Recommended'` and run `make link-recommended`. If you have an Internet connection, you can do this automatically by running in `'R_HOME/src/gnuwin32'`

```
make rsync-recommended
```

The following additional items are normally installed by `'Rtools215.exe'`. If instead you choose to do a completely manual build you will also need

- The Tcl/Tk support files are contained in `'Rtools215.exe'` and available as `.zip`'s from <http://www.stats.ox.ac.uk/pub/Rtools>. Please make sure you install the right version: there is a 32-bit version and a 64-bit version.
- You need `libpng`, `jpeg` and `libtiff` sources (available, e.g., from <http://www.libpng.org/>, <http://www.ijg.org> and <http://download.osgeo.org/libtiff/>). The earliest versions that have been tested are `'libpng-1.5.4.tar.gz'`, `'jpegsrc.v8c.tar.gz'`, `'tiff-3.9.4.tar.gz'` (including betas of `'tiff-4.0.0'`). It is also possible to use `'libjpeg-turbo'` from <http://sourceforge.net/projects/libjpeg-turbo/files/>.

Working in the directory `'R_HOME/src/gnuwin32/bitmap'`, install the `libpng` and `jpeg` sources in sub-directories. The `jpeg` sub-directory for version 8c is named `'jpeg-8c'`; if you use a different version (e.g. `'jpeg-7'` or `'libjpeg-turbo'`), copy file `'src/gnuwin32/MkRules.dist'` to `'src/gnuwin32/MkRules.local'` and edit the definition of `JPEGDIR`: the names of the `'libpng'` and `'libtiff'` directories can also be set there.

Example:

```
> tar -zxf libpng-1.5.5.tar.gz
> mv libpng-1.5.5 libpng
> tar -zxf jpegsrc.v8c.tar.gz
> tar -zxf tiff-3.9.5.tar.gz
> mv tiff-3.9.5/libtiff .
> rm -rf tiff-3.9.5
```

(and see the comment above about `'--no-same-owner'`).

3.1.3 Building the core files

Set the environment variable `TMPDIR` to point to a writable directory, with a path specified with forward slashes and no spaces. (The default is `/tmp`, which may not be useful on Windows.)

You may need to compile under a case-honouring file system: we found that a `samba`-mounted file system (which maps all file names to lower case) did not work.

Open a command window at `'R_HOME/src/gnuwin32'`. Look at `'MkRules.dist'` and if settings need to be altered, copy it to `'MkRules.local'` and edit the settings there. In particular, this is where a 64-bit build is selected. Then run

```
make all recommended
```

and sit back and wait while the basic compile takes place.

Notes:

- We have had reports that earlier versions of anti-virus software locking up the machine, but not for several years. However, aggressive anti-virus checking such as the on-access scanning of Sophos can slow the build down several-fold.
- By default Doug Lea's `malloc` in the file `'R_HOME/src/gnuwin32/malloc.c'` is used for R's internal memory allocations. You can opt out of this by setting `LEA_MALLOC=NO` in `'MkRules.dist'`, in which case the `malloc` in `'msvcrt.dll'` is used. This does impose a considerable performance penalty and has not been tested recently.
- You can run a parallel make by e.g.

```
make -j4 all
make -j4 recommended
```

but this is only likely to be worthwhile on a multi-core machine with ample memory, and is not 100% reliable.

- It is possible (mainly for those working on R itself) to set the (make or environment) variable `R_NO_BASE_COMPILE` to a non-empty value, which inhibits the byte-compilation of the base and recommended packages.

3.1.4 Building the bitmap files

The file `'R_HOME/library/grDevices/libs/{i386,x64}Rbitmap.dll'` is not built automatically.

Running `make` in `'R_HOME/src/gnuwin32/bitmap'` or `make bitmapdll` in `'R_HOME/src/gnuwin32'` should build `'Rbitmap.dll'` and install it under `'R_HOME/library/grDevices/libs'`.

3.1.5 Building the cairo devices

The devices based on cairographics (`svg`, `cairo_pdf`, `cairo_ps` and the `type = "cairo"` versions of `png`, `jpeg`, `tiff` and `bmp`) are implemented in a separate DLL `'winCairo.dll'` which is loaded when one of these devices is first used. It is not built by default, and needs to be built after `'Rbitmap.dll'`, by `make cairodevices`.

To enable the building of these devices you need to install the static cairographics libraries built by Simon Urbanek at <http://www.rforge.net/Cairo/files/cairo-current-win.tar.gz>. Set the macro `'CAIRO_HOME'` in `'MkRules.local'`. (Note that this tarball unpacks with a top-level directory `'src/':` `'CAIRO_HOME'` needs to include that directory in its path.)

3.1.6 Checking the build

You can test a build by running

```
make check
```

The recommended packages can be checked by

```
make check-recommended
```

Other levels of checking are

```
make check-devel
```

for a more thorough check of the R functionality, and

```
make check-all
```

for `check-devel` and `check-recommended`.

3.1.7 Building the manuals

The PDF manuals can be made by

```
make manuals
```

If you want to make the info versions (not including the Reference Manual), use

```
cd ../../doc/manual
make -f Makefile.win info
```

(all assuming you have `pdftex`/`pdflatex` installed and in your path).

See the [Section 2.3 \[Making the manuals\]](#), page 5 section in the Unix-alike section for setting options such as the paper size and the fonts used.

3.1.8 Building the Inno Setup installer

You need to have the files for a complete R build, including bitmap and Tcl/Tk support and the manuals, as well as the recommended packages and Inno Setup (see [Section D.2 \[The Inno Setup installer\]](#), page 65).

Once everything is set up

```
make distribution
make check-all
```

will make all the pieces and the installers and put them in the ‘`gnuwin32/cran`’ subdirectory, then check the build. This works by building all the parts in the sequence:

```
rbuild (the executables, the FAQ docs etc.)
rpackage (the base packages)
htmldocs (the HTML documentation)
bitmapdll (the bitmap support files)
cairodevices (the cairo-based graphics devices)
recommended (the recommended packages)
vignettes (the vignettes in package grid:
  only needed if building from an svn checkout)
manuals (the PDF manuals)
rinstaller (the install program)
crandir (the CRAN distribution directory, only for 64-bit builds)
```

The parts can be made individually if a full build is not needed, but earlier parts must be built before later ones. (The ‘`Makefile`’ doesn’t enforce this dependency—some build

targets force a lot of computation even if all files are up to date.) The first four targets are the default build if just `make` (or `make all`) is run.

If you want to customize the installation by adding extra packages, replace `make rinstaller` by something like

```
make rinstaller EXTRA_PKGS='pkg1 pkg2 pkg3'
```

An alternative way to customize the installer starting with a binary distribution is to first make a full installation of R from the standard installer (that is, select ‘Full Installation’ from the ‘Select Components’ screen), then add packages and make other customizations to that installation. Then (after having customized file ‘MkRules’, possibly *via* ‘MkRules.local’, and having made R in the source tree) in ‘src/gnuwin32/installer’ run

```
make myR IMAGEDIR=rootdir
```

where ‘rootdir’ is the path to the root of the customized installation (in double quotes if it contains spaces or backslashes).

Both methods create an executable with a standard name such as ‘R-2.15.0-win.exe’, so please rename it to indicate that it is customized. If you intend to *distribute* a customized installer please do check that license requirements are met – note that the installer will state that the contents are distributed under GPL-2 and this has a requirement for *you* to supply the complete sources (including the R sources even if you started with a binary distribution of R, and also the sources of any extra packages (including their external software) which are included).

The defaults for the startup parameters may also be customized. For example

```
make myR IMAGEDIR=rootdir MDISDI=1
```

will create an installer that defaults to installing R to run in SDI mode. See ‘src/gnuwin32/installer/Makefile’ for the names and values that can be set.

The standard CRAN distribution of a 32/64-bit installer is made by first building 32-bit R (just

```
make 32-bit
```

is needed), and then building 64-bit R with the macro `HOME32` set in file ‘MkRules.local’ to the top-level directory of the 32-bit build. Then the `make rinstaller` step copies the files that differ between architectures from the 32-bit build as it builds the installer image.

3.1.9 Building the MSI installer

It is also possible to build an installer for use with Microsoft Installer. This is intended for use by sysadmins doing automated installs, and is not recommended for casual use.

It makes use of the Windows Installer XML (WiX) toolkit *version 3.0 or 3.5* available from <http://wix.sourceforge.net/>. Once WiX is installed, set the path to its home directory in ‘MkRules.local’.

You need to have the files for a complete R build, including bitmap and Tcl/Tk support and the manuals, as well as the recommended packages. There is no option in the installer to customize startup options, so edit ‘etc/Rconsole’ and ‘etc/Rprofile.site’ to set these as required. Then

```
cd installer
make msi
```

which will result in a file with a name like ‘R-2.15.0-win32.msi’. This can be double-clicked to be installed, but those who need it will know what to do with it (usually by running `msiexec /i` with additional options). Properties that users might want to set from the `msiexec` command line include ‘ALLUSERS’, ‘INSTALLDIR’ (something like ‘c:\Program Files\R\R-2.15.0’) and ‘RMENU’ (the path to the ‘R’ folder on the start menu) and ‘STARTDIR’ (the starting directory for R shortcuts, defaulting to something like ‘c:\Users\name\Documents\R’).

The MSI installer can be built both from a 32-bit build of R (‘R-2.15.0-win32.msi’) and from a 64-bit build of R (‘R-2.15.0-win64.msi’, optionally including 32-bit files by setting the macro `HOME32`, when the name is ‘R-2.15.0-win.msi’). Unlike the main installer, a 64-bit MSI installer can only be run on 64-bit Windows.

Thanks to David del Campo (Dept of Statistics, University of Oxford) for suggesting WiX and building a prototype installer.

3.1.10 Cross-building on Linux

Support for cross-building was withdrawn at R 2.9.0.

3.1.11 64-bit Windows builds

To build a 64-bit version of R you need a 64-bit toolchain: the only one discussed here is based on the work of the MinGW-w64 project (<http://sourceforge.net/projects/mingw-w64/>), but commercial compilers such as those from Intel and PGI could be used (and have been by R redistributors).

Support for MinGW-w64 was developed in the R sources over the period 2008–10 and was first released as part of R 2.11.0. The assistance of Yu Gong at a crucial step in porting R to MinGW-w64 is gratefully acknowledged, as well as help from Kai Tietz, the lead developer of the MinGW-w64 project.

Windows 64-bit is now completely integrated into the R and package build systems.

3.2 Testing an Installation

The Windows installer contains a set of test files used when building R. These are an optional part of the installation, and if it is desired to run tests on the installation these should be selected as well as the help source files (perhaps most easily by doing a ‘Full Installation’).

The `Rtools` are not needed to run these tests. but more comprehensive analysis of errors will be given if `diff` is in the path.

Once this has been done, launch either `Rgui` or `Rterm`, preferably with ‘--vanilla’. Then

```
library("tools")
testInstalledBasic("both")
testInstalledPackages("base")
testInstalledPackages("recommended")
```

runs the basic tests and then all the tests on the standard and recommended packages. These tests can be run from anywhere: they write their results in the ‘**tests**’ folder of the R home directory (as given by `R.home()`).

4 Installing R under (Mac) OS X

The current version of pqR has not been tested under OS X. There is no known reason why it shouldn't work, but there has likely been some change that will cause problems. This section is retained for future reference once this has been remedied. It applies at present only to R-2.15.0, not to pqR.

The `'bin/macosx'` directory of a CRAN site contains binaries for OS X for a base distribution and a large number of add-on packages from CRAN to run on OS X 10.[567].

The simplest way is to use `'R-2.15.0.pkg'`: just double-click on the icon. Note that Tcl/Tk and the Fortran compiler need to be installed separately if needed.

See the [R for Mac OS X FAQ](#) for more details.

4.1 Building from source on (Mac) OS X

If you want to build this port from the sources, you should read the R for Mac OS X FAQ for full details. You will need to collect and install some tools as explained in that document. Then you have to unpack the R sources and configure R appropriately, for example

```
tar -zxvf R-2.15.0.tar.gz
cd R-2.15.0
./configure --with-blas='-framework vecLib' --with-lapack \
  --with-aqua --enable-R-framework
make
```

and then sit back and wait. The first two options are the default and use the BLAS and LAPACK built into OS X. This has pros and cons: it used to be faster (but has not been on some recent multicore hardware) but less accurate.

The second line of options are also default on OS X, but needed only if you want to build R for use with R.app Console, and imply `'--enable-R-shlib'` to build R as a shared/dynamic library. These options configure R to be built and installed as a framework called `'R.framework'`. The default installation path for `'R.framework'` is `'/Library/Frameworks'` but this can be changed at configure time by specifying the flag `'--enable-R-framework[=DIR]'` or at install time as

```
make prefix=/where/you/want/R.framework/to/go install
```

(the final `'R.framework'` directory should not be included in the path).

For compatibility with the CRAN distribution you may need to specify `'--with-included-gettext'` to avoid linking against a `'libintl'` dynamic library you may have available, for example in `'/usr/local/lib'`.

Note that building the `'R.app'` GUI console is a separate project: see the OS X FAQ for details.

5 Running R

How to start R and what command-line options are available is discussed in [Section “Invoking R”](#) in *An Introduction to R*.

You should ensure that the shell has set adequate resource limits: R expects a stack size of at least 8MB and to be able to open at least 256 file descriptors. (Any modern OS will have default limits at least as large as these, but apparently NetBSD does not. Use the shell command `ulimit (sh/bash)` or `limit (csh/tcsh)` to check.)

R makes use of a number of environment variables, the default values of many of which are set in file `'R_HOME/etc/Renviron'` (there are none set by default on Windows and hence no such file). These are set at `configure` time, and you would not normally want to change them – a possible exception is `R_PAPERSIZE` (see [Section B.4.1 \[Setting paper size\]](#), [page 47](#)). The paper size will be deduced from the `'LC_PAPER'` locale category if it exists and `R_PAPERSIZE` is unset, and this will normally produce the right choice from `'a4'` and `'letter'` on modern Unix-alikes (but can always be overridden by setting `R_PAPERSIZE`).

Various environment variables can be set to determine where R creates its per-session temporary directory. The environment variables `TMPDIR`, `TMP` and `TEMP` are searched in turn and the first one which is set and points to a writable area is used. If none do, the final default is `'/tmp'` on Unix-alikes and the value of `R_USER` on Windows.

Some Unix-alike systems are set up to remove files and directories periodically from `'/tmp'`, for example by a `cron` job running `tmpwatch`. Set `TMPDIR` to another directory before running long-running jobs on such a system.

Note that `TMPDIR` will be used to execute `configure` scripts when installing packages, so if `'/tmp'` has been mounted as `'noexec'`, `TMPDIR` needs to be set to a directory from which execution is allowed.

6 Add-on packages

It is helpful to use the correct terminology. A *package* is loaded from a *library* by the function `library()`. Thus a library is a directory containing installed packages; the main library is `'R_HOME/library'`, but others can be used, for example by setting the environment variable `R_LIBS` or using the R function `.libPaths()`.

6.1 Default packages

The set of packages loaded on startup is by default

```
> getOption("defaultPackages")
[1] "datasets" "utils"      "grDevices" "graphics"  "stats"      "methods"
```

(plus, of course, **base**) and this can be changed by setting the option in startup code (e.g. in `'~/Rprofile'`). It is initially set to the value of the environment variable `R_DEFAULT_PACKAGES` if set (as a comma-separated list). Setting `R_DEFAULT_PACKAGES=NULL` ensures that only package **base** is loaded.

Changing the set of default packages is normally used to reduce the set for speed when scripting: in particular not using **methods** will reduce the start-up time by a factor of up to two (and this is done by `Rscript`). But it can also be used to customize R, e.g. for class use.

6.2 Managing libraries

R packages are installed into *libraries*, which are directories in the file system containing a subdirectory for each package installed there.

R comes with a single library, `'R_HOME/library'` which is the value of the R object `'.Library'` containing the standard and recommended¹ packages. Both sites and users can create others and make use of them (or not) in an R session. At the lowest level `'.libPaths()'` can be used to add paths to the collection of libraries or to report the current collection.

R will automatically make use of a site-specific library `'R_HOME/site-library'` if this exists (it does not in a vanilla R installation). This location can be overridden by setting² `'.Library.site'` in `'R_HOME/etc/Rprofile.site'`, or (not recommended) by setting the environment variable `R_LIBS_SITE`. Like `'.Library'`, the site libraries are always included by `'.libPaths()'`.

Users can have one or more libraries, normally specified by the environment variable `R_LIBS_USER`. This has a default value (use `'Sys.getenv("R_LIBS_USER")'` within an R session to see what it is), but only is used if the corresponding directory actually exists (which by default it will not).

Both `R_LIBS_USER` and `R_LIBS_SITE` can specify multiple library paths, separated by colons (semicolons on Windows).

¹ unless they were excluded in the build.

² its binding is locked once that files has been read, so users cannot easily change it.

6.3 Installing packages

Packages may be distributed in source form or compiled binary form. Installing source packages which contain C/C++/Fortran code requires that compilers and related tools be installed. Binary packages are platform-specific and generally need no special tools to install, but see the documentation for your platform for details.

Note that you may need to specify implicitly or explicitly the library to which the package is to be installed. This is only an issue if you have more than one library, of course.

If installing packages on a Unix-alike to be used by other users, ensure that the system `umask` is set to give sufficient permissions (see also `Sys.umask` in R). (To a large extent this is unnecessary in recent versions of R, which install packages as if `umask = 022`.)

For most users it suffices to call `'install.packages(pkgname)'` or its GUI equivalent if the intention is to install a CRAN package and internet access is available.³ On most systems `'install.packages()'` will allow packages to be selected from a list box.

To install packages from source in a Unix-alike use

```
R CMD INSTALL -l /path/to/library pkg1 pkg2 ...
```

The part `'-l /path/to/library'` can be omitted, in which case the first library of a normal R session is used (that shown by `.libPaths()[1]`).

Ensure that the environment variable `TMPDIR` is either unset (and `'/tmp'` exists and can be written in and executed from) or points to a valid temporary directory.

There are a number of options available: use `R CMD INSTALL --help` to see the current list.

Alternatively, packages can be downloaded and installed from within R. First set the option `CRAN` to your nearest CRAN mirror using `chooseCRANmirror()`. Then download and install packages `pkg1` and `pkg2` by

```
> install.packages(c("pkg1", "pkg2"))
```

The essential dependencies of the specified packages will also be fetched. Unless the library is specified (argument `lib`) the first library in the library search path is used: if this is not writable, R will ask the user (in an interactive session) if the default user library should be created, and if allowed to will install the packages there.

If you want to fetch a package and all those it depends on (in any way) that are not already installed, use e.g.

```
> install.packages("Rcmdr", dependencies = TRUE)
```

`install.packages` can install a source package from a local `'tar.gz'` file by setting argument `repos` to `NULL`: this will be selected automatically if the name given is a single `'tar.gz'` file.

`install.packages` can look in several repositories, specified as a character vector by the argument `repos`: these can include a CRAN mirror, Bioconductor, Omegahat, R-forge, local archives, local files, ...). Function `setRepositories()` can select amongst those repositories that the R installation is aware of.

Naive users sometimes forget that as well as installing a package, they have to use `library` to make its functionality available.

³ If a proxy needs to be set, see `?download.file`.

6.3.1 Windows

What `install.packages` does by default is different on Unix-alikes (except OS X) and Windows. On Unix-alikes it consults the list of available *source* packages on CRAN (or other repository/ies), downloads the latest version of the package sources, and installs them (via R CMD INSTALL). On Windows it looks (by default) at the list of *binary* versions of packages available for your version of R and downloads the latest versions (if any), although optionally it will also download and install a source package by setting the `type` argument.

On Windows `install.packages` can also install a binary package from a local ‘zip’ file by setting argument `repos` to `NULL`. `Rgui.exe` has a menu **Packages** with a GUI interface to `install.packages`, `update.packages` and `library`.

Windows binary packages for R are nowadays distributed as a single binary containing either or both architectures.

A few of the binary packages need other software to be installed on your system: see for example <http://cran.r-project.org/bin/windows/contrib/2.14/@ReadMe>. For 64-bit builds, packages using Gtk+ (**Cairo**, **RGtk2**, **cairoDevice** and those that depend on them) need the ‘bin’ directory of a bundled distribution from <http://www.gtk.org/download-windows-64bit.html> in the path: it should work to have both Gtk+ ‘bin’ directories in the path on a 64-bit version of R.

R CMD INSTALL works in Windows to install source packages if you have set up the tools needed (see [Appendix D \[The Windows toolset\]](#), page 64). No additional tools are needed if the package does not contain compiled code, and `install.packages(type="source")` will work for such packages (and for those with compiled code if the tools are in the path).

We have seen occasional permission problems after unpacking source packages on some Vista/Windows 7/Server 2008 systems: these have been circumvented by setting the environment variable `R_INSTALL_TAR` to ‘tar.exe’.

If you have only a source package that is known to work with current R and just want a binary Windows build of it, you could make use of the building service offered at <http://win-builder.r-project.org/>.

For almost all packages R CMD INSTALL will attempt to install both 32- and 64-bit builds of a package if run from a 32/64-bit install of R on a 64-bit version of Windows. It will report success if the installation of the architecture of the running R succeeded, whether or not the other architecture was successfully installed.

The exceptions are packages with a non-empty ‘configure.win’ script or which make use of ‘src/Makefile.win’. If ‘configure.win’ does something appropriate to both architectures use⁴ option ‘--force-biarch’: otherwise R CMD INSTALL --merge-multiarch can be applied to a source tarball to merge separate 32- and 64-bit installs. (This can only be applied to a tarball, and will only succeed if both installs succeed.)

If you have a package without compiled code and no Windows-specific help, you can zip up an installation on another OS and install from the that zip file on Windows. However, such a package can be installed from the sources on Windows without any additional tools.

⁴ for a small number of CRAN packages where this is known to be safe and is needed by the autobuilder this is the default. Look at the source of ‘tools:::install_packages’ for the list.

6.3.2 OS X

On OS X `install.packages` works as it does on other Unix-alike systems, but there are additional types `mac.binary*` (the default in the CRAN distribution) that can be passed to `install.packages` in order to download and install binary packages from a suitable repository, and type `mac.binary.leopard` is the default for CRAN builds of R. These OS X binary package files have the extension ‘`tgz`’. The R.app GUI provides for installation of either binary or source packages, from CRAN or local files.

6.3.3 Customizing package compilation

The R system and package-specific compilation flags can be overridden or added to by setting the appropriate Make variables in the personal file ‘`HOME/.R/Makevars-R_PLATFORM`’ (but ‘`HOME/.R/Makevars.win`’ or ‘`HOME/.R/Makevars.win64`’ on Windows), or if that does not exist, ‘`HOME/.R/Makevars`’, where ‘`R_PLATFORM`’ is the platform for which R was built, as available in the `platform` component of the R variable `R.version`.

Package developers are encouraged to use this mechanism to enable a reasonable amount of diagnostic messaging (“warnings”) when compiling, such as e.g. ‘`-Wall -pedantic`’ for tools from GCC, the Gnu Compiler Collection.

Note that this mechanism can also be used when it necessary to change the optimization level for a particular package. For example

```
## for C code
CFLAGS=-g -O
## for C++ code
CXXFLAGS=-g -O
## for Fortran code
FFLAGS=-g -O
## for Fortran 95 code
FCFLAGS=-g -O
```

There is also provision for a site-wide ‘`Makevars.site`’ file under ‘`R_HOME/etc`’ (in a sub-architecture-specific directory if appropriate). This is read immediately after ‘`Makeconf`’.

6.3.4 Multiple sub-architectures

When installing packages from their sources, there are some extra considerations on installations which use sub-architectures. These are commonly used on (Mac) OS X and Windows, but can in principle be used on other platforms.

When a source package is installed by a build of R which supports multiple sub-architectures, the normal installation process installs the packages for all sub-architectures, but only tests it can be loaded under the current sub-architecture. The exceptions are

Unix-alikes

where there is an ‘`configure`’ script, or a file ‘`src/Makefile`’.

Windows

where there is a non-empty ‘`configure.win`’ script, or a file ‘`src/Makefile.win`’ (with some exceptions where the package is known to have an architecture-independent ‘`configure.win`’, or if ‘`--force-biarch`’ is used to assert so).

In those cases only the current architecture is installed. Further sub-architectures can be installed by

```
R CMD INSTALL --libs-only pkg
```

using the path to R or `R --arch` to select the additional sub-architecture. On Windows there is also `R CMD INSTALL --merge-multiarch` to build and merge the two architectures, starting with a source tarball.

6.3.5 Byte-compilation

As from R 2.14.0 the base and recommended packages are byte-compiled by default. Other packages can be byte-compiled on installation by using the option ‘`--byte-compile`’ with `R CMD INSTALL` or with `install.packages(type = "source")`.

Not all contributed packages work correctly when byte-compiled (for example because they interfere with the sealing of namespaces). For most packages (especially those which make extensive use of compiled code) the speed-up is small. Unless a package is used frequently the time spent in byte-compilation can outweigh the time saved in execution: also byte-compilation can add substantially to the installed size of the package.

Byte-compilation can be controlled on a per-package basis by the ‘ByteCompile’ field in the ‘DESCRIPTION’ file.

6.4 Updating packages

The command `update.packages()` is the simplest way to ensure that all the packages on your system are up to date. Set the `repos` argument as in the previous section. The `update.packages()` downloads the list of available packages and their current versions, compares it with those installed and offers to fetch and install any that have later versions on the repositories.

An alternative interface to keeping packages up-to-date is provided by the command `packageStatus()`, which returns an object with information on all installed packages and packages available at multiple repositories. The `print` and `summary` methods give an overview of installed and available packages, the `upgrade` method offers to fetch and install the latest versions of outdated packages.

One sometimes-useful additional piece of information that `packageStatus()` returns is the status of a package, as “ok”, “upgrade” or “unavailable” (in the currently selected repositories). For example

```
> inst <- packageStatus()$inst
> inst[inst$Status != "ok", c("Package", "Version", "Status")]
```

	Package	Version	Status
Biobase	Biobase	2.8.0	unavailable
RCurl	RCurl	1.4-2	upgrade
Rgraphviz	Rgraphviz	1.26.0	unavailable
rgdal	rgdal	0.6-27	upgrade

6.5 Removing packages

Packages can be removed in a number of ways. From a command prompt they can be removed by

```
R CMD REMOVE -l /path/to/library pkg1 pkg2 ...
```

From a running R process they can be removed by

```
> remove.packages(c("pkg1", "pkg2"),
  lib = file.path("path", "to", "library"))
```

Finally, in most installations one can just remove the package directory from the library.

6.6 Setting up a package repository

Utilities such as `install.packages` can be pointed at any CRAN-style repository, and R users may want to set up their own. The ‘base’ of a repository is a URL such as <http://www.omegahat.org/R/>: this must be an URL scheme that `download.packages` supports (which also includes ‘ftp://’ and ‘file://’, but not on most systems ‘https://’). Under that base URL there should be directory trees for one or more of the following types of package distributions:

- "source": located at ‘src/contrib’ and containing ‘.tar.gz’ files. Other forms of compression can be used, e.g. ‘.tar.bz2’ or ‘.tar.xz’ files.
- "win.binary": located at ‘bin/windows/contrib/x.y’ for R versions x.y.z and containing ‘.zip’ files for Windows.
- "mac.binary.leopard": located at ‘bin/macosx/leopard/contrib/x.y’ for R versions x.y.z and containing ‘.tgz’ files.

Each terminal directory must also contain a ‘PACKAGES’ file. This can be a concatenation of the ‘DESCRIPTION’ files of the packages separated by blank lines, but only a few of the fields are needed. The simplest way to set up such a file is to use function `write_PACKAGES` in the **tools** package, and its help explains which fields are needed. Optionally there can also be a ‘PACKAGES.gz’ file, a gzip-compressed version of ‘PACKAGES’—as this will be downloaded in preference to ‘PACKAGES’ it should be included for large repositories. (If you have a mis-configured server that does not report correctly non-existent files you will need ‘PACKAGES.gz’.)

To add your repository to the list offered by `setRepositories()`, see the help file for that function.

A repository can contain subdirectories, when the descriptions in the ‘PACKAGES’ file of packages in subdirectories must include a line of the form

```
Path: path/to/subdirectory
```

—once again `write_PACKAGES` is the simplest way to set this up.

6.7 Checking installed source packages

It can be convenient to run R CMD `check` on an installed package, particularly on a platform which uses sub-architectures. The outline of how to do this is, with the source package in directory ‘*pkgname*’ (or a tarball filename):

```
R CMD INSTALL -l libdir pkgname > pkgname.log 2>&1
R CMD check -l libdir --install=check:pkgname.log pkgname
```

Where sub-architectures are in use the R CMD `check` line can be repeated with additional architectures by


```
R --arch arch CMD check -l libdir --extra-arch --install=check:pkgname.log pkg-
name
```

where ‘--extra-arch’ selects only those checks which depend on the installed code and not those which analyse the sources. (If multiple sub-architectures fail only because they need different settings, e.g. environment variables, ‘--no-multiarch’ may need to be added to the `INSTALL` lines.) On (Mac) OS X and other Unix-alikes the architecture to run is selected by ‘--arch’: this can also be used on Windows with ‘`R_HOME/bin/R.exe`’, but it is more usual to select the path to the `Rcmd.exe` of the desired architecture.

So on Windows to install, check and package for distribution a source package from a tarball which has been tested on another platform one might use

```
.../bin/i386/Rcmd INSTALL -l libdir tarball --build > pkgname.log 2>&1
.../bin/i386/Rcmd check -l libdir --extra-arch --install=check:pkgname.log pkg-
name
.../bin/x64/Rcmd check -l libdir --extra-arch --install=check:pkgname.log pkg-
name
```

where one might want to run the second and third lines in a different shell with different settings for environment variables and the path (to find external software, notably for Gtk+).

`R CMD INSTALL` can do a i386 install and then add the x64 DLL from a single command by

```
R CMD INSTALL --merge-multiarch -l libdir tarball
```

and ‘--build’ can be added to zip up the installation.

7 Internationalization and Localization

Internationalization refers to the process of enabling support for many human languages, and *localization* to adapting to a specific country and language.

Historically R worked in the ISO Latin-1 8-bit character set and so covered English and most Western European languages (if not necessarily their currency symbols). Since R 2.1.0 it has supported multi-byte character sets such as UTF-8 and others used for Chinese, Japanese and Korean.

Current builds of R support all the character sets that the underlying OS can handle. These are interpreted according to the current `locale`, a sufficiently complicated topic to merit a separate section. Note though that R has no built-in support for right-to-left languages and bidirectional output, relying on the OS services. For example, how character vectors in UTF-8 containing both English digits and Hebrew characters are printed is OS-dependent (and perhaps locale-dependent).

The other aspect of the internationalization is support for the translation of messages. This is enabled in almost all builds of R.

7.1 Locales

A *locale* is a description of the local environment of the user, including the preferred language, the encoding of characters, the currency used and its conventions, and so on. Aspects of the locale are accessed by the R functions `Sys.getlocale` and `Sys.localeconv`.

The system of naming locales is OS-specific. There is quite wide agreement on schemes, but not on the details of their implementation. A locale needs to specify

- A human language. These are generally specified by a lower-case two-character abbreviation following ISO 639 (see e.g. http://en.wikipedia.org/wiki/ISO_639-1).
- A ‘territory’, used mainly to specify the currency. These are generally specified by an upper-case two-character abbreviation following ISO 3166 (see e.g. http://en.wikipedia.org/wiki/ISO_3166). Sometimes the combination of language and territory is used to specify the encoding, for example to distinguish between traditional and simplified Chinese.
- A charset encoding, which determines both how a byte stream should be divided into characters, and which characters the subsequences of bytes represent.
- Optionally, a modifier, for example to indicate that Austria is to be considered pre- or post-Euro. The modifier is also used to indicate the script (`@latin`, `@cyrillic`, `@iqtelif`) or language dialect (e.g. `saaho`, a dialect of Afar, and `bokmal` and `nynorsk`, dialects of Norwegian regarded by some OSes as separate languages, `no` and `nn`).

R is principally concerned with the first (for translations) and third. Note that the charset may be deducible from the language, as some OSes offer only one charset per language, and most OSes have only one charset each for many languages. Note too the remark above about Chinese.

7.1.1 Locales under Linux

Modern Linux uses the XPG¹ locale specifications which have the form ‘en_GB’, ‘en_GB.UTF-8’, ‘aa_ER.UTF-8@saaho’, ‘de_AT.iso885915@euro’, the components being in the order listed above. (See `man locale` and `locale -a` for more details.) Similar schemes are used by most Unix-alikes: some (including some distributions of Linux) use ‘.utf8’ rather than ‘.UTF-8’.

7.1.2 Locales under Windows

Windows also uses locales, but specified in a rather less concise way. Most users will encounter locales only via drop-down menus, but more information and lists can be found at http://msdn.microsoft.com/library/default.asp?url=/library/en-us/vccore98/html/_crt_language_and_country_strings.asp.

It offers only one encoding per language.

Some care is needed with Windows’ locale names. For example, `chinese` is Traditional Chinese and not Simplified Chinese as used in most of the Chinese-speaking world.

7.1.3 Locales under OS X

OS X supports locales in its own particular way, but the R GUI tries to make this easier for users. See <http://developer.apple.com/documentation/MacOSX/Conceptual/BPInternational/> for how users can set their locales. As with Windows, end users will generally only see lists of languages/territories. Users of R in a terminal may need to set the locale to something like ‘en_GB.UTF-8’ if it defaults to ‘C’ (as it often does when logging it remotely and in batch jobs).

Internally OS X uses a form similar to Linux. It is based on ICU locales IDs (<http://userguide.icu-project.org/locale>) and not XPG ones, but utilities such as `Sys.setlocale()` do now normally accept XPG forms. So there are locales like `de_AT.ISO8859-15` (German in Austria in Latin-9, which covers the Euro): the main difference from other Unix-alikes is that where a character set is not specified it is assumed to be UTF-8.

7.2 Localization of messages

The preferred language for messages is by default taken from the locale. This can be overridden first by the setting of the environment variable `LANGUAGE` and then² by the environment variables `LC_ALL`, `LC_MESSAGES` and `LANG`. (The last three are normally used to set the locale and so should not be needed, but the first is only used to select the language for messages.) The code tries hard to map locales to languages, but on some systems (notably Windows) the locale names needed for the environment variable `LC_ALL` do not all correspond to XPG language names and so `LANGUAGE` may need to be set. (One example is ‘`LC_ALL=es`’ on Windows which sets the locale to Estonian and the language to Spanish.)

It is usually possible to change the language once R is running *via* (not Windows) `Sys.setlocale("LC_MESSAGES", "new_locale")`, or by setting an environment variable

¹ ‘X/Open Portability Guide’, which has had several versions.

² On some systems setting `LC_ALL` or `LC_MESSAGES` to ‘C’ disables `LANGUAGE`.

such as `LANGUAGE`, *provided*³ the language you are changing to can be output in the current character set. But this is OS-specific, and has been known to stop working on an OS upgrade.

Messages are divided into *domains*, and translations may be available for some or all messages in a domain. R makes use of the following domains.

- Domain `R` for basic C-level error messages.
- Domain `R-pkg` for the `R stop`, `warning` and `message` messages in each package, including `R-base` for the `base` package.
- Domain `pkg` for the C-level messages in each package.
- Domain `RGui` for the menus etc of the R for Windows GUI front-end.

Dividing up the messages in this way allows R to be extensible: as packages are loaded, their message translation catalogues can be loaded too.

Translations are looked for by domain according to the currently specified language, as specifically as possible, so for example an Austrian (`'de_AT'`) translation catalogue will be used in preference to a generic German one (`'de'`) for an Austrian user. However, if a specific translation catalogue exists but does not contain a translation, the less specific catalogues are consulted. For example, R has catalogues for `'en_GB'` that translate the Americanisms (e.g., `'gray'`) in the standard messages into English.⁴ Two other examples: there are catalogues for `'es'`, which is Spanish as written in Spain and these will by default also be used in Spanish-speaking Latin American countries, and also for `'pt_BR'`, which are used for Brazilian locales but not for locales specifying Portugal.

Translations in the right language but the wrong charset be made use of by on-the-fly re-encoding. The `LANGUAGE` variable (only) can be a colon-separated list, for example `'se:de'`, giving a set of languages in decreasing order of preference. One special value is `'en@quot'`, which can be used in a UTF-8 locale to have American error messages with pairs of quotes translated to Unicode directional quotes.

If no suitable translation catalogue is found or a particular message is not translated in any suitable catalogue, 'English'⁵ is used.

See <http://developer.r-project.org/Translations.html> for how to prepare and install translation catalogues.

³ If you try changing from French to Russian except in a UTF-8 locale, you will most likely find messages change to English.

⁴ the language written in England: some people living in the USA appropriate this name for their language.

⁵ with Americanisms.

8 Choosing between 32- and 64-bit builds

Many current CPUs have both 32- and 64-bit sets of instructions: this has long been true for UltraSparc and more recently for MIPS, PPC and ‘x86_64’ (sometimes known as ‘amd64’ and ‘Intel64’ and earlier as ‘EM64T’: practically all current ‘ix86’ CPUs support this set of instructions). Most OSes running on such CPUs offer the choice of building a 32-bit or a 64-bit version of R (and details are given below under specific OSes). For most a 32-bit version is the default, but for some (e.g., ‘x86_64’ Linux and (Mac) OS X ≥ 10.6) 64-bit is.

All current versions of R use 32-bit integers and IEC 60559¹ double-precision reals, and so compute to the same precision² and with the same limits on the sizes of numerical quantities. The principal difference is in the size of the pointers.

64-bit builds have both advantages and disadvantages:

- The total virtual memory space made available to a 32-bit process is limited by the pointer size to 4GB, and on most OSes to 3GB (or even 2GB). The limits for 64-bit processes are much larger (e.g. 8–128TB).

R allocates memory for large objects as needed, and removes any unused ones at garbage collection. When the sizes of objects become an appreciable fraction of the address limit, fragmentation of the address space becomes an issue and there may be no hole available that is the size requested. This can cause more frequent garbage collection or the inability to allocate large objects. As a guide, this will become an issue with objects more than 10% of the size of the address space (around 300Mb) or when the total size of objects in use is around one third (around 1Gb).

- Most 32-bit OSes by default limit file sizes to 2GB (and this may also apply to 32-bit builds on 64-bit OSes). This can often be worked around: and `configure` selects suitable defines if this is possible. (We have also largely worked around that limit on 32-bit Windows.) 64-bit builds have much larger limits.
- Because the pointers are larger, R’s basic structures are larger. This means that R objects take more space and (usually) more time to manipulate. So 64-bit builds of R will, all other things being equal, run slower than 32-bit builds. (On Sparc Solaris the difference was 15-20%.)
- However, ‘other things’ may not be equal. In the specific case of ‘x86_64’ *vs* ‘ix86’, the 64-bit CPU has features (such as SSE2 instructions) which are guaranteed to be present but are optional on the 32-bit CPU, and also has more general-purpose registers. This means that on chips like a desktop Intel Core 2 Duo the vanilla 64-bit version of R is around 10% faster on both Linux and OS X. (Laptop CPUs are relatively slower in 64-bit mode.)

So, for speed you may want to use a 32-bit build, but to handle large datasets (and perhaps large files) a 64-bit build. You can often build both and install them in the same place: See [Section 2.6 \[Sub-architectures\], page 8](#). (This is done in the OS X and Windows binary distributions.)

¹ also known as IEEE 754

² at least when storing quantities: the on-FPU precision is allowed to vary

Even on 64-bit builds of R there are limits on the size of R objects (see `help("Memory-limits")`), some of which stem from the use of 32-bit integers (especially in FORTRAN code). On all builds of R, the maximum length (number of elements) of a vector is $2^{31} - 1$, about 2 billion, and on 64-bit builds the size of a block of memory allocated is limited to $2^{34} - 1$ bytes (8GB). It is anticipated these will be raised eventually³ but the need for 8GB objects is (when this was written in 2011) exceptional.

³ this comment has been in the manual since 2005.

9 The standalone Rmath library

The routines supporting the distribution and special¹ functions in R and a few others are declared in C header file ‘`Rmath.h`’. These can be compiled into a standalone library for linking to other applications. (Note that they are not a separate library when R is built, and the standalone version differs in several ways.)

The makefiles and other sources needed are in directory ‘`src/nmath/standalone`’, so the following instructions assume that is the current working directory (in the build directory tree on a Unix-alike if that is separate from the sources).

‘`Rmath.h`’ contains ‘`R_VERSION_STRING`’, which is a character string containing the current R version, for example “2.15.0”.

There is full access to R’s handling of NaN, Inf and -Inf via special versions of the macros and functions

```
ISNAN, R_FINITE, R_log, R_pow and R_pow_di
```

and (extern) constants `R_PosInf`, `R_NegInf` and `NA_REAL`.

There is no support for R’s notion of missing values, in particular not for `NA_INTEGER` nor the distinction between NA and NaN for doubles.

A little care is needed to use the random-number routines. You will need to supply the uniform random number generator

```
double unif_rand(void)
```

or use the one supplied (and with a shared library or DLL you will have to use the one supplied, which is the Marsaglia-multicarry with an entry point

```
set_seed(unsigned int, unsigned int)
```

to set its seeds).

The facilities to change the normal random number generator are available through the constant `N01_kind`. This takes values from the enumeration type

```
typedef enum {
    BUGGY_KINDERMAN_RAMAGE,
    AHRENS_DIETER,
    BOX_MULLER,
    USER_NORM,
    INVERSION,
    KINDERMAN_RAMAGE
} N01type;
```

(and ‘`USER_NORM`’ is not available).

9.1 Unix-alikes

If R has not already be made in the directory tree, `configure` must be run as described in the main build instructions.

Then (in ‘`src/nmath/standalone`’)

¹ e.g. Bessel, beta and gamma functions

```
make
```

will make standalone libraries ‘libRmath.a’ and ‘libRmath.so’ (‘libRmath.dylib’ on Mac OS X): ‘make static’ and ‘make shared’ will create just one of them.

NB: certain compilers are unable to do compile-time IEC 60559 arithmetic and so cannot compile ‘mlutils.c’ and several other files. The known example is old versions of Sun’s cc (e.g. Forte 6 and 7).

To use the routines in your own C or C++ programs, include

```
#define MATHLIB_STANDALONE
#include <Rmath.h>
```

and link against ‘-lRmath’ (and ‘-lm’ if needed on your OS). The example file ‘test.c’ does nothing useful, but is provided to test the process (via `make test`). Note that you will probably not be able to run it unless you add the directory containing ‘libRmath.so’ to the LD_LIBRARY_PATH environment variable.

The targets

```
make install
make uninstall
```

will (un)install the header ‘Rmath.h’ and shared and static libraries (if built). Both `prefix=` and `DESTDIR` are supported, together with more precise control as described for the main build.

‘make install’ installs a file for `pkg-config` to use by e.g.

```
$(CC) 'pkg-config --cflags libRmath' -c test.c
$(CC) 'pkg-config --libs libRmath' test.o -o test
```

On some systems ‘make install-strip’ will install a stripped shared library.

9.2 Windows

You need to set up² almost all the tools to make R and then run (in a Unix-like shell)

```
(cd ../../gnuwin32; make MkRules)
(cd ../../include; make -f Makefile.win config.h Rconfig.h Rmath.h)
make -f Makefile.win
```

For ‘cmd.exe’ use

```
cd ../../include
make -f Makefile.win config.h Rconfig.h Rmath.h
cd ../nmath/standalone
make -f Makefile.win
```

This creates a static library ‘libRmath.a’ and a DLL ‘Rmath.dll’. If you want an import library ‘libRmath.dll.a’ (you don’t need one), use

```
make -f Makefile.win shared implib
```

To use the routines in your own C or C++ programs using MinGW, include

```
#define MATHLIB_STANDALONE
#include <Rmath.h>
```

² including copying ‘MkRules.dist’ to ‘MkRule.local’ and selecting the architecture.

and link against `-lRmath`. This will use the first found of `libRmath.dll.a`, `libRmath.a` and `Rmath.dll` in that order, so the result depends on which files are present. You should be able to force static or dynamic linking *via*

```
-Wl,-Bstatic -lRmath -Wl,dynamic  
-Wl,-Bdynamic -lRmath
```

or by linking to explicit files (as in the `test` target in `Makefile.win`: this makes two executables, `test.exe` which is dynamically linked, and `test-static.exe`, which is statically linked).

It is possible to link to `Rmath.dll` using other compilers, either directly or via an import library: if you make a MinGW import library as above, you will create a file `Rmath.def` which can be used (possibly after editing) to create an import library for other systems such as Visual C++.

If you make use of dynamic linking you should use

```
#define MATHLIB_STANDALONE  
#define RMATH_DLL  
#include <Rmath.h>
```

to ensure that the constants like `NA_REAL` are linked correctly. (Auto-import will probably work with MinGW, but it is better to be sure. This is likely to also work with VC++, Borland and similar compilers.)

Appendix A Essential and useful other programs under a Unix-alike

This appendix gives details of programs you will need to build R on Unix-like platforms, or which will be used by R if found by `configure`.

Remember that some package management systems (such as RPM and deb) make a distinction between the user version of a package and the development version. The latter usually has the same name but with the extension ‘`-devel`’ or ‘`-dev`’: you need both versions installed.

A.1 Essential programs and libraries

You need a means of compiling C and FORTRAN 77 (see [Section B.7 \[Using FORTRAN\]](#), [page 48](#)). Some add-on packages also need a C++ compiler. Your C compiler should be IEC 60059¹, POSIX 1003.1 and C99-compliant.² R tries to choose suitable flags for the C compilers it knows about, but you may have to set `CC` or `CFLAGS` suitably. For recent versions of `gcc` with `glibc` this means including ‘`-std=gnu99`’³. If the compiler is detected as `gcc`, ‘`-std=gnu99`’ will be appended to `CC` unless it conflicts with a setting of `CFLAGS`. (Note that options essential to run the compiler even for linking, such as those to set the architecture, should be specified as part of `CC` rather than in `CFLAGS`.)

Unless you do not want to view graphs on-screen (or use a Mac) you need ‘`X11`’ installed, including its headers and client libraries. For recent Fedora distributions it means (at least) RPMs ‘`libX11`’, ‘`libX11-devel`’, ‘`libXt`’ and ‘`libXt-devel`’. On Debian we recommend the meta-package ‘`xorg-dev`’. If you really do not want these you will need to explicitly configure R without X11, using ‘`--with-x=no`’.

The command-line editing (and command completion) depends on the GNU `readline` library: version 4.2 or later is needed for all the features to be enabled. Otherwise you will need to configure with ‘`--with-readline=no`’ (or equivalent).

A suitably comprehensive `iconv` function is essential. The R usage requires `iconv` to be able to translate between “`latin1`” and “`UTF-8`”, to recognize “” (as the current encoding) and “`ASCII`”, and to translate to and from the Unicode wide-character formats “`UCS-2`” [“`BL`”] “`E`” — this is true for `glibc` but not of most commercial Unixes. However, you can make use of GNU `libiconv` (possibly as a plug-in replacement: see <http://www.gnu.org/software/libiconv/>).

An implementation of XDR is required. This is part of RPC and historically has been part of ‘`libc`’ on a Unix-alike: however some builds⁴ of `glibc 2.14` hide it. The intention seems to be that the TI-RPC library be used instead, in which case `libtirpc` (and its development version) needs to be installed, and its headers need to be on the C include path (and `configure` tries ‘`/usr/include/tirpc`’ if the headers are not found on the standard include path). The R sources contain a simple implementation of XDR which in recent

¹ also known as IEEE 754

² Note that C11 compilers (when they appear) need not be C99-compliant: R requires support for `double complex` which is optional in C11 but is mandatory in C99.

³ ‘`-std=c99`’ excludes POSIX functionality, but ‘`config.h`’ will turn on all GNU extensions to include the POSIX functionality.

⁴ apparently when built by default, but not for example as built for Fedora 15.

versions can be used on platforms with 32-bit or 64-bit `long` (and earlier ones will fail to compile unless `long` is 32-bit).

The OS needs to have enough support⁵ for wide-character types: this is checked at configuration.

A `tar` program is needed to unpack the sources and packages (including the recommended packages). A version⁶ that can automagically detect compressed archives is preferred for use with `untar()`: the configure script looks for `gtar` and `gnutar` before `tar`: use environment variable `TAR` to override this.

There need to be suitable versions of the tools `grep` and `sed`: the problems are usually with old AT&T and BSD variants. `configure` will try to find suitable versions (including looking in `/usr/xpg4/bin` which is used on some commercial Unixes).

You will not be able to build most of the manuals unless you have `makeinfo` version 4.7 or later installed, and if not some of the HTML manuals will be linked to CRAN. To make PDF versions of the manuals you will also need file `'texinfo.tex'` installed (which is part of the GNU `texinfo` distribution but is often made part of the `TEX` package in re-distributions) as well as `texi2dvi`.⁷ Further, the versions of `texi2dvi` and `'texinfo.tex'` need to be compatible: we have seen problems with older `TEX` distributions (TeXLive 2007 and MiKTeX 2.8) used with `texinfo` 4.13.

The PDF documentation (including `'doc/NEWS.pdf'`) and building vignettes needs `tex` and `latex`, or `pdftex` and `pdflatex`. We require `LATEX` version 2005/12/01 or later (for UTF-8 support). Building PDF package manuals (including the R reference manual) and vignettes is sensitive to the version of the `LATEX` package `hyperref` and we recommend that the `TEX` distribution used is keep up-to-date. A number of `LATEX` packages are required (including `url.sty`, and `listings.sty`) and others such as `hyperref` and `inconsolata` are desirable (and without them you will need to change R's defaults: see [Section 2.3 \[Making the manuals\]](#), page 5).

If you want to build from the R Subversion repository you need both `makeinfo` and `pdflatex`.

The essential programs should be in your `PATH` at the time `configure` is run: this will capture the full paths.

A.2 Useful libraries and programs

The ability to use translated messages makes use of `gettext` and most likely needs GNU `gettext`: you do need this to work with new translations, but otherwise the version contained in the R sources will be used if no suitable external `gettext` is found.

The 'modern' version of the `X11()`, `jpeg()`, `png()` and `tiff()` graphics devices uses the `cairo` and (optionally) `Pango` libraries. Cairo version 1.2.0 or later is required. Pango needs to be at least version 1.10, and 1.12 is the earliest version we have tested. (For Fedora users

⁵ specifically, the C99 functionality of headers `'wchar.h'` and `'wctype.h'`, types `wctans_t` and `mbstate_t` and functions `mbrtowc`, `mbstowcs`, `wcrtomb`, `wscoll`, `wcstombs`, `wctrans`, `wctype`, and `iswctype`.

⁶ Such as GNU `tar` 1.15 or later, `bsdtar` (from <http://code.google.com/p/libarchive/>, as used by FreeBSD and OS 10.[67]) or `tar` from the Heirloom Toolchest (<http://heirloom.sourceforge.net/tools.html>).

⁷ `texi2dvi` is normally a shell script. Some versions, e.g. that from `texinfo` 4.13a, need to be run under `bash` rather than a Bourne shell as on, say, Solaris.

we believe the `pango-devel` RPM and its dependencies suffice.) R checks for `pkg-config`, and uses that to check first that the ‘`pangocairo`’ package is installed (and if not, ‘`cairo`’) and if additional flags are needed for the ‘`cairo-xlib`’ package, then if suitable code can be compiled. These tests will fail if `pkg-config` is not installed, and are likely to fail if `cairo` was built statically (unusual). Most systems with `Gtk+` 2.8 or later installed will have suitable libraries. OS X comes with none of these libraries, but `cairo` support (without `Pango`) has been added to the binary distribution: `pkg-config` is still needed and can be installed from the sources.

For the best font experience with these devices you need suitable fonts installed: Linux users will want the `urw-fonts` package. On platforms which have it available, the `msttcorefonts` package⁸ provides TrueType versions of Monotype fonts such as Arial and Times New Roman. Another useful set of fonts is the ‘liberation’ TrueType fonts available at <https://www.redhat.com/promo/fonts/>,⁹ which cover the Latin, Greek and Cyrillic alphabets plus a fair range of signs. These share metrics with Arial, Times New Roman and Courier New, and contain fonts rather similar to the first two (http://en.wikipedia.org/wiki/Liberation_fonts). Then there is the ‘Free UCS Outline Fonts’ project (<http://www.gnu.org/software/freefont/>) which are OpenType/TrueType fonts based on the URW fonts but with extended Unicode coverage. See the R help on X11 on selecting such fonts.

The bitmapped graphics devices `jpeg()`, `png()` and `tiff()` need the appropriate headers and libraries installed: `jpeg` (version 6b or later, or `libjpeg-turbo`) or `libpng` (version 1.2.7 or later, including 1.4.x and 1.5.x) and `zlib` or `libtiff` (any recent version of 3.x.y – 3.9.[45] have been tested) respectively. They also need support for either X11 or `cairo` (see above).

If you have them installed (including the appropriate headers and of suitable versions), system versions of `zlib`, `libbz2` and `PCRE` will be used if specified by ‘`--with-system-zlib`’ (version 1.2.3 or later), ‘`--with-system-bzlib`’ or ‘`--with-system-pcre`’ (version 8.10 or later, preferably 8.21 which is what is supplied with R): otherwise versions in the R sources will be compiled in. As the latter suffice and are tested with R you should not need to change this.

`liblzma` from `xz-utils` version 4.999 or later (preferably 5.0.0 or later) will be used if installed: the version in the R sources can be selected instead by configuring with ‘`--with-system-xz=no`’.

Use of the X11 clipboard selection requires the `Xmu` headers and libraries. These are normally part of an X11 installation (e.g. the Debian meta-package ‘`xorg-dev`’), but some distributions have split this into smaller parts, so for example recent versions of Fedora require the ‘`libXmu`’ and ‘`libXmu-devel`’ RPMs.

Some systems (notably OS X and at least some FreeBSD systems) have inadequate support for collation in multibyte locales. It is possible to replace the OS’s collation support by that from ICU (International Components for Unicode, <http://site.icu-project.org/>), and this provides much more precise control over collation on all systems. ICU is available as sources and as binary distributions for (at least) most Linux distributions, Solaris,

⁸ also known as `ttf-mscorefonts-installer` in the Debian/Ubuntu world: see also http://en.wikipedia.org/wiki/Core_fonts_for_the_Web.

⁹ `ttf-liberation` in Debian/Ubuntu.

FreeBSD and AIX, usually as `libicu` or `icu4c`. It will be used by default where available (including on OS X ≥ 10.4): should a very old or broken version of ICU be found this can be suppressed by `--without-ICU`.

The `bitmap` and `dev2bitmap` devices and also `embedFonts()` use `ghostscript` (<http://www.cs.wisc.edu/~ghost>). This should either be in your path when the command is run, or its full path specified by the environment variable `R_GSCMD` at that time.

A.2.1 Tcl/Tk

The `tcltk` package needs Tcl/Tk ≥ 8.4 installed: the sources are available at <http://www.tcl.tk/>. To specify the locations of the Tcl/Tk files you may need the configuration options

```
'--with-tcltk'
    use Tcl/Tk, or specify its library directory

'--with-tcl-config=TCL_CONFIG'
    specify location of 'tclConfig.sh'

'--with-tk-config=TK_CONFIG'
    specify location of 'tkConfig.sh'
```

or use the configure variables `TCLTK_LIBS` and `TCLTK_CPPFLAGS` to specify the flags needed for linking against the Tcl and Tk libraries and for finding the `'tcl.h'` and `'tk.h'` headers, respectively. If you have both 32- and 64-bit versions of Tcl/Tk installed, specifying the paths to the correct config files may be necessary to avoid confusion between them.

Versions of Tcl/Tk up to 8.5.10 have been tested (including most versions of 8.4.x, but not recently).

A.2.2 Java support

`configure` looks for Java support on the host system, and if it finds it sets some settings which are useful for Java-using packages. `JAVA_HOME` can be set during the `configure` run to point to a specific JRE/JDK.

Principal amongst these are setting some library paths to the Java libraries and JVM, which are stored in environment variable `R_JAVA_LD_LIBRARY_PATH` in file `'R_HOME/etc/ldpaths'` (or a sub-architecture-specific version). A typical setting for `'x86_64'` Linux is

```
JAVA_HOME=/usr/lib/jvm/java-1.6.0-openjdk-1.6.0.0.x86_64/jre
R_JAVA_LD_LIBRARY_PATH=${JAVA_HOME}/lib/amd64/server:${JAVA_HOME}/lib/amd64
```

Note that this unfortunately depends on the exact version of the JRE/JDK installed, and so may need updating if the Java installation is updated. This can be done by running R CMD `javareconf`. The script re-runs Java detection in a manner similar to that of the `configure` script and updates settings in both `'Makeconf'` and `'R_HOME/etc/ldpaths'`. See R CMD `javareconf --help` for details.

Another alternative of overriding those setting is to set `R_JAVA_LD_LIBRARY_PATH` (e.g. in `'~/.Renviron'`), or use `'/etc/ld.so.conf'` to specify the Java runtime library paths to the system. Other settings are recorded in `'etc/Makeconf'` (or a sub-architecture-specific version), e.g.

```

JAVA = /usr/bin/java
JAVAC = /usr/bin/javac
JAVA_HOME = /usr/java/jdk1.5.0_06/jre
JAVA_LD_LIBRARY_PATH = $(JAVA_HOME)/lib/amd64/server:$(JAVA_HOME)/lib/amd64:\
$(JAVA_HOME)/../lib/amd64:/usr/local/lib64
JAVA_LIBS = -L$(JAVA_HOME)/lib/amd64/server -L$(JAVA_HOME)/lib/amd64
            -L$(JAVA_HOME)/../lib/amd64 -L/usr/local/lib64 -ljvm

```

where ‘`JAVA_LIBS`’ contains flags necessary to link JNI programs. Some of the above variables can be queried using R CMD `config`.

A.3 Linear algebra

A.3.1 BLAS

The linear algebra routines in R can make use of enhanced BLAS (Basic Linear Algebra Subprograms, <http://www.netlib.org/blas/faq.html>) routines. However, these have to be explicitly requested at configure time: R provides an internal BLAS which is well-tested and will be adequate for most uses of R.

You can specify a particular BLAS library *via* a value for the configuration option ‘`--with-blas`’ and not to use an external BLAS library by ‘`--without-blas`’ (the default). If ‘`--with-blas`’ is given with no =, its value is taken from the environment variable `BLAS_LIBS`, set for example in ‘`config.site`’. If neither the option nor the environment variable supply a value, a search is made for a suitable BLAS. If the value is not obviously a linker command (starting with a dash or giving the path to a library), it is prefixed by ‘`-l`’, so

```
--with-blas="foo"
```

is an instruction to link against ‘`-lfoo`’ to find an external BLAS (which needs to be found both at link time and run time).

The configure code checks that the external BLAS is complete (it must include all double precision and double complex routines, as well as `LSAME`), and appears to be usable. However, an external BLAS has to be usable from a shared object (so must contain position-independent code), and that is not checked.

Some enhanced BLASes are compiler-system-specific (`sunperf` on Solaris¹⁰, `libessl` on IBM, `vecLib` on OS X). The correct incantation for these is usually found *via* ‘`--with-blas`’ with no value on the appropriate platforms.

Some of the external BLASes are multi-threaded. One issue is that R profiling (which uses the `SIGPROF` signal) may cause problems, and you may want to disable profiling if you use a multi-threaded BLAS. Note that using a multi-threaded BLAS can result in taking more CPU time and even more elapsed time (occasionally dramatically so) than using a similar single-threaded BLAS.

Note that under Unix (but not under Windows) if R is compiled against a non-default BLAS and ‘`--enable-BLAS-shlib`’ is **not** used, then all BLAS-using packages must also be. So if R is re-built to use an enhanced BLAS then packages such as **quantreg** will need to be re-installed.

R relies on IEC 60559 compliance of an external BLAS. This can be broken if for example the code assumes that terms with a zero factor are always zero and do not need to be computed—whereas `x*0` can be `NaN`. This is checked in the test suite.

¹⁰ Using the Oracle Solaris Studio `cc` and `f95` compilers

A.3.1.1 ATLAS

ATLAS (<http://math-atlas.sourceforge.net/>) is a “tuned” BLAS that runs on a wide range of Unix-alike platforms. Unfortunately it is usually built as a static library that on some platforms cannot be used with shared objects such as are used in R packages. Be careful when using pre-built versions of ATLAS (they seem to work on ‘ix86’ platforms, but not always on ‘x86_64’ ones).

The usual way to specify ATLAS will be via

```
--with-blas="-lf77blas -latlas"
```

if the libraries are in the library path, otherwise by

```
--with-blas="-L/path/to/ATLAS/libs -lf77blas -latlas"
```

For example, ‘x86_64’ Fedora needs

```
--with-blas="-L/usr/lib64/atlas -lf77blas -latlas"
```

For systems with multiple CPU cores it is possible to use a multi-threaded version of ATLAS, by specifying

```
--with-blas="-lptf77blas -lpthread -latlas"
```

Consult its file ‘INSTALL.txt’ for how to build ATLAS with position-independent code (at least on version 3.8.0 and later): that file also describes how to build ATLAS as a shared library.

ATLAS can also be used on Windows: see [Section 3.1.2 \[Getting the source files\]](#), [page 12](#) when building from source, and [R Windows FAQ](#) for adding pre-compiled support to binary versions.

A.3.1.2 ACML

For ‘x86_64’ and ‘i686’ processors under Linux there is the AMD Core Math Library (ACML) <http://www.amd.com/acml>. For the gcc version we could use

```
--with-blas="-lacml"
```

if the appropriate library directory (such as ‘/opt/acml5.1.0/gfortran64/lib’) is in the LD_LIBRARY_PATH. For other compilers, see the ACML documentation. There is a multi-threaded Linux version of ACML available for recent versions of gfortran. To make use of this you will need something like

```
--with-blas="-L/opt/acml5.1.0/gfortran64_mp/lib -lacml_mp"
```

(and you may need to arrange for the directory to be in ld.so cache).

See [Section A.3.1.5 \[Shared BLAS\]](#), [page 43](#) for an alternative (and in many ways preferable) way to use ACML.

The version last tested (5.1.0) failed the ‘reg-BLAS.R’ test in its handling of NAs.

A.3.1.3 Goto BLAS

Dr Kazushige Goto wrote another tuned BLAS which is available for several processors and OSes. The current version is known as GotoBLAS2, and has (in November 2010) been re-released under a much less restrictive licence. Source code can be obtained from <http://www.tacc.utexas.edu/tacc-projects/gotoblas2/>

Once it is built and installed, it can be used by configuring R with


```
--with-blas="-lgoto2"
```

See [Section A.3.1.5 \[Shared BLAS\]](#), page 43 for an alternative (and in many ways preferable) way to use it.

Our understanding is that this project is now frozen and so will not be updated for CPUs released since mid-2010. However, OpenBLAS (<http://xianyi.github.com/OpenBLAS/>) is a descendant project.

A.3.1.4 Intel MKL

For Intel processors under Linux, there is Intel's Math Kernel Library (<http://www.intel.com/software/products/mkl/>). You are strongly encouraged to read the MKL User's Guide, which is installed with the library, before attempting to link to MKL. There are also versions of MKL for Mac OS X and Windows, but they do not work with the standard compilers used for R on those platforms.

The MKL interface has changed several times, and may change again: the following notes apply to version 10.0, and prior to that 9.

Version 10 of MKL supports two linking models: the default model, which is backward compatible with version 9 (see below), and the pure layered model. The layered model gives the user fine-grained control over four different library layers: interface, threading, computation, and run-time library support. Some examples of linking to MKL using this layered model are given below. (These examples are for GCC compilers on 'x86_64'.) The choice of interface layer is important on 'x86_64' since the Intel Fortran compiler returns complex values in different registers from the GNU Fortran compiler. You must therefore use the interface layer that matches your compiler (`mkl_intel*` or `mkl_gf*`).

R can be linked to a sequential version of MKL by something like

```
MKL_LIB_PATH=/opt/intel/mkl/10.0.3.020/lib/em64t/
export LD_LIBRARY_PATH=$MKL_LIB_PATH
MKL="-L${MKL_LIB_PATH} -lmkl_gf_lp64 -lmkl_sequential -lmkl_lapack -lmkl_core"
./configure --with-blas="$MKL" --with-lapack
```

The order of the libraries is important. The option '`--with-lapack`' is used since MKL contains a copy of LAPACK as well as BLAS (see [Section A.3.2 \[LAPACK\]](#), page 43).

Threaded MKL may be used by replacing the line defining the variable MKL with

```
MKL="-L${MKL_LIB_PATH} -lmkl_gf_lp64 -lmkl_gnu_thread \
      -lmkl_lapack -lmkl_core -liomp5 -lpthread"
```

The default number of threads will be chosen by the OpenMP software, but can be controlled by setting `OMP_NUM_THREADS` or `MKL_NUM_THREADS`.

Static threaded MKL may be used with

```
MKL="      -L${MKL_LIB_PATH} \
      -Wl,--start-group \
          ${MKL_LIB_PATH}/libmkl_gf_lp64.a \
          ${MKL_LIB_PATH}/libmkl_gnu_thread.a \
          ${MKL_LIB_PATH}/libmkl_core.a \
      -Wl,--end-group \
      -lgomp -lpthread"
```

(Thanks to Ei-ji Nakama).

The default linking model, which is also used by version 9 of MKL, can be used by

```
--with-blas="-lmkl -lguide -lpthread"
```

This is multi-threaded, but in version 9 the number of threads defaults to 1. It can be increased by setting `OMP_NUM_THREADS`. (Thanks to Andy Liaw for the information.)

A.3.1.5 Shared BLAS

The BLAS library will be used for many of the add-on packages as well as for R itself. This means that it is better to use a shared/dynamic BLAS library, as most of a static library will be compiled into the R executable and each BLAS-using package.

R offers the option of compiling the BLAS into a dynamic library `libRblas` stored in `'R_HOME/lib'` and linking both R itself and all the add-on packages against that library.

This is the default on all platforms except AIX unless an external BLAS is specified and found: for the latter it can be used by specifying the option `'--enable-BLAS-shlib'`, and it can always be disabled via `'--disable-BLAS-shlib'`.

This has both advantages and disadvantages.

- It saves space by having only a single copy of the BLAS routines, which is helpful if there is an external static BLAS such as used to be standard for ATLAS.
- There may be performance disadvantages in using a shared BLAS. Probably the most likely is when R's internal BLAS is used and R is *not* built as a shared library, when it is possible to build the BLAS into `'R.bin'` (and `'libR.a'`) without using position-independent code. However, experiments showed that in many cases using a shared BLAS was as fast, provided high levels of compiler optimization are used.
- It is easy to change the BLAS without needing to re-install R and all the add-on packages, since all references to the BLAS go through `libRblas`, and that can be replaced. Note though that any dynamic libraries the replacement links to will need to be found by the linker: this may need the library path to be changed in `'R_HOME/etc/ldpaths'`.

Another option to change the BLAS in use is to symlink a dynamic BLAS library (such as ACML or Goto's) to `'R_HOME/lib/libRblas.so'`. For example, just

```
mv R_HOME/lib/libRblas.so R_HOME/lib/libRblas.so.keep
ln -s /opt/acml5.1.0/gfortran64_mp/lib/libacml_mp.so R_HOME/lib/libRblas.so
```

will change the BLAS in use to multithreaded ACML. A similar link works for recent versions of the Goto BLAS and perhaps for MKL (provided the appropriate `'lib'` directory is in the run-time library path or `ld.so` cache).

A.3.2 LAPACK

Provision is made for using an external LAPACK library, principally to cope with BLAS libraries which contain a copy of LAPACK (such as `sunperf` on Solaris, `vecLib` on OS X and ACML on `'ix86'/'x86_64'` Linux). However, the likely performance gains are thought to be small (and may be negative), and the default is not to search for a suitable LAPACK library, and this is definitely **not** recommended. You can specify a specific LAPACK library or a search for a generic library by the configuration option `'--with-lapack'`. The default for `'--with-lapack'` is to check the BLAS library and then look for an external library `'-llapack'`. Sites searching for the fastest possible linear algebra may want to build a LAPACK library using the ATLAS-optimized subset of LAPACK. To do so specify something like


```
--with-lapack="-L/path/to/ATLAS/libs -llapack -lcblas"
```

since the ATLAS subset of LAPACK depends on `libcblas`. A value for ‘`--with-lapack`’ can be set *via* the environment variable `LAPACK_LIBS`, but this will only be used if ‘`--with-lapack`’ is specified (as the default value is `no`) and the BLAS library does not contain LAPACK.

Since ACML contains a full LAPACK, if selected as the BLAS it can be used as the LAPACK *via* ‘`--with-lapack`’.

If you do use ‘`--with-lapack`’, be aware of potential problems with bugs in the LAPACK 3.0 sources (or in the posted corrections to those sources). In particular, bugs in `DGEEV` and `DGESDD` have resulted in error messages such as

```
DGEBRD gave error code -10
```

. Other potential problems are incomplete versions of the libraries, seen several times over the years. For problems compiling LAPACK using recent versions of `gcc` on ‘`ix86`’ Linux, see [Section C.8 \[New platforms\]](#), page 62.

Please **do** bear in mind that using ‘`--with-lapack`’ is ‘definitely **not** recommended’: it is provided **only** because it is necessary on some platforms. Reporting problems where it is used unnecessarily will simply irritate the R helpers.

A.3.3 Caveats

As with all libraries, you need to ensure that they and R were compiled with compatible compilers and flags. For example, this has meant that on Sun Sparc using the native compilers the flag ‘`-dalign`’ is needed so `sunperf` can be used.

On some systems it is necessary that an external BLAS/LAPACK was built with the same FORTRAN compiler used to build R: known problems are with R built with `gfortran`, see [Section B.7.1 \[Using gfortran\]](#), page 49.

Appendix B Configuration on a Unix-alike

B.1 Configuration options

`configure` has many options: running

```
./configure --help
```

will give a list. Probably the most important ones not covered elsewhere are (defaults in brackets)

```
'--with-x'
    use the X Window System [yes]

'--x-includes=DIR'
    X include files are in DIR

'--x-libraries=DIR'
    X library files are in DIR

'--with-readline'
    use readline library (if available) [yes]

'--enable-R-profiling'
    attempt to compile support for Rprof() [yes]

'--enable-memory-profiling'
    attempt to compile support for tracemem() [no]

'--enable-R-shlib'
    build R as a shared/dynamic library [no]

'--enable-BLAS-shlib'
    build the BLAS as a shared/dynamic library [yes, except on AIX]
```

You can use `'--without-foo'` or `'--disable-foo'` for the negatives.

You will want to use `'--disable-R-profiling'` if you are building a profiled executable of R (e.g. with `'-pg'`).

Flag `'--enable-R-shlib'` causes the make process to build R as a dynamic (shared) library, typically called `'libR.so'`, and link the main R executable `'R.bin'` against that library. This can only be done if all the code (including system libraries) can be compiled into a dynamic library, and there may be a performance¹ penalty. So you probably only want this if you will be using an application which embeds R. Note that C code in packages installed on an R system linked with `'--enable-R-shlib'` is linked against the dynamic library and so such packages cannot be used from an R system built in the default way. Also, because packages are linked against R they are on some OSes also linked against the dynamic libraries R itself is linked against, and this can lead to symbol conflicts.

If you need to re-configure R with different options you may need to run `make clean` or even `make distclean` before doing so.

¹ We have measured 15–20% on 'i686' Linux and around 10% on 'x86_64' Linux.

B.2 Helper threads

Support for computations in helper threads is enabled by default, and may be disabled with the `--disable-helper-threads` configuration option. Disabling support for helper threads will produce a small speed improvement, compared to running `pqr` with helper thread support enabled, but with no helper threads.

If the BLAS routines used for matrix multiplication are not thread-safe, the `--disable-mat-multi-with-BLAS-in-helpers` option should be used, to prevent tasks that call the BLAS from being run in helper threads.

B.3 Internationalization support

Translation of messages is supported via GNU `gettext` unless disabled by the configure option `'--disable-nls'`. The `configure` report will show NLS as one of the 'Additional capabilities' if support has been compiled in, and running in an English locale (but not the `C` locale) will include

```
Natural language support but running in an English locale
in the greeting on starting R.
```

B.4 Configuration variables

If you need or want to set certain configure variables to something other than their default, you can do that by either editing the file `'config.site'` (which documents many of the variables you might want to set: others can be seen in file `'etc/Renviron.in'`) or on the command line as

```
./configure VAR=value
```

If you are building in a directory different from the sources, there can be copies of `'config.site'` in the source and the build directories, and both will be read (in that order). In addition, if there is a file `'~/R/config'` (or failing that) `'~/Rconfig'`, it is read between the `'config.site'` files in the source and the build directories.

There is also a general `autoconf` mechanism for `'config.site'` files, which are read before any of those mentioned in the previous paragraph. This looks first at a file specified by the environment variable `CONFIG_SITE`, and if not is set at files such as `'/usr/local/share/config.site'` and `'/usr/local/etc/config.site'` in the area (exemplified by `'/usr/local'`) where R would be installed.

These variables are *precious*, implying that they do not have to be exported to the environment, are kept in the cache even if not specified on the command line, checked for consistency between two configure runs (provided that caching is used), and are kept during automatic reconfiguration as if having been passed as command line arguments, even if no cache is used.

See the variable output section of `configure --help` for a list of all these variables.

If you find you need to alter configure variables, it is worth noting that some settings may be cached in the file `'config.cache'`, and it is a good idea to remove that file (if it exists) before re-configuring. Note that caching is turned *off* by default: use the command line option `'--config-cache'` (or `'-C'`) to enable caching.

B.4.1 Setting paper size

One common variable to change is `R_PAPERSIZE`, which defaults to `'a4'`, not `'letter'`. (Valid values are `'a4'`, `'letter'`, `'legal'` and `'executive'`.)

This is used both when configuring R to set the default, and when running R to override the default. It is also used to set the paper size when making PDF manuals.

The configure default will most often be `'a4'` if `R_PAPERSIZE` is unset. (If the (Debian Linux) program `paperconf` is found or the environment variable `PAPERSIZE` is set, these are used to produce the default.)

B.4.2 Setting the browsers

Another precious variable is `R_BROWSER`, the default HTML browser, which should take a value of an executable in the user's path or specify a full path.

Its counterpart for PDF files is `R_PDFVIEWER`.

B.4.3 Compilation flags

If you have libraries and header files, e.g., for GNU readline, in non-system directories, use the variables `LDFLAGS` (for libraries, using `'-L'` flags to be passed to the linker) and `CPPFLAGS` (for header files, using `'-I'` flags to be passed to the C/C++ preprocessors), respectively, to specify these locations. These default to `'-L/usr/local/lib'` (`LDFLAGS`, `'-L/usr/local/lib64'` on most 64-bit Linux OSes) and `'-I/usr/local/include'` (`CPPFLAGS`) to catch the most common cases. If libraries are still not found, then maybe your compiler/linker does not support re-ordering of `'-L'` and `'-l'` flags (this has been reported to be a problem on HP-UX with the native `cc`). In this case, use a different compiler (or a front end shell script which does the re-ordering).

These flags can also be used to build a faster-running version of R. On most platforms using `gcc`, having `'-O3'` in `CFLAGS` and `FFLAGS` produces worthwhile performance gains with `gcc` and `gfortran`. On systems using the GNU linker (especially those using R as a shared library), it is likely that including `'-Wl,-O1'` in `LDFLAGS` is worthwhile, and `'-Bdirect,--hash-style=both,-Wl,-O1'` is recommended at <http://lwn.net/Articles/192624/>. Tuning compilation to a specific CPU family (e.g. `'-mtune=native'` for `gcc`) can give worthwhile performance gains, especially on older architectures such as `'ix86'`.

B.4.4 Making manuals

The default settings for making the manuals are controlled by `R_RD4PDF` and `R_PAPERSIZE`.

B.5 Setting the shell

By default the shell scripts such as `'R'` will be `'#!/bin/sh'` scripts (or using the `SHELL` chosen by `'configure'`). This is almost always satisfactory, but on a few systems `'/bin/sh'` is not a Bourne shell or clone, and the shell to be used can be changed by setting the configure variable `R_SHELL` to a suitable value (a full path to a shell, e.g. `'/usr/local/bin/bash'`).

B.6 Using make

To compile R, you will most likely find it easiest to use GNU **make**, although the Sun **make** works on Solaris, as does the native FreeBSD **make**. The native **make** has been reported to fail on SGI Irix 6.5 and Alpha/OSF1 (aka Tru64).

To build in a separate directory you need a **make** that uses the **VPATH** variable, for example GNU **make**, or Sun **make** on Solaris 7 or later.

dmake has also been used. e.g, on Solaris 10.

If you want to use a **make** by another name, for example if your GNU **make** is called '**gmake**', you need to set the variable **MAKE** at configure time, for example

```
./configure MAKE=gmake
```

B.7 Using FORTRAN

To compile R, you need a FORTRAN compiler. The default is to search for **f95**, **fort**, **xlf95**, **ifort**, **ifc**, **efc**, **pgf95** **lf95**, **gfortran**, **ftn**, **g95**, **f90**, **xlf90**, **pghpf**, **pgf90**, **epcf90**, **g77**, **f77**, **xlf**, **f77**, **pgf77**, **cf77**, **fort77**, **fl32**, **af77** (in that order)², and use whichever is found first; if none is found, R cannot be compiled. However, if **CC** is **gcc**, the matching FORTRAN compiler (**g77** for **gcc** 3 and **gfortran** for **gcc** 4) is used if available.

The search mechanism can be changed using the configure variable **F77** which specifies the command that runs the FORTRAN 77 compiler. If your FORTRAN compiler is in a non-standard location, you should set the environment variable **PATH** accordingly before running **configure**, or use the configure variable **F77** to specify its full path.

If your FORTRAN libraries are in slightly peculiar places, you should also look at **LD_LIBRARY_PATH** or your system's equivalent to make sure that all libraries are on this path.

Note that only FORTRAN compilers which convert identifiers to lower case are supported.

You must set whatever compilation flags (if any) are needed to ensure that FORTRAN **integer** is equivalent to a C **int** pointer and FORTRAN **double precision** is equivalent to a C **double** pointer. This is checked during the configuration process.

Some of the FORTRAN code makes use of **COMPLEX*16** variables, which is a Fortran 90 extension. This is checked for at configure time³, but you may need to avoid compiler flags⁴ asserting FORTRAN 77 compliance.

For performance reasons⁵ you may want to choose a FORTRAN 90/95 compiler.

It may be possible to use **f2c**, the FORTRAN-to-C converter (<http://www.netlib.org/f2c>), via a script. (An example script is given in '**scripts/f77_f2c**': this can be customized by setting the environment variables **F2C**, **F2CLIBS**, **CC** and **CPP**.) You will need to ensure that the FORTRAN type **integer** is translated to the C type **int**. Normally '**f2c.h**' contains '**typedef long int integer;**', which will work on a 32-bit platform but not on a 64-bit platform. If your compiler is not **gcc** you will need to set **FPICFLAGS** appropriately.

² On HP-UX **fort77** is the POSIX compliant FORTRAN compiler, and comes after **g77**.

³ as well as its equivalence to the **Rcomplex** structure defined in '**R_ext/Complex.h**'.

⁴ In particular, avoid **g77**'s '**-pedantic**', which gives confusing error messages.

⁵ e.g., to use an optimized BLAS on Sun/Sparc

B.7.1 Using gfortran

gfortran is the F95 compiler that is part of **gcc** 4.x.y. There were problems compiling R with the first release (**gcc** 4.0.0) and more with pre-releases, but these are resolved in later versions.

On Linux ‘x86_64’ systems there is an incompatibility in the return conventions for double-complex functions between **gfortran** and **g77** which results in the final example in **example(eigen)** hanging or segfaulting under external BLASs built under **g77**. This should be detected by a **configure** test.

The default **FFLAGS** and **FCFLAGS** chosen (by **autoconf**) for a GNU FORTRAN compiler is ‘-g -O2’. This has caused problems (segfaults and infinite loops) on ‘x86_64’ Linux in the past, but seems fine with **gfortran** 4.4.4 and later: for **gfortran** 4.3.x set **FFLAGS** and **FCFLAGS** to use at most ‘-O’.

B.8 Compile and load flags

A wide range of flags can be set in the file ‘**config.site**’ or as configure variables on the command line. We have already mentioned

CPPFLAGS header file search directory (‘-I’) and any other miscellaneous options for the C and C++ preprocessors and compilers

LDFLAGS path (‘-L’), stripping (‘-s’) and any other miscellaneous options for the linker and others include

CFLAGS debugging and optimization flags, C

MAIN_CFLAGS
ditto, for compiling the main program

SHLIB_CFLAGS
for shared objects

FFLAGS debugging and optimization flags, FORTRAN

SAFE_FFLAGS
ditto for source files which need exact floating point behaviour

MAIN_FFLAGS
ditto, for compiling the main program

SHLIB_FFLAGS
for shared objects

MAIN_LDFLAGS
additional flags for the main link

SHLIB_LDFLAGS
additional flags for linking the shared objects

LIBnn the primary library directory, ‘lib’ or ‘lib64’

CPICFLAGS
special flags for compiling C code to be turned into a shared object

FPICFLAGS

special flags for compiling Fortran code to be turned into a shared object

CXXPICFLAGS

special flags for compiling C++ code to be turned into a shared object

FCPICFLAGS

special flags for compiling Fortran 95 code to be turned into a shared object

DEFS

defines to be used when compiling C code in R itself

Library paths specified as ‘-L/lib/path’ in **LDFLAGS** are collected together and prepended to **LD_LIBRARY_PATH** (or your system’s equivalent), so there should be no need for ‘-R’ or ‘-rpath’ flags.

Variables such as **CPICFLAGS** are determined where possible by **configure**. Some systems allows two types of PIC flags, for example ‘-fpic’ and ‘-fPIC’, and if they differ the first allows only a limited number of symbols in a shared object. Since R as a shared library has about 6200 symbols, if in doubt use the larger version.

To compile a profiling version of R, one might for example want to use ‘**MAIN_CFLAGS**=-pg’, ‘**MAIN_FFLAGS**=-pg’, ‘**MAIN_LDFLAGS**=-pg’ on platforms where ‘-pg’ cannot be used with position-independent code.

Beware: it may be necessary to set **CFLAGS** and **FFLAGS** in ways compatible with the libraries to be used: one possible issue is the alignment of doubles, another is the way structures are passed.

On some platforms **configure** will select additional flags for **CFLAGS**, **CPPFLAGS**, **FFLAGS**, **CXXFLAGS** and **LIBS** in **R_XTRA_CFLAGS** (and so on). These are for options which are always required, for example to force IEC 60559 compliance.

Appendix C Platform notes

This section provides some notes on building R on different Unix-alike platforms. These notes are based on tests run on one or two systems in each case with particular sets of compilers and support libraries. Success in building R depends on the proper installation and functioning of support software; your results may differ if you have other versions of compilers and support libraries.

Older versions of this manual (for R < 2.10.0) contain notes on platforms such as HP-UX, IRIX and Alpha/OSF1 for which we have had no recent reports.

C.1 X11 issues

The ‘X11()’ graphics device is the one started automatically on Unix-alikes when plotting. As its name implies, it displays on a (local or remote) X server, and relies on the services provided by the X server.

The ‘modern’ version of the ‘X11()’ device is based on ‘cairo’ graphics and (in most implementations) uses ‘fontconfig’ to pick and render fonts. This is done on the server, and although there can be selection issues, they are more amenable than the issues with ‘X11()’ discussed in the rest of this section.

When X11 was designed, most displays were around 75dpi, whereas today they are of the order of 100dpi or more. If you find that X11() is reporting¹ missing font sizes, especially larger ones, it is likely that you are not using scalable fonts and have not installed the 100dpi versions of the X11 fonts. The names and details differ by system, but will likely have something like Fedora’s

```
xorg-x11-fonts-75dpi
xorg-x11-fonts-100dpi
xorg-x11-fonts-IS08859-2-75dpi
xorg-x11-fonts-Type1
xorg-x11-fonts-cyrillic
```

and you need to ensure that the ‘-100dpi’ versions are installed and on the X11 font path (check via `xset -q`). The ‘X11()’ device does try to set a pointsize and not a pixel size: laptop users may find the default setting of 12 too large (although very frequently laptop screens are set to a fictitious dpi to appear like a scaled-down desktop screen).

More complicated problems can occur in non-Western-European locales, so if you are using one, the first thing to check is that things work in the C locale. The likely issues are a failure to find any fonts or glyphs being rendered incorrectly (often as a pair of ASCII characters). X11 works by being asked for a font specification and coming up with its idea of a close match. For text (as distinct from the symbols used by plotmath), the specification is the first element of the option “X11fonts” which defaults to

```
"-adobe-helvetica-%s-%s-***%d-***-***-***"
```

If you are using a single-byte encoding, for example ISO 8859-2 in Eastern Europe or KOI8-R in Russian, use `xlsfonts` to find an appropriate family of fonts in your encoding (the last field in the listing). If you find none, it is likely that you need to install further font

¹ for example, X11 font at size 14 could not be loaded.

packages, such as ‘`xorg-x11-fonts-ISO8859-2-75dpi`’ and ‘`xorg-x11-fonts-cyrillic`’ shown in the listing above.

Multi-byte encodings (most commonly UTF-8) are even more complicated. There are few fonts in ‘`iso10646-1`’, the Unicode encoding, and they only contain a subset of the available glyphs (and are often fixed-width designed for use in terminals). In such locales *fontsets* are used, made up of fonts encoded in other encodings. If the locale you are using has an entry in the ‘`XLC_LOCALE`’ directory (typically ‘`/usr/share/X11/locale`’, it is likely that all you need to do is to pick a suitable font specification that has fonts in the encodings specified there. If not, you may have to get hold of a suitable locale entry for X11. This may mean that, for example, Japanese text can be displayed when running in ‘`ja_JP.UTF-8`’ but not when running in ‘`en_GB.UTF-8`’ on the same machine (although on some systems many UTF-8 X11 locales are aliased to ‘`en_US.UTF-8`’ which covers several character sets, e.g. ISO 8859-1 (Western European), JISX0208 (Kanji), KSC5601 (Korean), GB2312 (Chinese Han) and JISX0201 (Kana)).

On some systems scalable fonts are available covering a wide range of glyphs. One source is TrueType/OpenType fonts, and these can provide high coverage. Another is Type 1 fonts: the URW set of Type 1 fonts provides standard typefaces such as Helvetica with a larger coverage of Unicode glyphs than the standard X11 bitmaps, including Cyrillic. These are generally not part of the default install, and the X server may need to be configured to use them. They might be under the X11 ‘`fonts`’ directory or elsewhere, for example,

```
/usr/share/fonts/default/Type1
/usr/share/fonts/ja/TrueType
```

C.2 Linux

Linux is the main development platform for R, so compilation from the sources is normally straightforward with the standard compilers.

Remember that some package management systems (such as RPM and deb) make a distinction between the user version of a package and the developer version. The latter usually has the same name but with the extension ‘`-devel`’ or ‘`-dev`’: you need both versions installed. So please check the `configure` output to see if the expected features are detected: if for example ‘`readline`’ is missing add the developer package. (On most systems you will also need ‘`ncurses`’ and its developer package, although these should be dependencies of the ‘`readline`’ package(s).)

When R has been installed from a binary distribution there are sometimes problems with missing components such as the FORTRAN compiler. Searching the ‘`R-help`’ archives will normally reveal what is needed.

It seems that ‘`ix86`’ Linux accepts non-PIC code in shared libraries, but this is not necessarily so on other platforms, in particular on 64-bit CPUs such as ‘`x86_64`’. So care can be needed with BLAS libraries and when building R as a shared library to ensure that position-independent code is used in any static libraries (such as the Tcl/Tk libraries, `libpng`, `libjpeg` and `zlib`) which might be linked against. Fortunately these are normally built as shared libraries with the exception of the ATLAS BLAS libraries.

The default optimization settings chosen for `CFLAGS` etc are conservative. It is likely that using ‘`-mtune`’ will result in significant performance improvements on recent CPUs (especially for ‘`ix86`’): one possibility is to add ‘`-mtune=native`’ for the best possible

performance on the machine on which R is being installed: if the compilation is for a site-wide installation, it may still be desirable to use something like `'-mtune=core2'`.² It is also possible to increase the optimization levels to `'-O3'`: however for many versions of the compilers this has caused problems in at least one CRAN package.

For platforms with both 64- and 32-bit support, it is likely that

```
LDFLAGS="-L/usr/local/lib64 -L/usr/local/lib"
```

is appropriate since most (but not all) software installs its 64-bit libraries in `'/usr/local/lib64'`. To build a 32-bit version of R on `'x86_64'` with Fedora 16 we used

```
CC="gcc -m32"
CXX="g++ -m32"
F77="gfortran -m32"
FC=${F77}
OBJC=${CC}
LDFLAGS="-L/usr/local/lib"
LIBnn=lib
```

Note the use of `'LIBnn'`: `'x86_64'` Fedora installs its 64-bit software in `'/usr/lib64'` and 32-bit software in `'/usr/lib'`. Linking will skip over inappropriate binaries, but for example the 32-bit Tcl/Tk configure scripts are in `'/usr/lib'`. It may also be necessary to set the `pkg-config` path, e.g. by

```
export PKG_CONFIG_PATH=/usr/local/lib/pkgconfig:/usr/lib/pkgconfig
```

64-bit versions of Linux are built with support for files > 2Gb, and 32-bit versions will be if possible unless `'--disable-largefile'` is specified.

To build a 64-bit version of R on `'ppc64'` (also known as `'powerpc64'`) with gcc 4.1.1, Ei-ji Nakama used

```
CC="gcc -m64"
CXX="gxx -m64"
F77="gfortran -m64"
FC="gfortran -m64"
CFLAGS="-mminimal-toc -fno-optimize-sibling-calls -g -O2"
FFLAGS="-mminimal-toc -fno-optimize-sibling-calls -g -O2"
```

the additional flags being needed to resolve problems linking against `'libnmath.a'` and when linking R as a shared library.

C.2.1 Clang

R has been built with Linux `'ix86'` and `'x86_64'` C and C++ compilers (<http://clang.llvm.org>, versions 2.9 and 3.0) based on the Clang front-ends, invoked by `CC=clang CXX=clang++`, together with `gfortran`. These take very similar options to the corresponding GCC compilers.

C.2.2 Intel compilers

Intel compilers have been used under `'ix86'` and `'x86_64'` Linux. Brian Ripley used version 9.0 of the compilers for `'x86_64'` on Fedora Core 5 with

² or `-mtune=corei7` for Intel Core i3/15/17 with gcc >= 4.6.0.

```

CC=icc
CFLAGS="-g -O3 -wd188 -ip -mp"
F77=ifort
FLAGS="-g -O3 -mp"
CXX=icpc
CXXFLAGS="-g -O3 -mp"
FC=ifort
FCFLAGS="-g -O3 -mp"
ICC_LIBS=/opt/compilers/intel/cce/9.1.039/lib
IFC_LIBS=/opt/compilers/intel/fce/9.1.033/lib
LDFLAGS="-L$ICC_LIBS -L$IFC_LIBS -L/usr/local/lib64"
SHLIB_CXXLD=icpc

```

configure will add ‘-c99’ to CC for C99-compliance. This causes warnings with `icc` 10 and later, so use `CC="icc -std=c99"` there. The flag ‘-wd188’ suppresses a large number of warnings about the enumeration type ‘`Rboolean`’. Because the Intel C compiler sets ‘`__GNUC__`’ without complete emulation of `gcc`, we suggest adding `CPPFLAGS=-no-gcc`.

To maintain correct IEC 60559 arithmetic you most likely need add flags to `CFLAGS`, `FFLAGS` and `CXXFLAGS` such as ‘-mp’ (shown above) or ‘-fp-model precise -fp-model source’, depending on the compiler version.

For some comments on building on an Itanium (‘ia64’) Linux system with `gcc` or the Intel compilers see http://www.nakama.ne.jp/memo/ia64_linux/.

Others have reported success with versions 10.x and 11.x.

C.2.3 Oracle Solaris Studio compilers

Brian Ripley tested the Sun Studio 12 compilers, since renamed to Oracle Solaris Studio, (<http://developers.sun.com/sunstudio/index.jsp>) On ‘x86_64’ Linux with

```

CC=suncc
CFLAGS="-xO5 -xc99 -xlibmil -nofstore"
CPICFLAGS=-Kpic
F77=sunf95
FFLAGS="-O5 -libmil -nofstore"
FPICFLAGS=-Kpic
CXX="sunCC -library=stlport4"
CXXFLAGS="-xO5 -xlibmil -nofstore -features=tmplrefstatic"
CXXPICFLAGS=-Kpic
FC=sunf95
FCFLAGS=$FFLAGS
FCPICFLAGS=-Kpic
LDFLAGS=-L/opt/sunstudio12.1/rtlibs/amd64
SHLIB_LDFLAGS=-shared
SHLIB_CXXLDFLAGS=-G
SHLIB_FCLDFLAGS=-G
SAFE_FFLAGS="-O5 -libmil"

```

‘-m64’ could be added, but was the default. Do not use ‘-fast’: see the warnings under Solaris. (The C++ options are also explained under Solaris.)

Others have found on at least some versions of ‘ix86’ Linux that the configure flag ‘--disable-largefile’ was needed (since ‘glob.h’ on that platform presumed gcc was being used).

C.3 FreeBSD

Rainer Hurling has reported success on ‘amd64’ FreeBSD 9.0 (and on earlier versions in the past), and Brian Ripley tested ‘amd64’ FreeBSD 8.2. Since Darwin (the base OS of (Mac) OS X) is based on FreeBSD we find testing on Darwin tends to pick up most potential problems on FreeBSD. However, FreeBSD lacks adequate collation support for multi-byte locales (but a port of ICU is available), and does not yet implement C99 complex math functions (for which R’s substitutes are used).

The native BSD **make** suffices to build R but a number of packages require GNU **make**, despite the recommendations of the “Writing R Extensions” manual. (The BSD version is **bsdmake** on Darwin.)

The simplest way to get the additional software needed to build R is to install a pre-compiled version first, e.g. by

```
pkg_add -r R
```

(on the system this was tested on, this installed Tcl, Tk, blas, lapack and gcc-4.6.2 which includes gfortran46). A listing of dependencies (not necessarily for current R) can be found at <http://www.freebsd.org/ports/lang.html>: you will however also need a T_EX system³ to build the manuals.

Then R itself can be built by something like

```
./configure CC=gcc46 F77=gfortran46 CXX=g++46 FC=gfortran46
```

There are also FreeBSD packages for a small eclectic collection of CRAN packages.

C.4 (Mac) OS X

You can build R as a Unix application on OS X using the Apple Developer Tools (‘Xcode’) and gfortran. You may also need to install an X sub-system or configure with ‘--without-x’. The X window manager is part of the standard OS X distribution since OS X version 10.3 (Panther), but it is typically not pre-installed prior to 10.5 (Leopard). You will also need gfortran and libreadline (or configure with ‘--without-readline’).

For more information on how to find these tools please read the [R for Mac OS X FAQ](#) or look at <http://r.research.att.com/tools/>. You will typically need to install Xcode and a matching version of gfortran from the tools page.

The vecLib library can be used *via* the (default) configuration options

```
--with-blas="-framework vecLib" --with-lapack
```

to provide higher-performance versions of the BLAS and LAPACK routines. Building R without these options *via*

```
--without-blas --without-lapack
```

can be done (and is provided as an alternative in the binary distribution).

³ TeXLive is recommended.

C.4.1 64-bit builds

64-bit builds are supported on 10.5.x (Leopard) and later. All that is needed is to select suitable compiler options, e.g. for most Intel Macs

```
CC='gcc -arch x86_64'
CXX='g++ -arch x86_64'
F77='gfortran -arch x86_64'
FC='gfortran -arch x86_64'
OBJC='gcc -arch x86_64'
```

in ‘`config.site`’ or on the `configure` command line. (Or on Leopard specify ‘`gcc-4.2`’ etc: those versions are the default on Snow Leopard.)

C.4.2 Snow Leopard

On Snow Leopard you will most likely to need to specify ‘`-arch i386`’ for a 32-bit build and ‘`-arch x86_64`’ for a 64-bit build: the Apple compilers default to 64-bit but the `gfortran` supplied on <http://r.research.att.com> defaults to 32-bit.

Another quirk is that the X11 libraries are not in the default linking path, so something like ‘`LIBS=-L/usr/X11/lib`’ may be required (or you can use the `configure` options ‘`--x-includes=/usr/X11/include --x-libraries=/usr/X11/lib.`’).

So for a 64-bit build of R you need a file ‘`config.site`’ in the top-level build directory containing

```
CC='gcc -arch x86_64'
CXX='g++ -arch x86_64'
F77='gfortran -arch x86_64'
FC='gfortran -arch x86_64'
OBJC='gcc -arch x86_64'
LIBS=-L/usr/X11/lib
```

whereas for a 32-bit build it should have

```
CC='gcc -arch i386'
CXX='g++ -arch i386'
F77='gfortran -arch i386'
FC='gfortran -arch i386'
OBJC='gcc -arch i386'
LIBS=-L/usr/X11/lib
```

C.4.3 Lion

With Xcode 4.2 you need to install a package named like <http://r.research.att.com/tools/gcc-42-5666.3-darwin11.pkg> to provide compilers named `gcc-4.2`, `g++-4.2` and `gfortran-4.2`. These default to 64-bit, so for a 64-bit build ‘`config.site`’ in the top-level build directory should contain

```
CC=gcc-4.2
CXX=g++-4.2
F77=gfortran-4.2
FC=gfortran-4.2
OBJC=gcc-4.2
```

and for a 32-bit build add `'-arch i386'` as displayed under Snow Leopard.

It is also possible to build R using Apple's C/C++ compilers supplied with Xcode, but these do need to be supplemented by a Fortran compiler (such as `gfortran-4.2`). `/usr/bin/gcc` is a link to `llvm-gcc`, an LLVM-based compiler with a `gcc 4.2.1` front end, and `clang` can also be used (and `clang++` for C++).

C.5 Solaris

R has been built successfully on Solaris 10 (both Sparc and 'x86') using the (zero cost) Oracle Solaris Studio compilers: there has been some success with `gcc 4/gfortran`. Sun packages for R used to be available from <http://www.sunfreeware.com/> for both 32-bit architectures, but recently have often been many versions old. (Recent Sun machines are AMD Opterons or Intel Xeons ('amd64') rather than 'x86', but 32-bit 'x86' executables are the default.)

There have been no reports on Solaris 11. Solaris 9 and earlier are now so old that it is unlikely that R is still used with them, and they will not be considered here.

The Solaris versions of several of the tools needed to build R (e.g. `make`, `ar` and `ld`) are in `'/usr/ccs/bin'`, so if using those tools ensure this is in your path. A version of the preferred GNU `tar` is (if installed) in `'/usr/sfw/bin'`, as sometimes are tools like `makeinfo`. It may be necessary to avoid the tools in `'/usr/ucb'`: POSIX-compliant versions of some tools can be found in `'/usr/xpg4/bin'` and `'/usr/xpg6/bin'`.

A large selection of Open Source software can be installed from <http://www.opencsw.org> (and also <http://www.blastwave.org>) via `pkg-get`, by default installed under `'/opt/csw'`.

You will need GNU `libiconv` and `readline`: the Solaris version of `iconv` is not sufficiently powerful.

The native `make` suffices to build R but a small number of packages require GNU `make` (some without good reason and without declaring it as 'SystemRequirements' in the 'DESCRIPTION' file).

Some people have reported that the Solaris `libintl` needs to be avoided, for example by using `'--disable-nls'` or `'--with-included-gettext'` or using `libintl` from OpenCSW.

When using the Oracle compilers⁴ do *not* specify `'-fast'`, as this disables IEEE arithmetic and `make check` will fail.

For the Solaris Studio compilers a little juggling of paths was needed to ensure GNU `libiconv` (in `'/usr/local'`) was used rather than the Solaris `iconv`:

```
CC="cc -xc99"
CFLAGS="-O -xlibmieee"
F77=f95
FFLAGS=-O
CXX="CC -library=stlport4"
CXXFLAGS=-O
FC=f95
FCFLAGS=$FFLAGS
FCLIBS="-lfai -lfsu"
```

⁴ including `gcc` for Sparc from Oracle.

```
R_LD_LIBRARY_PATH="/usr/local/lib:/opt/csw/gcc4/lib:/opt/csw/lib"
```

For a 64-bit target add ‘-m64’ to the compiler macros and use something like `LD_FLAGS=-L/usr/local/lib/sparcv9` or `LD_FLAGS=-L/usr/local/lib/amd64` as appropriate. It will also be necessary to point `pkg-config` at the 64-bit directories, e.g. one of

```
PKG_CONFIG_PATH=/opt/csw/lib/amd64/pkgconfig:/usr/lib/amd64/pkgconfig
PKG_CONFIG_PATH=/opt/csw/lib/sparcv9/pkgconfig:/usr/lib/sparcv9/pkgconfig
```

and to specify a 64-bit Java VM by e.g.

```
JAVA_LD_LIBRARY_PATH = $(JAVA_HOME)/lib/amd64/server
JAVA_LIBS = -L$(JAVA_HOME)/lib/amd64/server \
-R$(JAVA_HOME)/lib/amd64/server -ljvm
```

With Solaris Studio 12.[23] on Sparc, `FCLIBS` needs to be

```
FCLIBS="-lfai -lfai2 -lfsu"
```

(and possibly other Fortran libraries, but this suffices for the packages currently on CRAN).

Currently ‘amd64’ and ‘sparcv9’ builds work out-of-the-box with Sun Studio 12u1 but not Solaris Studio 12.2 and later: ‘libRblas.so’ and ‘lapack.so’ are generated with code that causes relocation errors (which is being linked in from the Fortran libraries). This means that building R as a shared library may be impossible with Solaris Studio \geq 12.2. For a standard build the trick seems to be to manually set `FLIBS` to avoid the troublesome libraries. For example, on ‘amd64’ set in ‘`config.site`’ something like

```
FLIBS_IN_S0="-R/opt/solarisstudio12.3/lib/amd64
/opt/solarisstudio12.3/lib/amd64/libfui.so
/opt/solarisstudio12.3/lib/amd64/libfsu.so"
```

For 64-bit Sparc, set in ‘`config.site`’ something like

```
FLIBS="-R/opt/solarisstudio12.3/prod/lib/sparc/64
-lifai -lsunimath -lfai -lfai2 -lfsu -lfsumai -lfprodai -lfminlai -lfmaxlai
-lfminvai -lfmaxvai -lfui -lsunmath -lmtsk
/opt/solarisstudio12.3/prod/lib/sparc/64/libfsu.so.1"
```

By default the Solaris Studio compilers do not by default conform to the C99 standard (appendix F 8.9) on the return values of functions such as `log`: use ‘-xlibmieee’ to ensure this.

You can target specific Sparc architectures for (slightly) higher performance: ‘-xtarget=native’ (in `CFLAGS` etc) tunes the compilation to the current machine.

Using `-xlibmil` in `CFLAGS` and `-xlibmil` in `FFLAGS` allows more system mathematical functions to be inlined.

On ‘x86’ you will get marginally higher performance *via*

```
CFLAGS="-x05 -xc99 -xlibmieee -xlibmil -nofstore -xtarget=native"
FFLAGS="-O5 -libmil -nofstore -xtarget=native"
CXXFLAGS="-x05 -xlibmil -nofstore -xtarget=native"
SAFE_FFLAGS="-libmil -fstore -xtarget=native"
```

but the use of `-nofstore` can be less numerically stable, and some packages (notably **mgcv** on ‘x86’) failed to compile at higher optimization levels with version 12.3.

The Solaris Studio compilers provide several implementations of the C++ standard which select both the set of headers and a C++ runtime library. These are selected

by the ‘`-library`’ flag, which as it is needed for both compiling and linking is best specified as part of the compiler. The examples above use ‘`stlport4`’, currently the most modern of the options: the default (but still needed to be specified as it is needed for linking) is ‘`Cstd`’: see http://developers.sun.com/solaris/articles/cmp_stlport_libCstd.html. Note though that most external Solaris C++ libraries will have been built with ‘`Cstd`’ and so an R package using such libraries also needs to be. Occasionally the flag ‘`-library=stlport4,Crun`’ has been needed.

Several CRAN packages using C++ need the more liberal interpretation given by adding

```
CXXFLAGS="-features=tmplrefstatic"
```

The performance library `sunperf` is available for use with the Solaris Studio compilers. If selected as a BLAS, it must also be selected as LAPACK *via* (for Solaris Studio 12.2)

```
./configure --with-blas='-library=sunperf' --with-lapack
```

This has often given test failures in the past, in several different places. At the time of writing it fails in ‘`tests/reg-BLAS.R`’, and on some builds, including for ‘`amd64`’, it fails in `example(eigen)`.

C.5.1 Using gcc

If using `gcc`, ensure that the compiler was compiled for the version of Solaris in use. (This can be ascertained from `gcc -v`.) `gcc` makes modified versions of some header files, and several reports of problems were due to using `gcc` compiled on one version of Solaris on a later version.

Compilation for a 32-bit Sparc target with `gcc 4.6.2` needed

```
CPPFLAGS=-I/opt/csw/include
LDFLAGS="-L/opt/csw/gcc4/lib -L/opt/csw/lib"
```

and for a 64-bit Sparc target

```
CC="gcc -m64"
F77="gfortran -m64"
CXX="g++ -m64"
FC=$F77
CPPFLAGS=-I/opt/csw/include
LDFLAGS="-L/opt/csw/gcc4/lib/sparcv9 -L/opt/csw/lib/sparcv9"
```

Note that paths such as ‘`/opt/csw/gcc4/lib/sparcv9`’ may need to be in the `LD_LIBRARY_PATH` during configuration.

The compilation can be tuned to a particular cpu: the CRAN check system uses `-mtune=niagara2`.

Compilation for an ‘`x86`’ target with `gcc 4.6.2` needed

```
CC="/opt/csw/gcc4/bin/gcc -m32"
CPPFLAGS="-I/opt/csw/include -I/usr/local/include"
F77="/opt/csw/gcc4/bin/gfortran -m32"
CXX="/opt/csw/gcc4/bin/g++ -m32"
FC="/opt/csw/gcc4/bin/gfortran -m32"
LDFLAGS="-L/opt/csw/gcc4/lib -L/opt/csw/lib -L/usr/local/lib"
```

(`-L/opt/csw/lib` is needed since `TexLive 2011` was built using 32-bit `gcc`, and we need ‘`/opt/csw/lib`’ in `R_LD_LIBRARY_PATH`.)

For ‘amd64’ the builds have failed to complete in several different ways, currently with relocation errors for ‘libRblas.so’.

C.6 AIX

We no longer support AIX prior to 4.2, and `configure` will throw an error on such systems.

Ei-ji Nakama was able to build under AIX 5.2 on ‘powerpc’ with GCC 4.0.3 in several configurations. 32-bit versions could be configured with ‘--without-iconv’ as well as ‘--enable-R-shlib’. For 64-bit versions he used

```
OBJECT_MODE=64
CC="gcc -maix64"
CXX="g++ -maix64"
F77="gfortran -maix64"
FC="gfortran -maix64"
```

and was also able to build with the IBM `xlc` and Hitachi `f90` compilers by

```
OBJECT_MODE=64
CC="xlc -q64"
CXX="g++ -maix64"
F77="f90 -cpu=pwr4 -hf77 -parallel=0 -i,L -O3 -64"
FC="f90 -cpu=pwr4 -hf77 -parallel=0 -i,L -O3 -64"
FLIBS="-L/opt/ofort90/lib -lh90vecmath -lh90math -lf90"
```

Some systems have `f95` as an IBM compiler that does not by default accept FORTRAN 77. It needs the flag ‘-qfixed=72’, or to be invoked as `xlf_r`.

The AIX native `iconv` does not support encodings ‘latin1’ nor ‘’ and so cannot be used. (As far as we know GNU `libiconv` could be installed.)

Fan Long reports success on AIX 5.3 using

```
OBJECT_MODE=64
LIBICONV=/where/libiconv/installed
CC="xlc_r -q64"
CFLAGS="-O -qstrict"
CXX="xlC_r -q64"
CXXFLAGS="-O -qstrict"
F77="xlf_r -q64"
AR="ar -X64"
CPPFLAGS="-I$LIBICONV/include -I/usr/lpp/X11/include/X11"
LDFLAGS="-L$LIBICONV/lib -L/usr/lib -L/usr/X11R6/lib"
```

On one AIX 6.x system it was necessary to use `R_SHELL` to set the default shell to be Bash rather than Zsh.

Kurt Hornik and Stefan Theussl at WU (Wirtschaftsuniversität Wien) successfully built R on a ‘powerpc’ (8-CPU Power6 system) running AIX 6.1, configuring with or without ‘--enable-R-shlib’ (Ei-ji Nakama’s support is gratefully acknowledged).

It helps to describe the WU build environment first. A small part of the software needed to build R and/or install packages is available directly from the AIX Installation DVDs, e.g., Java 6, X11, and Perl. Additional open source software (OSS) is packaged for AIX in ‘.rpm’ files and available from both IBM’s “AIX Toolbox for Linux

Applications” (<http://www-03.ibm.com/systems/power/software/aix/linux/>) and <http://www.oss4aix.org/download/>. The latter website typically offers more recent versions of the available OSS. All tools needed and libraries downloaded from these repositories (e.g., GCC, Make, libreadline, etc.) are typically installed to ‘/opt/freeware’, hence corresponding executables are found in ‘/opt/freeware/bin’ which thus needs to be in PATH for using these tools. As on other Unix systems one needs GNU libiconv as the AIX version of iconv is not sufficiently powerful. Additionally, for proper Unicode compatibility one should install the corresponding package from the ICU project (<http://www.icu-project.org/download/>), which offers pre-compiled binaries for various platforms which in case of AIX can be installed via unpacking the tarball to the root file system. For full L^AT_EX support one can install the T_EX Live DVD distribution (<http://www.tug.org/texlive/>): it is recommended to update the distribution using the tlmgr update manager. For 64-bit R builds supporting Tcl/Tk this needs to be installed from the sources as available pre-compiled binaries supply only 32-bit shared objects.

The recent WU testing was done using compilers from both the GNU Compiler Collection (version 4.2.4) which is available from one of the above OSS repositories, and the IBM C/C++ (XL C/C++ 10.01) as well as FORTRAN (XL Fortran 12.01) compilers (<http://www14.software.ibm.com/webapp/download/byproduct.jsp#X>).

To compile for a 64-bit ‘powerpc’ (Power6 CPU) target one can use

```
CC="gcc -maix64 -pthread"
CXX="g++ -maix64 -pthread"
FC="gfortran -maix64 -pthread"
F77="gfortran -maix64 -pthread"
CFLAGS="-O2 -g -mcpu=power6"
FFLAGS="-O2 -g -mcpu=power6"
FCFLAGS="-O2 -g -mcpu=power6"
```

for the GCC and

```
CC=xlc
CXX=xlc++
FC=xlf
F77=xlf
CFLAGS="-qarch=auto -qcache=auto -qtune=auto -O3 -qstrict -ma"
FFLAGS="-qarch=auto -qcache=auto -qtune=auto -O3 -qstrict"
FCFLAGS="-qarch=auto -qcache=auto -qtune=auto -O3 -qstrict"
CXXFLAGS="-qarch=auto -qcache=auto -qtune=auto -O3 -qstrict"
```

for the IBM XL compilers. For the latter, it is important to note that the decision for generating 32-bit or 64-bit code is done by setting the OBJECT_MODE environment variable appropriately (recommended) or using an additional compiler flag (‘-q32’ or ‘-q64’). By default the IBM XL compilers produce 32 bit code. Thus, to build R with 64-bit support one needs to either export OBJECT_MODE=64 in the environment or, alternatively, use the ‘-q64’ compiler options.

It is strongly recommended to install Bash and use it as the configure shell, e.g., via setting CONFIG_SHELL=/usr/bin/bash in the environment, and to use GNU Make (e.g., via (MAKE=/opt/freeware/bin/make)).

Further installation instructions to set up a proper R development environment can be found in the “R on AIX” project on R-Forge (<http://R-Forge.R-project.org/projects/aix/>).

C.7 Cygwin

The Cygwin emulation layer on Windows can be treated as a Unix-alike OS. This is unsupported, but experiments have been conducted and a few workarounds added. R requires C99 complex type support, which is available as from Cygwin 1.7.8 (March 2011). However, the (new) implementation of `cacos` gives incorrect results, so we undefine `HAVE_CACOS` in `src/main/complex.c` on that platform.

Many versions of Cygwin during 2011 were unable to build R: 1.7.9-1 with GCC 4.5.3-3 in November 2011 was able to do so.

Only building as a shared library can possibly work,⁵ so use e.g

```
./configure --disable-nls --enable-R-shlib FLIBS=-lgfortran
make
```

Enabling NLS does work if required, although adding `--with-included-gettext` is preferable. You will see many warnings about the use of auto-import. Setting `FLIBS` explicitly seems needed currently as the auto-detection gives an incorrect values.

You will need the **tetex-extra** Cygwin package to build `NEWS.pdf` and the vignettes.

Note that this gives you a command-line application using `readline` for command editing. The `'X11'` graphics device will work if a suitable X server is running, and the standard Unix-alike ways of installing source packages work. There was a bug in the `usr/lib/tkConfig.sh` script in the version we looked at, which needs to have

```
TK_LIB_SPEC='-ltk84'
```

The overhead of using shell scripts makes this noticeably slower than a native build of R on Windows.

Even when R can be built, not all the tests passed: there were incorrect results from wide-character regular expressions code and from sourcing CR-delimited files.

Do not use Cygwin’s BLAS library: it is known to give incorrect results.

C.8 New platforms

There are a number of sources of problems when installing R on a new hardware/OS platform. These include

Floating Point Arithmetic: R requires arithmetic compliant with IEC 60559, also known as IEEE 754. This mandates the use of plus and minus infinity and NaN (not a number) as well as specific details of rounding. Although almost all current FPUs can support this, selecting such support can be a pain. The problem is that there is no agreement on how to set the signalling behaviour; Sun/Sparc, SGI/IRIX and `'ix86'` Linux require no special action, FreeBSD requires a call to (the macro) `fpsetmask(0)` and OSF1 requires that computation be done with a `'-ieee_with_inexact'` flag etc. On a new platform you must find out the magic recipe and add some code to make it work. This can often be done via the file `'config.site'` which resides in the top level directory.

⁵ Windows DLLs need to have all links resolved at build time and so cannot resolve against `'R.bin'`.

Beware of using high levels of optimization, at least initially. On many compilers these reduce the degree of compliance to the IEEE model. For example, using `-fast` on the Solaris Studio compilers has caused R's NaN to be set incorrectly.

Shared Objects: There seems to be very little agreement across platforms on what needs to be done to build shared objects. there are many different combinations of flags for the compilers and loaders. GNU libtool cannot be used (yet), as it currently does not fully support FORTRAN: one would need a shell wrapper for this). The technique we use is to first interrogate the X window system about what it does (using `xmkmf`), and then override this in situations where we know better (for tools from the GNU Compiler Collection and/or platforms we know about). This typically works, but you may have to manually override the results. Scanning the manual entries for `cc` and `ld` usually reveals the correct incantation. Once you know the recipe you can modify the file `'config.site'` (following the instructions therein) so that the build will use these options.

It seems that `gcc 3.4.x` and later on `'ix86'` Linux defeat attempts by the LAPACK code to avoid computations entirely in extended-precision registers, so file `'src/modules/lapack/dlamc.f'` may need to be compiled without optimization. Set the configure variable `SAFE_FFLAGS` to the flags to be used for this file. If configure detects GNU FORTRAN it adds flag `'-ffloat-store'` to `FFLAGS`. (Other settings are needed when using `icc` on `'ix86'` Linux, for example. Using `'-mpc64'` is preferable on more recent GCC compilers.)

If you do manage to get R running on a new platform please let us know about it so we can modify the configuration procedures to include that platform.

If you are having trouble getting R to work on your platform please feel free to use the `'R-devel'` mailing list to ask questions. We have had a fair amount of practice at porting R to new platforms . . .

Appendix D The Windows toolset

If you want to build R or add-on packages from source in Windows, you will need to collect, install and test an extensive set of tools. See <http://cran.r-project.org/bin/windows/Rtools/> for the current locations and other updates to these instructions. (Most Windows users will not need to build add-on packages from source; see [Chapter 6 \[Add-on packages\]](#), [page 21](#) for details.)

We have found that the build process for R is quite sensitive to the choice of tools: please follow our instructions **exactly**, even to the choice of particular versions of the tools.¹ The build process for add-on packages is somewhat more forgiving, but we recommend using the exact toolset at first, and only substituting other tools once you are familiar with the process.

This appendix contains a lot of prescriptive comments. They are here as a result of bitter experience. Please do not report problems to the R mailing lists unless you have followed all the prescriptions.

We have collected most of the necessary tools (unfortunately not all, due to license or size limitations) into an executable installer named² ‘Rtools215.exe’, available from <http://cran.r-project.org/bin/windows/Rtools/>. You should download and run it, choosing the default “Package authoring installation” to build add-on packages, or the “full installation” if you intend to build R.

You will need the following items to build R and packages. See the subsections below for detailed descriptions.

- The command line tools (in ‘Rtools*.exe’)
- The MinGW-w64 32/64-bit toolchain to compile C, Fortran and C++.

For installing simple source packages containing data or R source but no compiled code, none of these are needed. Perl is no longer needed to build R nor to install nor develop source packages.

A complete build of R including PDF manuals, and producing the installer will also need the following:

- L^AT_EX
- The Inno Setup installer
- (optional) qpdf

It is important to set your PATH properly. The installer ‘Rtools*.exe’ optionally sets the path to components that it installs.

Your PATH may include ‘.’ first, then the ‘bin’ directories of the tools, the compiler toolchain and L^AT_EX. Do not use filepaths containing spaces: you can always use the short forms (found by `dir /x` at the Windows command line). Network shares (with paths starting \\) are not supported.

For example for a 32-bit build, all on one line,

¹ For example, the Cygwin version of `make 3.81` fails to work correctly.

² for R 2.14.2 and later.

```
PATH=c:\Rtools\bin;c:\Rtools\gcc-4.6.3\bin;c:\MiKTeX\miktex\bin;  
c:\R\R-2.15\bin\i386;c:\windows;c:\windows\system32
```

It is essential that the directory containing the command line tools comes first or second in the path: there are typically like-named tools³ in other directories, and they will **not** work. The ordering of the other directories is less important, but if in doubt, use the order above.

Our toolset contains copies of Cygwin DLLs that may conflict with other ones on your system if both are in the path at once. The normal recommendation is to delete the older ones; however, at one time we found our tools did not work with a newer version of the Cygwin DLLs, so it may be safest not to have any other version of the Cygwin DLLs in your path.

D.1 L^AT_EX

The ‘MiKTeX’ (<http://www.miktex.org/>) distribution of L^AT_EX includes a suitable port of pdftex. The ‘basic’ version of ‘MiKTeX’ almost suffices (the **grid** vignettes need ‘fancyvrb.sty’), but it will install the 15Mb ‘lm’ package if allowed to (although that is not actually used). The ‘Rtools*.exe’ installer does *not* include any version of L^AT_EX.

It is also possible to use the TeXLive distribution from <http://www.tug.org/texlive/>.

Please read [Section 2.3 \[Making the manuals\]](#), [page 5](#) about how to make ‘refman.pdf’ and set the environment variable R_RD4PDF suitably; ensure you have the required fonts installed or that ‘MiKTeX’ is set up to install L^AT_EX on first use.

D.2 The Inno Setup installer

To make the installer package (‘R-2.15.0-win.exe’) we currently require Inno Setup 5.3.7 or later (including 5.4.x) from <http://jrsoftware.org/>. We use the Unicode version and recommend that version be used. This is *not* included in ‘Rtools*.exe’.

Copy file ‘src/gnuwin32/MkRules.dist’ to ‘src/gnuwin32/MkRules.local’ and edit it to set ISDIR to the location where Inno Setup was installed.

D.3 The command line tools

This item is installed by the ‘Rtools*.exe’ installer.

If you choose to install these yourself, you will need suitable versions of at least **basename**, **cat**, **cmp**, **comm**, **cp**, **cut**, **date**, **diff**, **du**, **echo**, **expr**, **gzip**, **ls**, **make**, **makeinfo**, **mkdir**, **mv**, **rm**, **rsync**, **sed**, **sh**, **sort**, **tar**, **texindex**, **touch** and **uniq**; we use those from the Cygwin distribution (<http://www.cygwin.com/>) or compiled from the sources. You will also need **zip** and **unzip** from the Info-ZIP project (<http://www.info-zip.org/>). All of these tools are in ‘Rtools*.exe’.

Beware: ‘Native’ ports of **make** are **not** suitable (including those called ‘MinGW make’ at the MinGW SourceForge site and **mingw32-make** in some MinGW-w64 distributions). There were also problems with other versions of the Cygwin tools and DLLs. To avoid frustration, please use our tool set, and make sure it is at the front of your path (including

³ such as **sort**, **find** and perhaps **make**.

before the Windows system directories). If you are using a Windows shell, type `PATH` at the prompt to find out.

You may need to set the environment variable `CYGWIN` to a value including `'nodosfilewarning'` to suppress messages about Windows-style paths.

D.4 The MinGW-w64 toolchain

Technically you need more than just a compiler so the set of tools is referred to as a 'toolchain'.

The released version of R 2.15.0 will be built with a different toolchain from R 2.12.0 to 2.14.1. The preferred toolchain is part of `Rtools215.exe`: this uses a beta version of `gcc` 4.6.3 and version 2.0.1 of the MinGW-w64 project's runtime.

This toolchain uses *multilib*: that is there is a single front-end such as `gcc.exe` for each of the compilers and 32-bit (the default) and 64-bit compilation are selected by the flags⁴ `'-m32'` and `'-m64'` respectively. The tools are all 32-bit Windows executables and should be able to run on any current version of Windows—however you do need a 64-bit version of Windows to build 64-bit R as the build process runs R.

To select a 32-bit or 64-bit build of R, set the options in `'MkRules.local'` appropriately (following the comments in the file).

Some external software libraries will need to be re-compiled under the new toolchain: especially those providing a C++ interface. Many of those used by CRAN packages are available from <http://www.stats.ox.ac.uk/pub/Rtools/multilib/>. Users developing packages with **Rcpp** need to ensure that they use a version built with exactly the same toolchain as their package: the recommendation is to build **Rcpp** from its sources yourself.

There is support for OpenMP and pthreads in this toolchain. As the performance of OpenMP on Windows is poor for small tasks, it is not used for R itself.

D.5 Useful additional programs

The process of making the installer will make use of `qpdf` to compact some of the package vignettes, if it is available. Windows binaries of `qpdf` are available from <http://sourceforge.net/projects/qpdf/files/>. Set the path to the `qpdf` installation in file `'MkRules.local'`.

Developers of packages will find some of the 'goodies' at <http://www.stats.ox.ac.uk/pub/Rtools/goodies> useful.

There is a version of the `file` command that identifies the type of files, and is used by `Rcmd check` if available. The binary distribution is included in `'Rtools215.exe'`.

The file `'xzutils.zip'` contains the program `xz` which can be used to (de)compress files with that form of compression.

⁴ these flags apply to the compilers: some of the tools use different flags. 32-bit builds are the default.

Function and variable index

C

`configure` 3, 4, 6, 7, 46, 48

I

`install.packages` 22

M

`make` 48

R

`R_HOME` 3

`remove.packages` 25

U

`update.packages` 25

Concept index

A

AIX 60

B

BLAS library 40, 48, 55, 59

F

FORTRAN 48

FreeBSD 55

I

Installation 6

Installing under Unix-alikes 3

Installing under Windows 12

Internationalization 28

L

LAPACK library 43, 55, 59

Libraries 21

Libraries, managing 21

Libraries, site 21

Libraries, user 21

Linux 3, 52

Locale 28

Localization 28

M

Manuals 5

Manuals, installing 8

O

Obtaining pqR and R 1

OS X 3, 19, 55

P

Packages 21

Packages, default 21

Packages, installing 22

Packages, removing 25

Packages, updating 25

R

Rbitmap.dll 14

Repositories 26

S

Site libraries 21

Solaris 57

Sources for R 1

Subversion 2, 37

U

User libraries 21

V

Vignettes 37

W

winCairo.dll 14

Environment variable index

B

BLAS_LIBS 40

C

CC 48

CONFIG_SITE 46

CPP 48

CYGWIN 66

D

DESTDIR 8, 34

F

F2C 48

F2CLIBS 48

FPICFLAGS 48

J

JAVA_HOME 39

L

LANG 29

LANGUAGE 29, 30

LAPACK_LIBS 44

LC_ALL 29

LC_COLLATE 11

LC_MESSAGES 29

LD_LIBRARY_PATH 34, 41, 48, 50, 59

O

OBJECT_MODE 61

P

PAPERSIZE 47

PATH 37, 48, 61, 64

R

R_ARCH 9

R_BROWSER 47

R_DEFAULT_PACKAGES 21

R_DISABLE_HTTPD 5

R_GSCMD 39

R_INSTALL_TAR 23

R_JAVA_LD_LIBRARY_PATH 39

R_LIBS 21

R_LIBS_SITE 21

R_LIBS_USER 21

R_PAPERSIZE 5, 20, 47

R_PDFVIEWER 47

R_RD4PDF 6, 47, 65

R_SHELL 60

R_USER 20

T

TAR 37

TAR_OPTIONS 1, 13

TEMP 20

TMP 20

TMPDIR 3, 14, 20, 22