


# Module -13 Assignment


Q1.) Problem Statement: Create an image gallery using a CSS grid.



The screenshot shows the VS Code editor with the 'Answer1.html' file open. The file contains the following HTML code:

```
1 <!DOCTYPE html>
2 <html lang="en">
3 <head>
4   <meta charset="UTF-8">
5   <meta name="viewport" content="width=device-width, initial-scale=1.0">
6   <title>Image Gallery</title>
7   <link rel="stylesheet" href="styles1.css">
8 </head>
9 <body>
10   <div class="gallery">
11     <div class="gallery-item">
12       
13     </div>
14     <div class="gallery-item">
15       
16     </div>
17     <div class="gallery-item">
18       
19     </div>
20     <div class="gallery-item">
21       
22     </div>
23     <div class="gallery-item">
24       
25     </div>
26     <div class="gallery-item">
27       
28     </div>
29   </div>
30 </body>
31 </html>
32
```

The Explorer sidebar on the left shows the project structure, including the 'Images' folder and the 'styles1.css' file. The terminal at the bottom shows the output of the 'git status' command, indicating that the files are staged for commit.




The screenshot shows the VS Code editor with the 'styles1.css' file open. The file contains the following CSS code:

```
1 .gallery {
2   display: grid;
3   grid-template-columns: repeat(4, 1fr);
4   grid-template-rows: repeat(2, 200px);
5   grid-gap: 10px;
6   max-width: 1000px;
7   margin: 0 auto;
8 }
9
10 .gallery-item {
11   position: relative;
12   overflow: hidden;
13   border-radius: 5px;
14 }
15
16 .gallery-item img {
17   width: 100%;
18   height: 100%;
19   object-fit: cover;
20 }
21
22 .gallery-item:nth-child(1) {
23   grid-column: span 1;
24   grid-row: span 1;
25 }
26
27 .gallery-item:nth-child(2) {
28   grid-column: span 1;
29   grid-row: span 1;
30 }
31
32 .gallery-item:nth-child(3) {
33   grid-column: span 2;
34   grid-row: span 1;
35 }
36
37 .gallery-item:nth-child(4) {
38   grid-column: span 1;
39   grid-row: span 1;
40 }
41
42 .gallery-item:nth-child(5) {
43   grid-column: span 1;
44   grid-row: span 2;
45 }
46
47 .gallery-item:nth-child(6) {
48   grid-column: span 2;
49   grid-row: span 1;
50 }
51
52 @media (max-width: 768px) {
53   .gallery {
54     grid-template-columns: repeat(2, 1fr);
55   }
56 }
57
```

The Explorer sidebar on the left shows the project structure, including the 'styles1.css' file. The terminal at the bottom shows the output of the 'git status' command, indicating that the files are staged for commit.




**Q2.) Problem Statement: Write code to arrange containers with texts A, B, C, and D as shown in the below image.**



The screenshot shows a VS Code editor with a file explorer on the left and a code editor on the right. The file explorer shows a project structure with various files and folders. The code editor displays the following HTML and CSS code:


```
1 <!DOCTYPE html>
2 <html lang="en">
3 <head>
4   <meta charset="UTF-8">
5   <meta name="viewport" content="width=device-width, initial-scale=1.0">
6   <title>Container Layout</title>
7   <link rel="stylesheet" href="style2.css">
8 </head>
9 <body>
10  <div class="container">
11    <div class="box">A</div>
12    <div class="box">B</div>
13    <div class="box">C</div>
14    <div class="box">D</div>
15  </div>
16 </body>
17 </html>
```

```
1 {
2   margin: 0;
3   padding: 0;
4   box-sizing: border-box;
5 }
6
7 body {
8   display: flex;
9   justify-content: center;
10  align-items: center;
11  height: 100px;
12  background-color: #e0e0e0;
13 }
14
15 .container {
16   display: grid;
17   grid-template-columns: 1fr 1fr;
18   grid-template-rows: 1fr 1fr;
19   gap: 10px;
20   padding: 20px;
21   background-color: #ffffff;
22   border: 2px solid #000000;
23 }
24
25 .box {
26   display: flex;
27   justify-content: center;
28   align-items: center;
29   background-color: #ffffff;
30   font-size: 2em;
31   font-family: Arial, sans-serif;
32   padding: 20px;
33 }
```



The screenshot shows a VS Code editor with a file explorer on the left and a code editor on the right. The code editor displays the following CSS code:

```
1 {
2   margin: 0;
3   padding: 0;
4   box-sizing: border-box;
5 }
6
7 body {
8   display: flex;
9   justify-content: center;
10  align-items: center;
11  height: 100px;
12  background-color: #e0e0e0;
13 }
14
15 .container {
16   display: grid;
17   grid-template-columns: 1fr 1fr;
18   grid-template-rows: 1fr 1fr;
19   gap: 10px;
20   padding: 20px;
21   background-color: #ffffff;
22   border: 2px solid #000000;
23 }
24
25 .box {
26   display: flex;
27   justify-content: center;
28   align-items: center;
29   background-color: #ffffff;
30   font-size: 2em;
31   font-family: Arial, sans-serif;
32   padding: 20px;
33 }
34
35 /* Specific grid positioning */
36 .container > div:nth-child(1) {
37   grid-column: 1 / 3;
38   grid-row: 1;
39 }
40
41 .container > div:nth-child(2) {
42   grid-column: 2;
43   grid-row: 2;
44 }
45
46 .container > div:nth-child(3) {
47   grid-column: 1;
48   grid-row: 2;
49 }
50
51 .container > div:nth-child(4) {
52   grid-column: 1;
53   grid-row: 3;
54 }
55 }
```



### Q3.) Problem Statement: Explain the use of grid-auto-row and grid-auto-column using code examples.

The grid-auto-rows and grid-auto-columns properties in CSS Grid Layout control the size of implicitly created rows and columns. These rows and columns are created automatically by the browser when there aren't enough rows or columns defined to fit the placed grid items.

1. **grid-auto-rows**: Specifies the size for automatically created rows (i.e., rows created by the grid layout when an item is placed outside the explicitly defined rows).

Example: <!DOCTYPE html>

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
<style>
```

```
.container {
```

```
  display: grid;
```

```
  grid-template-columns: 100px 100px; /* Two columns */
```

```
  grid-auto-rows: 150px; /* Automatically created rows will be 150px tall */
```

```
  gap: 10px;
```

```
  background-color: #f0f0f0;
```

```
}
```

```
.box {
```

```
  background-color: #ffb6c1;
```

```
  display: flex;
```

```
  justify-content: center;
```

```
  align-items: center;
```

```
  font-size: 1.5em;
```

```
  height: 100px;
```

```
}
```

```
/* Place the fourth box in the second row, which will be automatically created */
```

```
.box:nth-child(4) {
```

```
  grid-column: 1; /* First column */
```

```
  grid-row: 2; /* Second row (auto-created) */
```

```

    }
  </style>
</head>
<body>
  <div class="container">
    <div class="box">1</div>
    <div class="box">2</div>
    <div class="box">3</div>
    <div class="box">4</div> <!-- This will be in the automatically created second
row -->
  </div>
</body>
</html>

```

2. **grid-auto-columns:** Specifies the size for automatically created columns (i.e., columns created when an item is placed outside the explicitly defined columns).

Example: <!DOCTYPE html>

```

<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <style>
    .container {
      display: grid;
      grid-template-rows: 100px; /* One row */
      grid-template-columns: 100px 100px; /* Two columns */
      grid-auto-columns: 150px; /* Automatically created columns will be 150px wide */
      gap: 10px;
      background-color: #f0f0f0;
    }


    .box {
      background-color: #ffb6c1;
      display: flex;
      justify-content: center;
      align-items: center;
      font-size: 1.5em;
    }
  </style>

```



```
    /* Place the fourth box in the third column, which will be automatically created */
    .box:nth-child(4) {
        grid-column: 3; /* Third column (auto-created) */
    }
</style>
</head>
<body>
    <div class="container">
        <div class="box">1</div>
        <div class="box">2</div>
        <div class="box">3</div>
        <div class="box">4</div> <!-- This will be in the automatically created third column -->
    </div>
</body>
</html>
```

**Q4.) Problem Statement: Write CSS to show numbers as shown in the figure, without altering the below html code.**

```
<div class="container">
  <div class="box box1">1</div>
  <div class="box box2">2</div>
  <div class="box box3">3</div>
  <div class="box box4">4</div>
  <div class="box box5">5</div>
  <div class="box box6">6</div>
  <div class="box box7">7</div>
  <div class="box box8">8</div>
</div>
```







**Q5.) Problem Statement: Explain the difference between justify-items and justify-self using code examples.**

In CSS Grid Layout, justify-items and justify-self are both used to control the horizontal alignment of grid items, but they work at different levels.

1. **justify-items**: Aligns **all grid items** within their grid cells along the row (horizontal) axis.

Example: <!DOCTYPE html>

```
<html lang="en">
```

```
<head>
```

```
<meta charset="UTF-8">
```

```
<meta name="viewport" content="width=device-width, initial-scale=1.0">
```

```
<style>
```

```
.container {
```

```
  display: grid;
```

```
  grid-template-columns: 100px 100px; /* Two columns */
```

```
  grid-template-rows: 100px 100px; /* Two rows */
```

```
  gap: 10px;
```

```
  justify-items: center; /* Align all items in the center horizontally */
```

```
  background-color: #f0f0f0;
```

```
}
```

```
.box {
```

```
  background-color: #ffb6c1;
```

```
  display: flex;
```

```
  justify-content: center;
```

```
  align-items: center;
```

```
  font-size: 1.5em;
```

```
}
```

```
</style>
</head>
<body>
  <div class="container">
    <div class="box">1</div>
    <div class="box">2</div>
    <div class="box">3</div>
    <div class="box">4</div>
  </div>
</body>
</html>
```

2. **justify-self**: Aligns a **specific grid item** within its grid cell along the row (horizontal) axis.

Example: <!DOCTYPE html>

```
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <style>
    .container {
      display: grid;
      grid-template-columns: 100px 100px; /* Two columns */
      grid-template-rows: 100px 100px; /* Two rows */
      gap: 10px;
      background-color: #f0f0f0;
    }
  </style>
</head>
<body>
  <div class="container">
    <div class="box">1</div>
    <div class="box">2</div>
    <div class="box">3</div>
    <div class="box">4</div>
  </div>
</body>
</html>
```

```
.box {  
    background-color: #ffb6c1;  
    display: flex;  
    justify-content: center;  
    align-items: center;  
    font-size: 1.5em;  
}
```

```
/* Specific alignments for individual grid items */
```

```
.box:nth-child(1) {  
    justify-self: start; /* Align box 1 to the start of its cell */  
}
```

```
.box:nth-child(2) {  
    justify-self: end; /* Align box 2 to the end of its cell */  
}
```

```
.box:nth-child(3) {  
    justify-self: center; /* Align box 3 at the center of its cell */  
}
```

```
.box:nth-child(4) {  
    justify-self: stretch; /* Box 4 stretches to fill its cell */  
}
```

```
</style>
```

```
</head>
```

```
<body>
```

```
<div class="container">
```

<div class="box">1</div>

<div class="box">2</div>

<div class="box">3</div>

<div class="box">4</div>

</div>

</body>

</html>