

(base) sorenbasnet@Sorens-MacBook-Pro-2 datafiles % ./guide
GUIDE Classification and Regression Trees and Forests
Version 46.1 (Build date: January 23, 2026)
Compiled with NAG Fortran 7.2 on macOS Sequoia 15.6.1 for Apple ARM processors
Copyright (c) 1997-2026 Wei-Yin Loh. All rights reserved.
Software based upon work partially supported by the U.S. Army Research Office,
National Science Foundation, National Institutes of Health,
Bureau of Labor Statistics, USDA Economic Research Service, and Eli Lilly.

Choose one of the following options:

0. Read the warranty disclaimer

1. Create a GUIDE input file

Input your choice: 1

Name of batch input file: input.txt

Input 1 for model fitting, 2 for importance or DIF scoring, 3 for data conversion ([1:3], <cr>=1):

Name of batch output file: output.txt

Input 1 for single tree, 2 for ensemble ([1:2], <cr>=1):

Input 1 for classification, 2 for regression, 3 for propensity score tree

Input your choice ([1:3], <cr>=1):

Input 1 for default options, 2 otherwise ([1:2], <cr>=1):

Input name of DSC file (max 100 characters);

enclose with matching quotes if it has spaces: body.dsc

Reading DSC file ...

Training sample file: bodydata.txt

Missing value code: NA

Records in data file start on line 2

24 N variables changed to S

D variable is Gender

Reading data file ...

Number of records in data file: 507

Length of longest entry in data file: 5

Checking for missing values ...

Finished checking

Recoding D values to integers

Finished recoding

Number of classes: 2

Re-checking data ...

Assigning codes to missing values, if any ...

Data checks complete

Rereading data ...

Class #Cases Proportion

F 260 0.51282051

M 247 0.48717949

Numbers of N, F, S, and P below exclude constant variables

Total	#cases w/	#missing					
#cases	miss.	D	ord. vals	#X-var	#N-var	#F-var	#S-var
507	0	0	0	0	0	0	24
#P-var	#M-var	#B-var	#C-var	#I-var			
0	0	0	0	0			

Number of cases used for training: 507

Finished reading data file

Choose 1 for estimated priors, 2 for equal priors, 3 to input priors from a file

Input 1, 2, or 3 ([1:3], <cr>=1):

Choose 1 for unit misclassification costs, 2 to input costs from a file

Input 1 or 2 ([1:2], <cr>=1):

Default max. number of split levels: 15

Input 0=skip LaTeX tree, 1=tree without node numbers, 2=with node numbers ([0:2], <cr>=2):

Input file name to store LaTeX code (use .tex as suffix): class.tex

You can store the variables and/or values used to split and fit in a file

Choose 1 to skip this step, 2 to store split and fit variables,

3 to store split variables and their values

Input your choice ([1:3], <cr>=1):

Input 2 to save fitted values and node IDs, 1 otherwise ([1:2], <cr>=2):

Input name of file to store node ID and fitted value of each case: classfit.txt

You can output an R function for predicting future observations

Input 1 to skip this step

Input 2 to output an R function that applies to the training data

Input 3 to output an R function that applies to a new data set

Input your choice ([1:3], <cr>=2):

Input filename to write R function: class.r

Input rank of top variable to split root node ([1:24], <cr>=1):

Input file is created!

Run GUIDE with the command: guide < input.txt

Press ENTER or RETURN to quit

guide < input.txt