
CRYSTEK MICROWAVE
A Division of Crystek Corporation

Voltage Controlled Oscillator-VCO
CVCO55BE-0800-1600


PERFORMANCE SPECIFICATION	MIN	TYP	MAX	UNITS
Lower Frequency:			800	MHz
Upper Frequency:	1600			MHz
Tuning Voltage:	0.5		19.0	VDC
Supply Voltage:	11.0	11.5	12.0	VDC
Output Power:	+3.0	+7.5	+12.0	dBm
Supply Current:		15	30	mA
Harmonic Suppression (2nd Harmonic):		-10		dBc
Pushing:			2.0	MHz/V
Pulling, all Phases:			10.0	MHz pk-pk
Tuning Sensitivity:		60		MHz/V
Phase Noise @ 10kHz offset:		-95		dBc/Hz
Phase Noise @ 100kHz offset:		-115		dBc/Hz
Load Impedance:		50		Ω
Input Capacitance:			47	pF
Operating Temperature Range:	-40		+85	°C
Storage Temperature Range:	-45		+90	°C

RoHS Compliant

Phase Noise (1 Hz BW, Typical)



Tuning Curve (Typical)




Product Control:			
Crystek Part Number:	CVCO55BE-0800-1600	Release Date:	17-Sep-2025
Revision Level:	J	Responsible:	C. Vales


CRYSTEK CORPORATION
16850 Oriole Road • Fort Myers, Florida 33912
Phone: 239-561-3311 • 800-237-3061
www.crystek.com

Voltage Controlled Oscillator-VCO
CVCO55BE-0800-1600

BOTTOM VIEW





SIDE VIEW





TOP VIEW






Pad	Connection
2 10 14 Others	Vt RF-OUTPUT Vcc GROUND

- Unless otherwise specified, Dimensions are in: IN / (mm)
- Pad Location Dimensions are in: Inches

TAPE AND REEL



Drawing not to scale

Product Control:			
Crystek Part Number:	CVCO55BE-0800-1600	Release Date:	17-Sep-2025
Revision Level:	J	Responsible:	C. Vales

Crystek Corporation reserves the right to make changes to its products and/or information contained herein without notice. No liability is assumed as a result of its use or application.

CRYSTEK CORPORATION
16850 Oriole Road • Fort Myers, Florida 33912
Phone: 239-561-3311 • 800-237-3061
www.crystek.com