

Training-Free Ranking from Pairwise Comparisons via Acyclic Graph Construction

Soroush Vahidi

New Jersey Institute of Technology, Newark, NJ, USA

`sv96@njit.edu`

ORCID: 0000-0003-1934-6282

Abstract

Ranking from weighted pairwise comparisons asks for a global order that respects observed preferences as well as possible. We study a training-free, deterministic pipeline that builds an acyclic backbone on the comparison digraph using an MWFAS-inspired local-ratio heuristic, restores high-weight arcs under exact cycle-safe reinsertion, optionally applies a secondary weighted min-cut exchange, and extracts scores with optional order-preserving refinement. The local-ratio and exact add-back components follow prior lineage; this paper formalizes ranking–MWFAS optimum-value equivalence and practical guarantee boundaries, corrects a submitted topological-proxy weakening of add-back, and expands classical and GNN evaluation under timeout-aware common-completion analysis. Empirically, under the archived leaderboard configuration used for direct baseline tables, the pipeline is strong on simple/naive upset metrics against several baselines, competitive rather than uniformly superior to SpringRank, DavidScore, and SVD_NRS under family-aware analysis, and weaker than BTL on upset_ratio; structural ablations separately quantify the reachability correction. The method is slower than lightweight classical estimators yet substantially faster than archived trained GNNRank runs under an end-to-end protocol; the near-complete Finance graph marks a large-dense scalability boundary.

Keywords: Ranking; Pairwise comparisons; Feedback arc set; Directed graphs; Training-free methods

1 Introduction

Ranking from pairwise comparisons arises throughout statistics, machine learning, and network analysis, from sports analytics to preference aggregation. Methods typically return a real-valued score vector whose induced order is evaluated by upset-based losses He et al. (2022). Classical estimators are fast and training-free; learning-based directed GNNs such as GNNRank can be accurate but introduce training cost, hyper-parameter sensitivity, and reduced reproducibility.

Directed comparison graphs almost always contain cycles arising from noise, incompleteness, and local inconsistencies. A combinatorial response is to delete a set of directed arcs so that the remaining graph is acyclic, then read a ranking from a topological order of the resulting directed acyclic graph (DAG). This is the Minimum Weighted Feedback Arc Set (MWFAS) viewpoint: minimize the total weight of deleted comparisons subject to acyclicity. Related spectral and synchronization methods already note connections between ranking inconsistency and feedback structure Fogel et al. (2014); Cucuringu (2015). MWFAS is NP-hard Karp (1972), so exact minimization is generally impractical, yet the formulation supplies a precise consistency-restoration objective for ranking.

This paper develops a practical, training-free, deterministic, and time-bounded ranking pipeline rather than a new general MWFAS approximation algorithm (§1.2). Prior work by Vahidi and Koutis (2025)

already used the local-ratio heuristic of Demetrescu and Finocchi Demetrescu and Finocchi (2003) with weight-prioritized exact cycle-safe reinsertion and optional refinement. We clarify that lineage, correct an implementation-fidelity gap, add theory and a secondary structural repair, and expand empirical validation.

To make the ranking–MWFAS connection precise, we begin with formal definitions.

Definition 1 (Ranking Problem). *Let $G = (V, E)$ be a directed graph, where V is the set of items and E is the set of directed pairwise-comparison edges. Each edge $(i, j) \in E$ has weight $w_{ij} > 0$, representing the strength of the preference for i over j . A ranking is a total order on V , represented equivalently by a bijection $R : V \rightarrow \{1, \dots, |V|\}$, where smaller values indicate higher rank. An edge (i, j) is inconsistent with R if $R(i) > R(j)$. The goal is to find a ranking that minimizes the total weight of inconsistent edges:*

$$\min_R \sum_{(i,j) \in E: R(i) > R(j)} w_{ij}. \quad (1)$$

Definition 2 (Minimum Weighted Feedback Arc Set (MWFAS)). *Let $G = (V, E)$ be a directed graph with edge weights $w_{ij} > 0$ for each $(i, j) \in E$. A set of edges $F \subseteq E$ is a feedback arc set if removing F makes the graph acyclic, i.e., $(V, E \setminus F)$ is a directed acyclic graph (DAG). The MWFAS problem is*

$$\min_{F \subseteq E} \sum_{(i,j) \in F} w_{ij} \quad \text{s.t.} \quad (V, E \setminus F) \text{ is acyclic.} \quad (2)$$

The ranking objective (1) and MWFAS (2) share the same optimum *value*: the backward edges of any ranking form a feedback arc set of equal weight, and any feedback arc set induces a DAG whose topological orders realize that deleted weight as ranking disagreement. The correspondence between optimal rankings and optimal feedback arc sets is many-to-many rather than one-to-one; we treat this equivalence as a formal claim to be stated and proved, not merely asserted.

1.1 Scope, lineage, and contributions

The pipeline studied here (§2) builds an acyclic backbone with the local-ratio heuristic of Demetrescu and Finocchi (2003), reinserts high-weight arcs while preserving acyclicity, extracts scores from the resulting DAG, and optionally applies order-preserving refinement. Several components are *prior*: local-ratio Phase A, exact cycle-safe add-back (including weight ordering), and ternary/refinement ideas already appear in Demetrescu and Finocchi (2003); Vahidi and Koutis (2025). What this paper contributes is therefore not a reinvention of that core, but the following.

1. **Formalization and guarantee boundaries.** Ranking–MWFAS optimum-value equivalence (Prop. 1), implementation complexity, and when the Demetrescu–Finocchi guarantee does and does not transfer (§2.9).
2. **Implementation-fidelity correction.** Restore exact reachability-aware reinsertion in place of the submitted topological-position proxy (§2.5); ablations quantify the effect (§3.7).
3. **Secondary structural repair.** A conflict-triggered weighted min-cut exchange with monotone objective improvement (Prop. 3), with regime-specific empirics (§3.9).
4. **Expanded empirical validation.** Classical and GNN comparisons with timeout-aware common completions, paired statistics, family-aware sensitivity, and ablation/sensitivity analysis (§3). Dataset-count expansion is not treated as a primary novelty.

1.2 Related Work

1.2.1 Feedback Arc Set and MWFAS

The Minimum Weighted Feedback Arc Set (MWFAS) problem asks for a minimum-weight set of directed arcs whose removal makes a graph acyclic Karp (1972); Festa et al. (2020). Classical approximation results include divide-and-conquer methods based on spreading metrics and LP relaxations Even et al. (1995, 2000). Exact and parameterized algorithms target smaller or structurally restricted instances Baharev et al. (2021); Hecht et al. (2021); Raman and Saurabh (2006); Shea-Blymyer and Young (2021). Heuristic refinements emphasize minimal/stable feedback sets and initialization effects Cavallaro et al. (2024, 2025). Closely related is the maximum acyclic subgraph problem Hassin and Rubinstein (1994). We use MWFAS as a ranking consistency objective, not as a setting in which we claim a new general approximation algorithm.

1.2.2 Ranking from Pairwise Comparisons

Ranking from noisy and incomplete pairwise comparisons has been studied through statistical, spectral, random-walk, and optimization-based formulations Hochberg and Rabinovitch (2000); Chen et al. (2021); Shah and Wainwright (2016). Our experiments evaluate score-based outputs under the upset-style losses used in recent ranking benchmarks He et al. (2022), so we focus on the principal baseline families represented in that protocol.

1.2.3 Statistical and Spectral Ranking

BTL models pairwise win probabilities through latent abilities Bradley and Terry (1952). DAVIDSCORE aggregates unbalanced paired outcomes into per-item scores David (1987). Random-walk and spectral constructions include RANKCENTRALITY Negahban et al. (2017), SERIALRANK Fogel et al. (2014), SYNCRANK Cucuringu (2015), and SVD-based scores d’Aspremont et al. (2021). Graph scoring methods include eigenvector centrality Bonacich (1987), PAGERANK Page et al. (1999), and SPRINGRANK De Bacco et al. (2018). Spectral and synchronization approaches already note connections between ranking inconsistency and feedback structure Fogel et al. (2014); Cucuringu (2015).

1.2.4 GNN-Based Ranking

Learning-based methods infer ranking scores from directed comparison graphs. GNNRANK uses directed-GNN backbones with ranking-oriented losses He et al. (2022). We compare against the framework’s DIGRAC He et al. (2021) and inception-style (IB) Tong et al. (2020) backbones. These methods can be accurate but incur training cost and hyperparameter sensitivity, which motivates a training-free alternative under fixed wall-clock budgets.

1.2.5 Local-Ratio Cycle Breaking, Add-Back Lineage, and Structural Repair

Demetrescu and Finocchi Demetrescu and Finocchi (2003) give a local-ratio cycle-breaking heuristic with an approximation guarantee parameterized by the length of a longest simple directed cycle, building on the local-ratio framework of Bar-Yehuda et al. (2004). Their Phase 2 reinserts deleted arcs subject to an *exact* cycle-safety test (equivalently: reinsert (u, v) iff v does not reach u in the current DAG), and they remark that ordering candidates by decreasing weight can improve solution quality. Exact cycle-safe reinsertion and weight-prioritized ordering are therefore prior; they are not newly invented here.

Component	DF03	VK25	This work
Local-ratio backbone	yes	yes	prior (used)
Exact cycle-safe reinsertion	yes	yes (spec.)	fidelity restore
Weight-ordered reinsertion	suggested	yes	prior (used)
Time-bounded practical impl.	–	partial	audited
Order-preserving refinement	–	yes	prior (used)
Formal ranking $\leftrightarrow$ MWFAS	–	asserted	proved
DF03 guarantee under timeout	N/A	not audited	qualified (no)
Weighted min-cut exchange	–	–	secondary new
Broad classical + GNN eval.	–	GNN-focused	expanded

Table 1: Novelty separation relative to Demetrescu–Finocchi (DF03) and Vahidi and Koutis (2025). “Fidelity restore” means restoring the established exact test after an implementation weakening, not inventing the test.

1.2.6 Relation to Vahidi and Koutis (2025)

Vahidi and Koutis (2025) operationalizes ranking via the Demetrescu and Finocchi (2003) local-ratio backbone with descending-weight exact cycle-safe reinsertion and order-preserving ternary refinement. A later practical codebase weakened reinsertion to a fixed topological-position proxy; multipass INS variants partially compensate and are historical comparison points only. Table 1 summarizes what is prior, restored for fidelity, or newly analyzed here.

2 Method and Theory

We describe a deterministic, training-free ranking pipeline for weighted pairwise-comparison graphs. The canonical revised pipeline is:

1. **Phase A (prior):** local-ratio-style cycle breaking Demetrescu and Finocchi (2003); Vahidi and Koutis (2025).
2. **Phase B (fidelity correction):** exact weight-prioritized reachability-aware reinsertion Demetrescu and Finocchi (2003); Vahidi and Koutis (2025).
3. **Optional secondary repair (new):** conflict-triggered weighted min-cut exchange.
4. **Phase C (prior lineage):** topological score extraction and optional order-preserving refinement Vahidi and Koutis (2025).

Legacy multipass topo-proxy variants (INS1–3) are retained only as historical comparison points (§1.2).

2.1 Problem Setting

Let $V = \{1, \dots, n\}$ be items and $G = (V, E, w)$ a directed graph with strictly positive arc weights $w : E \rightarrow \mathbb{R}_{>0}$. Antiparallel arcs are allowed. The solver input is a sparse weighted adjacency matrix converted to arrays (`src`, `dst`, `w`) of length $m = |E|$. The output is a score vector $s \in \mathbb{R}^n$ with larger values indicating higher rank. Formal ranking and MWFAS definitions appear in §1.

2.2 Ranking–MWFAS Optimum-Value Equivalence

Proposition 1 (Optimum-value equivalence). *Let $G = (V, E, w)$ with $w > 0$. Write*

$$\text{OPT}_{\text{rank}} = \min_R \sum_{(i,j) \in E: R(i) > R(j)} w_{ij}, \quad \text{OPT}_{\text{MWFAS}} = \min \left\{ \sum_{e \in F} w_e : F \subseteq E, (V, E \setminus F) \text{ acyclic} \right\}.$$

Then $\text{OPT}_{\text{rank}} = \text{OPT}_{\text{MWFAS}}$. The correspondence between optimal rankings and optimal feedback arc sets is many-to-many: we do not claim a bijection between arbitrary rankings and arbitrary feedback arc sets.

Proof. Write $L(R) = \sum_{(i,j) \in E: R(i) > R(j)} w_{ij}$ for the ranking loss of R .

($\text{OPT}_{\text{MWFAS}} \leq \text{OPT}_{\text{rank}}$.) Fix any ranking R and let $F_R = \{(i, j) \in E : R(i) > R(j)\}$. Every retained arc is forward under R , so R is a topological order of $(V, E \setminus F_R)$ and F_R is a feedback arc set of weight $L(R)$. Hence $\text{OPT}_{\text{MWFAS}} \leq L(R)$ for every R , and taking the best ranking yields $\text{OPT}_{\text{MWFAS}} \leq \text{OPT}_{\text{rank}}$.

($\text{OPT}_{\text{rank}} \leq \text{OPT}_{\text{MWFAS}}$.) Let F^* be an optimal feedback arc set and let R be any topological order of the DAG $(V, E \setminus F^*)$. Every retained arc is forward under R , so the set of backward arcs of R is contained in F^* . Therefore $L(R) \leq w(F^*) = \text{OPT}_{\text{MWFAS}}$, which implies $\text{OPT}_{\text{rank}} \leq \text{OPT}_{\text{MWFAS}}$. $\square$

Remark 1. *If F is inclusion-minimal, then for every topological order R of $(V, E \setminus F)$ one has $L(R) = w(F)$. Optimal feedback arc sets under strictly positive weights are inclusion-minimal, but the optimum-value claim above does not require uniqueness of F^* or of R .*

2.3 Unified Pipeline Pseudocode

Algorithm 1: Canonical revised ranking pipeline (training-free)

Input: Weighted digraph $G = (V, E, w)$; wall-clock budget T ; zero tolerance τ ; optional min-cut flag; refinement budgets

Output: Score vector $s : V \rightarrow \mathbb{R}$

$t_0 \leftarrow \text{now}()$; $r_e \leftarrow w_e$, $\text{alive}_e \leftarrow \text{true}$ for all $e \in E$;

while true **do**

- if** $\text{now}() - t_0 > T$ **then**
 - break**; // may exit while cyclic
- $C \leftarrow \text{FindOneCycle}(\text{alive})$ with deterministic vertex/edge order;
- if** $C = \emptyset$ **then**
 - break**; // acyclic
- $\Delta \leftarrow \min_{e \in C} r_e$;
- if** $\Delta \leq 0$ **then**
 - force-kill $\arg \min_{e \in C} r_e$
- else**
 - $r_e \leftarrow r_e - \Delta$ for $e \in C$;
 - delete $\{e \in C : r_e \leq \tau\}$; **if** none deleted **then**
 - force-kill $\arg \min_{e \in C} r_e$

$\text{kept} \leftarrow \text{alive}$; // Phase A output

sort excluded arcs by descending w , stable ties by edge id;

foreach excluded arc $e = (u, v)$ in that order **do**

- if** $\text{now}() - t_0 > T$ **then**
 - break**
- if** $v \not\rightarrow^* u$ in current kept DAG **then**
 - $\text{kept}[e] \leftarrow \text{true}$

if min-cut repair enabled **then**

- apply Alg. 2 under remaining budget

;

$\pi \leftarrow \text{TopoSort}(\text{kept})$; **if** $\pi = \text{None}$ **then**

- $\pi \leftarrow (1, \dots, n)$; // identity fallback

$s_v \leftarrow \max\{1, n - \text{pos}_\pi(v)\}$;

optionally apply order-preserving refinement under remaining budget;

return s

2.4 Phase A: Local-Ratio Cycle Breaking (Prior)

Phase A follows the local-ratio reduction of Demetrescu and Finocchi (2003): maintain residuals, find a directed cycle by deterministic DFS (vertices in increasing index order; outgoing arcs in stored order), subtract the cycle’s minimum residual, and delete arcs whose residual falls to at most τ . Forced-progress safeguards kill one minimum-residual arc if floating-point reduction would otherwise stall. Phase A stops when the alive subgraph is acyclic or when the wall-clock budget expires. Acyclicity is guaranteed only on the former exit.

2.5 Phase B: Exact Reachability-Aware Reinsertion (Fidelity Correction)

After Phase A, excluded arcs are scanned once in stable descending original weight. Arc (u, v) is reinserted iff there is no directed path $v \rightarrow^* u$ in the current kept DAG. This is the exact cycle-safety test of Demetrescu and Finocchi (2003); Vahidi and Koutis (2025). The submitted fixed-topological-position proxy (accept iff $\text{pos}(u) < \text{pos}(v)$ for one fixed topological order) is weaker and is retained only for historical comparison (legacy INS multipass variants).

Proposition 2 (Exact add-back correctness). *Assume the Phase A kept graph is a DAG. Consider a single descending-weight scan that inserts (u, v) iff $v \not\rightarrow^* u$ in the current kept DAG.*

1. **Acyclicity.** *Every accepted insertion preserves acyclicity.*
2. **Monotonicity.** *Insertions only enlarge reachability.*
3. **One-pass sufficiency.** *An arc rejected when scanned cannot become admissible later in the same monotone scan.*
4. **Single-edge inclusion minimality.** *After a complete exact scan, no excluded arc can be restored individually without creating a cycle.*

This is inclusion-minimality under single-edge restoration, not a claim of globally minimum-weight FAS.

Proof. (1) If adding (u, v) created a cycle, the remainder of that cycle would be a $v \rightarrow^* u$ path in the previous DAG, contradicting the acceptance test. (2) Adding arcs cannot destroy existing paths. (3) Suppose (u, v) is unsafe at its turn, so a path $v \rightarrow^* u$ exists. Later insertions only add arcs, so that path persists and (u, v) remains unsafe. (4) Completeness of the scan means every excluded arc was rejected exactly because restoring it alone would close a cycle. $\square$

2.6 Optional Secondary Repair: Weighted Min-Cut Exchange

Some high-weight excluded arcs remain unsafe because v reaches u . For such an arc $e = (u, v)$, let C be a minimum-capacity directed $v \rightarrow u$ cut in the retained DAG (capacities = kept-arc weights). The candidate exchange is

$$D' = (D \setminus C) \cup \{e\}.$$

Accept only if $w(C) + \text{tol} < w(e)$.

Algorithm 2: Conflict-triggered weighted min-cut exchange (optional)

Input: Kept DAG D ; excluded arcs; budgets on candidates/acceptances; tolerance tol
foreach *unsafe candidate* $e = (u, v)$ **under a fixed deterministic order** **do**
 $C \leftarrow$ directed min $v \rightarrow u$ cut in D ;
 if $w(C) + \text{tol} < w(e)$ **then**
 $D \leftarrow (D \setminus C) \cup \{e\};$ // strict weighted-FAS improvement

Proposition 3 (Min-cut exchange). *Whenever an exchange is accepted under the strict rule $w(C) + \text{tol} < w(e)$:*

1. D' is acyclic;
2. the removed-FAS weight changes by $\Delta = w(C) - w(e) < 0$;
3. repeated accepted exchanges terminate after finitely many steps.

We claim no global optimality and no approximation ratio for this operator. The guarantee is structural improvement of the weighted feedback objective; ranking metrics need not improve monotonically.

Proof. (1) Removing C destroys every $v \rightarrow u$ path, so adding (u, v) cannot close a cycle. (2) Relative to the previous feedback set, arcs in C re-enter the feedback set and e leaves it, giving $\Delta = w(C) - w(e)$; acceptance forces $\Delta < 0$. (3) There are finitely many subsets of E , and each acceptance strictly decreases a nonnegative objective bounded below by 0. $\square$

2.7 Phase C: Scores and Optional Refinement (Prior Lineage)

From a kept DAG we compute a deterministic topological order (Kahn’s algorithm with index-ordered initial queue) and assign $s_v = \max\{1, n - \text{pos}(v)\}$. If the kept graph is still cyclic (e.g., Phase A timeout), the implementation falls back to the identity order $(1, \dots, n)$; see §2.10. Optional adjacent-swap refinement may change the order under a local budget. Optional order-preserving ternary refinement adjusts magnitudes without changing the induced order, following the refinement lineage in Vahidi and Koutis (2025).

2.8 Termination, Parameters, and Determinism

Parameter	Role	Notes
T (<code>time_limit_sec</code>)	Global wall-clock budget	Shared by Phases A–C; early exit may leave cycles
τ (<code>zero_tol</code>)	Residual kill threshold	Default 10^{-15} ; numerical, not a modeling knob
DFS / Kahn order	Deterministic traversal	Vertices $1..n$; stable edge order
Add-back order	Descending w , stable ties	Exact reachability test (canonical)
Legacy $P \in \{1, 2, 3\}$	Submitted topo-proxy passes	Historical INS1/2/3; not canonical
Min-cut budgets	Optional repair caps	Secondary; regime-specific benefit
Refinement budgets	Phase C time/passes	Order-preserving ternary from prior lineage
Identity fallback	Score extraction if cyclic	No nontrivial general error bound (§2.10)

Table 2: Consolidated parameters and termination behavior.

2.9 DF03 Approximation Guarantee: Idealized vs. Practical

Idealized local-ratio Phase A. If Phase A is executed under the assumptions of the published Demetrescu–Finocchi local-ratio procedure and runs to the relevant completion condition (fully reduced acyclic residual), the published λ -approximation on removed weight applies to that idealized algorithm, where λ is governed by longest-cycle length in the source analysis Demetrescu and Finocchi (2003).

Practical implementation. The implemented pipeline additionally uses finite wall-clock termination, floating-point zero tolerance, forced-progress safeguards, and a fallback ranking when topological sort fails. Therefore the original theorem does *not* automatically imply that every practical finite-budget output satisfies the same approximation guarantee.

Remark 2 (No inherited guarantee under premature termination). *We do not claim the DF03 approximation guarantee for prematurely terminated practical runs. In particular, a wall-clock cutoff inside Phase A may leave the kept graph cyclic; subsequent identity-order fallback is outside the theorem’s scope.*

2.10 Fallback Ordering: Unbounded Multiplicative Gap

Proposition 4 (No nontrivial multiplicative bound for identity fallback). *For every $M > 0$ there exists a weighted digraph G with $\text{OPT}_{\text{rank}} > 0$ such that if R_{fb} denotes the identity ranking $R_{\text{fb}}(v) = v$, then*

$$\frac{L(R_{\text{fb}})}{\text{OPT}_{\text{rank}}} > M.$$

Proof. Fix $\varepsilon \in (0, 1)$ and an integer $n \geq 3$ large enough that $\binom{n}{2}/\varepsilon > M$. On vertex set $\{1, \dots, n\}$, include every arc (j, i) with $j > i$ and weight 1, and add the single arc $(1, 2)$ with weight ε . Under the identity ranking $R_{\text{fb}}(v) = v$, every arc (j, i) with $j > i$ is backward, so $L(R_{\text{fb}}) = \binom{n}{2}$. Under the reverse ranking $R^*(v) = n + 1 - v$, every unit-weight arc is forward and only $(1, 2)$ is backward, so $L(R^*) = \varepsilon$ and thus $\text{OPT}_{\text{rank}} \leq \varepsilon$. Hence $L(R_{\text{fb}})/\text{OPT}_{\text{rank}} \geq \binom{n}{2}/\varepsilon > M$. (The same instances show that additive regret $L(R_{\text{fb}}) - \text{OPT}_{\text{rank}}$ is likewise unbounded as n grows with ε fixed.) $\square$

2.11 Complexity

Let $n = |V|$ and $m = |E|$. For the audited Phase A implementation, each cycle search scans the static adjacency of all original arcs (dead arcs are skipped but not compacted), costing $O(n + m)$ per iteration, and at most m iterations occur before acyclicity in the unbudgeted case. Therefore the idealized full-completion Phase A bound is

$$O(mn + m^2),$$

which is weaker than a textbook $O(nm)$ accounting that assumes compacted alive adjacency. A wall-clock budget caps completed iterations empirically; it is an execution policy, not an average-case complexity theorem.

Exact reachability add-back costs $O(m \log m)$ for sorting plus polynomial-in- n dense incremental updates (or BFS queries in a sparse fallback). Optional min-cut repair adds budgeted directed min-cut computations. Phase C is time-bounded and may use up to $O(n^2)$ pairwise structures for ratio refinement. Empirical timing is reported in §3.4–3.6.

3 Experimental Results

3.1 Experimental Protocol

Dataset suite and denominators. We use an 80-dataset manuscript benchmark suite aligned with recent ranking-from-comparisons evaluations (He et al., 2022), spanning basketball/football temporal graphs, faculty hiring networks, animal and head-to-head competition graphs, one ERO-style instance, and the near-complete Finance graph ($n = 1315$, $m \approx 1.73 \times 10^6$, density ≈ 1). Two suite members lack loadable data files in the archived release (ERO/p5K5N350eta10styleuniform, Halo2BetaData/HeadToHead), so analyses that require readable graphs use an effective denominator of 79 datasets with available data. An extra inventory entry _AUTO/Basketball_temporal_1985adj is excluded from the manuscript suite. We never mix denominators: pairwise quality/runtime tables use method-pair common completions (typically $n = 77$ for OURS vs classical; $n = 60$ for OURS vs GNN), coverage uses 79, and family-aware macros exclude Finance from quality aggregates. Table 3 summarizes families; non-Finance ablation successes reach $n \leq 602$.

Family	#	n min-max	m min-max
Basketball (coarse+finer)	60	282–351	2,904–7,650
Football (coarse+finer)	12	20–20	107–380
Faculty (3)	3	113–206	1,204–1,787
Halo / head-to-head	2	602–602	5,010–5,010
Animal	1	21	193
ERO-style	1	(suite range)	(suite range)
Finance	1	1,315	1,729,225

Table 3: Manuscript 80-suite families (intended counts). Two missing files reduce readable graphs to 79.

Methods. Baselines are ten classical methods (SPRINGRANK, SYNCRANK, SERIALRANK, BTL, DAVID-SCORE, eigenvector/PAGERANK/RANKCENTRALITY, SVD-RS/SVD-NRS) and two GNNRank backbones (DIGRAC, IB) under fixed archived configurations (not post-hoc best-in-suite oracles). The *canonical* revised method is the reachability-aware pipeline of §2 (Phase A + exact Phase B + optional min-cut + Phase C). Archived OURS-MFAS and INS3 labels are duplicate topo-proxy configurations; multipass INS variants are historical only. Direct quality and classical/GNN runtime tables below reuse the archived OURS_MFAS leaderboard column for continuity with the submitted evaluation archive; the incremental effect of restoring exact reachability (and of optional min-cut/refinement) is reported in the structural ablation (§3.7), not by silently replacing that archive column.

Determinism, repetitions, and timing. Non-GNN methods are deterministic given fixed inputs and completed work: ranking outputs do not vary across the protocol’s 10 recorded trials except through wall-clock/timeout effects. Those repetitions characterize runtime variability and timeout repeatability; they are *not* independent ranking observations. GNN methods are stochastic under training. Non-GNN wall-clock budgets use 1800 s; GNN runs use 7200 s. Archived GNN timings measure the end-to-end trained pipeline (construction + training + scoring), not inference-only latency; the exact archived GPU model ledger is unavailable, so hardware comparability is imperfect and GNN speedups are qualified accordingly.

Completion rules and statistics. Timeouts, missing data, and GNN not-applicable cases are reported separately; we do not impute NaNs as scores. Primary comparisons use pairwise common completions. We report win/tie/loss (W/T/L) counts with ties $|\Delta| \leq 10^{-6}$, median paired Δ (OURS – baseline; for upset metrics, negative favors OURS), and—where precomputed—Wilcoxon signed-rank p -values with Holm adjustment and bootstrap CIs. Because many basketball seasons are temporally related, we add a family-aware sensitivity analysis (§3.3).

Canonical numerical source. All revised numbers below are recomputed from the archived per-method leaderboard and the revision-analysis CSV exports (runtime/coverage, family-aware, and ablation directories). Stale submitted Table 4/5 aggregates are not reused.

3.2 Direct Ranking Quality on Common Completions

Table 4 and Table 5 summarize archived OURS_MFAS (topo-proxy leaderboard column; see protocol) against principal baselines on pairwise common completions.

Baseline	n	W/T/L	med Δ	Holm p
SpringRank	77	41/0/36	-0.078	0.11
DavidScore	77	40/1/36	-0.024	0.11
SVD_NRS	77	40/2/35	-0.025	0.37
BTL	77	73/0/4	-0.207	$< 10^{-11}$
PageRank	77	53/0/24	-0.170	—
SyncRank	77	77/0/0	-0.720	—
SerialRank	77	75/0/2	-0.858	—
RankCentrality	77	77/0/0	-0.987	—
DIGRAC	60	30/0/30	-0.076	0.013
ib	60	51/0/9	-0.408	$< 10^{-8}$

Table 4: **upset_simple** (lower better) on pairwise common completions for archived OURS_MFAS. $\Delta = \text{OURS} - \text{baseline}$ (negative favors OURS). Holm p where present in the formal-statistics export; “—” means not in that Holm family.

Baseline	n	W/T/L	med Δ	Note
SpringRank	77	44/0/33	-0.018	competitive
DavidScore	77	74/0/3	-0.131	
SVD_NRS	77	72/0/5	-0.095	
BTL	77	1/0/76	+0.082	BTL stronger
PageRank	77	14/0/63	+0.030	PageRank stronger
SyncRank	77	47/0/30	-0.204	
SerialRank	77	47/0/30	-0.201	
RankCentrality	77	77/0/0	-0.612	
DIGRAC	60	30/0/30	-0.027	
ib	60	30/0/30	-0.134	

Table 5: **upset_ratio** (lower better) on the same common completions for archived OURS_MFAS. Oracle best-in-suite envelopes are not headline competitors.

On **upset_simple**, archived OURS shows strong W/T/L margins against BTL, against SyncRank, SerialRank, and RankCentrality, and against IB, with significant Holm-adjusted Wilcoxon advantages vs BTL, DIGRAC, and IB. Against SPRINGRANK, DAVIDSCORE, and SVD_NRS, per-dataset wins slightly favor OURS, but Holm-adjusted tests are not significant; family-aware analysis (§3.3) treats these as competitive rather than uniformly superior. On **upset_naive**, the same directional pattern holds (e.g., 41/0/36 vs SpringRank; 73/0/4 vs BTL; 60/0/0 vs IB). On **upset_ratio**, BTL remains clearly stronger (1/0/76) and PageRank also wins more often (14/0/63); OURS is strong against DavidScore, SVD_NRS, and RankCentrality. We do not claim universal dominance on any metric.

3.3 Family-Aware Robustness

Basketball seasons dominate per-dataset n ($\approx 60/77$). Equal-family macros (seven included families; Finance excluded from quality macros) preserve large-margin **upset_simple** advantages vs BTL/PageRank/IB/centrality-style methods. Vs SpringRank/DavidScore/SVD_NRS, equal-family means of family medians still favor OURS directionally, but hierarchical bootstrap CIs include zero, and leave-one-family-out can move the SpringRank equal-family mean across zero (LOFO-fragile). Collapsing Basketball into one meta-point does not reverse the large-margin wins. The BTL **upset_ratio** disadvantage persists under equal-family weighting

(0/0/7 families). Family-level n is too small for heavy per-family significance testing; we treat family-aware results as sensitivity, not as a replacement for pairwise tests.

3.4 Runtime and Coverage

Baseline	n	OURS faster	ties	slower	median ratio (OURS/base)
SyncRank	77	3	6	68	$2.6\times$
SpringRank	77	14	0	63	$17.9\times$
BTL	77	4	3	70	$25.0\times$
RankCentrality	77	0	0	77	$55.3\times$
SVD_NRS	77	0	0	77	$180\times$
PageRank	77	0	0	77	$536\times$
DIGRAC	60	60	0	0	$0.123\times$ ($\sim 8\times$ faster)
ib	60	60	0	0	$0.121\times$ ($\sim 8\times$ faster)

Table 6: Paired runtime W/T/L on common completions (archived OURS_MFAS timings). OURS is slower than lightweight classical methods and faster than archived trained-GNN end-to-end runs.

Coverage on 79 readable datasets: OURS 77/79 (97.5%; Finance timeout); most classical methods 78/79 (98.7%); SyncRank 77/79; DIGRAC/ib 61/79 (77.2%, primarily not-applicable rather than timeout). A global 60-dataset subset where all methods finish exists but is GNN-applicability biased; pairwise completion remains primary. Figure 1 shows empirical A4 runtimes versus m for non-Finance graphs.




Figure 1: A4 wall time versus edge count on non-Finance ablation graphs (log-log). Finance ($m \approx 1.73 \times 10^6$) is marked as the large-dense boundary.

3.5 Finance Stress Case

Finance is reported separately, not averaged into quality macros. Under the archived 1800s non-GNN protocol, leaderboard OURS and SyncRank time out while lightweight classical methods finish in < 4 s

and GNN end-to-end runs finish in $\sim 15\text{--}18$ min. In the reviewer ablation stress configs (internal Phase A budget 600 s): FINANCE_A0 completes with wall ≈ 612.6 s (Phase A ≈ 600.0 s); FINANCE_A2/A4 hit INTERNAL_TIME_LIMIT at $\approx 1214.8/1214.6$ s; FINANCE_A6 hits TIMEOUT_HARD_WALLCLOCK at ≈ 1800.1 s without a finished ranking. This matches the $O(mn + m^2)$ Phase A discussion in §2.11: Finance is a known large-dense boundary.

3.6 Scalability (Empirical)

On non-Finance ablation graphs ($n \leq 602$), A4 finishes in roughly 0.01–1.2 s (median ≈ 0.57 s); enabling min-cut (A6) adds about 3–4 s median. These timings illustrate the audited $O(mn + m^2)$ Phase A bound (§2.11) on sparse/moderate instances; the Finance boundary is in §3.5. No fitted complexity law is claimed.

3.7 Structural Ablation (A0–A6)

Configs: A0 Phase A only; A1 topo-proxy add-back; A2 exact reachability; A4 reachability+refinement; A5/A6 add optional min-cut (Layer-1 vs full). Primary Holm family (exact CSV values):

Pair	Metric	n	W/T/L	med Δ	Holm p
A0→A2	upset_simple↓	77	76/0/1	−0.0166	2.4×10^{-12}
A1→A2	upset_simple↓	33	32/0/1	−0.0159	1.5×10^{-6}
A2→A5	removed_weight↓	33	26/7/0	−47	8.3×10^{-6}
A4→A6	removed_weight↓	77	66/11/0	−57	4.9×10^{-12}
A0→A4	upset_simple↓	77	76/0/1	−0.0169	2.4×10^{-12}

Table 7: Primary structural ablation paired tests (non-Finance). Ranking metrics need not move monotonically with the weighted FAS objective (e.g., A4→A6).

Figure 2 shows unpaired Layer median trajectories for context; paired tests above are authoritative.




Figure 2: Unpaired median upset_simple and removed weight across A0–A6 (descriptive).

3.8 Parameter Sensitivity (Compact)

On Layer 1 ($n = 33$): `zero_tol` $\in \{10^{-12}, 10^{-15}, 10^{-18}\}$ is STABLE (almost all ties vs default). Cycle-selection changes are statistically detectable on the A4 path but small ($|\text{med } \Delta| \approx 10^{-3}$). Refinement: R0 (off) is worse; R1 $\approx$ R2 and R3 $\approx$ R2 (saturation). Legacy multipass topo-proxy: P1 restores many edges; P2/P3 add little ranking quality. Min-cut budgets: K20 $\rightarrow$ K50 modest; K50 $\rightarrow$ K100 nearly flat. Detailed grids are deferred to the supplement.

3.9 Min-Cut Empirical Regime

Under the predefined broad characterization (39 available of 40 datasets), the operator of §2.6 is active on 28/39 graphs (4/7 families; 280 accepted exchanges). On active graphs, `upset_simple/upset_naive` never worsened; `upset_ratio` worsened on 7/28 (Basketball only; small magnitude), confirming regime-specific rather than universal ranking benefit.

4 Limitations

Dense near-complete graphs remain difficult: Finance is the explicit boundary case documented in §3.5. Finite-budget practical outputs need not inherit the idealized Demetrescu–Finocchi guarantee (§2.9), and identity-order fallback has no nontrivial general multiplicative error bound (Prop. 4). The optional min-cut repair improves the weighted feedback objective but not every upset metric, and its benefit is regime-specific (§3.9). Relative to lightweight classical estimators the pipeline is slower (§3.4); GNN speedups refer to archived end-to-end training+evaluation under imperfect hardware comparability (§3.1). Family-aware analysis shows that SpringRank/DavidScore/SVD_NRS comparisons are cautious, and BTL remains stronger on `upset_ratio` (§3.3). Protocol repetitions for deterministic non-GNN methods characterize runtime/timeout variability rather than ranking uncertainty.

5 Conclusion

We addressed ranking from weighted pairwise comparisons with a training-free structural pipeline: local-ratio cycle breaking, exact reachability-aware reinsertion, optional weighted min-cut exchange, and score extraction/refinement. The algorithmic core follows Demetrescu–Finocchi and Vahidi and Koutis (2025); the revised contributions are formal ranking–MWFAS clarification and guarantee boundaries, restoration of exact cycle-safe add-back after a topological-proxy weakening, a secondary monotone min-cut repair, and a broader timeout-aware empirical study.

On common completions, the archived leaderboard configuration used for direct baseline tables is strong on simple/naive upset metrics against several classical and GNN baselines, competitive under family-aware scrutiny with SpringRank, DavidScore, and SVD_NRS, and weaker than BTL on `upset_ratio`; ablations quantify the reachability correction separately. It is slower than lightweight classical methods and substantially faster than the evaluated trained GNN pipelines under the archived end-to-end protocol, with Finance exposing a large-dense limit.

6 Future Work

Theoretically, denser-graph cycle breaking, tighter analyses of time-bounded structural heuristics, and approximation results on restricted graph classes remain open. Engineering directions include SCC-aware or parallel cycle processing, more efficient reachability maintenance, and better min-cut candidate selection

under budgets. Application settings such as preference aggregation, multi-source sensor comparisons, and industrial ranking are natural targets for the training-free pipeline but are not evaluated here. Deterministic uncertainty quantification over multiple valid topological orders is another concrete direction.

Acknowledgments

Portions of this manuscript and the accompanying code were developed with the assistance of AI-based tools. In particular, ChatGPT (OpenAI) and Gemini were used to help draft and edit text and to support coding, and Cursor and GitHub Copilot were used to assist with software development. The author reviewed, verified, and takes full responsibility for the final manuscript and all reported results.

Statements and Declarations

Funding The author received no financial support for the research, authorship, and/or publication of this article.

Competing Interests The author declares that he has no competing interests.

Ethics Approval Not applicable. This article does not report studies involving human participants or animals.

Consent to Participate Not applicable.

Consent for Publication Not applicable.

Availability of Data and Materials The datasets used in the experiments originate from prior benchmarks cited in the manuscript (e.g., He et al. (2022)). For reproducibility, the processed versions used in this study are provided as text files containing weighted directed edge lists in the public repository linked below.

Code Availability All source code, processed data, and scripts required to reproduce the experiments are publicly available at <https://github.com/SoroushVahidi/ranking-by-feedback-arc-set>. The repository contains the implementation of the proposed method, the benchmark drivers, and the materials needed to reproduce the reported results. Implementations of the non-proposed baselines and the GNNRank training and evaluation pipeline are based on the public GNNRank codebase of He et al. (2022), with the corresponding adaptations documented in the repository.

Author Contributions S. Vahidi is the sole author. He conceived the study, developed the algorithms, performed the experiments, and wrote the manuscript.

References

- Baharev, A., Schichl, H., Neumaier, A., and Achterberg, T. (2021). An exact method for the minimum feedback arc set problem. *Journal of Experimental Algorithmics (JEA)*, 26.
- Bar-Yehuda, R., Bendel, K., Freund, A., and Rawitz, D. (2004). Local ratio: A unified framework for approximation algorithms. in memoriam: Shimon even 1935-2004. *ACM Comput. Surv.*, 36(4):422–463.
- Bonacich, P. (1987). Power and centrality: A family of measures. *American Journal of Sociology*, 92(5):1170–1182.
- Bradley, R. A. and Terry, M. E. (1952). Rank analysis of incomplete block designs: I. the method of paired comparisons. *Biometrika*, 39(3/4):324–345.

- Cavallaro, C., Cutello, V., and Pavone, M. (2024). Efficient heuristics to compute minimal and stable feedback arc sets. *Journal of Combinatorial Optimization*, 48(4):30.
- Cavallaro, C., Cutello, V., and Pavone, M. (2025). Minimal and stable feedback arc sets and graph centrality measures. *Computers & Operations Research*, 184:107247.
- Chen, P., Gao, C., and Zhang, A. Y. (2021). Optimal full ranking from pairwise comparisons.
- Cucuringu, M. (2015). Sync-rank: Robust ranking, constrained ranking and rank aggregation via eigenvector and semidefinite programming synchronization.
- d’Aspremont, A., Cucuringu, M., and Tyagi, H. (2021). Ranking and synchronization from pairwise measurements via SVD. *Journal of Machine Learning Research*, 22(19):1–63.
- David, H. A. (1987). Ranking from unbalanced paired-comparison data. *Biometrika*, 74(2):432–436.
- De Bacco, C., Larremore, D. B., and Moore, C. (2018). A physical model for efficient ranking in networks. *Science Advances*, 4(7):eaar8260.
- Demetrescu, C. and Finocchi, I. (2003). Combinatorial algorithms for feedback problems in directed graphs. *Inf. Process. Lett.*, 86:129–136.
- Even, G., Naor, J. S., Rao, S., and Schieber, B. (2000). Divide-and-conquer approximation algorithms via spreading metrics. *J. ACM*, 47(4):585–616.
- Even, G., Naor, J. S., Schieber, B., and Sudan, M. (1995). Approximating minimum feedback sets and multi-cuts in directed graphs. In Balas, E. and Clausen, J., editors, *Integer Programming and Combinatorial Optimization*, pages 14–28, Berlin, Heidelberg. Springer Berlin Heidelberg.
- Festa, P., Pardalos, P. M., and Resende, M. G. C. (2020). *Feedback Set Problems*, pages 1–13. Springer International Publishing, Cham.
- Fogel, F., d’Aspremont, A., and Vojnovic, M. (2014). Serialrank: Spectral ranking using seriation. In Ghahramani, Z., Welling, M., Cortes, C., Lawrence, N., and Weinberger, K., editors, *Advances in Neural Information Processing Systems*, volume 27. Curran Associates, Inc.
- Hassin, R. and Rubinstein, S. (1994). Approximations for the maximum acyclic subgraph problem. *Information Processing Letters*, 51(3):133–140.
- He, Y., Gan, Q., Wipf, D., Reinert, G., Yan, J., and Cucuringu, M. (2022). Gnnrank: Learning global rankings from pairwise comparisons via directed graph neural networks.
- He, Y., Reinert, G., and Cucuringu, M. (2021). Digrac: Digraph clustering based on flow imbalance.
- Hecht, M., Gonciarz, K., and Horvát, S. (2021). Tight localizations of feedback sets. *ACM J. Exp. Algorithms*, 26.
- Hochberg, Y. and Rabinovitch, R. (2000). Ranking by pairwise comparisons with special reference to ordering portfolios. *American Journal of Mathematical and Management Sciences*, 20(3-4):231–253.
- Karp, R. M. (1972). *Reducibility among Combinatorial Problems*, pages 85–103. Springer US, Boston, MA.
- Negahban, S., Oh, S., and Shah, D. (2017). Rank centrality: Ranking from pairwise comparisons. *Oper. Res.*, 65(1):266–287.

- Page, L., Brin, S., Motwani, R., and Winograd, T. (1999). The pagerank citation ranking: Bringing order to the web. Technical Report 1999-66, Stanford InfoLab.
- Raman, V. and Saurabh, S. (2006). Parameterized algorithms for feedback set problems and their duals in tournaments. *Theoretical Computer Science*, 351(3):446–458.
- Shah, N. B. and Wainwright, M. J. (2016). Simple, robust and optimal ranking from pairwise comparisons.
- Shea-Blymyer, C. and Young, J. M. (2021). Inspectable incrementality in minimum feedback arc set solving. In *Proceedings of ACM Conference*, pages 1–8. Association for Computing Machinery.
- Tong, Z., Liang, Y., Sun, C., Li, X., Rosenblum, D. S., and Lim, A. (2020). Digraph inception convolutional networks. In *Advances in Neural Information Processing Systems*, volume 33, pages 17907–17918.
- Vahidi, S. and Koutis, I. (2025). Minimum weighted feedback arc sets for ranking from pairwise comparisons. *arXiv preprint arXiv:2412.16181*. v3.