

Testing in Node.js + Express

One of the core things to do while writing your code is testing it.

It's highly ignored in most codebases but we're going to try to get close to how testing happens in MERN stack codebases

Goal would be to understand

1. How to test an express backend
2. Mocking, spying, jest, vitest
3. Unit tests vs integration tests vs end to end tests
4. How to integrate testing and coverage in CI/CD

Code for today - <https://github.com/100xdevs-cohort-2/week-24-testing/>

Testing a simple app

Final code - <https://github.com/100xdevs-cohort-2/week-24-testing/tree/main/1-simple-test>

Jest is one of many famous testing frameworks in Typescript

- Initialize a simple TS project

```
npm init -y
npx tsc --init
```

- Change rootDir and srcDir

```
"rootDir": "./src",
"outDir": "./dist",
```

- Create `src/index.ts`

```
export function sum(a: number, b: number) {
  return a + b
}
```

- Add ts-jest as a dependency

```
npm install --save-dev ts-jest @jest/globals
```

- Initialize jest.config.ts

```
npx ts-jest config:initialize
```

- Update package.json

```
"scripts": {
  "test": "jest"
},
```

- Add tests (index.test.ts)

```
import {describe, expect, test} from '@jest/globals',
import {sum} from '../index';

describe('sum module', () => {
  test('adds 1 + 2 to equal 3', () => {
    expect(sum(1, 2)).toBe(3);
  });
});
```

- Run `npm run test`

Testing an express app

Code - <https://github.com/100xdevs-cohort-2/week-24-testing/tree/main/2-simple-express-app>

Let's say we have an express app that doesn't have any DB connections

- Initialize a simple TS project

```
npm init -y
npx tsc --init
```

- Change rootDir and srcDir

```
"rootDir": "./src",
"outDir": "./dist",
```

- Add dependencies

```

npm install --save-dev ts-jest @jest/globals @types/express
npm i supertest @types/supertest
npm install express

```

- Initialize jest.config.ts

```

npx ts-jest config:initialise

```

- Create `src/index.ts`

```

import express from "express";

export const app = express();
app.use(express.json());

app.post("/sum", (req, res) => {
  const a = req.body.a;
  const b = req.body.b;
  const answer = a + b;

  res.json({
    answer
  });
});

```

- Update package.json scripts

```

"test": "jest"

```

- Add `tests/sum.test.ts`

```

import {describe, expect, test, it} from '@jest/globals';
import request from "supertest";
import { app } from "../index"

describe("POST /sum", () => {
  it("should return the sum of two numbers", async () => {
    const res = await request(app).post("/sum").send({
      a: 1,
      b: 2
    });
  });
});

```

Copy

```

    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(3);
  });

  it("should return the sum of two negative numbers", async () => {
    const res = await request(app).post("/sum").send({
      a: -1,
      b: -2
    });
    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(-3);
  });

  it("should return the sum of two zero number", async () => {
    const res = await request(app).post("/sum").send({
      a: 0,
      b: 0
    });
    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(0);
  });
});

```

- Update jest.config.js

```

/** @type {import('ts-jest').JestConfigWithTsJest} Copy
module.exports = {
  preset: 'ts-jest',
  testEnvironment: 'node',
  testMatch: ["<rootDir>/src/tests/**/*.ts"]
};

```

Slightly more complex endpoint

Code - <https://github.com/100xdevs-cohort-2/week-24-testing/tree/main/3-express-with-zod>

Lets add zod to add solid input validation and return erroneous status codes if the input is incorrect

- Install zod

```
npm install zod
```

- Update `index.ts`

```
import express from "express";
import { z } from "zod";

export const app = express();
app.use(express.json());

const sumInput = z.object({
  a: z.number(),
  b: z.number()
});

app.post("/sum", (req, res) => {
  const parsedResponse = sumInput.safeParse(req.body);

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    });
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  res.json({
    answer
  });
});

app.get("/sum", (req, res) => {
  const parsedResponse = sumInput.safeParse({
    a: Number(req.headers["a"]),
    b: Number(req.headers["b"])
  });

  if (!parsedResponse.success) {
```

```
        return res.status(411).json({
            message: "Incorrect inputs"
        })
    }

    const answer = parsedResponse.data.a + parsedResponse.data.b;

    res.json({
        answer
    });
});
```

- Update `sum.test.ts`

Copy

```
import {describe, expect, test, it} from '@jest/globals';
import request from "supertest";
import { app } from "../index"

describe("POST /sum", () => {
    it("should return the sum of two numbers", async () => {
        const res = await request(app).post("/sum").send({
            a: 1,
            b: 2
        });
        expect(res.statusCode).toBe(200);
        expect(res.body.answer).toBe(3);
    });

    it("should return 411 if no inputs are provided", async () => {
        const res = await request(app).post("/sum").send({});
        expect(res.statusCode).toBe(411);
        expect(res.body.message).toBe("Incorrect inputs");
    });
});

describe("GET /sum", () => {
    it("should return the sum of two numbers", async () => {
        const res = await request(app)
            .get("/sum")
            .set({
                a: "1",
                b: "2"
            })
    });
});
```

```
        .send();
        expect(res.statusCode).toBe(200);
        expect(res.body.answer).toBe(3);
    });

    it("should return 411 if no inputs are provided", async () => {
        const res = await request(app)
            .get("/sum").send();
        expect(res.statusCode).toBe(411);
    });
});
```

Moving from jest to vitest

<https://vitest.dev/> is the mildly recent entrant in the testing framework market.

It has a bunch of benefits over jest, specially has great support for TS.

So we'll be moving to vitest for all future tests

It is highly compatible with jest

Link to why vitest - <https://vitest.dev/guide/why.html>

Simple express project with vitest

Code - <https://github.com/100xdevs-cohort-2/week-24-testing/tree/main/4-express-with-vitest>

- Init express app

```
npm init -y
npx tsc --init
npm install express @types/express zod
```

Copy

- Update tsconfig

```
"rootDir": "./src",
"outDir": "./dist"
```

Copy

- Write a simple `src/index.ts` file

```
import express from "express";
import { z } from "zod";
```

Copy

```
export const app = express();
app.use(express.json());

const sumInput = z.object({
  a: z.number(),
  b: z.number()
})

app.post("/sum", (req, res) => {
  const parsedResponse = sumInput.safeParse(req.body)

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    })
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  res.json({
    answer
  })
});

app.get("/sum", (req, res) => {
  const parsedResponse = sumInput.safeParse({
    a: Number(req.headers["a"]),
    b: Number(req.headers["b"])
  })

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    })
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  res.json({
    answer
  })
});
```



We're not doing an `app.listen` here. This is because we don't want the app to actually start when the tests are running.

Usually you create a `bin.ts` file or `main.ts` file that imports app and actually listens on a port

- Install vitest

```
npm i -D vitest
```

- Add a simple `test/index.test.ts` file

```
import { expect, test } from 'vitest'

test('true === true', () => {
  expect(true).toBe(true)
})
```

- Add a script to test in package.json

```
"test": "vitest"
```

RERUN rerun all tests x2

```
✓ src/tests/index.test.ts (1)
  ✓ 1 === 1
```

```
Test Files  1 passed (1)
Tests       1 passed (1)
Start at    13:33:11
Duration    4ms
```

PASS Waiting for file changes...
press **h** to show help, press **q** to quit

- Add supertest

```
npm i supertest @types/supertest
```

- Update test - Notice all we had to do was update the imports. `vitest` is highly compatible with the jest api

Copy

```
import {describe, expect, test, it} from 'vitest';
import request from "supertest";
import { app } from "../index"

describe("POST /sum", () => {
  it("should return the sum of two numbers", async () => {
    const res = await request(app).post("/sum").send({
      a: 1,
      b: 2
    });
    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(3);
  });

  it("should return 411 if no inputs are provided", async () => {
    const res = await request(app).post("/sum").send({});
    expect(res.statusCode).toBe(411);
    expect(res.body.message).toBe("Incorrect inputs");
  });
});

describe("GET /sum", () => {
  it("should return the sum of two numbers", async () => {
    const res = await request(app)
      .get("/sum")
      .set({
        a: "1",
        b: "2"
      })
      .send();
    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(3);
  });

  it("should return 411 if no inputs are provided", async () => {
    const res = await request(app)
      .get("/sum").send();
    expect(res.statusCode).toBe(411);
  });
});
```

```
});
```

```
> 4-express-with-vitest@1.0.0 test
> vitest
```

```
DEV v1.6.0 /Users/harkiratsingh/Projects/testing/4-express-with-vitest
```

```
✓ src/tests/index.test.ts (4)
  ✓ POST /sum (2)
    ✓ should return the sum of two numbers
    ✓ should return 411 if no inputs are provided
  ✓ GET /sum (2)
    ✓ should return the sum of two numbers
    ✓ should return 411 if no inputs are provided
```

```
Test Files 1 passed (1)
```

```
Tests 4 passed (4)
```

```
Start at 13:41:27
```

```
Duration 203ms (transform 27ms, setup 0ms, collect 74ms, tests 21ms, environment 0ms, prepare 39ms)
```

```
PASS Waiting for file changes...
```

```
press h to show help, press q to quit
```

Adding a database

There are two approaches to take when you add external services to your backend.

You can

1. Mock out the external service calls (unit tests).
2. Start the external services when the tests are running and stop them after the tests end (integration/end to end tests)

- Add prisma to your codebase

```
npm i prisma
npx prisma init
```

- Add a basic schema in `schema.prisma`

```
model Sum {
  id          Int @id @default(autoincrement())
  a           Int
```

```

    b      Int
    result Int
  }

```

- Generate the client (notice we don't need to migrate since we won't actually need a DB)

```
npx prisma generate
```

- Create `src/db.ts` which exports the prisma client. This is needed because we will be mocking this file out eventually

```

import { PrismaClient } from "@prisma/client";
export const prismaClient = new PrismaClient();

```

- Update `src/index.ts` to store the requests in the db

```

import express from "express";
import { z } from "zod";
import { prismaClient } from "./db";

export const app = express();
app.use(express.json());

const sumInput = z.object({
  a: z.number(),
  b: z.number()
});

app.post("/sum", async (req, res) => {
  const parsedResponse = sumInput.safeParse(req.body);

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    });
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  await prismaClient.sum.create({
    data: {
      a: parsedResponse.data.a,
      b: parsedResponse.data.b,

```

```

        result: answer
      }
    })

    res.json({
      answer
    })
  });

app.get("/sum", (req, res) => {
  const parsedResponse = sumInput.safeParse({
    a: Number(req.headers["a"]),
    b: Number(req.headers["b"])
  })

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    })
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  res.json({
    answer
  })
});

```

- Notice how the tests begin to error out now

```

24
→ 25 await prismaClient.sum.create(
Can't reach database server at `localhost`:`5432`

Please make sure your database server is running at `localhost`:`5432`.
> In.handleRequestError node_modules/@prisma/client/runtime/library.js:122:7154
> In.handleAndLogRequestError node_modules/@prisma/client/runtime/library.js:122:6188
> In.request node_modules/@prisma/client/runtime/library.js:122:5896
> l node_modules/@prisma/client/runtime/library.js:127:11167
> src/index.ts:25:5
23|         const answer = parsedResponse.data.a + parsedResponse.data.b;
24|
25|         await prismaClient.sum.create({
    |         ^
26|           data: {
27|             a: parsedResponse.data.a,

```

Mocking dependencies

Ref - <https://vitest.dev/guide/mocking.html>


When writing **unit tests**, you **mock out** all **external service** calls.

This means you test the **core** of your logic, and assume the **database calls** would succeed.

This is done so tests can run without starting a **database** / **external services**

Mocking

Mocking, as the name suggests, means **mocking** the behaviour of a file/class/variable when tests are running.



Creating a mock

Mock an exported function

1. Example with `vi.mock` :

WARNING

Don't forget that a `vi.mock` call is hoisted to top of the file. It will always be executed before all imports.

```
// ./some-path.js
export function method() {}
```

ts

```
import { method } from './some-path.js'

vi.mock('./some-path.js', () => ({
  method: vi.fn()
}))
```

ts

Mocking our prismaClient

To mock out the `prismaClient` , you can add the following code to the top of `index.test.ts`

```
vi.mock('../db', () => ({
  prismaClient: { sum: { create: vi.fn() } }
}));
```

Copy

Since we know we are only calling

```
prismaClient.sum.create
```

Copy

I have **mocked** the implementation of that function. A **mock** does nothing and returns **undefined** when the function call succeeds.

Try running `npm run test` now. It should succeed

```

○ → 5-express-vitest-prisma git:(master) ✖ npm run test

> 4-express-with-vitest@1.0.0 test
> vitest

DEV v1.6.0 /Users/harkiratsingh/Projects/testing/5-express-vitest-prisma

✓ src/tests/index.test.ts (4)
  ✓ POST /sum (2)
    ✓ should return the sum of two numbers
    ✓ should return 411 if no inputs are provided
  ✓ GET /sum (2)
    ✓ should return the sum of two numbers
    ✓ should return 411 if no inputs are provided

Test Files  1 passed (1)
Tests       4 passed (4)
Start at   14:31:31
Duration   288ms (transform 59ms, setup 0ms, collect 140ms, tests 25ms, environment 0ms, prepare 48ms)

PASS Waiting for file changes...
press h to show help, press q to quit

```

Problems



Can you guess the two problems that exist here?

1. What if I want to use the value that the database call returns? Right now, it will return `undefined` while a real DB call would return some real data
2. I have to constantly keep upgrading the `mock` since in the future I might use the

Deep mocking

Another way to `mock` variables is to let `vitest` figure out the types and mock out all the attributes of the object being mocked.

For example, the `prismaClient` object has a lot of functions -

```
console.log(Object.keys(prismaClient))
```

Copy

```
stdout | src/index.ts:7:9
[
  '_originalClient',
  '_middlewares',
  '_createPrismaPromise',
  '$extends',
  '_extensions',
  '_previewFeatures',
  '_clientVersion',
  '_activeProvider',
  '_tracingHelper',
  '_errorFormat',
  '_runtimeDataModel',
  '_engineConfig',
  '_accelerateEngineConfig',
  '_engine',
  '_requestHandler',
  '_metrics',
  '_appliedParent',
  'sum',
  '$parent'
]
```

What if we could mock out all these keys in a single function call?

Deep mocking

- Install vitest-mock-extended

```
npm i -D vitest-mock-extended
```

Copy

- Create `__mocks__/db.ts`

```
import { PrismaClient } from '@prisma/client'
import { beforeEach } from 'vitest'
```

Copy

```
import { mockDeep, mockReset } from 'vitest-mock-extended'

export const prismaClient = mockDeep<PrismaClient>()
```

- Remove the `mock` we added in `index.test.ts`, simply add a `vi.mock("../db")`


```
// vi.mock('../db', () => ({
//   prismaClient: { sum: { create: vi.fn() }}
// }));
vi.mock('../db');
```

Copy

- Try running the tests

```
npm run test
```

Copy



```
PROBLEMS  OUTPUT  DEBUG CONSOLE  TERMINAL  PORTS

RERUN src/tests/index.test.ts x8

✓ src/tests/index.test.ts (4)
✓ POST /sum (2)
  ✓ should return the sum of two numbers
  ✓ should return 411 if no inputs are provided
✓ GET /sum (2)
  ✓ should return the sum of two numbers
  ✓ should return 411 if no inputs are provided

Test Files  1 passed (1)
Tests       4 passed (4)
Start at    14:40:14
Duration    85ms

PASS Waiting for file changes...
press h to show help, press q to quit
```

Problem

What if we are using the return value from the database call?

```
import express from "express";
import { z } from "zod";
import { prismaClient } from "../db";

export const app = express();
app.use(express.json());
```

Copy

```
const sumInput = z.object({
  a: z.number(),
  b: z.number()
})

app.post("/sum", async (req, res) => {
  const parsedResponse = sumInput.safeParse(req.body)

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    })
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  const response = await prismaClient.sum.create({
    data: {
      a: parsedResponse.data.a,
      b: parsedResponse.data.b,
      result: answer
    }
  })

  res.json({
    answer,
    id: response.id
  })
});

app.get("/sum", async (req, res) => {
  const parsedResponse = sumInput.safeParse({
    a: Number(req.headers["a"]),
    b: Number(req.headers["b"])
  })

  if (!parsedResponse.success) {
    return res.status(411).json({
      message: "Incorrect inputs"
    })
  }

  const answer = parsedResponse.data.a + parsedResponse.data.b;

  const response = await prismaClient.sum.create({
    data: {
```

```

        a: parsedResponse.data.a,
        b: parsedResponse.data.b,
        result: answer
      }
    })

    res.json({
      answer,
      id: response.id
    })
  });

```

PROBLEMS
OUTPUT
DEBUG CONSOLE
TERMINAL
PORTS

RERUN src/index.ts x1

```

> src/tests/index.test.ts (4) 10015ms
  > POST /sum (2) 5011ms
    ✕ should return the sum of two numbers 5003ms
    ✓ should return 411 if no inputs are provided
  > GET /sum (2) 5004ms
    ✕ should return the sum of two numbers 5002ms
    ✓ should return 411 if no inputs are provided

```

Failed Tests 2

```

FAIL src/tests/index.test.ts > POST /sum > should return the sum of two numbers
FAIL src/tests/index.test.ts > GET /sum > should return the sum of two numbers
Error: Test timed out in 5000ms.
If this is a long-running test, pass a timeout value as the last argument or configure it globally with "testTimeout".

```

[1/2]–

Unhandled Errors

Vitest caught 2 unhandled errors during the test run. This might cause false positive tests. Resolve unhandled errors to make sure your tests are not affected.

Unhandled Rejection

```

TypeError: Cannot read properties of undefined (reading 'id')
> src/index.ts:34:22
    34 |     res.json({

```

Mocking return values

You can mock the values returned from a `mock` by using `mockResolvedValue`

Update index.test.ts

```

import { prismaClient } from '../__mocks__'
prismaClient.sum.create.mockResolvedValue({

```

```
    id: 1,  
    a: 1,  
    b: 1,  
    result: 3  
  });
```

Final index.test.ts

Copy

```
import {describe, expect, test, it, vi} from 'vitest';  
import request from "supertest";  
import { app } from "../index"  
import { prismaClient } from '../__mocks__/db'  
  
vi.mock('../db');  
  
describe("POST /sum", () => {  
  it("should return the sum of two numbers", async () => {  
    prismaClient.sum.create.mockResolvedValue({  
      id: 1,  
      a: 1,  
      b: 1,  
      result: 3  
    });  
  
    const res = await request(app).post("/sum").send({  
      a: 1,  
      b: 2  
    });  
    expect(res.statusCode).toBe(200);  
    expect(res.body.answer).toBe(3);  
  });  
  
  it("should return 411 if no inputs are provided", async () => {  
    const res = await request(app).post("/sum").send({});  
    expect(res.statusCode).toBe(411);  
    expect(res.body.message).toBe("Incorrect inputs");  
  });  
});  
  
describe("GET /sum", () => {  
  it("should return the sum of two numbers", async () => {  
    prismaClient.sum.create.mockResolvedValue({
```

```
      id: 1,
      a: 1,
      b: 1,
      result: 3
    });

    const res = await request(app)
      .get("/sum")
      .set({
        a: "1",
        b: "2"
      })
      .send();
    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(3);
  });

  it("should return 411 if no inputs are provided", async () => {
    const res = await request(app)
      .get("/sum").send();
    expect(res.statusCode).toBe(411);
  });
});
```



We only need to mock in one of the tests because in the second one, control never reaches the place where `id` is needed

Spys vs Mocks

While `mocks` let you `mock` the functionality of a function call, spies let you `spy` on function calls.

Right now, we've mocked out the database call. Which means even if I pass in wrong inputs to the `prismaClient.user.create` function, tests would still pass

Problem

Try flipping the a and b inputs

```
const response = await prismaClient.sum.create({  
  data: {  
    a: parsedResponse.data.b,  
    b: parsedResponse.data.a,  
    result: answer  
  }  
})
```

Try running the tests, they would still work

```
npm run test
```

This means our tests are flaky. They succeed even when the code is incorrect.

Solution

Let's put a `spy` on the `prismaClient.sum.create` function which ensures that the db call inputs are correct

Change the first test to be

```
it("should return the sum of two numbers", async () => {  
  prismaClient.sum.create.mockResolvedValue({  
    id: 1,  
    a: 1,  
    b: 1,  
    result: 3  
  });  
  
  vi.spyOn(prismaClient.sum, "create");  
  
  const res = await request(app).post("/sum").send({  
    a: 1,
```

```

        b: 2
    });

    expect(prismaClient.sum.create).toHaveBeenCalledWith({
      data: {
        a: 1,
        b: 2,
        result: 3
      }
    });

    expect(res.statusCode).toBe(200);
    expect(res.body.answer).toBe(3);
  });

```

Notice that the tests begin to fail

```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS
Number of calls: 1
> src/tests/index.test.ts:24:39
22 |     });
23 |
24 |     expect(prismaClient.sum.create).toHaveBeenCalledWith({
    |                                         ^
25 |       a: 1,
26 |       b: 2,

Test Files  1 failed (1)
Tests      1 failed | 3 passed (4)
Start at   15:46:43
Duration   90ms

FAIL Tests failed. Watching for file changes...
press h to show help, press q to quit

```

Revert the application logic

Make the application logic right again

```

const response = await prismaClient.sum.create({
  data: {
    a: parsedResponse.data.a,
    b: parsedResponse.data.b,
    result: answer
  }
});

```

```
}  
})
```

Adding a CI/CD pipeline

- Create a CI/CD pipeline that runs `npm run test`
- Create `.github/workflows/test.yml`

```
name: CI/CD Pipeline
```

[Copy](#)

```
on:
```

```
  pull_request:
```

```
    branches:
```

```
      - main
```

```
jobs:
```

```
  build:
```

```
    runs-on: ubuntu-latest
```

```
  steps:
```

```
    - name: Checkout code
```

```
      uses: actions/checkout@v2
```

```
    - name: Set up Node.js
```

```
      uses: actions/setup-node@v2
```

```
      with:
```

```
        node-version: 20
```

```
    - name: Install dependencies
```

```
      working-directory: 5-express-vitest-prisma
```

```
      run: npm install && npx prisma generate
```

```
    - name: Run tests
```

```
      working-directory: 5-express-vitest-prisma
```

```
      run: npm run test
```

Final code - <https://github.com/100xdevs-cohort-2/week-24-testing>

PR #1 - <https://github.com/100xdevs-cohort-2/week-24-testing/pull/2>

PR #2 - <https://github.com/100xdevs-cohort-2/week-24-testing/pull/3>

Unit tests vs integration tests vs end to end tests

Unit tests

If you mock out external services (DBs, kafka, redis), then you're testing just the functionality of the method. These are called unit tests

Integration tests

If you don't mock out these services but actually start them locally, then it is considered an integration test

End to end tests

If you have a full stack app and you actually open a browser and test things, it's called an end to end test

