(https://profile.intra.42.fr)

SCALE FOR PROJECT 21SH (/PROJECTS/21SH)

You should evaluate 2 students in this team

★

Git repository

vogsphere@vogsphere.21   🗐

Introduction

Please respect the following rules:
- Remain polite, courteous, respectful and constructive throughout the
correction process. The well-being of the community depends on it.
- Identify with the person (or the group) graded the eventual dysfunctions
of the work. Take the time to discuss and debate the problems you have
identified.
- You must consider that there might be some difference in how your peers
might have understood the project's instructions and the scope of its
functionalities. Always keep an open mind and grade him/her as honestly
as possible. The pedagogy is valid only if the peer-evaluation is
conducted seriously.

Guidelines

- Only grade the work that is in the student or group's
GiT repository.

- Double-check that the GiT repository belongs to the student
or the group. Ensure that the work is for the relevant project
and also check that "git clone" is used in an empty folder.

- Check carefully that no malicious aliases was used to fool you
and make you evaluate something other than the content of the
official repository.

- To avoid any surprises, carefully check that both the correcting
and the corrected students have reviewed the possible scripts used
to facilitate the grading.

- If the correcting student has not completed that particular
project yet, it is mandatory for this student to read the
entire subject prior to starting the defence.

- Use the flags available on this scale to signal an empty repository,
non-functioning program, a norm error, cheating etc. In these cases,
the grading is over and the final grade is 0 (or -42 in case of

cheating). However, with the exception of cheating, you are
encouraged to continue to discuss your work (even if you have not
finished it) in order to identify any issues that may have caused
this failure and avoid repeating the same mistake in the future.

Attachments

☐ 21sh (https://cdn.intra.42.fr/pdf/pdf/6696/21sh.en.pdf)

Mandatory part

*Reminder : Remember that for the duration of the defence, no segfault, nor other unexpected, premature, uncontrolled
or unexpected termination of the program, else the final grade is 0. Use the appropriate flag. This rule is active
thoughout the whole defence.*

Author file

Check that the author file is at the root of the repository
and formatted as explained in the subject. If not defence the
is finished and final grade is 0.

☑ Yes   ✕ No

Memory leaks

Throughout the defence, pay attention to the amount of memory
used by 21sh (using the command top for example) in order
to detect any anomalies and ensure that allocated memory is
properly freed. If there is one memory leak (or more), the final
grade is 0.

☑ Yes   ✕ No

Fork and execve

"fork" and "execve" form the basis of a minimalist shell
like the minishell. Therefore, those functions should be used in the code.
Otherwise, sit means that the instructions were misunderstood. Defence
is finished and final grade is 0. The only way to succeed this project
to use the list of authorized functions. There is no other solution.

Execute the following 4 tests. If at least one fails, no points will
be awarded for this section. Move to the next one.

- Run 21sh, then run the following command "$> foo". It must fail with a
proper error message and then give back the prompt.

- Run the following command "$> /bin/ls". ls must be properly executed
and then give back the prompt.

- Run the following command "$> /bin/ls -laF". ls must be properly executed
with the -l, -a, -F flags and then give back the prompt.

- Run the following command "$> /bin/ls -l -a -F". ls must be properly
executed with the -l, -a, -F flags and then give back the prompt.

⟡ Yes   ✕ No

Builtins

In this section we'll evaluate the implementation of built-ins such
as "exit", "echo" et "cd". A shell needs to include these basic features,
even if it sounds prehistoric to you. Execute the following 8 tests.

If at least one fails, no points will be awarded for this section.
Move to the next one.

- Run 21sh, then run the following command "$> exit". The program
must terminate proprely and give back the parent's shell. Run
the 21sh again.

- Run a command such as "$> echo "It works"".
The message must be properly displayed.

- Run a command such as "$> echo It works" (without the double quotes).
The message must be properly displayed.

- Run a command such as "$> cd /absolute/path/of/your/choice",
then run the following command "$> /bin/pwd". /bin/pwd
must confirm that the current folder was updated.

- Run a command such as "$> cd relative/path/of/your/choice", then
run the following command "$> /bin/pwd". /bin/pwd must confirm
that the current folder was updated.

- Run the following command "$> cd", then run "$> /bin/pwd". /bin/pwd
must confirm that the current folder is the user's home folder.

- Run the following command "$> cd -", then run "$> /bin/pwd". /bin/pwd
must confirm that the current folder is the folder relative/path/of/your/choice
used before.

- Run the following command "$> cd ~/path/of/your/choice",
then run "$> /bin/pwd". "$> /bin/pwd". /bin/pwd must confirm
that the current folder was updated.

⟡ Yes   ✕ No

Environment management

In this section we'll evaluate the implementation of specific built-ins
such as "env ", "setenv " and "unsetenv ". Execute the following 7
tests.

If at least one fails, no points will be awarded for this
section. Move to the next one.

- Run the following command "$> env". Environment variables
must be displayed as key=value.

- Run a command such as "$> setenv FOO bar" or "$> setenv FOO=bar"
depending on the implemented syntax. Then run the following command
"$> env". The environment must display a FOO variable with the value bar.

- Run the following command "$> /usr/bin/env". 21sh must send the
appropriate environment to ran binaries. /usr/bin/env must display
environment including FOO and its value bar.

- Run the following command "$> unsetenv FOO". Then run "$> env".
The environment variable FOO must not be displayed anymore.

- Run the following command again "$> unsetenv FOO". Then run
"$> env". Environment must not change.

- Run the following command again "$> /usr/bin/env ".
/usr/bin/env must not display variable FOO anymore.

⊘ Yes   ✕ No

PATH management

In this section we'll evaluate the implementation of PATH in
your shell.

Execute the following 6 tests:

- Run the following command "$> unsetenv PATH", then run
"$> setenv PATH "/bin:/usr/bin" or "$> setenv
"PATH=/bin:/usr/bin" depending on the implemented syntax.
Then run the following command "$> ls". /bin/ls must be
properly executed.

- Run the following command "$> emacs". /usr/bin/emacs
must be properly executed.

- Run the following command "$> unsetenv PATH", then run
"$> ls". It must fail.

- Run now the following command "$> emacs". It must also
fail.

- Run the following command "$> /bin/ls". /bin/ls must
be properly executed.

- Run the following command "$> /usr/bin/emacs".
/usr/bin/emacs must be properly executed.

If at least one fails, no points will be awarded for this
section. Move to the next one.

⊘ Yes   ✕ No

Command line management

In this section we'll evaluate the command line management.

Execute the following 4 tests:

- Run an empty command "$> ". The shell must do nothing and give
back the prompt.

- Run a command made of just a single space "$> ". The shell
must do nothing and give back the prompt.

- Run a command made of spaces and tabulations. The shell
must do nothing and give back the prompt.

- Run a command made of spaces and tabulations before and
after its named and between its parameters such as
"$> /bin/ls -l -A". All those
spaces and tabulations musn't interfere with the
command's execution.

If at least one fails, no points will be awarded for this
section. Move to the next one.

⊘ Yes   ✕ No

Signal

In this section we'll evaluate signal management and more specifically
Ctrl-C. Execute the following 3 tests.

If at least one fails, no points will be awarded for this section.
Move to the next one.

- Instead of typing a command press Ctrl-C.
The shell must just give back the prompt

- Type a random command but instead of running it press Ctrl-C.
The 21sh must give back and empty prompt.

- Run the following command "$> cat", then when cat waits for
inputs on the standard input, press Ctrl-C.
The 21sh must kill cat's process and give back the prompt.

⊘ Yes   ✕ No

Pipes

In this section we'll evaluate pipe management.
Execute the following 4 tests.
If at least one fails, no points will be awarded for this
section. Move to the next one.

- Run the following command "$> ls | cat -e". The shell must
display the content of the folder with a '$' at the end of
each line.

- Run the following command "$> ls | sort | cat -e". The shell
must display the sorted content of the folder with a '$' at
each line's end.

- Run the following command "$> base64 /dev/urandom | head -c
1000 | grep 42 | wc -l | sed -e 's/1/Yes/g' -e 's/0/No/g'".
The shell must display "Yes" if the string "42" was found
in the random characters, it'll display "No" otherwise.

      ✓ Yes   ✕ No

Redirections

In this section we'll evaluate redirections.
Execute the following 5 tests.
If at least one fails, no points will be awarded for this
section. Move to the next one.

- Run the following command "$> echo "Testing redirections," >
/tmp/test.txt" and check that the /tmp/test.txt file contains
the string "Testing redirections".

- Run the following command "$> echo "with multiple lines" >>
/tmp/test.txt" and check that the /tmp/test.txt file contains
the strings "Testing redirections," and "with multiple lines"
on 2 lines.

- Run the following command "$> wc -c < /tmp/test.txt" and check
that the displayed value is 42.

- Run the following command "$> cat -e << EOF", then type the
following poem without the triple double quote but with the
newlines:
"""
Roses are red
Violets are blue
All my base are belong to you
And so are you
"""
Then press ctrl+d to stop the input. The command's output

must be exactly as follow:
All my base are belong to you$
And so are you$
Roses are red$
Violets are blue$

- Run the following command "$> cat -e << EOF >> /tmp/test.txt"
and write again the last poem. Check that the /tmp/test.txt
file contains the following 6 lines:
Testing redirections,$
with multiple lines$
All my base are belong to you$
And so are you$
Roses are red$
Violets are blue$

⊘ Yes   ✕ No

Several commands following each other

In this section we'll evaluate the managagement of several commands
following each other with the ';' separator. Execute the following
test.
If it fails, no points will be awarded for this section. Move to
the next one.

- Run the following command \"$> ls -1; touch newfile; ls -1\".
Both ls must be executed, the only difference being the "newfile"
file.

⊘ Yes   ✕ No

A lil bit of everything

In this section we'll evaluate pipe, redirections, ';' all
together.

Execute the following 2 tests:

- Run the following command "$> mkdir test ; cd test ; ls -a ; ls | cat | wc -c > fifi ; cat fifi"
The output must be:
. ..
5

- Run the following command "$> cd /tmp; sort << EOF | cat -e > sorted_poem ; sed -e 's/Roses/Turnips/' <
sorted_poem > better_poem; cd -; echo "I prefer turnips anyway" >> /tmp/better_poem; cat /tmp/better_poem"
and type the following poem without the triple double quote
but with the newlines:
"""
Roses are red
Violets are blue

All my base are belong to you
I love you
"""

The output must be (without triple double quote):
"""

All my bases are belong to you$
I love you$
Turnips are red$
Violets are blue$
I prefer turnips anyway
"""

If at least one fails, no points will be awarded for this
section. Move to the next one.

     ✓ Yes   ✕ No

File descriptor aggregation

In this section we'll evaluate file descriptor aggregation.
Execute the following 3 tests.
If at least one fails, no points will be awarded for this
section. Move to the next one.

- Run the following command "$> rm nosuchfile 2>&-" making sure
beforehand that there is indeed no file named 'nosuchfile'
in the current folder. The error message shouldn't be
displayed.

- Run the following command "$> rm nosuchfile 2>&1 | cat -e"
making sure beforehand that there is indeed no file named
'nosuchfile' in the current folder. The output must be:
"rm: nosuchfile: No such file or directory$"

- Run the following command "echo "No dollar character" 1>&2 | cat -e".
The output must be: "No dollar character".

     ✓ Yes   ✕ No

Simple line edition

In this section we'll evaluate simple line edition.
Execute the following 4 tests.
If at least one fails, no points will be awarded for this section.
Move to the next one.

- It must be possible to move the cursor left or right in the
active command line using left and right arrows.

- It must be possible to edit the active command line where the
cursor is located.

- It must be possible to jump at the beginning or at the end of
the line using home and end keys.

- It must be possible to navigate through command line's history
using up and down keys.

✓ Yes   ✕ No

Advanced line edition

In this section we'll evaluate simple line edition.
Execute the following 3 tests.
If at least one fails, no points will be awarded for this
section. Move to the next one.

- It must be possible to move one word at a time left and
right in the active command line using ctrl + left or
right arrow. (1 point)

- It must be possible to copy/paste part or all of the active
commande line with keyboard shortcuts. (2 points)

- It must be possible to write and edit a command line on several
lines at the same time. (2 points)

Rate it from 0 (failed) through 5 (excellent)

⑤

ctrl+D and ctrl+C

In this section we'll evaluate ctrl+D and ctrl+C management.
Execute the following 5 tests.
If at least one fails, no points will be awarded for this
section. Move to the next one.

- Press ctrl+D when the active command line is empty. The
shell must exit properly.

- Press ctrl+D when the active command line isn't empty.
Nothing should happen.

- Run the command "$> cat", type a few characters then press
ctrl+D 2 times. The first must output the characters typed
the second one should give back the prompt.

- Press ctrl+C when the active command line is empty and when
it isn't empty. In both cases the shell must give the prompt
back.

- Run the command "$> cat" then press ctrl+C. The shell must
kill cat's proccess and give back the prompt.

⌀ Yes   ✕ No

Quotes management

In this section we'll evaluate quotes management.
Execute the following test.
If it fails, no points will be awarded for this section. Move
to the next one.

- Run the command '$> echo "', then press enter. The shell
must start a new line and wait for the end of the command.
Type some more lines, and close the double quote. The
shell must get the whole command and execute it normally.
For example:
"""
$> echo "
*>Roses are red
*>Violets are blue
*>All my base are belong to you
*>I love you
*>"

Roses are red
Violets are blue
All my base are belong to you
I love you

$>
"""

⌀ Yes   ✕ No

Bonus

Reminder : Remember that for the duration of the defence, no segfault, nor other unexpected, premature, uncontrolled or unexpected termination of the program, else the final grade is 0. Use the appropriate flag. This rule is active thoughout the whole defence. We will look at your bonuses if and only if your mandatory part is EXCELLENT. This means that your must complete the mandatory part, beginning to end, and your error management must be flawless, even in cases of twisted or bad usage. So if the mandatory part didn't score all the point during this defence bonuses will be totally IGNORED.

Autres features

If there is other bonuses you can grade up to five of them.

Rate it from 0 (failed) through 5 (excellent)

⑤

Ratings

Don't forget to check the flag corresponding to the defense

✔ Ok   ★ Outstanding project

📄 Empty work   📄 Incomplete work   💬 No author file   💀 Invalid compilation   📑 Norme

📚 Cheat   ☤ Crash   👤 Incomplete group   💧 Leaks   🚫 Forbidden function

Conclusion

Leave a comment on this evaluation

[   ]

[**Finish evaluation**]

General term of use of the site (https://signin.intra.42.fr/legal/terms/6)
Privacy policy (https://signin.intra.42.fr/legal/terms/5)
Legal notices (https://signin.intra.42.fr/legal/terms/3)
Declaration on the use of cookies (https://signin.intra.42.fr/legal/terms/2)
Terms of use for video surveillance (https://signin.intra.42.fr/legal/terms/1)
Rules of procedure (https://signin.intra.42.fr/legal/terms/4)