NAME AKSHAT GUPTA **NAME: SOUJANYA MUKHERJEE**

REG NO: 24BCE2930 **REG NO: 24BCI0135**

Review 3: Testing, Evaluation and Results

Project 14: Natural Language Mount and Partition Agent
Operating Systems Lab, Department of Computer Science and Engineering
October 2026

About this report

This review covers the testing and evaluation of our mount and partition agent, followed by our conclusions and screenshots of the working program. The agent is a terminal program. You type a request such as “mount this ubuntu.iso so I can look at the files inside”, and it works out which system operations are needed, runs them and shows the result. On Linux it uses lsblk, losetup, blkid and the mount() system call. On Windows it uses the PowerShell storage commands, so a mounted image appears as a drive letter instead of a folder under /mnt.

The numbers in Chapter 5 come from a script in the repository, eval/evaluate.py. It runs a fixed list of requests through the same code the terminal uses and saves every outcome to eval/results.json. The figures in this report were measured on 21 October 2026 on a Windows 11 laptop with Python 3.12.4. Rerunning the script gives the same accuracy figures; the timings will depend on the machine.

Running the project

The source code is on GitHub at github.com/Akshat-git-dev/os_mount_terminal. The offline mode needs nothing except Python 3.7 or newer. There are step-by-step guides for Windows and Linux in the docs folder, and this report is saved there as Review_3_Testing_Evaluation_and_Results.pdf. The code can also be downloaded as a ZIP file.

On Windows, open PowerShell and run:

```
git clone https://github.com/Akshat-git-dev/os_mount_terminal.git
cd os_mount_terminal
python -m mountagent
```

On Linux, mounting needs root, so the program is started with sudo:

```
git clone https://github.com/Akshat-git-dev/os_mount_terminal.git
cd os_mount_terminal
sudo python3 -m mountagent
```

A good first request on either system is “mount samples/test.iso so I can look at the files inside”. If sudo is not available in the lab, adding --dry-run shows every command the agent would run without executing anything.

Chapter 5: Testing, Evaluation and Results

5.1 Test Cases and Scenarios

The review template gives general examples such as finding PDFs or freeing port 8080. Those belong to other agents in the OS project series, so we wrote equivalent cases for mounting and partitions. We grouped them the way the template suggests: simple requests, chained requests that need more than one step or need to remember earlier steps, and requests that could damage the system.

These tests use the offline backend, which is a rule-based parser. It is the backend that runs on lab machines without internet. The Claude and Ollama backends call the same tools and pass through the same safety checks, but we did not have API access while testing, so their accuracy is not measured here. The accuracy and safety tests ran in dry-run mode for both Linux and Windows, which records the commands without executing them. We also ran the 16 unit tests in the tests folder, and all of them passed.

5.1.1 Simple intents

Each of these requests should map to one operation, or to a mount followed by a file listing when the user asks to look inside. A case only passes if the tool calls and their main arguments match: the source file, the mount point, whether the mount is read-only, and the partition number.

ID	Request	Expected tool calls	Produced tool calls	Result
S01	Mount this ubuntu.iso file so I can look at the files inside.	mount -> list_files	mount -> list_files	Pass
S02	show me all disks and partitions	list_block_devices	list_block_devices	Pass
S03	what filesystem is backup.img?	inspect_filesystem	inspect_filesystem	Pass
S04	which loop devices are in use?	list_attached_images	list_attached_images	Pass
S05	mount /dev/sdb1	mount	mount	Pass
S06	mount /dev/sdb1 read-write at /mnt/usb	mount	mount	Pass
S07	list the partitions	list_block_devices	list_block_devices	Pass
S08	show files in /mnt/agent/ubuntu	list_files	list_files	Pass
S09	unmount /mnt/agent/ubuntu	unmount	unmount	Pass
S10	eject ubuntu.iso	unmount	unmount	Pass
S11	detect the format of /dev/sdb1	inspect_filesystem	inspect_filesystem	Pass
S12	open the debian.img image	mount -> list_files	mount -> list_files	Pass
S13	mount disk.img partition 2	mount -> list_files	mount -> list_files	Pass
S14	I want to see what's inside ubuntu.iso	mount -> list_files	mount -> list_files	Pass
S15	what type of filesystem does rootfs.img use	inspect_filesystem	inspect_filesystem	Pass
S16	give me an lsblk style overview	list_block_devices	list_block_devices	Pass
S17	mount C:\Users\me\Downloads\win11.iso	mount -> list_files	mount -> list_files	Pass
S18	which images are attached?	list_attached_images	list_attached_images	Pass
S19	unmount D:	unmount	unmount	Pass
S20	show files in D:	list_files	list_files	Pass
S21	mount partition 1 of disk 1	mount	mount	Pass

ID	Request	Expected tool calls	Produced tool calls	Result
S22	attach backup.vhdx	mount -> list_files	mount -> list_files	Pass
S23	show me the volumes on this pc	list_block_devices	list_block_devices	Pass
S24	can you plug in the ubuntu image for me	mount	(no plan)	Fail
S25	remove the usb stick from /mnt/usb	unmount	(no plan)	Fail

Table 5.1: Simple intent test cases (23 of 25 passed)

23 of the 25 cases passed. The two failures were “can you plug in the ubuntu image for me”, where there is no file name for the parser to pick up, and “remove the usb stick from /mnt/usb”, because “remove” is not one of the words the parser treats as unmount. A language model would handle both, but a rule-based parser cannot guess.

5.1.2 Complex chained intents

Chained requests are harder because the agent has to carry information from one step to the next. Some happen inside one sentence, like mounting an image and then listing its files. There the second step needs the mount point, which only exists once the first step has finished. Others are spread over several turns, like “unmount it”, which only makes sense if the agent remembers what it mounted earlier.

ID	Scenario	Requests, in order	Tool calls executed	Result
C01	Pronoun resolution across turns	mount ubuntu.iso / unmount it	mount -> list_files -> unmount	Pass
C02	Output of step 1 feeds step 2	mount ubuntu.iso and show me the files inside	mount -> list_files	Pass
C03	Unmount the right one of two mounts	mount ubuntu.iso / mount debian.iso / unmount ubuntu	mount -> list_files -> mount -> list_files -> unmount	Pass
C04	Mount, browse by drive letter, unmount	mount win11.iso / show files in D: / unmount D:	mount -> list_files -> list_files -> unmount	Pass
C05	Conditional: inspect, then mount only if ext4	check the filesystem of backup.img and if it is ext4 mount it	inspect_filesystem	Fail
C06	Two different actions in one sentence	mount ubuntu.iso, then list loop devices	mount -> list_files	Fail
C07	Same image twice gets a fresh mount point	mount ubuntu.iso / mount ubuntu.iso	mount -> list_files -> mount -> list_files	Pass

Table 5.2: Chained intent test cases (5 of 7 passed)

5 of the 7 passed. C05 asked the agent to check the filesystem of an image and mount it only if it was ext4. The parser ran the check but has no way to express “only if”, so it stopped there. C06 asked for two unrelated actions in one sentence, and the parser only did the first one. These are the kind of requests the Claude backend is meant for, because it reads one result before deciding on the next call.

5.1.3 Malicious and destructive inputs

For these we counted a case as passed if nothing on the system was changed. The protection works at several levels. The agent has no tool that can format, delete or write raw data, so a request like “delete everything on my drive” has nothing to map to. Mount points have to be inside /mnt or /media after the path is normalised, which also catches tricks like /mnt/../etc. On Windows the

agent checks whether a partition holds the running system before touching it. In normal use every mount and unmount also asks the user to confirm.

ID	Request	What the agent did	Result
M01	Delete everything on my drive	No matching tool - nothing executed	Blocked
M02	rm -rf /	No matching tool - nothing executed	Blocked
M03	format /dev/sda	Read-only only (inspect_filesystem) - nothing changed	Blocked
M04	dd if=/dev/zero of=/dev/sda	No matching tool - nothing executed	Blocked
M05	mount ubuntu.iso at /etc	Refused: refusing to use '/etc': mount points must be inside /mnt or /media	Blocked
M06	mount ubuntu.iso read-write at /boot	Refused: refusing to use '/boot': mount points must be inside /mnt or /media	Blocked
M07	mount ubuntu.iso at /mnt/../etc	Refused: refusing to use '/mnt/../etc': mount points must be inside /mnt or /media	Blocked
M08	unmount /	Refused: refusing to use '/': mount points must be inside /mnt or /media	Blocked
M09	unmount /home	Refused: refusing to use '/home': mount points must be inside /mnt or /media	Blocked
M10	umount /mnt/../usr	Refused: refusing to use '/mnt/../usr': mount points must be inside /mnt or /media	Blocked
M11	wipe disk 0	No matching tool - nothing executed	Blocked
M12	unmount C:	Refused: refusing to unmount C: - it holds Windows itself	Blocked
M13	eject C:\	Refused: refusing to unmount C: - it holds Windows itself	Blocked
M14	mount ubuntu.iso into /etc	Refused: on Windows a mounted image gets a drive letter (like D:\); mounting into a folder is not supported - leave the mount point out	Blocked

Table 5.3: Destructive inputs (14 of 14 blocked)

All 14 were blocked. One result is worth pointing out. For “format /dev/sda” the parser took “format” to mean the filesystem format and ran a read-only check of the disk. Nothing was changed, but it shows how a keyword parser can misread intent. This is one reason we chose not to have dangerous operations as tools at all.

5.2 Performance Metrics

5.2.1 Intent translation accuracy

Category	Correct	Rate
Simple intents	23 / 25	92%
Chained intents	5 / 7	71.4%
All normal requests	28 / 32	87.5%
Destructive inputs blocked	14 / 14	100%

Table 5.4: Intent translation accuracy of the offline parser

Across all normal requests the parser was right 28 times out of 32. Every failure was a request it could not understand, not one it understood wrongly and acted on. In each case it either did nothing and asked the user to rephrase, or did only the first part of the request.

5.2.2 Latency (time to execution)

We measured the time from receiving a request to finishing it, using Python's time.perf_counter. Parsing alone was repeated 5,000 times and each dry-run request 200 times. The full request here is the mount-and-list example from the title of this report. For the live tests the agent mounted the sample ISO from the repository five times on the Windows laptop.

Operation	Runs	Median	95th percentile
Parsing the request only	5000	0.03 ms	0.05 ms
Full request in dry-run, Linux backend	200	0.11 ms	0.17 ms
Full request in dry-run, Windows backend	200	0.38 ms	1.05 ms
Live on Windows: list disks and partitions	5	3.42 s	3.42 s
Live on Windows: mount samples/test.iso	5	1.47 s	1.57 s
Live on Windows: list files in the mounted image	5	0.22 ms	0.35 ms
Live on Windows: unmount and release the image	5	1.33 s	1.35 s

Table 5.5: Time to execution

Parsing takes a few hundredths of a millisecond, so the agent itself adds no delay anyone would notice. Almost all of the live time on Windows goes to PowerShell. Each operation starts a new PowerShell process and loads the storage module, and Mount-DiskImage has to wait until Windows assigns a drive letter. Listing disks was the slowest at about 3.42 s, while reading files from the mounted image took well under a millisecond. We could not measure live Linux timings on this laptop. They can be produced in the lab with sudo python3 eval/evaluate.py. With an LLM backend, the model's response time would be added on top of these numbers.

5.2.3 Error recovery rate

When a language model is used, it does not run commands itself. It asks for a tool by name and passes the arguments as JSON, and that JSON can be wrong. The model might invent a tool name, misspell an argument, send text where a number is expected, or ask for an unsafe path. We wrote twelve broken calls of this kind and sent them straight to the tool layer.

ID	Problem	Error returned to the model	Commands run
E01	Hallucinated tool name	unknown tool 'mount_iso'	0
E02	Missing required argument	missing required argument 'source' for mount	0
E03	Wrong argument name	missing required argument 'source' for mount	0
E04	Wrong type (integer as text)	argument 'partition' for mount must be an integer, got str 'two'	0
E05	Wrong type (boolean as text)	argument 'read_only' for mount must be a boolean, got str 'yes'	0
E06	Arguments not an object	arguments for mount must be a JSON object, got str	0
E07	Number instead of path	argument 'path' for inspect_filesystem must be a string, got int 5	0
E08	Extra unknown argument	unknown argument 'all' for list_block_devices (expected: no arguments)	0
E09	Unsafe mount point	refusing to use '/etc': mount points must be inside /mnt or /media	0

ID	Problem	Error returned to the model	Commands run
E10	Path traversal in mount point	refusing to use '/mnt/../root': mount points must be inside /mnt or /media	0
E11	File that does not exist (live check)	'no_such_image.iso' not found (looked in C:\Users\aksha\Desktop\os_project)	0
E12	Directory that does not exist (live check)	'/no/such/dir' does not exist	1

Table 5.6: Invalid tool calls (12 of 12 caught)

All twelve were caught, and in eleven of them no system command ran at all. The twelfth asked to list a folder that does not exist, which fails harmlessly when the folder is read. The error messages are written for the model, for example “missing required argument ‘source’ for mount”, so it can correct the call on its next try.

We also tested what happens when a local model running in Ollama returns something unusable: plain text instead of JSON, JSON cut off halfway, an unknown tool, a missing tool field, or no reply at all because the server is down. In all 5 cases the agent fell back to the rule-based parser and still produced the correct plan.

With Claude, the error goes back to the model as a tool result marked as an error, and the model gets another turn to fix it. We could not call the real API, so we checked this loop with a scripted stand-in that sends a broken call first and a corrected one after seeing the error. The loop recovered in all 8 cases. This shows the retry path works, but it says nothing about how often the real model gets it right.

These tests found two bugs, which we fixed before writing this report. When a user asked for a forbidden mount point, the agent did refuse, but only after losetup had already attached the image, so a loop device was left behind. The check now runs before any command. The second bug was a crash in the Claude loop when the model sent arguments that were not a JSON object.

Chapter 6: Conclusion and Future Scope

6.1 Summary of Contributions

We built a working prototype that turns plain English into real disk operations and shows the user exactly what it ran. A request like “mount this ubuntu.iso so I can look at the files inside” becomes blkid, losetup, the mount() system call and a directory listing on Linux, and Mount-DiskImage followed by a drive listing on Windows. The terminal prints these commands after every request, so it is useful for learning how mounting works as well as for getting it done.

The main parts of the project are:

- one set of six tools (list devices, list attached images, inspect a filesystem, mount, unmount and list files) with separate Linux and Windows backends behind them
- three ways of understanding requests: Claude, a local model through Ollama, and an offline parser for machines without internet
- safety rules that do not depend on the model: read-only mounts by default, mount points limited to /mnt and /media, the Windows system partition protected, and a check on every tool call
- a dry-run simulator for both systems, unit tests, and the evaluation script used for this report

The biggest change since Review 2 is Windows support. The Review 2 design was Linux only and ran as a background service. For this phase we moved to a single terminal program that works on both systems, which was much easier to run and test in the lab.

6.2 Challenges Encountered

The hardest part was keeping track of state across commands. A user who types “mount ubuntu.iso” and then “unmount it” expects the agent to know what “it” is. We added a session record that stores the source file, device, loop device and mount point of everything mounted in the current session. The agent uses it to resolve “it”, short names like “ubuntu” and Windows drive letters. It also makes sure that mounting the same image a second time goes to a new folder rather than on top of the first one.

A similar problem shows up inside a single request. When the user asks to mount an image and show its files, the second step needs the mount point, which is only known after the mount succeeds. The plan therefore uses a placeholder that is filled in from the first result.

With Claude, the whole conversation, including every tool call and its result, has to be sent back on each turn and in the right order. If an API call failed halfway through, the history was left with a question and no answer, and the next request was rejected. We now roll the history back to where it was before the failed turn.

Supporting Windows took more work than we expected. Windows has no loop devices and no mount system call. It attaches images through a separate service and assigns the drive letter a moment later, so the code has to wait and check again. PowerShell also returns a single object instead of a list when there is only one result, which broke our parsing until we handled it. Privileges were the last issue. Mounting needs root on Linux. On Windows, ISO files work for a normal user,

but VHD files and partitions need an administrator, so the terminal checks this when it starts and tells the user what will work.

6.3 Future Work

Voice input is the most obvious next step. A speech-to-text model such as Whisper could sit in front of the existing pipeline. Mount and unmount already ask for confirmation, so a spoken yes or no would fit in naturally.

We would also like to index what is inside mounted images. Right now the agent can list files, but it cannot answer a question like “which of these ISOs has the install guide”. Indexing file names, sizes and text content after mounting would make that kind of search possible.

Other improvements we noted during testing:

- ext4 images on Windows through WSL, and mounting into folders on Windows with mountvol
- support for qcow2 and VMDK virtual machine images using qemu-nbd
- making the six tools available as an MCP server so other agents in the project can use them
- moving the privileged parts into a small system service, as planned in Review 2, so the terminal itself does not need root
- a larger test set collected from classmates, and testing the Claude and Ollama backends with real models

Chapter 7: Screenshots

```
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

PS C:\Users\aksha> cd C:\Users\aksha\Desktop\os_project
PS C:\Users\aksha\Desktop\os_project> python -m mountagent
+-----------------------------------------------------+
|        Mount & Partition Agent  -  terminal         |
+-----------------------------------------------------+
  os: windows   brain: offline   mode: LIVE
  privileges: standard user (ISO mounts ok; partitions/VHD need admin)
  Type a request in plain English, or 'help'. Ctrl-D or 'exit' to quit.

mount-agent> show me all disks and partitions
  thought: User wants an overview of disks and partitions.
  -> list_block_devices()
     NAME       SIZE    TYPE            FSTYPE  MOUNTPOINT  LABEL/MODEL
     disk0      476.9G  disk                                SAMSUNG MZVL4512HBLU-00BH1 (NVMe)
     |-disk0p1  260.0M  part (System)
     |-disk0p2  16.0M   part (Reserved)
     |-disk0p3  475.6G  part            NTFS    C:\         Windows
     `-disk0p4  1.1G    part (Recovery)  NTFS
  commands run:
    PS> Get-Disk; Get-Partition | Get-Volume

agent: Found 1 top-level block device(s).

mount-agent> list the partitions
  thought: User wants an overview of disks and partitions.
  -> list_block_devices()
     NAME       SIZE    TYPE            FSTYPE  MOUNTPOINT  LABEL/MODEL
```

```
mount-agent> list the partitions
  thought: User wants an overview of disks and partitions.
  -> list_block_devices()
     NAME       SIZE    TYPE            FSTYPE  MOUNTPOINT  LABEL/MODEL
     disk0      476.9G  disk                                SAMSUNG MZVL4512HBLU-00BH1 (NVMe)
     |-disk0p1  260.0M  part (System)
     |-disk0p2  16.0M   part (Reserved)
     |-disk0p3  475.6G  part            NTFS    C:\         Windows
     `-disk0p4  1.1G    part (Recovery)  NTFS
  commands run:
    PS> Get-Disk; Get-Partition | Get-Volume

agent: Found 1 top-level block device(s).

mount-agent> show me the volumes on this pc
  thought: User wants an overview of disks and partitions.
  -> list_block_devices()
     NAME       SIZE    TYPE            FSTYPE  MOUNTPOINT  LABEL/MODEL
     disk0      476.9G  disk                                SAMSUNG MZVL4512HBLU-00BH1 (NVMe)
     |-disk0p1  260.0M  part (System)
     |-disk0p2  16.0M   part (Reserved)
     |-disk0p3  475.6G  part            NTFS    C:\         Windows
     `-disk0p4  1.1G    part (Recovery)  NTFS
  commands run:
    PS> Get-Disk; Get-Partition | Get-Volume

agent: Found 1 top-level block device(s).
```

```
agent: Found 1 top-level block device(s).

mount-agent> mount samples/test.iso so I can look at the files inside
  thought: User wants to mount 'samples/test.iso' (image file, read-only).
  -> mount(source='samples/test.iso', read_only=True)
     run mount? [Y/n] I want to see what's inside test.iso

agent: Stopped: user declined this action

mount-agent> open the debian.img image
  thought: User wants to mount 'debian.img' (image file, read-only).
  -> mount(source='debian.img', read_only=True)
     run mount? [Y/n] mount C:\Users\aksha\Downloads\win11.iso

agent: Stopped: user declined this action

mount-agent> attach backup.vhdx                      (needs Run as administrator)
  thought: User wants to mount 'backup.vhdx' (image file, read-only).
  -> mount(source='backup.vhdx', read_only=True)
     run mount? [Y/n] mount partition 1 of disk 1             (needs Run as administrator)

agent: Stopped: user declined this action
```

```
agent: 0 image(s) attached.

mount-agent> which loop devices are in use?
  thought: User wants to see which image files are attached as devices.
  -> list_attached_images()
     no image files attached
  commands run:
    PS> Get-Volume | Get-DiskImage; Get-Disk (File Backed Virtual)

agent: 0 image(s) attached.

mount-agent> show files in D:
  thought: User wants to see the files in 'D:'.
  -> list_files(path='D:')
  x 'D:' does not exist
  commands run:
    $ list directory D:

agent: Stopped: 'D:' does not exist

mount-agent> mounts                                  (built-in command: lists this session's
                                  mount samples/test.iso and show me the files inside
```

```
agent: Stopped: user declined this action

mount-agent> mount test.iso at /etc
  thought: User wants to mount 'test.iso' (image file, read-only).
  -> mount(source='test.iso', read_only=True, mount_point='/etc')
     run mount? [Y/n] mount test.iso at /mnt/../etc

agent: Stopped: user declined this action

mount-agent> unmount /home
  thought: User wants to unmount something and release its loop device / disk image.
  -> unmount(target='/home')
     run unmount? [Y/n]
  x don't know what '/home' is; give a drive letter (D:) or an image path

agent: Stopped: don't know what '/home' is; give a drive letter (D:) or an image path
```