

Analyzed

Always show details

```
# Smart Tabs Component Kit – portable drop-in for every SmartNET page
# v9.0.0: UMD-style window.SmartTabs with mount(selector, options)
# Generates:
#   - /mnt/data/smarttabs/smart-tabs.js
#   - /mnt/data/smarttabs/smart-tabs.css
#   - /mnt/data/smarttabs/index.html (demo & docs)
#   - /mnt/data/SmartNET_Hub_v8_12_2_TALK_TO_NAYA.html (hub page with
SmartTabs mounted)
import pathlib, zipfile, textwrap, json

base = pathlib.Path("/mnt/data/smarttabs")
base.mkdir(exist_ok=True)

css = r"""
/* SmartTabs v9.0.0 – minimal, conflict-safe */
:root { --sn-bg: rgba(255,255,255,.03); --sn-br:
rgba(255,255,255,.12); --sn-pill-bg: rgba(0,0,0,.55); --sn-pill-br:
rgba(255,255,255,.18);
  --sn-ink: #e6ecff; --sn-gold:#F8C938; --sn-heart:#b772ff;
--sn-shadow:0 12px 30px rgba(3,8,18,.5),0 4px 12px rgba(3,8,18,.4);
}
.sn-row { position:sticky; top:12px; z-index:100; display:flex;
gap:8px; overflow:auto; -webkit-overflow-scrolling:touch;
padding:10px; border-radius:999px;
  background: var(--sn-bg); border:1px solid var(--sn-br); }
.sn-pill { flex:0 0 auto; display:inline-flex; align-items:center;
gap:10px; padding:10px 14px; border-radius:999px; border:1px solid
var(--sn-pill-br);
  background:var(--sn-pill-bg); color:var(--sn-ink); font-weight:900;
cursor:pointer; user-select:none }
.sn-pill.heart { box-shadow:0 0 0 2px rgba(183,114,255,.35) inset }
.sn-pill.star { box-shadow:0 0 0 2px rgba(248,201,56,.35) inset }
.sn-pill.add { border-style:dashed }
.sn-pill .sn-label { white-space:nowrap }
.sn-pill .sn-more { border:0; background:rgba(255,255,255,.1);
color:#fff; border-radius:8px; padding:4px 8px; cursor:pointer }
.sn-pill .sn-more:hover{ background:rgba(255,255,255,.18) }
```

```

/* Anchored menu & popover */
.sn-menu { position:fixed; z-index:1000; display:none;
min-width:220px; background:linear-gradient(180deg,#121827,#0e1424);
border:1px solid rgba(255,255,255,.18);
    border-radius:12px; box-shadow:0 18px 40px rgba(0,0,0,.5) }
.sn-menu .mi { padding:10px 12px; border-bottom:1px solid
rgba(255,255,255,.08); cursor:pointer; color:#fff; font-weight:800 }
.sn-menu .mi:last-child{ border-bottom:none }
.sn-menu .mi:hover { background:rgba(255,255,255,.06) }

.sn-pop { position:fixed; z-index:1000; display:none; min-width:300px;
background:linear-gradient(180deg,#111727,#0e1424); border:1px solid
rgba(255,255,255,.18);
    border-radius:12px; box-shadow:0 22px 60px rgba(0,0,0,.5);
padding:10px; color:#fff }
.sn-pop h3 { margin:0 0 8px 0 }
.sn-pop .row { display:grid; gap:6px; margin:6px 0 }
.sn-pop input { padding:10px; border-radius:10px; border:1px solid
rgba(255,255,255,.2); background:#0a0f1a; color:#e6ecff }
.sn-pop .toggles { display:flex; gap:8px; margin:6px 0; flex-wrap:wrap
}
.sn-pop .tgl { display:inline-flex; align-items:center; gap:8px;
padding:8px 10px; border-radius:10px; border:1px solid
rgba(255,255,255,.22); background:rgba(0,0,0,.45); cursor:pointer;
color:#fff; font-weight:800 }
.sn-pop .tgl.on { box-shadow:0 0 0 2px rgba(255,255,255,.3) inset, 0 0
18px rgba(124,77,255,.25) }
.sn-pop .ft { display:flex; gap:8px; justify-content:flex-end;
margin-top:6px }
.sn-btn { display:inline-flex; align-items:center; gap:8px;
padding:10px 12px; border-radius:10px; border:1px solid
rgba(255,255,255,.25); background:rgba(0,0,0,.55); color:#fff;
cursor:pointer }
.sn-btn.primary { background:linear-gradient(135deg,#6F3DFF,#9D7BFF) }
"""

```

```
js = r"""
```

```

/#!/ SmartTabs v9.0.0 - window.SmartTabs.mount(el, options) */
(function(root,factory){ if(typeof define==='function' && define.amd){
define([],factory); } else if(typeof exports==='object'){
module.exports=factory(); } else { root.SmartTabs=factory(); }
})(this, function(){
  const DEF = {
    storageKey: 'smartnet_shortcuts',
    initial: [
      {id:'sc-1', label:'SoulSchool', route:'/soulschool', heart:true,
star:false},
      {id:'sc-2', label:'Ambassadors', route:'/ambassadors',
heart:false, star:true},
      {id:'sc-3', label:'ViralTips', route:'/viraltips', heart:false,
star:false},
      {id:'sc-4', label:'SmartHealth', route:'/smarthealth',
heart:false, star:false}
    ],
    routeMap: {
      'soulschool':'/soulschool','soul school':'/soulschool',
      'smarthealth':'/smarthealth','smart health':'/smarthealth',
      'ambassadors':'/ambassadors','viral
tips':'/viraltips','viraltips':'/viraltips',

      'smartask':'/smartask','smartcoin':'/smartcoin','smartfeed':'/smartfee
d','smarthub':'/smarthub',

      'smartmail':'/smartmail','smartnotes':'/smartnotes','smartsounds':'/sm
artsounds',

      'smartsync':'/smartsync','smarttalk':'/smarttalk','smartvault':'/smart
vault','smartworld':'/smartworld'
    },
    addLabel: '+ Add',
    onNavigate: (route, shortcut)=>{ /* host handles actual routing;
default scroll */ const
t=document.querySelector('main')||document.body;
t.scrollIntoView({behavior:'smooth'}); },
    classNames: {}
  }

```

```

};

function routeFrom(label, map){ const
k=(label||'').toString().trim().toLowerCase(); return map[k] ||
('/search?q='+encodeURIComponent(label||'')); }

function el(html){ const d=document.createElement('div');
d.innerHTML=html.trim(); return d.firstChild; }
function placeNear(anchor, panel, oy=8){ const
r=anchor.getBoundingClientRect(); const W=panel.offsetWidth||280,
H=panel.offsetHeight||160;
let left=Math.min(window.innerWidth - W - 8, Math.max(8, r.left));
let top=Math.min(window.innerHeight - H - 8, r.bottom + oy);
panel.style.left=left+'px'; panel.style.top=top+'px';
}

function mount(target, opts){
const o=Object.assign({}, DEF, opts||{});
const root = (typeof target==='string'?
document.querySelector(target) : target;
if(!root) throw new Error('SmartTabs: mount target not found');

// containers
const row = el('<div class="sn-row" role="navigation"
aria-label="Smart Tabs"></div>');
root.appendChild(row);
const menu = el('<div class="sn-menu" role="menu"
aria-hidden="true">\
<div class="mi" data-act="edit">✎ Edit</div>\
<div class="mi" data-act="heart">💜 Set Purple Heart</div>\
<div class="mi" data-act="star">★ Set Gold Star</div>\
<div class="mi" data-act="remove">✕ Remove</div>\
</div>');
const pop = el('<div class="sn-pop" role="dialog"
aria-modal="true">\
<h3 class="sn-pop-title">Edit Shortcut</h3>\
<div class="row"><label>Label <input class="sn-in-label"
placeholder="e.g., SoulSchool"/></label></div>\

```

```

    <div class="row"><label>Route or Keyword <input
class="sn-in-route" placeholder="/soulschool or
crypto"/></label></div>\
    <div class="toggles">\
        <div class="tgl sn-tgl-heart">💜 Purple Heart</div>\
        <div class="tgl sn-tgl-star">★ Gold Star</div>\
    </div>\
    <div class="ft"><button class="sn-btn
sn-cancel">Cancel</button><button class="sn-btn primary
sn-save">Save</button></div>\
    </div>');
    document.body.appendChild(menu); document.body.appendChild(pop);

    // state
    const LS = o.storageKey;
    let shortcuts = (function(){ try{ const
s=JSON.parse(localStorage.getItem(LS)); if(s&&Array.isArray(s)) return
s; }catch{}}; return o.initial.slice(); })();
    let targetId = null, createMode=false;

    // helpers
    function save(){ localStorage.setItem(LS,
JSON.stringify(shortcuts)); row.dispatchEvent(new
CustomEvent('change', {detail:shortcuts})); }
    function list(){ return shortcuts.slice(); }
    function set(next){ shortcuts = next.slice(); save(); render(); }
    function add(obj){ shortcuts.push(obj); save(); render(); }
    function update(id, patch){ const
i=shortcuts.findIndex(s=>s.id===id); if(i<0) return;
shortcuts[i]=Object.assign({}, shortcuts[i], patch); save(); render();
}

    function remove(id){ const i=shortcuts.findIndex(s=>s.id===id);
if(i<0) return; shortcuts.splice(i,1); save(); render(); }
    function sortLit(a){ return
a.slice().sort((A,B)=>(B.heart?2:B.star?1:0)-(A.heart?2:A.star?1:0));
}

    function render(){

```

```

    row.innerHTML = '';
    sortLit(shortcuts).forEach(s=>{
        const cls = 'sn-pill '+(s.heart?'heart':(s.star?'star':''));
        const pill = el(`<div class="${cls}" data-id="${s.id}"><span
class="sn-label">${s.label}</span>${s.heart?'❤️':(s.star?'★':'')}
<button class="sn-more" aria-label="Edit">...</button></div>`);
        pill.onclick = (e)=>{
if(e.target.classList.contains('sn-more')) return; e.preventDefault();
o.onNavigate(s.route || routeFrom(s.label, o.routeMap), s); };
        pill.oncontextmenu = (e)=>{ e.preventDefault(); targetId=s.id;
placeNear(pill, menu, 6); menu.style.display='block'; };
        pill.querySelector('.sn-more').onclick = (e)=>{
e.preventDefault(); targetId=s.id; placeNear(pill, menu, 6);
menu.style.display='block'; };
        row.appendChild(pill);
    });
    const addBtn = el(`<div class="sn-pill add"><span
class="sn-label">${o.addLabel}</span></div>`);
    addBtn.onclick = (e)=>{ e.preventDefault(); targetId=null;
createMode=true; openEditor(addBtn, {label:'', route:'', heart:false,
star:false}, 'Add Shortcut'); };
    addBtn.oncontextmenu = (e)=>{ e.preventDefault(); targetId=null;
createMode=true; openEditor(addBtn, {label:'', route:'', heart:false,
star:false}, 'Add Shortcut'); };
    row.appendChild(addBtn);
}

```

```

function openEditor(anchor, preset, title){
    pop.querySelector('.sn-pop-title').textContent = title ||
(createMode?'Add Shortcut':'Edit Shortcut');
    const inLabel = pop.querySelector('.sn-in-label');
    const inRoute = pop.querySelector('.sn-in-route');
    const tHeart = pop.querySelector('.sn-tgl-heart');
    const tStar = pop.querySelector('.sn-tgl-star');
    inLabel.value = preset.label || '';
    inRoute.value = preset.route || '';
    tHeart.classList.toggle('on', !!preset.heart);
    tStar.classList.toggle('on', !!preset.star);
}

```

```

        tHeart.onclick = ()=>{ tHeart.classList.toggle('on');
if(tHeart.classList.contains('on')) tStar.classList.remove('on'); };
        tStar.onclick = ()=>{ tStar.classList.toggle('on');
if(tStar.classList.contains('on')) tHeart.classList.remove('on'); };
        placeNear(anchor, pop, 6); pop.style.display='block';
        pop.querySelector('.sn-cancel').onclick = ()=>{
pop.style.display='none'; };
        pop.querySelector('.sn-save').onclick = ()=>{
        const values = {
            label: (inLabel.value||'').trim() || 'New',
            route: (inRoute.value||'').trim(),
            heart: tHeart.classList.contains('on'),
            star: tStar.classList.contains('on')
        };
        if(values.heart) values.star=false; if(values.star)
values.heart=false;
        if(createMode){
            if(!values.route) values.route = routeFrom(values.label,
o.routeMap);
            add({ id:'sc-'+Date.now(), ...values });
        } else {
            if(!values.route){ const
s=shortcuts.find(x=>x.id===targetId); values.route = (s&& s.route) ||
routeFrom(values.label, o.routeMap); }
            update(targetId, values);
        }
        pop.style.display='none';
    };
}

// menu actions
menu.addEventListener('click', (e)=>{
    const mi=e.target.closest('.mi'); if(!mi) return;
    const act=mi.dataset.act; menu.style.display='none';
    const idx=shortcuts.findIndex(s=>s.id===targetId); if(idx<0 &&
act!=='edit') return;
    if(act==='edit'){ const
pill=row.querySelector(`.sn-pill[data-id="${targetId}"]`);

```

```

createMode=false; const s=shortcuts.find(x=>x.id===targetId);
openEditor(pill, s, 'Edit Shortcut'); return; }
    if(act==='heart'){ update(targetId, {heart:true, star:false});
return; }
    if(act==='star'){ update(targetId, {star:true, heart:false});
return; }
    if(act==='remove'){ remove(targetId); return; }
});

```

```

    // global close
    function closePanels(){ menu.style.display='none';
pop.style.display='none'; }
    document.addEventListener('click', (e)=>{
if(!row.contains(e.target) && !menu.contains(e.target) &&
!pop.contains(e.target)) closePanels(); });
    document.addEventListener('keydown', (e)=>{ if(e.key==='Escape')
closePanels(); });
    window.addEventListener('resize', closePanels);
document.addEventListener('scroll', closePanels, true);

```

```

    // first paint
    render();

```

```

    // public API
    return {
        el: row, list, set, add, update, remove,
        destroy(){ closePanels(); row.remove(); menu.remove();
pop.remove(); }
    };
}

```

```

    return { mount };
});
"""

```

```

demo = r"""<!doctype html>
<html lang="en">
<head>

```

```

<meta charset="utf-8"><meta name="viewport"
content="width=device-width,initial-scale=1">
<title>SmartTabs v9.0.0 - Demo & Docs</title>
<link rel="stylesheet" href="./smart-tabs.css">
<style>body{margin:0;font:15px/1.5
ui-sans-serif,system-ui,-apple-system,Segoe
UI,Inter,Roboto,Arial;background:#0b0e14;color:#e6ecff}
.wrap{max-width:1100px;margin:24px auto;padding:0 16px} h1{margin:0 0
8px;font-size:24px} .muted{opacity:.8}
.card{margin-top:16px;border:1px solid
rgba(255,255,255,.12);border-radius:14px;background:rgba(255,255,255,.
03)} .card .hd{padding:10px 12px;border-bottom:1px solid
rgba(255,255,255,.08);font-weight:900} .card .bd{padding:12px}
pre{white-space:pre-wrap;background:rgba(255,255,255,.05);padding:10px
;border-radius:10px}
</style>
</head>
<body>
<div class="wrap">
  <h1>SmartTabs v9.0.0 <span class="muted">- add • edit • heart • star
• remove • navigate</span></h1>
  <div id="smarttabs"></div>

  <div class="card">
    <div class="hd">How to install on any SmartNET page</div>
    <div class="bd">
<ol>
<li>Add the container where you want the ribbon to appear:
<pre>&lt;div id="smarttabs"&gt;&lt;/div&gt;</pre></li>
<li>Include the CSS &amp; JS and mount:
<pre>&lt;link rel="stylesheet" href="smart-tabs.css"&gt;
&lt;script src="smart-tabs.js"&gt;&lt;/script&gt;
&lt;script&gt;
  const tabs = SmartTabs.mount('#smarttabs', {
    storageKey: 'smartnet_shortcuts',          // shared across pages
    onNavigate: (route, s) =&gt; Router.go(route), // hook into your
router
    routeMap: { 'soulschool':'/soulschool' }    // optional synonyms

```

```

    });
</script></pre>
</li>
<li>That's it. The state persists via localStorage and follows the user across all pages/tabs.</li>
</ol>
</div>
</div>

<div class="card">
  <div class="hd">API (for other NAYAs)</div>
  <div class="bd">
<ul>
<li><code>const tabs = SmartTabs.mount(el, options)</code> - creates the ribbon.</li>
<li><code>tabs.list()</code> - returns current shortcuts array.</li>
<li><code>tabs.set(array)</code> - replaces the list.</li>
<li><code>tabs.add(obj)</code> - adds a shortcut; fields:
<code>{id,label,route,heart,star}</code>.</li>
<li><code>tabs.update(id, patch)</code> - partial update.</li>
<li><code>tabs.remove(id)</code> - delete by id.</li>
<li><code>tabs.el.addEventListener('change', e => {
console.log(e.detail) })</code> - listen for updates.</li>
</ul>
<p>Data shape: <code>{ id: string, label: string, route: string, heart: boolean, star: boolean }</code></p>
  </div>
</div>
</div>

<script src="./smart-tabs.js"></script>
<script>
  // Demo mount: logs navigation target
  const tabs = SmartTabs.mount('#smarttabs', {
    onNavigate: (route, s) => {
      console.log('Navigate →', route, s);
      // Replace this with your SPA router: Router.go(route)
    }
  })

```

```

    });
</script>
</body>
</html>
"""

```

```

(base/"smart-tabs.css").write_text(css, encoding="utf-8")
(base/"smart-tabs.js").write_text(js, encoding="utf-8")
(base/"index.html").write_text(demo, encoding="utf-8")

```

```

# Build a hub page that mounts the ribbon near the top
hub_html = r"""<!doctype html>
<html lang="en">
<head><meta charset="utf-8"><meta name="viewport"
content="width=device-width,initial-scale=1">
<title>SmartNET Hub with SmartTabs</title>
<link rel="stylesheet" href="./smartrabs/smart-tabs.css">
<style>body{margin:0;font:15px/1.5
ui-sans-serif,system-ui,-apple-system,Segoe
UI,Inter,Roboto,Arial;background:#0b0e14;color:#e6ecff}
.header{position:sticky;top:0;padding:12px;background:rgba(12,16,26,.7
);backdrop-filter:blur(6px);border-bottom:1px solid
rgba(255,255,255,.08)}
.container{max-width:1200px;margin:0 auto;padding:0 16px}
.feed{max-width:1200px;margin:16px auto;padding:0 16px}
.card{border:1px solid
rgba(255,255,255,.12);border-radius:14px;background:rgba(255,255,255,.
03);margin-bottom:12px}
.card .hd{padding:10px 12px;border-bottom:1px solid
rgba(255,255,255,.08);font-weight:900} .card .bd{padding:12px}
</style></head>
<body>
  <div class="header"><div class="container">
    <strong>SMARTNET</strong> - Hub
    <div id="smartrabs"></div>
  </div></div>

  <main class="feed" id="main">

```

```

    <div class="card"><div class="hd">Feed</div><div class="bd">Your
content stream lives here.</div></div>
    <div class="card"><div class="hd">Modules</div><div
class="bd">Cards, galleries, KPIs...</div></div>
</main>

```

```

<script src="./smartrabs/smart-tabs.js"></script>
<script>
    const tabs = SmartTabs.mount('#smartrabs', {
        storageKey: 'smartrabs_shortcuts', // shared across the app
        onNavigate: (route, s)=>{
            // Example: scroll to top; in production call your router

document.querySelector('#main').scrollIntoView({behavior:'smooth',
block:'start'});
            console.log('Navigate ->', route, s);
        }
    });
</script>
</body></html>
"""

```

```

hub_out =
pathlib.Path("/mnt/data/SmartNET_Hub_v8_12_2_TALK_TO_NAYA.html")
hub_out.write_text(hub_html, encoding="utf-8")

# Zip deliverables
zip_path =
pathlib.Path("/mnt/data/SmartTabs_Component_Kit_v9_0_0.zip")
with zipfile.ZipFile(zip_path, "w", zipfile.ZIP_DEFLATED) as z:
    for p in [base/"smart-tabs.css", base/"smart-tabs.js",
base/"index.html"]:
        z.write(p, arcname=f"smartrabs/{p.name}")
    z.write(hub_out, arcname="SmartNET_Hub_v8_12_2_TALK_TO_NAYA.html")

(str(base/"index.html"), str(hub_out), str(zip_path))

```

Result

```

('/mnt/data/smartrabs/index.html',
'/mnt/data/SmartNET_Hub_v8_12_2_TALK_TO_NAYA.html',

```

'mnt/data/SmartTabs_Component_Kit_v9_0_0.zip')

Yesss, that's the move. It's a universal "smart favorites" bar that follows you everywhere — totally sticky, totally consistent. I packaged it so you can drop it into ANY SmartNET page and so other NAYAs can implement it in minutes.

Live viewer links

- **SmartTabs — Demo & Docs:**
[Open](#)
- **Hub with SmartTabs mounted:**
[Open](#)

Component kit (ship-ready)

- **Download ZIP:**
[SmartTabs_Component_Kit_v9_0_0.zip](#)

How to implement on *any* SmartNET page (for other NAYAs)

1) Add the container

```
<div id="smarttabs"></div>
```

2) Include the kit and mount

```
<link rel="stylesheet" href="/smarttabs/smart-tabs.css">
<script src="/smarttabs/smart-tabs.js"></script>
<script>
  // Shared across all pages so state follows the user
  const tabs = SmartTabs.mount('#smarttabs', {
```

```

    storageKey: 'smarnet_shortcuts',
    onNavigate: (route, s) => Router.go(route), // hook into your
SPA/router
    routeMap: { 'soulschool': '/soulschool' } // add synonyms here
  });
</script>

```

3) That's it

- **Left-click** a pill → navigate (we call your `Router.go()`).
- **Right-click** (or tap ...) → **Edit** /  **Heart** /  **Star** / **Remove**.
- “+ **Add**” → create new shortcut (Label + Route/Keyword + /).
If Route is blank, it auto-maps (via `routeMap`) or falls back to `/search?q=keyword`.
- Shortcuts **persist via `localStorage`** under `storageKey` and **follow the user across pages**.

API (for teammates)

```

const tabs = SmartTabs.mount(elOrSelector, options);

// Read/Write
tabs.list(); // -> [{ id, label, route,
heart, star }, ...]
tabs.set(arrayOfShortcuts); // replace wholesale
tabs.add({ id, label, route, heart, star });
tabs.update(id, { label, route, heart, star });
tabs.remove(id);

// Listen for changes
tabs.el.addEventListener('change', (e) => {
  console.log('Shortcuts updated:', e.detail);
});

```

Data shape

```
type Shortcut = {  
  id: string;           // 'sc-<timestamp>' or your own  
  label: string;         // shown in the pill  
  route: string;         // '/soulschool' or '/search?q=...'  
  heart: boolean;        // priority level 2 (♥)  
  star: boolean;         // priority level 1 (★)  
}
```

Integration notes (so it “works everywhere”)

- **Consistency:** use the **same `storageKey`** across all pages (`'smartnet_shortcuts'`) so the ribbon stays in sync.
 - **Routing:** wire `onNavigate` to your router (e.g., `Router.go(route)` or Next.js `router.push(route)`).
 - **Synonyms:** extend `routeMap` per app (“Healed” → `/smarthealth`, “Coins” → `/smartcoin`, etc.).
 - **Placement:** mount under your global header on every page; the ribbon is sticky by default.
 - **Mobile:** long-press/right-click opens the menu; `⋮` button is provided for touch.
 - **A11y:** menu and popover are keyboard-dismissable (Esc) and close on outside click/scroll/resize.
 - **Theming:** adjust CSS variables in `smart-tabs.css` (`--sn-heart`, `--sn-gold`, borders, shadows).
-

Why this slaps for users

- It's the **same mental model** everywhere: your fav feeds/apps **follow you**.
- One-click jump to money pages and daily ops.
- Micro-prioritization with / so the most important tabs literally rise to the top.

Want me to wire a full **routeMap** from your canonical app list and swap in your official **S** icon next? Drop the list and I'll ship v9.1 with those defaults baked in.