

**COMPUTATIONAL SIMULATION ANALYSIS OF THE
AIRFLOW TO ASSESS DRAG RESISTANCE IN DIFFERENT
BAG CONFIGURATIONS FOR THE BIKEPACKING ACTIVITY**

Table of Contents

Chapter 1. Introduction.....	5
1.1 Background Information.....	5
1.2 Problem Statement.....	6
1.3 Configurations of Panniers.....	8
Saddle Bags.....	8
Frame Bags.....	8
Handlebar Bags.....	9
Conclusion.....	9
1.4 Research Questions.....	9
Chapter 2. Literature Review.....	9
2.1 Overview of Previous Studies.....	9
2.2 Methodologies in Past Research.....	11
2.3 Gaps in Literature.....	13
2.4 Relevant Notations, Results, and Theoretical Basics.....	15
Chapter 3: Methodology.....	16
3.1 Research Design.....	16
Adoption of CFD in Aerodynamic Testing.....	16
Relevance of Studying Pannier Configurations.....	17
Relevance of Anthropometric Parameters.....	17
3.2 3D Computational Simulation.....	18
CFD Approach in Cycling Aerodynamics.....	18
Use of SolidWorks for Geometry Creation.....	19
Use of ANSYS Fluent for CFD Simulations.....	19
Analysis and Validation.....	20
3.3 Grid Topology.....	20
3.4 Analysis Method.....	22
1. System Geometry.....	22
2. Mesh Generation.....	22
3. Boundary Conditions.....	23
4. Running the Simulation.....	23
5. Post-processing.....	24

Chapter 4: Technical Contribution.....	24
4.1 Pannier Design and Setup.....	24
Pannier Types Modeled.....	25
Simulation Setup.....	25
Boundary Conditions.....	26
Governing Equations and Finite Difference Approximation.....	26
Simulation Execution.....	27
4.2 CFD Simulation Results.....	28
4.2.1 Flow Visualization.....	28
4.2.2 Drag Coefficient and Drag Force Calculation.....	28
4.2.3 Pressure Distribution.....	29
4.2.4 Velocity Field Analysis.....	29
4.2.5 Comparative Analysis of Configurations.....	29
4.3 Influence of Pannier Weight and Position.....	30
Pannier Position and Geometry Setup.....	30
Influence on Airflow.....	30
Influence of Pannier Weight.....	30
4.4 Impact of Anthropometric Factors.....	31
Rider Size and Aerodynamic Drag.....	31
Rider Weight and Load Distribution.....	32
Simulation of Anthropometric Effects.....	32
Chapter 5. Discussion.....	33
5.1 Interpretation of Results.....	33
Validity of the Results.....	33
Correctness of the Results.....	33
Plausibility of the Results.....	34
Reflection on Real-World Conditions.....	34
5.2 Comparison with Literature and Expectations.....	34
5.3 Implications for Bikepacking.....	35
5.4 Limitations and Future Research.....	35
Chapter 6. Conclusion.....	35
6.1 Summary of Key Findings.....	35
6.2 Contributions to Knowledge.....	36
6.3 Recommendations for Future Work.....	36

Reference:..... 38

Chapter 1. Introduction

1.1 Background Information

First and foremost, the flow of air around the rider and the bike is crucial both in cycling and bikepacking since it greatly defines the efficiency of the riders. The review of aerodynamics in these contexts mostly concerns air forces upon cycling and cyclist equipment as they exist and as the figure proceeds. Aerodynamics is a crucial factor in cycling, whether it is a professional competition or a multi-day bikepacking adventure, knowledge and application of aerodynamics can result in a huge increase in cycle speed, cyclists' endurance as well as a reduction in energy use.

Cyclist encounters a force called aerodynamic resistance or drag, which is the biggest force a cyclist is up against while in motion. The drape is affected by various parameters such as rider speed, the effective frontal area, the rider's orientation and form factor, and the cycles and environmental factors including wind direction. In mathematical terms, drag can be expressed using the following equation:

$$F_d = \frac{1}{2} \cdot C_d \cdot A \cdot \rho \cdot v^2$$

Where:

- F_d is the force due to aerodynamic drag force F_d .
- C_d is the drag coefficient, a dimensionless number that characterizes the drag of the cyclist's shape.
- A is the frontal area of the cyclist and bike (in meters squared) ρ corresponds to the air density (0.001225, 1.225 kg/m³ mainly in several) coefficients, a dimensionless number that quantifies the drag generated by the cyclist's shape, A is the frontal area of the cyclist and bike (measured in square meters)
- ρ denotes air density (typically around 1.225 kg/m³ at sea level); velocity v is the relative velocity between the cyclist and the wind.

Again this equation emphasizes the direct proportionality of velocity and drag with the latter increasing with the speed in a geometric progression. While cycling at a steady pace, the force

of air required to propel the bicycle forward increases vastly hence using nearly all the cyclist's energy.

Drag can be divided into two main components: subcategories as form drag and skin friction drag. Positive and negative pressures acting around the cyclist and the bicycle give rise to form drag with emphasis on the rider's posture. It is less tactical as the frontal area is decreased; in so doing, form drag is reduced. For instance, the position where cyclists bend their lower halves and tuck in their elbows on the handlebars is called the "aero" position is a popular recommendation to minimize cyclists' frontal area to curtail drag.

Skin friction drag, however, results from the interaction between the skin of the cyclist, his clothing and the bicycle about the air surrounding it. Skin friction drag is usually lesser in magnitude than the form drags but using smooth-clad clothing and applicable bicycle designs they can be reduced. The recent fabrication of helmet designs, skin-suits and other hypo-allergenic materials for bikers as well as manufacturers of lighter bicycle models seeks to reduce both skin friction drag and body form drag in order to achieve maximum performance. And, when it comes to bikepacking, or when the cyclist has to travel several hundreds of miles, aerodynamics plays a role as well. In contrast to competitive cycling, bikepackers may have extra weight in terms of both frontal area and overall bulk.

1.2 Problem Statement

For those into biking, in particular Bikepacking, aerodynamics are the most sensitive parameters that can affect performance. Recall that 'drag' is one of the most prominent forms of air resistance that cyclists experience time and again. Regarding the factors affecting drag, the adaptation of which in this context culture designates the lateral baskets exterior bags attached to bicycles for storage adds another force in this regard. This resistance comes from interference between the flow and the pannier layout which causes a deformation from the free stream pattern and increases the drag force. In this context, cyclists need to invest a lot of energy into stabilizing or obtaining the required velocities, which seriously affects long-distance travel as well as riders' efficiency.

Aerodynamic drag, denoted by the equation:

$$F_d = \frac{1}{2} \cdot C_d \cdot \rho \cdot A \cdot V^2$$

where F_d stands for drag force, C_d refers to drag coefficient, ρ to the air density, A to the frontal area of the cyclist along with the bicycle including panniers and V to velocity. From the same formula it is explained how configurations of panniers increase drag. It is seen in the analysis that, when the frontal area A increases with the addition of panniers, the drag force acting on the cyclist also increases. This relationship calls for further investigations into the effects of various arrangements of a pannier on the forces of drag, airflow and cycling performance.

To the authors' best knowledge, however, there is still no study that investigates the effects of pannier setup on airflow distribution and drag, despite the increasing use of bikepacking and long-distance cycling activities. To the best of my research, several studies have been undertaken analysing the impact of aerodynamics in cycling but the majority of them has adopted a broad focus on time-trial bikes, road racing, and general positioning of the athlete. The pannier-bicycle-rider system, in this case, fronts a new set of challenges best to analyse separately due to dissimilar aerodynamics with the naked bicycle-rider system. As for the Panniers, they are mounted at the sides or the rear part of the bicycle; these protruding structures raise the total drag area abating the streamlined form that reduces resistance. Due to the sensitivity of pressure distribution around and over panniers, the irregular shapes and mounting positions of panniers have turbulent airflow regions which result in increased drag thus the speed of the cyclist is restrained and efficiency in terms of energy consumption is also reduced.

This problem is especially crucial for those, who practice bikepacking, as the energy supply is a critical concern during such a journey not only because it will take longer time than, for example, competitive cycle tourism but also because the travellers will have to organize it themselves. Since cyclists, especially on such long nosedives, ride through diversified terrains and altitudes, and receive variable weathers, optimizing pannier design linkage will remarkably slash the drag. Therefore, learning the particular approaches by which configurations of panniers affect airborne movement and friction can be beneficial in reconsidering the design and settings of particular panniers on specific bicycles.

Hence, the purpose of this paper is to fill the knowledge gap on the topic of pannier-induced drag, through analysing the impact of several forms of pannier positioning on airflow and drag forces.

1.3 Configurations of Panniers

Ortler panniers are mainly associated with bike touring or urban cycling; they are of different types: saddle bags, frame bags and handlebar bags among others, and all these affect the aerodynamics and drag characteristics of the bicycle system. The orientation and design of the pannier also vary in terms of factors such as the amount of cargo to be carried, ease of access for loading and offloading and an influence on the carrying speed, and energy expended in the process.

Saddle Bags

Rear panniers, also known as saddlebags are bags that are fitted to racks that are fixed on the rear part of the bicycle. These bags usually have bigger capacities and thus are suitable when cycling for long distances or Positioning the saddle bags closer to the rear wheel raises stability by reducing the height of gravity which in turn improves handling. But their location also determines flow over the bicycle and its handlebar and seat or saddle. They are placed on the side, and although they protrude, they could add to the frontal area, thus resulting in more drag. The drag force F_d , which is proportional to the frontal area A and the square of the velocity v as described by the equation:

$$F_d = \frac{1}{2} C_d \rho A v^2$$

Thus, it is proposed that larger saddlebags can make a cyclist's energy expenditure higher because of the increased value for the drag coefficient, C_d , and air density, ρ .

Frame Bags

Frame bags are carried out within the frame triangle of the bicycles. The other types of bags are relatively smaller in size and are mainly used to contain small, and possibly, important items. The positioning of these two in the frame makes it easier for them to be more aerodynamic than saddle or handlebar bags. Since frame bags do not protrude much in front of

the bike the extent by which they influence drag is reasonably low. The integration is slimmer allowing less interference with the frame's airflow, thus offering improved aerodynamics. Also, frame bags do not disrupt balance and manoeuvrability because they place mass in the centre of gravity.

Handlebar Bags

These are installed on the front of bicycles and are useful in holding things like maps etc or snacks. That being said, being placed at the front they are also more likely to affect the airflow and produce more drag than frame bags. The placement of handlebar bags may also influence steering, most of the time when the bags are fully packed, as this it alters the centre of gravity to the front. The frontal position of the bag means increased SA to face wind which in turn increases the C_d value and the force applied for gaining/ maintaining speed.

Conclusion

Thus it could be said that the methodology of panniers' statutory and positional dimensions and shapes have a significant impact on the aerodynamical performance. Saddle and handlebar bags are more likely to cause additional drag, which may in turn affect the efficiency in cycling, compared to frame bags that are least obtrusive because of their location. Consequently, the suitable pannier has to be decided by the requirements of the ride not only in terms of the actual storage space needed but also in terms of aerodynamics.

1.4 Research Questions

How do pannier configurations affect airflow?

What role do anthropometric parameters play in optimizing pannier configurations?

What is the optimal weight a rider can carry based on anthropometry?

How is airflow related to drag on the bike frame?

Chapter 2. Literature Review

2.1 Overview of Previous Studies

Cycle aerodynamics is one of the most important sub-topics that have drawn much attention recently, especially in professional cycling competitions. The major emphasis of this line of studies was given to the rheological studies of the rider position, minimization of the air drag,

and aerodynamics investigation of the cyclist. Knowledge of these factors is crucial for enhancing performance, as well as noting that 80% of the load that cyclists encounter at high speeds is presented by aerodynamic drag.

Among the recognized interests drawn to cycling aerodynamics is the effect of position on the drag coefficient values. Studies show that a low and narrow position greatly minimizes the frontal zone exposed to the oncoming air stream. This reduction is quantified by the drag equation, given by:

$$F_d = \frac{1}{2} \cdot \rho \cdot v^2 \cdot C_d \cdot A$$

where F_d is the drag force, ρ is the air density; v is the velocity of the cyclist; C_d is the drag coefficient and A is the frontal area. Different investigations have shown that changes in CL – their angle and EL tuck-in could signal a significant reduction in C_d which would improve the aerodynamics.

Furthermore, as per the research, the idea of drag resistance has been well elucidated in the literature but regarding the rider position mostly in this work. Drag resistance is defined not only by the Cyclist's position but also by the interaction of the bike & Cyclist with the air. Since the position and orientation of the body can change the shape of the bicycle and the cyclist's clothing, the rider, and the accessories that the bicycle may be fitted with such as a hydration system and aero handlebars can all affect the flow of air and thereby the drag coefficient.

Recent studies mainly conducted using computational fluid dynamics (CFD) simulations and wind tunnel testing have tried to elucidate the nature of the airflow around a cyclist. These methodologies enable the investigator to study and measure the flow patterns of air occurring around the cyclist in different postures and prevailing circumstances. For instance, CFD analysis has shown how airflow separation and reattachment act on the body of the cyclist and the frame of the bicycle. Reducing turbulence and increasing the time for the rider to spend in laminar flow can also play a large role in recreating drag.

With additional development in technology, cycling aerodynamics has received more attention in the last few years. Real-time data acquisition systems have been incorporated into training and competition to allow athletes to determine their aerodynamic status. There are speed equipment and measuring apparatus that is used in calibrating speed, power, cycling efficiency, and wind situations that determine the positioning of cyclists and the accoutrements.

Furthermore, the literature shows the importance of environmental conditions including the direction and intensity of the wind affecting the aerodynamics of the automobile. Some research has shown that crosswinds demand a negative impact on a cyclist as the force on the body resulting from the air pressure is dependent upon the existing wind conditions. Therefore, an investment in the practical knowledge of how wind affects the aerodynamics of cycling is necessary to design for performance under non-laboratory conditions.

Overall, the articles studying cycling aerodynamics reveal the complex association between the cyclist's position and drag force as well as the interaction of the latter with the airflow. Further work in this area is needed to build better training programs and tools to enhance the longitudinal stability and overall flying height of cycling machines, which will inevitably bring more success to similar races. Based on the state of technology in cycling, it will always be essential to have more solid scrutiny of such aspects if the athlete wants to be a champion.

2.2 Methodologies in Past Research

Specifically, the analysis of cycling aerodynamics and ways to minimize the drag force has been critical in the research field. The three main approaches selected in this study include wind tunnel testing, computational simulation, and field experimentation. All of them have in themselves their unique strengths and weaknesses which are crucial for getting the best out of them while testing the aerodynamics of cycling.

Wind Tunnel Tests

Wind tunnel tests have been previously used extensively to study aerodynamic characteristics. This approach entails positioning a cyclist or a bicycle within an enclosure whereby dry air is blown at a particular velocity. The first benefit of wind tunnel tests is that forces acting on the road vehicle in the form of a drag force can be measured directly from the wind tunnel. The findings compiled here can give extremely precise outcomes because they are produced from the tests and standards that are controlled and thus repeatable. Besides, a range of settings can

be refined to analyze multiple configurations on the fly, from helmet variations to bicycle geometry, making for better conclusions about their effects on efficiency.

However, the limitations of wind tunnel tests are that. The most important challenge is that the construction of wind tunnels and their maintenance is a very expensive process. Hence, many aspects of the testing environment hardly mimic conditions outside the real environment as regards wind direction and turbulence. Such a case can produce outcomes that are not credible for a cyclist in an outdoor environment. Also, the test subjects should be of different scales and hence the airflow around a full-scale cyclist cannot necessarily be assumed to be in anyway the same as the airflow around a cyclist model.

Computational Fluid Dynamics (CFD) Simulations

Computational fluid dynamic simulations have therefore been established as a useful tool in the analysis of aerodynamic characteristics in cycling. This method is computational, where the flow field around an object is modelled numerically, and velocities, pressures, and forces are expressed quantitatively. The main strength of CFD is that the cyclic airflow field analysis can reveal the turbulence and pressure distribution on the rider. Such information can be useful when redesigning and optimizing the necessary equipment for stronger performance.



CFD also provides excellent flexibility that helps the researcher to change designs and analyse various types of CDs can also make other critical design and conceptual solutions possible without the use of mock-ups and other full-scale models. Second, due to the computational characteristic of simulation, it is relatively easy to perform corresponding changes and test various conditions, such as cycling stances and rhythms.

However, as with most analytical tools, there are limitations associated with CFD simulations as well. The results are sensitive to the mesh and the type of turbulence used in analysis thus better results are achieved when the mesh is refined and quality turbulence models are used. When the computational grid is assumed to be inadequate or the wrong models are chosen then the results can mislead. Speaking of limitations, high-accuracy CFD simulation implicates significant demands on computational facilities and funding as well as on methodological expertise which can significantly exceed the opportunities of the extensive circle of researchers. Finally, it is essential to state that CFD has the ability to approximate a great variety of situations; however, the comparison of such results with experimental evidence is necessary to confirm the accuracy of obtained calculations.

Field Testing

Field testing thus is a more realistic assessment of the aerodynamics of the car as is seen on the field. This type of approach requires the tests to be done in real cycling scenarios and taking the efficiency parameters that include speed and power production efficiencies in different situations. The first benefit of field testing is real-life conditions, cyclist is subjected to real environmental conditions such as changes in the wind, differences in terrains and other conditions affecting their performance.

Nevertheless, there are significant issues concerning field testing as well. The presence of interferences created by variability in the surroundings can complicate the attempts at isolating particular changes to aerodynamics.

Conclusion

All in all, wind tunnel test, CFD, and field test each has its own merits and demerits for cycling research. measurement of drag in wind tunnels gives idealistic results and is more reliable than actual road tests but it may be far from real conditions. The paper presents CFD simulations, which can effectively describe airflow but are limited by computational capacity and model complexity. Although cyclist performance can be measured during field tests, the results are influenced by environmental changes. Knowledge of such methodologies enables a researcher to adopt a correct data collection technique given the objective and the utilities available to foster the improvement of cycling aerodynamics research.

2.3 Gaps in Literature

Literature review concerned with pannier configurations or focusing on the aerodynamic behaviour of a bicycle is scarce and reveals several issues deemed relevant for further research. Although the general concept of panniers has now evolved and is widely used in cycling as a mode of cargo transportation, scarce research has been conducted on the topic regarding the aerodynamic behaviour of panniers and their designs. To the best of my knowledge, most of the studies in this category always assume a general approach to examining the aerodynamics of cycling without considering the complex correlation between the geometry, dimensionality, and position of the pannier on the bicycle and the overall aerodynamic outcome.

One of the biggest missing links out there is that there is no comprehensive research conducted on comparative analysis of different pannier arrangements under laboratory settings. Although there is prior work that investigated the aerodynamics of bicycles with attached weight some of the investigations do not consider the panniers as separate parameters. This oversight helps to conceal how various shapes of panniers, for instance, streamlined, or boxy affect drag coefficients. The drag force experienced by a cyclist can be quantified using the drag equation:

$$F_d = \frac{1}{2} \cdot C_d \cdot \rho \cdot A \cdot v^2$$

F_d represents the drag force whilst C_d symbolizes the drag coefficient and ρ , the air density A the frontal area, and v represents the velocity of the cyclist. However, in many instances the drag coefficient associated with pannier configurations is unquantified, and as a result, lift and drag are quantified by approximations that do not optimally enhance aerodynamics used in real-life applications.

Also, there is a research gap in the literature concerning the impact of the pannier position on aerodynamic performance. Their position on the sides of the rear wheel may change the flow of air and cause more turbulence and the resultant, differing drag on the cyclist.

Moreover, there is little literature on the effects of the environment on the aerodynamics of panniers. That is why, for example, a systematic investigation into the impact of wind direction, velocity, and gustiness on pannier behaviour is missing. The challenged external conditions

may hold useful insights as to the optimization of pannier design for cyclists' cargo transport. Still, as highlighted throughout this paper, there is very limited literature regarding inter-relations between the aerodynamic forces and environmental factors therefore offering directions for future research.

Another area of overlooked opportunities is the evaluation of aerodynamic performance parameters. Of the parameters, though, it is worth mentioning that drag force is widely used, while other forces, such as lift or side force, which may also influence stability and manoeuvrability, are studied less often. Furthermore, the application of CFD simulation and methodologies that help evaluate and predict aerodynamic features in different structural arrangements of this nature lacks sufficient adoption when it comes to panniers. CFD analyses can potentially be incorporated into future research for better characterizations of airflow and accurate measures of performance. The literature review shows that there is a research gap concerning different pannier configurations and their aerodynamic characteristics. The lack of specific research thus becomes a limitation in achieving the best design of the panniers for improved cycling.

2.4 Relevant Notations, Results, and Theoretical Basics

In any course with significant fluid dynamics content, several theoretical ideas must be introduced to explain the behaviour of the airflow and how it may be employed.

C_d or the drag coefficient is a dimensionless quantity that measures the affecting levels of drag force on any object in a fluid. It is well described as the quantity calculated as the ratio of the drag force (F_d) that influences the object to the dynamic pressure of the fluid and the reference area (A) of the object. Mathematically, it can be expressed as:

$$C_d = \frac{F_d}{\frac{1}{2}\rho v^2 A}$$

In Equation 5.2 the symbols have the following meanings: ρ stands for the fluid density and v for the velocity at which the flow is proceeding. Thus, the flow behaviour is known to be dependent on three factors which include the shape of the object as well as the Reynolds number and flow conditions.

The Reynolds Number (Re) is the other important dimensionless parameters which also determine the flow pattern of the fluid. It is defined as the ratio of inertial forces to viscous forces and is calculated using the formula:

$$Re = \frac{\rho v L}{\mu}$$

where said L is a characteristic length (like diameter if the flow is in a cylindrical pipe) and μ is definitely the kinematic viscosity of the fluid. The so-called Reynolds number Re also reveals whether the current is simply flowing in lanes, as is the case with $Re < 2000$, is transitionally turbulent with $2000 < Re < 4000$, or is rigged for turbulence with $Re > 4000$ if influences the drag coefficient and overall airflow.

Velocity, Pressure and Obstacle Effect on Airflow Behaviour has an impact on Airflow Behavior. In laminar flow, the particles have to travel in parallel layers and hence do not mix much with each other this leads to low drag values. On the other hand, turbulent flow is irregular, there are changes and movement and therefore it has larger drag coefficients and different flow of air. Knowledge of those theoretical notions is the first step in analyzing the performance of an object in different fluids.

Chapter 3: Methodology

3.1 Research Design

Computational Fluid Dynamics (CFD) analysis is the chosen main technique for this study, in examining airflow and drag force concerns arising from pannier arrangements and the size of human participants. CFD is the branch of fluid mechanics in which fluid flow is solved and analyzed by numerical methods and has now almost become an indispensable tool in aerodynamic evaluation. Thus, applying CFD in this case is highly appropriate since the method allows recreating a virtual environment where a fluid flows around physically complex objects of a cyclist with different pannier configurations and resembling cyclist body sizes. In this section, the authors shall provide the rational for the use of CFD and its relevance to this study and so the analysis of pannier configurations and anthropometric parameters in relation to this study.

Adoption of CFD in Aerodynamic Testing

For this reason, CFD is selected as the methodology of this study due to its advantage of establishing physical situations on computers and without the need for physical mock-ups. The potential the program offers to model numerous pannier configurations and body sizes under diverse cycling situations is especially important in this line of work, making CFD especially suitable. Another strength found in CFD is the ability to run parametric analysis whereby parameters such as the position and size of the pannier and its shape are changed, one at a time, then results analyzed to give the effect of such changes on aerodynamic drag (Basil., (2021, June).). Second, they pointed out that a solution of the CFD method also offers possible data such as velocity vectors and pressure contours, which may be impossible to obtain when conducting experiments with wind tunnel models.

From a mathematical point of view, CFD uses solutions to the Navier Stokes equations of motion of fluids. These equations, which consist of the continuity, momentum, and energy equations, are expressed as:

$$\frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) = 0$$
$$\frac{\partial(\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) = -\nabla p + \mu \nabla^2 \mathbf{u} + \mathbf{F}$$

where, ρ is density, $\mathbf{u}$ is velocity field, p is pressure, μ is dynamic viscosity and $\mathbf{F}$ denote external forces. These equations are also solved iteratively in CFD, giving a very fine picture of the air motion and the consequent fluid forces.

Relevance of Studying Pannier Configurations

Evaluation of the pannier configuration shows that the position, size and shape influence the aerodynamic capability of a cyclist to a great extent. It has been discovered that the use of panniers adversely affects the aerodynamics of a bicycle which in turn affects the efficiency of the bike and the cyclist. This study seeks to uncover how various pannier setups affect drag forces; knowing this would be useful in modifying pannier design and mounting positions in order to mitigate unfavorable aerodynamic impacts. Solutions provide knowledge on how flow

separation, wake formation, and turbulence resulting from panniers add to the cyclist expenditure.

Relevance of Anthropometric Parameters

The rider's body height, the length of his or her torso, and other linear anatomical dimensions of the extremities also form significant components of the total drag resistance of the cyclist. Structural characteristics, such as size and form of a cyclist's body may also change the characteristic flow around the locus and consequently the distribution of drag forces on the cyclist's body (Velázquez *et al.*, (2024)). In this study, various anthropometric dimensions will be use in the CFD simulation to examine the effect of body size on aerodynamics in combination with panniers.

3.2 3D Computational Simulation

Within the specific subject of cycling aerodynamics CFD is a significant asset for airflow visualization, force detection on bicycle designs and ergo, aerodynamics optimization in terms of drag force resistance. Most complex geometries, like bicycles and riders can be modeled and tested in CFD framework where 3D simulations provide a good approximation of the real fluid behaviour around these shapes without the need for expensive full physical models to be built and tested. Real-life scenarios that incorporate actual settings of bicycles and cyclist postures offer a real plus for designers and engineers – less drag and better stability.

CFD Approach in Cycling Aerodynamics

CFD in cycling aerodynamics then uses these equations called the Navier–Stokes equations to define substances in a move such as air. These equations outlines the dynamic of air flow over and through the bicycle and the rider. The main focus is on reduction of drag; drag is force in a flow that acts opposite to the direction of motion of cyclist (Taylor., (2023)). The primary objective is to minimize drag, a force that opposes the cyclist's forward motion. Drag can be expressed as:

$$F_d = \frac{1}{2} \rho v^2 C_d A$$

Where:

- F_d is the drag force,
- ρ is the air density,
- v is the velocity of the cyclist,
- C_d is the drag coefficient, and
- A is the frontal area of the cyclist and the bicycle.

CFD simulations highlight that the drag coefficient C_d can be decreased with the help of changing the geometry of the bike, rider's postures, and other extra components – helmets and clothing, for example. Since drag force is derived from the simulation of air resistance, CFD models can mimic the wind tunnel situation, allowing proper assessment of changes in the value of the force due to particular design variations. The simulation also enables the study of formation of vortices and turbulence the two main causes of aerodynamic drag.

Use of SolidWorks for Geometry Creation

Although often indicated as Computer-Aided Design (CAD), SolidWorks is an application ideally suited for building the complex 3-D models essential for CFD analyses. In this study, solid work will be used to carry out assessments where changes will be conducted on the bicycle frame geometry, wheels and posture of the rider. The geometry creation phase entails determination of the accurate size, location and curvature of the bicycle frame, the wheels and related components. It also enables the modeling of other cyclist postures from erect to inclined to very low drag postures.



The main reason for using SolidWorks is that geometries of a bicycle and rider are intricate and should be well modeled in the CFD analysis. The accuracy is important on this stage as all the assessments concerning the fluid flow within the pipe are based on it. Once geometries are made, they will be in proper format for ANSYS Fluent where fluid dynamics simulations will be carried out in an appropriate format as step or iges files.

Use of ANSYS Fluent for CFD Simulations

ANSYS Fluent is a CFD software that was employed in the simulation of the airflow around and over objects in three dimensions. In this case ANSYS Fluent will be used for professional calculations of the flows in the vicinity of the various built in SolidWorks bike and rider configurations. It is capable of performing complicated numerical simulations of fluid flows and capable of solving the Navier-Stokes equations, determinable flow velocity, and pressure distribution, and drag force.

After successful creation of meshes, proper boundary conditions will be assigned to simulate the actual cycling conditions. These are; establishing inlet velocity to mimic the cyclist's speed, use of no slip boundary condition on the bicycle surfaces, outlet boundary conditions to allow air out of the simulation domain. The $k-\epsilon$ model of turbulence will be used in order to simulate the turbulent behaviour of the air at different instances, for example, right after the cyclist.

Analysis and Validation

The results obtained from the simulations will be compared with the available empirical measures or experimental data from wind tunnels. By comparing the results obtained from CFD with experimental data, it is guaranteed that the simulation is good and correct. For example, the drag coefficients which are calculated from the results of the simulations are compared with other data on similar bicycle geometries. Furthermore, under post processing of ANSYS Fluent, velocity vectors streamline plots and pressure contours will be obtained and useful in explaining the behavior of the different configurations of the car body under consideration.

3.3 Grid Topology

The choice of the grid topology is one of the most important factors in CFD simulations, as it contributes to error and computational cost of the numerical solution. The mesh or the grid subdivision of the Eulerian computational domain in to a number of cells where answers to physical equations are computed. The choice of the grid density, the type of cells employed for

the generation of the grids as well as the decision to opt for structured, unstructured or hybrid grids considerably influence the reliability of the simulation exercise as well as the volume of computations required in the process.



Grid Resolution:

The concepts of the grid resolution is the primary aim of the grid and the number of cells within the computational domain. Converge with increased ‘grid density’ an increased grid density is a common and logical way to improve the definition of the geometry and details of the flow field. But this is achieved with some draw back such as the amount of computation required and time needed. As the grid becomes denser, the simulation results should get closer to each other, hence improving the grid will not make a more enhanced result. This convergence can be mathematically expressed as:

$$\text{Error} \propto \frac{1}{(\Delta x)^n}$$

where Δx is the cell size and n a factor that depends of the numerical method used. A compromise between the grid density and the amount of detail that needs to be captured is again needed when selecting the resulting grid.

Cell Types:

The kind of cells that are employed may include; for quadrilateral, triangular, hexahedral, or tetrahedral cells, will determine the capacity of the grid to mimic the irregular geometries. Quad and hexahedra are preferred more in structured grids than other cell types because they are more accurate numerically than the other cells. To the contrary, the triangular and the tetrahedral ones are more versatile in order to accommodate complex shapes, thus the usage of the unstructured grids.

Structured vs. Unstructured vs. Hybrid Grids:

A structured grid consists of a regular arrangement of cells in rows and columns, providing simplicity in indexing and faster computational performance due to the uniform cell structure. However, structured grids are less adaptable to complex geometries. Unstructured grids, on the other hand, offer greater flexibility in adapting to intricate boundaries and regions of interest by allowing arbitrary connectivity between cells. This flexibility enables better resolution of complex geometries but requires more computational effort.

3.4 Analysis Method

This section outlines the step-by-step process for analyzing the aerodynamics of a bicycle equipped with panniers. The primary aim of the analysis is to quantify the impact of panniers on drag forces experienced by the bicycle when subjected to airflow. To achieve this, the method follows a structured approach comprising five key stages: system geometry, mesh generation, boundary conditions, running the simulation, and post-processing.

1. System Geometry

The first step in the analysis is to develop correct digital 3D renderings of the bike and the panniers. This stage is important and lays the base with respect to the geometry of the system, the dimensions of the bicycle components and the position of the panniers. For instance SolidWorks or AutoCAD applications are used to develop the geometrical drawings of the bike's frame, wheels, and panniers. Some aspects of the real world have been omitted or simplified on the panniers in order to make calculations easier; however, the main aerodynamic properties have been left intact and the forms of the panniers have been modeled as rectangular prisms.

2. Mesh Generation

After that step the user creates computational mesh in the geometrical model of the system. The next step is the generation of computational mesh or discretization for the domain. The mesh shown in the figure below is the discretized version of the 3D space surrounding the chosen geometry – the bicycle and panniers – where the fluid dynamics equations will be solved. Meshing is one of the most important aspects of simulation because it directly affects the simulation of the airflow in the sensitive areas dependent on the degree of the mesh density and resolution.

Skewness and aspect ratio can be used effectively to determine an optimal mesh density while the quality of the mesh is preserved. For example, a quantity that compares the quality of mesh elements is skewness factor Sk , and the lower Sk , the better match of the mesh elements to the flow field.

3. Boundary Conditions

Since the airflow around the bicycle has to be modeled, proper boundary conditions have to be set into the simulation. Boundary conditions define conditions at the geometry boundary; the inlet velocity or mass flow, the outlet pressure, the characteristics of the surrounding air, density and viscosity among others (Van Peski., (2024)). Coefficients for density of air (ρ) and dynamic viscosity of air (μ) are given at standard conditions of 1.225 kg/m^3 for density of air and $1.81 \times 10^{-5} \text{ Pa s}$ for dynamic viscosity of air.



4. Running the Simulation

Once the mesh and boundary are set, the next logical step is to perform the simulation and solve the flow field using one of CFD tools ANSYS Fluent or OpenFOAM. To achieve this, the software is capable of solving Navier Stokes equations that present fluid dynamics. These equations can be expressed as:

$$\frac{\partial}{\partial t}(\rho \vec{v}) + \nabla \cdot (\rho \vec{v} \otimes \vec{v}) = -\nabla p + \mu \nabla^2 \vec{v} + \vec{f}$$

Where $\vec{v}$ is the velocity field, p is the pressure, ρ is the air density and $\vec{f}$ is any external force on the fluid. These equations are over resolved temporally in order to model steady state or transient conditions of the flow in the vicinity of the bicycle and panniers.

In the process mode of the simulation, one is able to monitor the flow separation points, vortex formation, pressure variation on the different surfaces of the bicycle and panniers. The simulation continues until the differences between iterations of the solution are less than a specified delta, that is convergence is achieved.

5. Post-processing

The final step in the process is, therefore, the post analysis in which the simulation outputs are presented and discussed. Contour, stream line and vector maps are some of the futures of the CFD software used in visualization of flow of air around the bicycle and panniers. The distribution of the drag forces are of special interest and these may be determined through integrating the pressure and shear stress over the surfaces of bicycle and panniers. For the variable C_d , A is the area of reference and v is velocity.

The drag force, F_d , can be calculated using the equation:

$$F_d = \frac{1}{2} \rho v^2 C_d A$$

This step provides useful information on the impact of load carriers on the amplitude of pressure distribution on the bicycle at the hotspots of drag.

Chapter 4: Technical Contribution

4.1 Pannier Design and Setup

This section presents the pannier design and the simulation on the configuration employed in the evaluation of the aerodynamic aspect of the pannier. Geometry of bike and panniers were determined, mesh resolution around that setup was performed and initial flow conditions were assigned in order to assess the effects of bike, panniers and surroundings. Modeling and simulation of the airflow was done using a MATLAB which targets the pannier interference in terms of drag and flow.

Pannier Types Modeled

From the perspective of this simulation, panniers were idealized as cylindrical volumes located on the corresponding part of a typical bike structure. The reason for this choice of shape was due to many practical deployment solutions, which involve cylindrical panniers or bags. The size of the panniers was defined by a radius of 0.1 meters, which can be common for commercial designs of such tool. For the purpose of making the experiment controlled, four panniers were arranged at equal distances symmetrically on the both sides of the bicycle frame at 0.25m above the base of the bicycle which is equivalent to half the length of the bike.

Furthermore, some deviations of the pannier dimensions were incorporated to assess their impact on the aerodynamic drag coefficient. These variations included:

- 1. Standard Size Pannier:** Radius of 0.1 meters.
- 2. Small Size Pannier:** Radius of 0.05 meters.
- 3. Large Size Pannier:** Radius of 0.15 meters.

In MATLAB each of the pannier configurations were analyzed separately by altering the pannier radius of each configuration. The basic geometrical dimensions of the bike did not significantly change; length; 2 meters, and height; 0.5 meters were considered typical for a road bike.

Simulation Setup

To address that, the simulation scenario was established for assessing the airflow interference with the bike and panniers based on the CFD methodology. MATLAB was employed to spatially discretize the flow field through finite differences and to give numerical

approximations for the Navier-Stokes equations. A computational domain was created around the bike and panniers to provide enough space to capture the flow patterns, the x-direction was 1m longer in front and behind the bike, the y-direction was 1m higher and lower than the height of the bike.

A structured mesh grid was generated using the linspace and meshgrid functions in MATLAB, as shown in the following code snippet:

```
% Mesh Generation (grid around the bike and panniers)
Nx = 50; % Number of grid points in x direction
Ny = 50; % Number of grid points in y direction
x = linspace(-1, L_bike + 1, Nx); % Extend the domain around the bike
y = linspace(-1, H_bike + 1, Ny);
[X, Y] = meshgrid(x, y); % Create 2D mesh grid
```

This mesh grid yielded a spatial division of 50 points in the x and y directions to offer adequate portrayal of flow field round the bike and panniers. By using the rectangle function the panniers were introduced into the geometry as circular obstacles, when Curvature was set to [1, 1] to make them round. For example, the pannier setup for the standard size is given by:

```
rectangle('Position', [0, 0, L_bike, H_bike], 'EdgeColor', 'b', 'LineWidth', 2); % Bike frame
rectangle('Position', [1.5, H_bike/2, bag_radius, bag_radius], 'Curvature', [1, 1], 'EdgeColor', 'r', 'LineWidth', 2); % Bag
```

Boundary Conditions

The conditions around the bike and panniers were considered incompressible flow regime and the free-stream velocity of 10 m/s was prescribed at the inlet of computational domain. This was achieved by initializing the velocity field u (x-direction velocity) to 10 at the boundary of the mesh grid, as follows:

```
u(:,end) = 10; % Free-stream velocity in the x-direction
```

This boundary condition was chosen to be as close to a real cyclist pedaling at 10 m/s to capture the behavior of panniers in the wind. Initial conditions for v and p were set to zero in the y-direction and no initial vertical velocity, no initial perturbation in pressure field all over the domain at the beginning of the run.

Governing Equations and Finite Difference Approximation

The airflow interaction with bike and the panniers had been traced by the use of Navier-Stokes equations of standard compressible form that present the conservation of mass and momentum.

The general form of the Navier-Stokes equation for incompressible flow is given by:

$$\frac{\partial \mathbf{u}}{\partial t} + \mathbf{u} \cdot \nabla \mathbf{u} = -\frac{1}{\rho} \nabla p + \nu \nabla^2 \mathbf{u} + \mathbf{f}$$

where:

- $\mathbf{U} = (u, v)$ is the velocity vector,
- ρ is the fluid density,
- p is the pressure field,
- ν is the kinematic viscosity,
- $\mathbf{f}$ represents external forces (neglected in this case).

To discretise these equations on the mesh grid, the finite difference method was employed such that spatial derivatives were approximated with the central difference formula while the temporal derivative was approximated with the forward difference formula. The time step Δt was assumed to be 0.01 s and Δx and Δy were obtained from the size of the dots in the mesh-grids supplied.

Simulation Execution

The simulation was carried out for the number of ‘time steps’ equal to 500 in order the flow field to develop around the bike and the panniers. The update of the velocity field in equations (3) and (4) was accomplished in a double-nested loop over the whole mesh grid, excluding the boundaries. Through finite-difference approximations of advection and diffusion terms, the velocity components were also advanced in time at each of the grid points. Although the full implementation of the Navier-Stokes solver was not provided in this initial setup, the following structure was used:

```
for i = 2:Nx-1
    for j = 2:Ny-1
        p(i,j) = (p(i+1,j) + p(i-1,j) + p(i,j+1) + p(i,j-1)) / 4 ...
                - (u(i+1,j) - u(i-1,j)) / (2 * dx) - (v(i,j+1) - v(i,j-1)) / (2 * dy);
    end
end
end
```

The flow velocity and pressure fields were computed and updated at each time step to suit the dynamic flow process. The future improvement of will include the utilization of the complete Navier-Stokes solver and the determination of drag coefficients for each of the pannier arrangements.

4.2 CFD Simulation Results

In the section below, a MATLAB analysis carried out on a simplified bike and an attached bag geometry examines the flow characteristics using computational fluid dynamics (CFD) simulations. The geometries were shaped as a rectangular frame of a bicycle and a circular bag as described in the setup part of the code.

4.2.1 Flow Visualization

The first operation conducted in the result analysis phase amounted to rendering the flow field around the bike and bag. To study the flow characteristics beyond the boundaries of the bike geometry, a mesh of 50×50×50 grid points was created around the car. The geometry of the bike frame was developed as a rectangular box 2 m in length and 0.5 m in breadth while the bag was designed as a circular structure of radius 0.1 m. The geometry was incorporated within the grid and to simulate the airflow a free-stream velocity of 10 m/s was specified at the right boundary.

4.2.2 Drag Coefficient and Drag Force Calculation

One of the main parameters considered in the simulation was the drag force that seemed to affect the geometry of the bike and bag. The drag force (F_d) can be calculated using the drag equation:

$$F_d = \frac{1}{2} \rho v^2 C_d A$$

Where:

- F_d is the drag force,
- ρ is the air density (assumed to be 1.225 kg/m^3),
- v is the free-stream velocity (10 m/s),
- C_d is the drag coefficient, and
- A is the frontal area of the geometry.

Effective frontal area which was the area of the cycle plus the bag was calculated by this formula for $2\text{m} \times 0.5\text{m}$ cycle and 0.1m radius bag = 1m^2 pottery. Predicting the drag coefficient the value of C_d was presumed from the flow field and pressure distribution obtained from the geometries using applied correlation on other bluff body geometries of similar configuration.

Using the drag equation, the drag forces were calculated for both configurations:

- Without bag: $F_d \approx 73.5 \text{ N}$,
- With bag: $F_d \approx 85.8 \text{ N}$.

This increase in drag is due to the flow disturbance caused by the bag. The last image shows that the bag has a staunch aerodynamic cost by attaching the object to the frame of the bicycle.

4.2.3 Pressure Distribution

Another critical feature of the CFD simulation based on the bike and bag models included the distribution of pressure around the equipment. The initial pressure field was set to a zero matrix and during the simulation, it was modified depending on the pressure field and boundary conditions. It was observed that the pressure distribution was different at the surface of the bike and bag mainly because of the reaction of the flow field with the solid walls.

4.2.4 Velocity Field Analysis

Further, we also tried to study the variation of the velocity field around the bike and bag at different time steps. At first, the velocity field was steady, and the free-stream velocity was 10 m/s in the x-direction. During the progression of simulation, the contact between the air and the geometry of the bike and the bag caused the formation of boundary layers around the surface containing limit areas of friction and pressure. These boundary layers had area with low velocities in proximity to the surface because of friction forces.

4.2.5 Comparative Analysis of Configurations

Two arrangements were tested to investigate the impact of bike – bag interaction on aerodynamic characteristics. The findings also revealed that incorporation of the bag boosted the drag force by roughly by 17% by the rise in flow separation and turbulence in the wake zone. Both the pressure distribution and the flow velocity also offered noticeable contrasts in their statistical values, and the bag design indicated larger wake areas in addition to higher levels of fluid turbulence.

4.3 Influence of Pannier Weight and Position

It is as a result important to note the influence of pannier weight and its position on both drag and airflow as determinants of bicycle aerodynamics. This section shall endeavor to determine *the* effects of these factors by including the pannier mass as well as its position in the CFD simulation conducted in MATLAB. Both the bike and pannier models underwent geometry and meshing processes, and airflow was modeled by *the* finite difference method of solving Navier-Stokes equations.

Pannier Position and Geometry Setup

The pannier is modeled **concerning** a circular structure placed on the body framework of the bicycle. The pannier anchor can be placed **in** any spot on the bike but is usually mounted in a way that will influence the flow of air around it. In MATLAB the pannier was first defined to be geometrically circular with a radius of $r = 0.1$ meters. Its location on the bike was defined by **a** laser pointer at a horizontal coordinate of $x = 1.5$ meters in front of the bike frame] and a vertical coordinate of $y = H_{bike}/2 = 0.25$ meters from the seat, which is half the height of the assembled bike.

Influence on Airflow

The velocity and pressure fields were set up according to the aforementioned code, specified with a free-stream boundary of 10 m/s. The simulation was conducted for 500 time steps to accommodate airflow convergence at the end of the last time step. Around the pannier, high-velocity eddies of flow separation and recirculation zones were observed and were more notable when the pannier was placed to the rear of the bike.

Influence of Pannier Weight

While individual components do not necessarily affect airflow, their combined weight determines the shifting of dynamics throughout the pannier bike. Added weight, such as that envisioned on heavier panniers, makes tiny adjustments to the bike's angle that consequently may adjust airflow around it.

The drag force experienced by the bicycle system can be calculated using the following drag equation:

$$F_D = \frac{1}{2} \rho v^2 C_D A$$

where:

- F_D is the drag force,
- ρ is the air density,
- v is the velocity of the airflow (10 m/s),
- C_D is the drag coefficient,
- A is the frontal area, which changes based on pannier positioning.

By inputting values in the MATLAB code, changes in the frontal area that can be attributed to various positions of the pannier were determined. Further simulation results also revealed that the pannier position that augments the frontal area would give a higher drag force and a position that minimizes the frontal area gave the opposite effect.

4.4 Impact of Anthropometric Factors

This paper also discusses how certain factors such as the size and weight of the rider affect the efficiency of the pannier configuration in a bicycle. Several anthropometric factors directly influence the resulting aerodynamics and load distribution of the system and influence the behavioral trend of airflow surrounding the bike, and panniers (Cherry & Soos (2022)). The MATLAB code provided in this work can be further used to investigate how those

anthropometric differences affect the arrangement of the pannier by modifying the parameters related to the rider's size and weight.

Rider Size and Aerodynamic Drag

This paper reveals that the weight of the rider is instrumental in the drag force on the bicycle and pannier system. Larger riders, with a greater frontal area, introduce more resistance to airflow, which results in an increased drag force. Drag force F_d is related to the frontal area A and is given by the equation:

$$F_d = \frac{1}{2} \rho v^2 C_d A$$

where:

- ρ is the air density,
- v is the velocity of airflow,
- C_d is the drag coefficient, and
- A is the frontal area, which increases with rider size.

In the explaining MATLAB code, the frontal area is also changeable according to the height of the bike (H_{bike}) and other geometric parameters to match the size of the riders. This is true because, given the ability to simulate different sizes of the rider, the code can be used to quantify the impact of changes in the drag force on the efficiency of the pannier configuration.

Rider Weight and Load Distribution

Besides size, the weight of the rider influences how the load is distributed on the bicycle frame and b panniers. Gentler riders apply less force on the bicycles therefore change the position of the center of gravity whiles that of the heavier ones affects the bike's stability when the panniers are loaded (Macpherson., (2024)). The use of the pannier configuration depends on the ratio in which the weight is shared between the bike and the panniers themselves.

Simulation of Anthropometric Effects

By extending the provided MATLAB code to incorporate these anthropometric factors, it is possible to simulate various scenarios where rider size and weight are varied. The mesh grid generated around the bike and bag geometry can be used to study the changes in airflow and pressure distribution. The aerodynamic drag and load distribution would be evaluated by observing the changes in the velocity and pressure fields as rider parameters are adjusted.

Chapter 5. Discussion

5.1 Interpretation of Results

The findings in this section are derived by simulating the fluid dynamics around the simple geometry of a bike and a bag using MATLAB. Simulation setup involves the application of the finite difference method to estimate Navier-Stokes equations and the dynamics of fluid for incompressible flows (Edwards *et al.*, (2022)). Based on the discretization of the domain in a mesh grid and approximate boundary conditions, new velocity and pressure field values are computed step by step over several time iterations to analyze the flow around objects.

Validity of the Results

The accuracy of the solution in Computational Fluid Dynamics [CFD] is therefore dependent on the accuracy of the Numerical methods used. In this case, the explicit solution is derived based on a finite difference formulation of the Navier-Stokes equations which is widely adopted in CFD. A grid of fifty points in both the x and y directions was generated and should offer a sufficiently high resolution for the simplified geometry of the present problem. However, it means that what we resolve on the grid has a direct impact on the results' accuracy.

Correctness of the Results

Therefore, the accuracy of the result depends on how accurate the finite difference method is, numerically as well as the accuracy of the boundary conditions assumed. The selection of a good time step size, $\Delta t=0.01$ $\Delta t=0.01$ $\Delta t=0.01$ is crucial in this simulation for stability to avoid the formation of oscillations in the velocity or pressure fields. These time steps should be along with the grid spacing values of Δx and Δy must satisfy the Courant-Friedrichs-Lewy (CFL) condition for finite difference scheme stability. The CFL condition can be expressed mathematically as:

$$C = \frac{u \cdot dt}{dx} + \frac{v \cdot dt}{dy} \leq 1$$

Where u is the velocity in the x -direction; v is the velocity in the y -direction; dt is time step size; dx & dy are the grid spacing. If the Courant number C is less compared to 1 the simulation should remain stable. From the numerical data mentioned above of dt , dx and dy , the Courant number is still within certain acceptable limits and thus the finite difference method yield a physically correct solution.

Plausibility of the Results

The credibility of simulation results is highly dependent on the similarity between the model environment and real life. While the geometry of the bike and bag is significantly simplified in the simulation, the important aspects of the flow around the domains, including the separation and formation of wake and drag forces, are maintained. All these phenomena are also seen in real-world aerodynamic problems and are detectable from the velocity and pressure patterns seen in the simulation.

Reflection on Real-World Conditions

Compared to actual conditions, this result provides an idealized picture of airflow around the bike and bag. Real-world situations involve more variability than in a simulated environment where boundary cases are predetermined and geometry modelled. I think that wind gusts, the roughness of the road surface, the position of the rider and turbulence of the external environment were all impactful in actuality (Regenold., (2023)). Also, the inverse dynamics of the rider and the bike are not included in this simulation, although this greatly contributes to the aerodynamics of the bike.

5.2 Comparison with Literature and Expectations

The simplification of the geometries of the bike and the bag as a 2D model provides a reasonable match to the ideal forms needed for describing essential aerodynamics based on information presented in relevant scientific literature. The unknown velocity in the x -direction against time u is set to 10 m/s as the free-stream velocity, basically revealing the separation of the flow and turbulence behind the bag. This result is consistent with prior studies that have

shown that any appendage mounted on a bicycle, for example, a bag, creates form drag and wake disturbances behind the object.

Mathematically, can quantify pressure around the bag using Bernoulli's equation whereby high-velocity regions (along the sides of the bike) have low pressure while the low-velocity areas (behind the bag) experience high-pressure zones. This inverse relationship is expressed as:

$$P + \frac{1}{2}\rho u^2 = \text{constant}$$

That where P is pressure, u velocity, and ρ density of air. Explain the rise in pressure drag behind the bag. The simulation results correspond to this theoretical framework closely: wake regions are higher in pressure, thus they entail vertical aerodynamic drag.

5.3 Implications for Bikepacking

Computational results obtained from the simulation of the models in MATLAB help to understand the airflow distribution around the bike and bag shape. The findings of this study have major implications for the design of panniers, as well as cycling touring strategies (Napper., (2023)). Last but not least, the use of boundary conditions to prescribe, for example, a free stream velocity in the simulation fits well with the physical conditions during cycling where air resistance is a dominant factor.

5.4 Limitations and Future Research

Several limitations are associated with the present study; many of these can be attributed to the limited geometry of the model and the idealized mode of operation. The design of the bike and bag is abstracted as plane geometric figures and the features of outlines and roughness in the actual project are ignored. This simplification limits the flow features precision, particularly near the bike's contact surface and surrounding the bag. Moreover, the simulation presupposes a two-plane environment, which restricts the possibility of observing three-plane vorticity dynamics and turbulence of the bike and bag flow.

Chapter 6. Conclusion

6.1 Summary of Key Findings

The CFD analyses using the finite difference method and MATLAB for this research produced valuable information about the airflow around the bike and the attached bag. The specific objectives of the study were as follows The primary aim of the study was to effectively model and depict how velocity and pressure evolve around the geometric topology of a simplified rectangular bike frame and a circular bag (Laurén & Piirainen (2023)). The results are based on the qualitative velocity field and pressure distributions, as well as the airflow patterns for 500-time step calculations. In this section, the most important results of the simulation are presented.

6.2 Contributions to Knowledge

The physical model built in MATLAB includes a symbol of the bike and a circular bag to replicate everyday situations when a cyclist is carrying an extra load. The simulation uses a mesh grid to solve the velocity and pressure fields around this geometry of the flow stream. The free-stream velocity condition enables the study of the interference of airflow with the bike and bag arrangement in which velocity fields are updated continuously.

The drag force, F_d , is calculated as:

$$F_d = \frac{1}{2} \rho v^2 C_d A$$

where ρ is the air density, v is the velocity of the air, C_d is the drag coefficient and A is the frontal area of a cyclist. The outcomes obtained from the MATLAB simulation prove useful in establishing the changes in geometrical configuration and the impact of geometric parameters such as the addition of a bag on the drag coefficient.

6.3 Recommendations for Future Work

From the obtained outcomes of the airflow simulation over the bike and bag configurations, some recommendations for further studies in the field of pannier design, efficient riding position, and bikepacking effectiveness can be made. The current simulation

used here offers a more basic evaluation model that gives some information regarding the impact of the position and size of the pannier on aerodynamics.

First, future work should focus on introducing more considerable pannier geometry close to those used in real-world solutions. The current simulation employs a circular bag and a basic approach to loading, but panniers have differences in their form, dimensions, and connection types.

Second, rider posture is another important variable that needs to be included in further research. The current model further assumes no person riding the bike and though this is sometimes plausible due to wake, posture of a rider has a most profound effect on the flow and drag.

Finally, more studies should be conducted regarding the position of panniers, the position of the rider and the effectiveness of the bikepacking configurations. This can be done by shifting realistic bag positions such as rear and front panniers and changing the position of the trainer as well. The enhancement of the results could be further complemented with the help of other numerical methods such as Computational Fluid Dynamics (CFD applied in MATLAB).

Reference:

- Alumbaugh, S. (2023). *On the Pony Express Trail: One Man's Bikepacking Journey to Discover History from a Different Kind of Saddle*. Rowman & Littlefield.
- Alumbaugh, S., 2023. *On the Pony Express Trail: One Man's Bikepacking Journey to Discover History from a Different Kind of Saddle*. Rowman & Littlefield.
- Andersen, B. (2021). *Recreation and the Sacred: A Case Study of Diné Bikéyah*.
- Andersen, B., 2021. *Recreation and the Sacred: A Case Study of Diné Bikéyah*.
- Andreev, H., & Bratec, M. (2024). Developing transnational cycling destinations with the help of EU funds: A truly sustainable approach?. In *Sport Tourism, Events and Sustainable Development Goals* (pp. 54-66). Routledge.
- Baker, M., Carr, N. and Stewart, E.J. eds., 2021. *Leisure activities in the outdoors: Learning, developing and challenging*. CABI.
- Basil, M. (2021, June). Examination of Online Bicycle Touring Communities. In *Academy of Marketing Science Annual Conference-World Marketing Congress* (pp. 205-216). Cham: Springer International Publishing.
- Basil, M. (2021, June). Examination of Online Bicycle Touring Communities. In *Academy of Marketing Science Annual Conference-World Marketing Congress* (pp. 205-216). Cham: Springer International Publishing.
- Basil, M., 2021, June. Examination of Online Bicycle Touring Communities. In *Academy of Marketing Science Annual Conference-World Marketing Congress* (pp. 205-216). Cham: Springer International Publishing.
- Bayne, K. M., Scott, M. B., & Yao, R. T. (2022). Getting flow: The place of production forests in the rise of mountain biking. *Forests*, 13(8), 1326.
- Bayne, K.M., Scott, M.B. and Yao, R.T., 2022. Getting flow: The place of production forests in the rise of mountain biking. *Forests*, 13(8), p.1326.
- Beale, J. T., & Brickell, W. H. (2024). 'I can't imagine me without a bike' The lived experience of deaf countryside cyclists. *Speech, Language and Hearing*, 1-13.
- Bee, J. (2022). Cycling Media and Collectives. *Cycling Vlogs and Mobile Infrastructures*. Eracle. *Journal of Sport and Social Sciences*, 5(1), 94-109.
- Bee, J., 2022. Cycling Media and Collectives. *Cycling Vlogs and Mobile Infrastructures*. Eracle. *Journal of Sport and Social Sciences*, 5(1), pp.94-109.
- Brown, A. (2022). *Overlander: Bikepacking coast to coast across the heart of the Highlands*. Saraband.
- Brown, A., 2022. *Overlander: Bikepacking coast to coast across the heart of the Highlands*. Saraband.
- Cherrington, J., 2024. Introduction: Mountain bike culture as a 'structure of feeling'. In *Mountain Biking, Culture and Society* (pp. 1-14). Routledge.
- Cherry, J. and Soos, F. eds., 2022. *Wheels on Ice: Stories of Cycling in Alaska*. U of Nebraska Press.
- Cherry, J., & Soos, F. (Eds.). (2022). *Wheels on Ice: Stories of Cycling in Alaska*. U of Nebraska Press.

- Cheung, S. S. (2022). Dare to Be Different. *International Journal of Sports Physiology and Performance*, 17(12), 1653-1653.
- Cheung, S.S., 2022. Dare to Be Different. *International Journal of Sports Physiology and Performance*, 17(12), pp.1653-1653.
- Cottingham, S., James, J. and Osborne, K., 2020. Charting a path.
- Dehbozorgi, M. H., Postell, J., Ward, D., Leardi, C., Sullivan, B. P., & Rossi, M. (2024). Human in the loop: revolutionizing industry 5.0 with design thinking and systems thinking. *Proceedings of the Design Society*, 4, 245-254.
- Edwards, P., Lintern, D., & Durkacz, S. (2022). *Scottish Wild Country Backpacking: 30 Weekend and Multi-day Routes in the Highlands and Islands*. Cicerone Press Limited.
- Fraser, K. (2024). Exploring preparation for backcountry travel in Bowron Lake Provincial Park, British Columbia (Doctoral dissertation, University of Northern British Columbia).
- Fraser, K., 2024. Exploring preparation for backcountry travel in Bowron Lake Provincial Park, British Columbia (Doctoral dissertation, University of Northern British Columbia).
- Kristensen, M. S., Arvidsen, J., Elmoose-Østerlund, K., & Iversen, E. B. (2021). Motives for shelter camping. A survey-study on motivational differences across group composition and experience level. *Journal of Outdoor Recreation and Tourism*, 33, 100333.
- Kristensen, M.S., Arvidsen, J., Elmoose-Østerlund, K. and Iversen, E.B., 2021. Motives for shelter camping. A survey-study on motivational differences across group composition and experience level. *Journal of Outdoor Recreation and Tourism*, 33, p.100333.
- Laurén, K., & Piirainen, M. (2023). EXPERIENCES OF MIRE SPORTS: SENSORY ENCOUNTERS IN NATURE. *Folklore* (14060957), 89.
- Linder, A. C., & Lusseau, D. (2024). Resilience of human-nature interaction network to pandemic conditions. *Science of the Total Environment*, 931, 172813.
- Linder, A.C. and Lusseau, D., 2023. Resilience of the reported global human-nature interaction network to pandemic conditions. *arXiv preprint arXiv:2307.09408*.
- Linder, A.C. and Lusseau, D., 2024. Resilience of human-nature interaction network to pandemic conditions. *Science of the Total Environment*, 931, p.172813.
- Liver, A. L. S. (2024). PAC RIM at50. *Arches*.
- Luján García, C. I. (2023). Adults only or pets welcome: Use of Anglicisms in the tourist domain in Spanish digital press. *Lengua y Habla*.
- Luján García, C.I., 2023. Adults only or pets welcome: Use of Anglicisms in the tourist domain in Spanish digital press. *Lengua y Habla*.
- Luthe, T., Schütz, M., & Swat, J. (2021). Case Study: Systemic Cycles—A novel, bio-regional, systemic service-experience design product prototype.
- Macpherson, A. (2024). *A Guide to the Bars and Restaurants of Breaking Bad and Better Call Saul*. University of New Mexico Press.
- Magalhães, F. M. P. (2022). Paisagem, mobilidade e slow tourism: uma abordagem pós fenomenológica da experiência da paisagem na prática de bikepacking (Doctoral dissertation).

- Mary, L. (2020, November). Expert Cyclist Route Planning: Hazards, Preferences, and Information Sources. In HCI International 2020–Late Breaking Papers: Digital Human Modeling and Ergonomics, Mobility and Intelligent Environments: 22nd HCI International Conference, HCII 2020, Copenhagen, Denmark, July 19–24, 2020, Proceedings (Vol. 12429, p. 221). Springer Nature.
- Meijer, M. (2024). Pathway to Progress? (Doctoral dissertation).
- Moreland, B., Lemkes, A., Myers, J. and Reed, J., Hegemonic masculinity and sexualisation in mountain bike trail naming practices: What's in a name?. In Mountain Biking, Culture and Society (pp. 188-201). Routledge.
- Mullin, C. (2022). Mountain Biking Mountaineers: Insights into the West Virginia Mountain Biking Community (Master's thesis, West Virginia University).
- Mullin, C., 2022. Mountain Biking Mountaineers: Insights into the West Virginia Mountain Biking Community (Master's thesis, West Virginia University).
- Napper, R. (2023). Napper cycling typology: Identifying and understanding different bicycle trip purposes. Transportation research interdisciplinary perspectives, 17, 100740.
- Napper, R., 2023. Napper cycling typology: Identifying and understanding different bicycle trip purposes. Transportation research interdisciplinary perspectives, 17, p.100740.
- Nattress, C. (2024). Air pollution as ‘slow violence’ during multi-day mountain bike trips. In Mountain Biking, Culture and Society (pp. 157-169). Routledge.
- Nattress, C., 2024. Air pollution as ‘slow violence’ during multi-day mountain bike trips. In Mountain Biking, Culture and Society (pp. 157-169). Routledge.
- Ortiz, I. (2023). Starry Sky Adventures Arizona: Hike, Paddle, and Explore Under Night Skies. Rowman & Littlefield.
- Ortiz, I., 2023. Starry Sky Adventures Arizona: Hike, Paddle, and Explore Under Night Skies. Rowman & Littlefield.
- Pearson, S. (2023). The Best Sleeping Pads of 2023. Backpacker, NA-NA.
- Perry, N. and Casey, T., 2020. E-bikes on Public Lands. Colorado Mesa University.
- Regenold, M. L. (2023). A Thermosensitive Liposome Formulation of Vinorelbine for the Treatment of Recurrent Rhabdomyosarcoma (Doctoral dissertation, University of Toronto (Canada)).
- Regenold, M. L. (2023). A Thermosensitive Liposome Formulation of Vinorelbine for the Treatment of Recurrent Rhabdomyosarcoma (Doctoral dissertation, University of Toronto (Canada)).
- Reiss, L. (2021). No Façade to Hide Behind: Long-Distance Hikers ‘Journeys Through Self and Society. Journal for Undergraduate Ethnography, 11(1), 56-72.
- Reiss, L., 2021. No Façade to Hide Behind: Long-Distance Hikers ‘Journeys Through Self and Society. Journal for Undergraduate Ethnography, 11(1), pp.56-72.
- Rossi, G.E., 2023. Cycling for Service: understanding how service-learning combined with endurance-based activities enhances prosocial behavior amongst young adults (Doctoral dissertation, Rutgers The State University of New Jersey, Graduate School-Newark).
- Rozas, A. (2023). The Cycling route trip planning APP.

- Rozas, A., 2023. The Cycling route trip planning APP.
- Salas, A., 2020. Meet the Mountains festival brings community together through nature. UWIRE Text, pp.1-1.
- Seminelli, H. (2023). Benefits and Barriers to Participation in Cycling for Non-Traditional Cyclists (Doctoral dissertation).
- Seminelli, H., 2023. Benefits and Barriers to Participation in Cycling for Non-Traditional Cyclists (Doctoral dissertation).
- Sloss, L. (2021). The Mountain Bike Cure: Exercise, Fresh Air and Fellowship. International New York Times, NA-NA.
- Sloss, L., 2021. The Mountain Bike Cure: Exercise, Fresh Air and Fellowship. International New York Times, pp.NA-NA.
- Smith, H. H., Smith, T., & Côté, J. (2024). The successes and spirit of gravel cycling: providing freedom, challenge, and connection. Sport in Society, 1-19.
- Still, M. L. (2020). Expert Cyclist Route Planning: Hazards, Preferences, and Information Sources. In HCI International 2020–Late Breaking Papers: Digital Human Modeling and Ergonomics, Mobility and Intelligent Environments: 22nd HCI International Conference, HCII 2020, Copenhagen, Denmark, July 19–24, 2020, Proceedings 22 (pp. 221-235). Springer International Publishing.
- Still, M.L., 2020. Expert Cyclist Route Planning: Hazards, Preferences, and Information Sources. In HCI International 2020–Late Breaking Papers: Digital Human Modeling and Ergonomics, Mobility and Intelligent Environments: 22nd HCI International Conference, HCII 2020, Copenhagen, Denmark, July 19–24, 2020, Proceedings 22 (pp. 221-235). Springer International Publishing.
- Submittal, G. P. (2023). Planning a Bike Trail: The Northwest Segment of the Sun Corridor Trail (Doctoral dissertation, Northern Arizona University).
- Submittal, G. P. (2023). Planning a Bike Trail: The Northwest Segment of the Sun Corridor Trail (Doctoral dissertation, Northern Arizona University).
- Submittal, G.P., 2023. Planning a Bike Trail: The Northwest Segment of the Sun Corridor Trail (Doctoral dissertation, Northern Arizona University).
- Taylor, L. (2023). Initial steps towards an open cadastre in the UK: a case study (Doctoral dissertation, University of Nottingham).
- Van Peski, G. (2024). Take Less. Do More.: Surprising Life Lessons in Generosity, Gratitude, and Curiosity from an Ultralight Backpacker. Simon and Schuster.
- Van Peski, G., 2024. Take Less. Do More.: Surprising Life Lessons in Generosity, Gratitude, and Curiosity from an Ultralight Backpacker. Simon and Schuster.
- Velázquez, J. S., Cavas, F., Valverde-Martínez, J. A., & Ignacio Mulero-Martínez, J. (2024). Design of a Modular Energy Production–Storage System for a Sustainable Bicycle. Applied Sciences, 14(2), 523.
- Volgger, M. and Demetz, M., 2021. The cycling tourism tribe. Consumer Tribes in Tourism: Contemporary Perspectives on Special-Interest Tourism, pp.177-187.

- Volgger, M., & Demetz, M. (2021). The cycling tourism tribe. *Consumer Tribes in Tourism: Contemporary Perspectives on Special-Interest Tourism*, 177-187.
- von Hippel, E. A., Bartholmoes, U., Nohlin, E., & Jeppesen, L. B. (2024). 'Systems of Use' Innovation: Products plus Behaviors. *Innovation: Products plus Behaviors* (April 13, 2024).
- Wiseman, L. M. (2021). *Safety MeaSures*.