

Src\main\resources

Country.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="http://www.springframework.org/schema/beans
                           https://www.springframework.org/schema/beans/spring-beans.xsd">

    <!-- Existing India Bean -->
    <bean id="in" class="com.cognizant.spring_learn.model.Country">
        <property name="code" value="IN" />
        <property name="name" value="India" />
    </bean>

    <!-- New USA Bean -->
    <bean id="us" class="com.cognizant.spring_learn.model.Country">
        <property name="code" value="US" />
        <property name="name" value="United States" />
    </bean>

    <!-- List of Countries -->
    <bean id="countryList" class="java.util.ArrayList">
        <constructor-arg>
            <list>
                <ref bean="in" />
                <ref bean="us" />
            </list>
        </constructor-arg>
    </bean>

</beans>
```

src/main/java/com/cognizant/spring_learn/service

CountryService.java:

```
package com.cognizant.spring_learn.service;

import com.cognizant.spring_learn.model.Country;
import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;
import org.springframework.stereotype.Service;
import java.util.List;

@Service
public class CountryService {

    public Country getCountry(String code) {
```

```

        // Load the XML configuration
        ApplicationContext context = new
ClassPathXmlApplicationContext("country.xml");

        // Retrieve the countryList bean
        @SuppressWarnings("unchecked")
        List<Country> countryList = context.getBean("countryList",
List.class);

        // Use a Lambda expression stream to find the case-insensitive match
        return countryList.stream()
            .filter(country -> country.getCode().equalsIgnoreCase(code))
            .findFirst()
            .orElse(null);
    }
}

```

src/main/java/com/cognizant/spring_learn/controller:

CountryController.java:

```

package com.cognizant.spring_learn.controller;

import com.cognizant.spring_learn.model.Country;
import com.cognizant.spring_learn.service.CountryService;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.web.bind.annotation.GetMapping;
import org.springframework.web.bind.annotation.PathVariable;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestMethod;
import org.springframework.web.bind.annotation.RestController;

@RestController
public class CountryController {

    // Auto-inject the Service layer
    @Autowired
    private CountryService countryService;

    // Existing endpoint
    @RequestMapping(value = "/country", method = RequestMethod.GET)
    public Country getCountryIndia() {
        // ... existing code ...
        return null; // (Placeholder for your existing code)
    }

    // New endpoint for dynamic country lookup
    @GetMapping("/countries/{code}")
    public Country getCountry(@PathVariable String code) {

```

```
        // Pass the path variable directly to the service layer
        return countryService.getCountry(code);
    }
}
```

Outputs:

⏮ ⏭ ↻ <http://localhost:8083/countries/uS>

| YouTube WhatsApp Spotify – Web Player Big Timer Google Meet LinkedIn

Pretty-print ☐

```
{ "code": "US", "name": "United States" }
```

⏮ ⏭ ↻ <http://localhost:8083/countries/IN>

| YouTube WhatsApp Spotify – Web Player Big Timer Google Meet

Pretty-print ☐

```
{ "code": "IN", "name": "India" }
```

⏮ ⏭ ↻ <http://localhost:8083/countries/in>

| YouTube WhatsApp Spotify – Web Player Big Timer Google Meet LinkedIn

retty-print ☐

```
"code": "IN", "name": "India" }
```