

A background network diagram with white nodes and lines, some highlighted in yellow, green, blue, and pink.

NumPy

Dr. B.S.R.V. Prasad
Department of Mathematics
School of Advanced Sciences
Vellore Institute of Technology
Vellore

Python



Data Science Techniques



srvprasad.bh@gmail.com (Personal)



srvprasad.bh@vit.ac.in (Official)



NumPy

- ▶ is a general-purpose array-processing package.
- ▶ provides a high-performance multidimensional array object, and tools for working with these arrays.
- ▶ fundamental package for scientific computing with Python.
- ▶ contains various features including these important ones:
 - ▶ A powerful N-dimensional array object
 - ▶ Sophisticated (broadcasting) functions
 - ▶ Tools for integrating C/C++ and Fortran code
 - ▶ Useful linear algebra, Fourier transform, and random number capabilities

The recommended convention to import **NumPy** is:

```
1 import numpy as np
```

NumPy's main object is the homogeneous multidimensional array.

- ▶ It is a table of elements (usually numbers), all of the same type, indexed by a tuple of positive integers.
- ▶ In NumPy dimensions are called axes. The number of axes is rank.
- ▶ NumPy's array class is called ndarray. It is also known by the alias **array**.

1-D array construction



```
1 import numpy as np
2 a = np.array([0, 1, 2, 3])
3 print('Array a =',a)
4 print('Array a dimension = ',a.ndim)
5 print('Array a shape = ',a.shape)
6 print('Array a size (total no.of elements) = ',a.size)
7 print('Array a data type = ',a.dtype)
8 print('Array a length = ',len(a))
```

2-D array construction



```
1 import numpy as np
2 a = np.array([[0, 1, 2, 3.1],[4, 5, 6, 7]])
3 print('Array a =',a)
4 print('Array a dimension = ',a.ndim)
5 print('Array a shape = ',a.shape)
6 print('Array a size (total no.of elements) = ',a.size)
7 print('Array a data type = ',a.dtype)
8 print('Array a length = ',len(a)) #Returns the size of the
    first dimension
```

3-D array construction



```
1 import numpy as np
2 a = np.array([[[0, 1, 2, 3],[4, 5, 6, 7]],[[8, 9, 10,
    11],[12, 13, 14, 15]]])
3 print('Array a =',a)
4 print('Array a dimension = ',a.ndim)
5 print('Array a shape = ',a.shape)
6 print('Array a size (total no.of elements) = ',a.size)
7 print('Array a data type = ',a.dtype)
8 print('Array a length = ',len(a)) #Returns the size of the
    first dimension
```

There are other various ways to create arrays in NumPy.

- ▶ We can create an array from a regular Python list or tuple using the array function. The type of the resulting array is deduced from the type of the elements in the sequences.
- ▶ NumPy offers several functions to create arrays with initial placeholder content. For example: `np.zeros`, `np.ones`, `np.full`, `np.empty`, etc.
- ▶ To create sequences of numbers, NumPy provides a function analogous to range that returns arrays instead of lists.
 - ▶ **arange**: returns evenly spaced values within a given interval. step size is specified.
 - ▶ **linspace**: returns evenly spaced values within a given interval. num no. of elements are returned.

- ▶ **Reshaping array:** We can use reshape method to reshape an array.
 - ▶ Consider an array with shape $(a_1, a_2, a_3, \dots, a_N)$. We can reshape and convert it into another array with shape $(b_1, b_2, b_3, \dots, b_M)$.
 - ▶ The only required condition is: $a_1 \times a_2 \times a_3 \dots \times a_N = b_1 \times b_2 \times b_3 \dots \times b_M$. (i.e original size of array remains unchanged.)
- ▶ **Flatten array:** We can use flatten method to get a copy of array collapsed into one dimension. It accepts order argument. Default value is 'C' (for row-major order). Use 'F' for column major order.

NumPy Array Creation: Demonstration



```
1 # Python program to demonstrate
2 # array creation techniques
3 import numpy as np
4
5 # Creating array from list with type float
6 a = np.array([[1, 2, 4], [5, 8, 7]], dtype = 'float')
7 print ("Array created using passed list:\n", a)
8
9 # Creating array from tuple
10 b = np.array((1 , 3, 2))
11 print ("\nArray created using passed tuple:\n", b)
```

NumPy Array Creation: Demonstration



```
1 # Creating a 3X4 array with all zeros
2 c = np.zeros((3, 4))
3 print ("\nAn array initialized with all zeros:\n", c)
4
5 # Create a constant value array of complex type
6 d = np.full((3, 3), 6, dtype = 'complex')
7 print ("\nAn array initialized with all 6s. The Array type
      is complex:\n", d)
8
9 # Create an array with random values
10 e = np.random.random((2, 2))
11 print ("\nA random array:\n", e)
```

NumPy Array Creation: Demonstration



```
1 # Create a sequence of integers
2 # from 0 to 30 with steps of 5
3 f = np.arange(0, 30, 5)
4 print ("\nA sequential array with steps of 5:\n", f)
5
6 # Create a sequence of 10 values in range 0 to 5
7 g = np.linspace(0, 5, 10)
8 print ("\nA sequential array with 10 values between 0 and
    5:\n", g)
```

NumPy Array Creation: Demonstration



```
1 # Reshaping 3X4 array to 2X2X3 array
2 arr = np.array([[1, 2, 3, 4],
3                 [5, 2, 4, 2],
4                 [1, 2, 0, 1]])
5
6 newarr = arr.reshape(2, 2, 3)
7
8 print ("\nOriginal array:\n", arr)
9 print ("Reshaped array:\n", newarr)
```

NumPy Array Creation: Demonstration



```
1 # Flatten array
2 arr = np.array([[1, 2, 3], [4, 5, 6]])
3 flarr = arr.flatten()
4
5 print ("\nOriginal array:\n", arr)
6 print ("Fattened array:\n", flarr)
```

In NumPy the arrays data type will be determined automatically

```
1 a = np.array([1, 2, 3])
2 print(a.dtype)
3
4 a = np.array([1.0, 2, 3])
5 print(a.dtype)
6
7 a = np.array([1+1j, 2.0+2j, 3])
8 print(a.dtype)
9
10 a = np.array([True, False, False, True, False])
11 print(a.dtype)
12
13 a = np.array(['Vellore', 'Chennai', 'Vijayawada', 'Delhi', 'Bengaluru'
14              ])
15 print(a.dtype)
```

```
1 >>> a = np.arange(10)
2 >>> print(a)
3 >>> print(a[0]+a[2])
```

Please note that the index in Python starts from 0. The usual python idiom for reversing a sequence is supported.

```
1 >>> arr = np.array([[1,2,3,4,5], [6,7,8,9,10]])
2 >>> print(arr[1,2])
```

```
1 >>> arr = np.array([[[1, 2, 3], [4, 5, 6]], [[7, 8, 9], [10,
    11, 12]]])
2 >>> print(arr[0, 1, 2]) #Prints the value 6
```


Indexing and Slicing

Slicing Arrays



- ▶ Slicing in python means taking elements from one given index to another given index.
- ▶ We pass slice instead of index like this: [start:end].
- ▶ We can also define the step, like this: [start:end:step].
- ▶ If we don't pass start its considered 0
- ▶ If we don't pass end its considered length of array in that dimension
- ▶ If we don't pass step its considered 1

```
1 a = np.random.rand(5,4)
2
3 a[1,1] #List the second row second element
4
5 a[:,2] #List all elements in the third column
6
7 a[1,:] #List all element in the second row.
8 a[1] #Similar to above
9
10 a[1:5] #List the elements from the second to fifth element.
11
12 a[(2,3):(1,2)] #List the [a[2,1], a[3,2]] elements
```

Indexing and Slicing

Negative Indexing



```
1 >>> a[-3:-1]
2 >>> array([7, 8])
3
4 >>> a[-3:]
5 >>> array([7, 8, 9])
6
7 >>> arr = np.array([[1,2,3,4,5], [6,7,8,9,10]])
8 >>> print('Last element from 2nd dim: ', arr[1, -1])
```

```
1 >>> a = np.array(  
2     [[0,1,2,3,4,5],  
      [10,11,12,13,14,15],  
      [20,21,22,23,24,25],  
      [30,31,32,33,34,35],  
      [40,41,42,43,44,45],  
      [50,51,52,53,54,55]])
```

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

```
1 >>> a[0, 3:5]  
2 >>> array([3, 4])
```

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

Indexing and Slicing



0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

```
1 >>> a[4:, 4:]  
2 >>> array([[44, 45],  
3          [54, 55]])
```

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

Indexing and Slicing



0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

```
1 >>> a[:, 2]
2 >>> array([2, 12, 32, 42,
            52])
```

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

Indexing and Slicing



0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

```
1 >>> a[2::2, ::2]
2 >>> array([[20, 22, 24],
3          [40, 42, 44]])
```

0	1	2	3	4	5
10	11	12	13	14	15
20	21	22	23	24	25
30	31	32	33	34	35
40	41	42	43	44	45
50	51	52	53	54	55

Please note that Slicing of an array does not make a copy of the array. It just creates a view which refer to the original array. So, changing any elements in the slicing changes the elements in the original array

```
1 a = np.array([[0,1,2,3,4,5], [10,11,12,13,14,15],  
               [20,21,22,23,24,25], [30,31,32,33,34,35],  
               [40,41,42,43,44,45], [50,51,52,53,54,55]])  
2 a[:,2] = [1, 1, 1, 1, 1, 1]  
3 print(a)
```

To avoid this we need to use `copy()` command

```
1 a = np.array([[0,1,2,3,4,5], [10,11,12,13,14,15],  
               [20,21,22,23,24,25], [30,31,32,33,34,35],  
               [40,41,42,43,44,45], [50,51,52,53,54,55]])  
2 b = a[:,2].copy()  
3 b = np.array([1, 1, 1, 1, 1, 1])  
4 print(a)  
5 print(b)
```

```
1 # Integer array indexing example
2 temp = a[[0, 1, 2, 3], [3, 2, 1, 0]]
3 print ("\nElements at indices (0, 3), (1, 2), (2, 1),"
4         "(3, 0):\n", temp)
5 # boolean array indexing example
6 cond = a < 0.5 # cond is a boolean array
7 temp = a[cond]
8 print ("\nElements less than 0.5:\n", temp)
```

Basic Operations on Arrays



```
1 # Python program to demonstrate
2 # basic operations on single array
3 import numpy as np
4
5 a = np.array([1, 2, 5, 3])
6
7 # add 1 to every element
8 print ("Adding 1 to every element:", a+1)
9
10 # subtract 3 from each element
11 print ("Subtracting 3 from each element:", a-3)
12
13 # multiply each element by 10
14 print ("Multiplying each element by 10:", a*10)
```



```
1 # square each element
2 print ("Squaring each element:", a**2)
3
4 # modify existing array
5 a *= 2
6 print ("Doubled each element of original array:", a)
7
8 # transpose of array
9 a = np.array([[1, 2, 3], [3, 4, 5], [9, 6, 0]])
10
11 print ("\nOriginal array:\n", a)
12 print ("Transpose of array:\n", a.T)
```

```
1 # Python program to demonstrate
2 # unary operators in numpy
3 import numpy as np
4
5 arr = np.array([[1, 5, 6],
6                 [4, 7, 2],
7                 [3, 1, 9]])
8
9 # maximum element of array
10 print ("Largest element is:", arr.max())
11 print ("Row-wise maximum elements:",
12         arr.max(axis = 1))
```

```
1 # minimum element of array
2 print ("Column-wise minimum elements:",
3         arr.min(axis = 0))
4
5 # sum of array elements
6 print ("Sum of all array elements:",
7         arr.sum())
8
9 # cumulative sum along each row
10 print ("Cumulative sum along each row:\n",
11         arr.cumsum(axis = 1))
```