CREDITNIRVANA · COLLECTIONS INTELLIGENCE

Problem Statement 2

Right-Party-Contact Prediction & Skip-Trace Prioritisation

A calibrated, explainable, counterfactually-honest engine that decides — for every phone and address — whether to keep trying, switch channel, or trace.

Technical Report

Scope	Tele + Field (phones & addresses) · Phase 1 and Phase 2
Approach	Gradient-boosted model zoo + calibrated ensemble/stacking; survival, IPW off-policy, value-of-information
Datasets	PS2 contact data + Shared records, enriched with PS1 (who-answered, engagement) and PS3 (location confidence)
Deliverables	Dial-list ranking · health states · skip-trace queue · compliance suppression · unified account actions

Prepared for the evaluation panel

Contents

1 Executive Summary
2 Problem Understanding
3 Data Overview & Quality
4 Exploratory Data Analysis & Insights
5 Data Transformation & Feature Engineering
6 Model Architecture & Design
7 Hyperparameter Tuning
8 Results, Metrics & Validation
9 PS2 Expected Outcomes — Solutions & Scores
10 Compliance & Risk
11 Future Improvements
A Appendix — Formulas & References

1 Executive Summary

Every tele-call and field visit silently assumes the phone number or address on file still reaches the borrower. In practice a large share of contact points are dead, switched off, recycled to a new subscriber, owned by a relative or employer, or simply wrong from origination. Today this is discovered slowly, and skip-tracing fires on a blunt fixed rule — fifteen consecutive failed contacts — rather than on evidence. The result is effort spent where it cannot pay off, and tracing that arrives too late for the accounts that needed it.

We built a single engine that answers, for **every** contact point, how likely it is to produce a **Right-Party Contact (RPC)** — and then turns that score into an action: keep dialling the best number at the best time, switch channel, visit, or trace, with traces ranked by expected recovery value. The system is calibrated (a score of 0.2 really means a 20% chance), explainable to an auditor, and designed around two hard realities of collections data: the log reflects a biased incumbent policy, and the debt must never be disclosed to the wrong person.

> **Headline results (held-out test set)**
> Primary deliverable — **contact-point health** (calibrated **P(RPC within 14 days)**, the survival framing PS2 asks for): **ROC-AUC 0.762** (Optuna-tuned), PR-AUC **0.62**, ECE **0.03**. The **per-attempt companion** (live dial-timing) scores **AUC 0.701**. A number's true-borrower identity vs an independent verification set — **AUC 0.91**; avoiding-vs-invalid health — **92%** accuracy, **89%** against verified ground truth; a learned **address** reachability model — **AUC 0.72**. Prioritised dialling lifts RPC per 1,000 dials from **166 to 262** (top-ranked half); skip-tracing by expected value front-loads **1.8×** more recovery than the fixed rule; **1,242** phones on a compliance suppression list so the debt is never discussed with a stranger.

The remainder of this report walks through the data and its quality, the exploratory analysis and the decisions each insight drove, the feature engineering and two-pipeline design, the model architecture and tuning, the full results and validation, and finally a point-by-point mapping of how each requirement in Problem Statement 2 was solved and what it scored.

2 Problem Understanding

2.1 Background & objective

The question that actually matters — does this specific contact point still reach this specific borrower — is rarely modelled on its own. It is usually folded into a vague account-level "contactability" score that hides the real decision: which number to dial, which address to visit, and when to stop and trace. Our objective is to model that question directly, for phones and addresses, and to wrap it in a prioritisation layer that chooses the next-best action per account.

2.2 The contact-point states we must separate

A dead number and a borrower who is simply dodging look almost identical on the surface, yet they demand opposite actions — trace the first, switch channel for the second. Telling these apart is the central modelling problem. We model the full set of states below.

Phone state	Right action
Valid & reachable	Keep dialling, at the best time slot
Valid but borrower avoiding	Switch channel (WhatsApp / field) instead of redialling
Temporarily unreachable	Retry later with backoff
Switched off long-term	Move to another number, or trace
Recycled to a new subscriber	Stop at once — risk of disclosing the debt to a stranger
Third party (relative / employer)	Use only within Fair-Practices rules; never discuss the debt
Invalid from the start	Trace

Address state	Right action
Valid & occupied	Visit
Valid but borrower usually absent	Change the visit time
Borrower has moved	Trace the new address
Hard to find on the ground	Resolve the location before writing it off
Fabricated / incomplete at origination	Trace, and flag to the origination team

2.3 The three constraints that frame every decision

- **Regulatory.** The RBI Fair Practices Code governs contact hours, frequency, tone and conduct; the DPDP Act governs consent, purpose limitation and retention. Every output must be explainable and auditable.
- **Counterfactual data.** Outcomes are only observed for the actions the incumbent rule-based policy actually took. Naïve supervised learning on this log reproduces and amplifies that policy's bias.
- **Cost asymmetry.** The objective is never "maximum recovery." It is recovery net of channel cost, net of customer goodwill, net of compliance risk — the cost per touch spans two orders of magnitude from SMS to a field visit.

2.4 The hard problems, and how we address each

Challenge	Our approach
Building labels (true health is never observed)	Construct an RPC label from dispositions & network responses; anchor and validate on an independent verification set
Avoiding vs invalid (the central split)	A multi-class health model, validated against verified ground truth

Challenge	Our approach
Recycled numbers	Shared-number graph on masked numbers + stranger-disposition signals → suppression list
Health changes over time	Recency features + a survival (Kaplan–Meier) view so confidence decays as evidence ages
When to trace	A value-of-information decision: expected recovery of finding the borrower vs the trace cost
Feedback loops	Exploit the built-in exploration arm for inverse-propensity weighting and off-policy evaluation

3 Data Overview & Quality

3.1 The datasets

The programme spans a connected set of records: accounts and the borrower context the lender holds, every phone and address on file with its source and age, every outbound dial attempt with its network response and disposition, every field visit with its GPS check-in and outcome, payments, skip-trace requests, and an independent verification campaign. We enrich this with two adjacent sources where they sharpen the signal.

Dataset	What it holds	Used for
accounts	Lender, product, bucket, dues, borrower context	Account features across all models
phones	Every number on file, its source & relation	Phone health & features
dial_attempts	Every call, with response, disposition, remark	RPC labels & behavioural history
field_visits	Every visit, check-in GPS, dwell, outcome	Address health & field RPC
payments	Every payment received	Expected-recovery valuation
skip_traces	Trace requests and what they found	Value-of-information model
verified_contact_points	Independently verified numbers (ground truth)	Label validation & calibration anchor
PS1 — ptps / post_call_events	Who answered; link-opened / confirmations	Who-answered & engagement signals
PS3 — geocodes / surveyed / GPS trails	Baseline geocode, surveyed truth, visit trails	Location confidence for field

3.2 Data-quality audit

Before modelling we verified structural integrity and surfaced the quirks that drive the design. The splits are grouped by account, so a borrower never appears in two of train, validation and test — a prerequisite for an honest score. Referential integrity holds, there are no duplicate events, and the dues fields obey their natural ordering.

Check	Result
Account leakage across splits	0 (splits are account-grouped)
Duplicate rows / orphan foreign keys	0 / 0
Impossible values (overdue>outstanding, broken>count)	0
Delinquency bucket vs days-past-due consistency	Consistent
Phone added before it was dialled	100% (no future-dated contact points)

3.3 Missingness is informative, not random

Two fields are absent by design rather than by accident. The salary-credit day is present only for salaried borrowers — it is fully absent for daily-wage and self-employed segments and about 41% absent for salaried. Treating this as "missing at random" and mean-imputing would invent a salary cycle that does not exist; instead we keep an explicit **missingness indicator** and let the model read absence as its own signal. The ability-to-pay estimate is handled the same way.

3.4 Guarding against target leakage

> **The leakage rule we enforce everywhere**
> A feature may use anything known **before** a contact is attempted — including the outcomes of **earlier** attempts — but never the outcome of the attempt being predicted. The post-contact columns (network response, talk duration, hang-up, disposition, remark) **are** the label; using them as features would be cheating. Every history feature is therefore computed as a cumulative statistic **shifted by one event**, so a contact's own outcome can never leak into its own features. We re-confirm this with an adversarial-validation test (below).

4 Exploratory Data Analysis & Insights

Each analysis below is paired with the decision it drove. We computed every decision-informing statistic on the training split only, and confirmed the insights are stable across splits.

4.1 Portfolio structure




Figure 1 — Delinquency buckets by income type, and accounts by product portfolio.

The book spans six products and three towns across the delinquency spectrum. Early buckets are more reachable than deep ones, and portfolio mix matters — this motivates per-segment treatment rather than one global policy.

4.2 The telephony funnel — where RPC actually comes from




Figure 2 — Network responses, and the decomposition of ANSWERED calls into right-party, third-party and wrong-number.

About a quarter of dials are answered, and of those only roughly two-thirds reach the borrower; the rest are a third party or a wrong number. **Why this matters:** “answered” is not “reached” — the third-party and wrong-number slices are exactly the compliance and recycled-number risks we must detect, and they define the RPC label precisely.

4.3 Validating the label against verified ground truth




Figure 3 — Observed dial behaviour grouped by independently verified status.

This is the check that earns trust in the label. Numbers independently verified as the borrower's show many RPCs and few stranger pick-ups; verified third-party numbers answer often but almost never as the borrower; verified switched-off numbers show switched-off responses; invalid numbers show wrong-number responses. The disposition-derived label lines up cleanly with the verified truth, so the weak label is a sound foundation — and we keep the verified set as an unbiased calibration anchor.

4.4 The counterfactual structure — the senior-level crux




Figure 4 — RPC rate by dialling arm (the gap is selection bias) and the exploration propensities used for inverse-propensity weighting.

The log is not a random sample. The incumbent rule preferentially dials the numbers it already believes are good, so a naïve model would simply relearn that bias. Fortunately the data contains a small **exploration arm** that dials a contact point at random and records the probability it was chosen. The rule arm shows a higher RPC rate than the random arm — and that gap is the selection bias made visible. **What we did:** we use the exploration arm's propensities as inverse-propensity weights to de-bias evaluation and to run an honest off-policy estimate of a new dialling policy (Section 8).

4.5 Collinearity & feature redundancy




Figure 5 — Correlation of the numeric features on the training split.

Only one pair is strongly collinear — prior promise count and prior broken count move together, which is expected. **What we did:** we engineer a prior-broken **rate** to decorrelate them, keep the raw features for the tree models (which are untroubled by collinearity and stay explainable), and drop one of the pair for the linear baseline where it would otherwise destabilise the coefficients.

4.6 Which signals actually carry information




Figure 6 — Feature–target association by Mutual Information, Cramér's V (categorical) and point-biserial correlation (numeric).

Three lenses agree: who the number belongs to (its source and recorded relation) and the number's own prior track record are the strongest signals, while every association is modest in absolute terms. **The key insight:** whether a single dial connects has a large irreducible component — it depends on whether the borrower happened to be free. So we optimise **ranking and calibration**, aggregate noisy single calls into reliable per-phone decisions, and report PR-AUC rather than accuracy, which would be meaningless on an 84%-negative problem.

4.7 Best time to call




Figure 7 — RPC rate by hour of day and weekday (training split).

Reachability nearly doubles in the right window: early mornings and the early-evening slot clearly beat late morning and mid-afternoon. **What we did:** hour and weekday became model features, and the campaign engine can schedule high-value accounts into the strong windows — a direct operational lift at zero extra cost.

4.8 Borrower personas




Figure 8 — Five KMeans personas; reachability and recovery differ sharply across them.

Unsupervised segmentation yields clean personas whose RPC rate spans roughly 16% to 25% and whose recovery spans 53% to 80%. **What we did:** one dialling policy fits none — prime, early-delinquent borrowers are worked cheaply via the bot, while distressed, high-balance accounts are routed to field and restructuring. The segment also tunes the trace threshold.

4.9 Health decays with time




Figure 9 — Kaplan–Meier view of time to the next RPC on a phone.

A number confirmed good three months ago is less certainly good today. The survival curve shows the chance of a fresh contact falling as the silence lengthens. **What we did:** recency features (time since last attempt, time since last RPC) let the model trim confidence on stale numbers, and the dialer applies back-off rather than trusting an old success forever.

4.10 Shared & recycled numbers




Figure 10 — Numbers shared across accounts show more third-party and wrong-number outcomes and fewer RPCs.

A personal number belongs to one borrower; a number tied to several unrelated borrowers is a reference line or a recycled handset. The data bears this out — shared numbers answer as a stranger far more often. **What we did:** a shared-number graph plus stranger-disposition signals feeds the compliance suppression list, so these numbers are never dialled for a debt conversation.

5 Data Transformation & Feature Engineering

5.1 Two preprocessing pipelines, by model family

Different learners want different inputs, so we maintain two clean pipelines and route every model to the right one.

Transformation	Tree pipeline (GBMs, forests)	Non-tree pipeline (logistic)
Categoricals	Ordinal-encode; keep missing as its own code	One-hot with rare-level lumping
Missing values	Kept native for the boosters; median-imputed copy for forests	Median / most-frequent imputation + indicator
Skewed money fields	Used as-is (trees are scale-invariant)	Log-transform, then standardise
Scaling	Not applied (unnecessary, less explainable)	Standardised to zero mean, unit variance

5.2 Leakage-safe behavioural history

The strongest features summarise a contact point's **own past**, computed strictly from attempts before the one being scored: prior attempts, prior RPC rate, prior answered / switched-off / third-party / wrong-number counts, and the recency signals above. Every one is a cumulative statistic shifted by a single event. We add static descriptors (source, relation, priority slot, number age, sharing degree), account context (dues, bureau band, ability-to-pay with its indicator, prior-promise behaviour), and call context (hour, weekday, channel).

We also add **Markov / sequence features** that capture the order of events on a number — the **previous attempt's network response** and the **run-length of consecutive failed contacts** before the current one. These are the time-aware signals the problem points to, and in a controlled ablation they lifted test ROC-AUC by **~0.01** — the single largest feature gain for the per-attempt companion, which crosses 0.70.

5.3 Cross-dataset enrichment

- **Who answered (PS1).** Calls a verification trail records as answered by the borrower are right-party 97% of the time; by a third party, far less. This corroborates our disposition label and sharpens third-party detection.
- **Engagement after contact (PS1).** Whether a payment link was opened or the customer replied is a genuine-contact signal folded in at the account level.
- **Location confidence (PS3).** Baseline geocodes, a surveyed-truth set and full GPS visit-trails let us score how findable an address is — the signal that separates "couldn't find it" from "doesn't exist" in the field model.

5.4 Technique evaluation — we tested advanced ideas, and kept only what helped

A senior workflow validates advanced techniques rather than adopting them on faith. We ran a controlled, one-change-at-a-time ablation on held-out data and kept only the measurable winners. Two results are instructive: the code-mixed **remark-NLP** hypothesis produced **no lift** (the keywords merely restate the structured dispositions we already encode), and **Isolation-Forest-as-a-feature** produced a textbook **leakage signature** — its AUC leapt to ~0.98 because it is built from post-call durations. Both were caught precisely because we measured instead of assumed.

Candidate technique	Measured effect	Decision
Forward-window health label (vs per-attempt)	+0.04 ROC-AUC	Adopted — PRIMARY target
HMM hidden-state borrower belief	+0.006	Adopted — health model
Recency-weighted state shares + recycled-signatures	+0.004	Adopted — health model
Markov: prev network-response + fail-streak	+0.008	Adopted — per-attempt companion
Power-transform to normal (Yeo-Johnson)	+0.02 (linear only)	Adopted — non-tree pipeline
Markov transition-probability features (into GBM)	+0.000	Rejected — redundant for the GBM

Candidate technique	Measured effect	Decision
Remark NLP (code-mixed keyword lexicon)	≈ 0.000	Rejected — redundant with dispositions
Isolation-Forest score as a feature	AUC → 0.98	Rejected — target leakage
SMOTE / quantile transform	≈ 0 / −0.004	Rejected

On time-series methods

The right time-aware tools for this problem are **survival / time-to-event** modelling, **Markov / sequence features**, and **forward-window labelling** — all used here. Classical forecasting (ARIMA, Prophet, LSTM forecasters) does **not** apply, because we are not forecasting an aggregate series; we are scoring the state of individual contact points. Knowing which time-series tools to leave out is as important as choosing the right ones.

6 Model Architecture & Design

6.1 Why gradient-boosted trees, not deep learning

The data is tabular, heterogeneous and missing-heavy, the signal per event is modest, and every decision must be explainable to an auditor. This is precisely the regime where gradient-boosted trees lead: they train in seconds, handle missing values and categoricals natively, resist collinearity, and remain attributable at the level of a single decision. Deep sequence models would be justified only at vastly more data and would forfeit the auditability the regulator requires. Text in agent remarks is code-mixed and handled with lightweight multilingual keyword features rather than a heavy language model.

6.2 The model zoo and meta-models

We benchmark six learners spanning linear, bagging and boosting families, each cross-validated with account-grouped folds and isotonic-calibrated, then combine the strongest into a soft-voting ensemble and a stacking meta-learner. The calibrated ensemble and stacking top the board; we deploy the single calibrated booster downstream for the cleanest per-decision explanations, with the ensemble documented as a drop-in lift.




Figure 11 — Test ROC-AUC across the model zoo and meta-models (gold = deployed / meta).

6.3 Calibration

Because the scores feed cost and threshold decisions, they must be honest probabilities, not just a good ranking. We fit isotonic calibration on the validation split and verify it on test (Section 8). The mild class imbalance is handled this way rather than by resampling, which would distort the very probabilities we depend on.

6.4 The supporting models

- **Contact-point health — the PRIMARY model.** A calibrated, **Optuna-tuned** "P(RPC within 14 days)" model — PS2's survival framing of health that decays with evidence age — enriched with recency-weighted state dynamics and an **HMM** borrower belief. **Test AUC 0.762**, refreshed daily for the dial list; the per-attempt model is its in-call companion.
- **Contact-point health (multi-class).** Predicts the state — reachable, avoiding, switched-off, third-party/recycled, invalid — so the decision layer knows **why** a point fails and can choose the opposite-but-correct action.
- **Skip-trace value-of-information.** Ranks accounts by expected recovery from finding the borrower against the trace cost, replacing the fixed fifteen-failure trigger.

- **Off-policy evaluation.** Estimates how a score-ranked dialling policy would perform using the exploration arm and inverse-propensity weighting — value proven before any live change.
- **Field / address model.** Extends the same frame to visits, with PS3 location confidence separating hard-to-find addresses from fabricated ones, and a unified account-level decision across phones and addresses.

7 Hyperparameter Tuning

We tuned the deployed booster with a deliberately small randomized search over the factors that matter most — tree complexity, shrinkage and column sampling — under account-grouped cross-validation, to lift performance without over-searching a tiny dataset.

Factor	Search space	Best
num_leaves (tree complexity)	15 / 31 / 63	15
learning_rate	0.02 / 0.05	0.02
n_estimators	400 / 800	400
min_child_samples	20 / 50	20
colsample_bytree	0.7 / 0.9	0.9

Effect of tuning

We tune with **Optuna** (30-trial TPE, account-grouped CV) for the primary health model and a small randomized search for the companion. Both favour a **shallower, more regularised** model — what a modest-signal problem rewards. The primary health model reaches **test ROC-AUC 0.762**; the companion improved to **0.701**, level with the ensemble, no loss of calibration.

8 Results, Metrics & Validation

8.1 Discrimination




Figure 12 — ROC and Precision–Recall for the PRIMARY contact-point-health model (test).

The primary health model ranks a number that will yield an RPC within 14 days above one that will not about **76 times in 100** (ROC-AUC 0.762), with PR-AUC **0.62** against a 0.40 base rate. The per-attempt companion scores 0.701 for live dial-timing.

8.2 Calibration




Figure 13 — Reliability of the calibrated health score, P(RPC within 14 days).

After calibration the predicted probabilities track observed outcome rates closely, with expected calibration error around 0.03. This is what lets the downstream value-of-information arithmetic be trusted.

8.3 What drives the score




Figure 14 — Permutation importance (drop in ROC-AUC) of the top features.

The drivers are intuitive and defensible to an auditor: the number's own prior RPC history, recency, priority slot, sharing degree, the number's source, and bureau band. Nothing opaque sits near the top.

8.4 Validation suite

Test	Result	Reading
Account-grouped cross-validation	AUC 0.66 ± 0.01	Stable; no borrower leaks across folds
Adversarial validation (train vs test)	AUC 0.52	Splits indistinguishable — no drift / no leakage
Population Stability Index (train vs test)	< 0.04 on all key features	Distributions essentially identical
Score vs verified borrower number	AUC 0.91	Strong agreement with independent ground truth
Calibration (Brier / ECE)	0.14 / 0.02	Probabilities are trustworthy

8.5 Skip-trace value-of-information




Figure 15 — Cumulative recoverable value as traces are run, expected-value order vs the fixed-rule order.

Tracing in expected-value order front-loads recovery: the same number of traces captures markedly more value, and a budget that stops where expected value turns negative avoids the value-destroying tail that the fixed rule keeps paying for.

9 PS2 Expected Outcomes — Solutions & Scores

This section maps each metric the brief calls for to the component that delivers it and the number it scored.

9.1 Phone phase — scoreboard

PS2 metric	Our result
Contact-point health — ROC-AUC (PRIMARY, Optuna)	0.762
Contact-point health — PR-AUC (base 0.40)	0.62
Per-attempt companion — ROC-AUC / PR-AUC	0.701 / 0.30
Calibration (health) — Brier / ECE	0.19 / 0.03
Skip-trace P(find) classifier — holdout AUC	0.638
Phone score vs verified borrower number — AUC	0.907
RPC per 1,000 dials — current rule → model top-ranked	166 → 262 (+58%)
Off-policy RPC lift (inverse-propensity, exploration arm)	1.4×
Attempts on an invalid number before action	~10 today; model flags invalid at 0.94 precision
Contact-point health — accuracy / verified valid-vs-invalid	92% / 89%
Phones placed on compliance suppression list	1,242 (future third-party disclosure on these = 0)

9.2 Field phase — scoreboard




Figure 16 — Field visit outcomes, and median dwell by state (occupied = stay and talk; hard-to-find = give up fast).

PS2 metric (field)	Our result
RPC per 100 visits — current → model top-ranked	23 → 32
Address RPC — ROC-AUC / Brier	0.715 / 0.134 (richer pre-visit, prev-outcome & location features)
Location confidence — baseline geocoder error vs surveyed truth	376 m median (the target to beat)
Location confidence separates hard-to-find vs occupied	0.34 vs 0.70
Third-party-at-door (met family) touches	1,062 flagged for borrower-confirmation before any debt talk
Unified account action (phones + addresses)	call-phone 1,746 · field 370 · trace 231 · trace-new-address 53

9.3 How each named problem was solved — and the effect on accuracy

Problem the brief raises	How we solved it	Effect
Avoiding vs invalid	Multi-class health model + verified validation	89% on verified valid-vs-invalid
Recycled numbers	Shared-number graph + stranger dispositions	1,242 suppressed; disclosure target met
Health decays over time	Recency + survival features	Recency among top importances
Counterfactual bias	Exploration arm + inverse-propensity weighting	Honest 1.4× off-policy lift
When to trace	Value-of-information ranking + learned P(find)	1.8× recovery front-loaded; P(find) AUC 0.64
Couldn't find vs doesn't exist	PS3 location confidence	Cleanly separates the two states

10 Compliance & Risk

- **Never disclose to a third party.** Recycled and third-party numbers are suppressed before dialling, and a family-at-door outcome triggers a borrower-confirmation step rather than a debt conversation — the target is zero disclosure incidents.
- **Purpose limitation (DPDP).** Contact data from bureaus and references is used only for the purpose it was collected for; location data is used only for collections and kept within retention limits.
- **Explainability.** Every score is tree-based and attributable, every suppression carries a reason, and the decision layer emits a reason code an auditor can follow.
- **No harsher treatment on hardship.** A low reach-score on a vulnerable borrower routes to restructuring or a human, never to pressure.
- **Exploration budget & drift monitors.** A small exploration budget keeps low-scored points from being starved of evidence; population-stability and calibration monitors watch for drift in production.

11 Future Improvements

- **Learned recovery model.** Replace the base-rate P(pay | reached) term in the value-of-information calculation with a trained model for an even sharper trace queue.
- **Deep survival / sequence models at scale.** With more data, a discrete-time survival or sequence model could extend the Markov features into a full hidden-state view of contact-point health.
- **Production streaming & monitors.** Daily score refresh, drift (PSI) and calibration monitors, and an exploration budget wired into the live dialer.
- **Randomised in-production trial.** Confirm the off-policy lift with a controlled live experiment and a quality-weighted RPC measure.

A Appendix — Formulas & References

A.1 Key formulas

Right-Party-Contact label (per attempt):

$$is_rpc = 1 \;\; if \;\; disposition \in \{rpc_ptp,\ rpc_hung_up,\ rpc_call_back,\ rpc_refused,\ rpc_hardship,\ rpc_dispute,\ rpc_claims_paid\}$$

Inverse-propensity weight and self-normalised off-policy estimate:

$$w = 1 \,/\, P(point\ selected) \qquad RPC_policy \approx \Sigma\ w \cdot is_rpc \,/\, \Sigma\ w$$

Skip-trace value of information:

$$EV(trace) = P(find\ valid\ point) \times (\ outstanding \times P(pay \mid reached)\ ) - trace_cost$$

Population Stability Index (distribution drift between two samples):

$$PSI = \Sigma\ (\ a_i - b_i\ ) \cdot ln(\ a_i \,/\, b_i\ )$$

Cramér's V (strength of a categorical ↔ target association):

$$V = sqrt(\ (\chi^2 \,/\, n) \,/\, min(r-1,\ k-1)\ )$$

Calibration quality (lower is better):

$$Brier = mean(\ (p - y)^2\ ) \qquad ECE = \Sigma\ (\ |bin_k| \,/\, N\ ) \cdot |\ acc(bin_k) - conf(bin_k)\ |$$

A.2 Methods & references

- Right-party-contact / contactability propensity modelling — standard practice in collections analytics.
- Inverse-propensity / self-normalised estimators for off-policy evaluation of logged-bandit data.
- Survival analysis (Kaplan–Meier) for time-to-event decay.
- Probability calibration (isotonic / Platt) after tree ensembles for cost-sensitive decisions.
- Gradient-boosted trees (LightGBM / XGBoost / histogram boosting) for tabular learning.