Airfoil Lagrangian Kriging

Load the NACA airfoil coordinates and predict. The coordinates should be arranged in one sense. Meaning, that `XB` and `YB` are either in a clockwise or anti-clockwise arrangement.

Exact solution

The true velocity is computed using the BEM code. GRID discretization used:

```
    {python}
    # Grid parameters
    nGridX   = 30
    # X-grid for streamlines and contours
    nGridY   = 30
    # Y-grid for streamlines and contours
    xVals    = [min(XB)-0.5, max(XB)+0.5]
    # X-grid extents [min, max]
    yVals    = [min(YB)-0.2, max(YB)+0.2]
    # Y-grid extents [min, max]
```

In [1]:
```
# imports
import numpy as np
import matplotlib.pyplot as plt
from shapely.geometry import Polygon, Point
# from scipy.interpolate import griddata
from matrices import CovM, Umat
from covderivatives2D import AnalyticalSqExpdiff2D
from calibration import LOOMSESK2D, LOOVARSK2D, adamopt, Adam
```

```
Importing covderivatives.py
Importing covderivatives2D.py
```

In [2]:
```
# Image path to save the images.
IMGPATH = r'IMAGES/'

# load the NACA airfoil data
NACAname = r'0012'
XB, YB, nX, nY = np.loadtxt('data/NACA'+NACAname+'UIUCnormalvecs.dat',
                            unpack=True)
XX, YY, Vx, Vy = np.loadtxt('data/NACA'+NACAname+'BEMflow.dat',
                            unpack=True)
```

In [3]:
```
# TEST : normal vectors visualization.
# plt.quiver(XX, YY, Vx, Vy)
# plt.plot(XB, YB)
# for _ in range(XB.shape[0]):
#     plt.plot([XB[_], XB[_] + 0.05*nX[_]],
#              [YB[_], YB[_] + 0.05*nY[_]], c = 'red')
```

```
# # plt.ylim(-0.75, 0.75)                    # Smaller scale makes the normal vect
# plt.show()
```

Defining relevant points in the extended design space.

- Observation points (`Obs`). $v_x \rightarrow$ `m = (1,0)` . $v_y \rightarrow$ `m = (0,1)` .
- Boundary constraint points (`B`). `m = (1,0)` & `m = (0,1)` .
- Prediction points (`Pred`). `m = (1,0)` & `m = (0,1)` .

In [4]:
```
# USER INPUTS
## Observation locations with derivative orders.
nobs = 20                                  # number of observations (at inf. on eac
nm = 20                                    # number of observations in the middle o
nb = 30                                    # discretization for boundary collocatio
UQFLAG = 1                                 # For uncertainty prediction
ostep = int(np.sqrt(XX.shape[0])/nobs)     # step size to select observation points
mstep = int(np.sqrt(XX.shape[0])/nm)       # step size to select observation points
bstep = int(XB.shape[0]/nb)                # step size to select boundary points.
seed = 1                                   # Reproducibility
np.random.seed(seed)
```

In [5]:
```
# Observation locations
mask = np.zeros_like(XX, dtype = bool)      # mask to choose the right observation

for _ in np.where(XX==min(XX))[0][::ostep]:
    mask[_] = True;                         # observations at -infinity.
for _ in np.where(XX==max(XX))[0][::ostep]:
    mask[_] = True;                         # observations at +infinity.
for _ in np.where(YY==min(YY))[0][mstep::mstep]:
    mask[_] = True;                         # (upper) mid-domain observations (avoi
for _ in np.where(YY==max(YY))[0][mstep::mstep]:
    mask[_] = True;                         # (lower) mid-domain observations (avoi

nobs = np.sum(mask)                         # redefining nobs based on the chosen l
Obs = np.zeros((2*nobs, 2, 2))              # Observations of [Vx, Vy].

## Setting the appropriate locations.
Obs[:nobs, 0, 0] = XX[mask];
Obs[:nobs, 0, 1] = YY[mask]
Obs[nobs:, 0, :] = Obs[:nobs, 0, :]         # repeating the same observation locati

## Setting the right order of derivatives.
Obs[:nobs, 1, 0] = 1; Obs[nobs:, 1, 1] = 1  # m = (1,0) and m = (0,1)
```

In [6]:
```
# TEST : Is the `mask` vector properly defined?
# plt.scatter(XX[mask], YY[mask], marker = 'x')
# plt.quiver(XX[mask], YY[mask],
#            Vx[mask], Vy[mask])
# plt.show()
```

In [7]:
```
# boundary prediction points
Bx = XB[::bstep]; By = YB[::bstep]                  # chosen boundary coordinates.
p2 = Bx.shape[0]                                    # NUM of constrained prediction
B = np.zeros((2*p2, 2, 2))                          # initialize: sparse subset of
B[::2, 0, 0] = Bx; B[::2, 0, 1] = By
B[1::2, 0, :] = B[::2, 0, :]                        # locations repeating twice.
B[::2, 1, 0] = 1; B[1::2, 1, 1] = 1                 # m = (1,0) & m = (0,1)

# normal vectors
nvects = np.column_stack([nX[::bstep], nY[::bstep]])
```

In [8]:
```
# TEST : Are the boundary locations sensible?
# plt.scatter(B[::2, 0, 0], B[1::2, 0, 1], marker = 'x', s = 20, c = 'r')
# plt.plot(XB, YB)
# plt.show()

# TEST : Are the normal vectors summing to 1.0
# print(nvects[:,0]**2 + nvects[:,1]**2)
```

In [9]:
```
# TEST : Are the prediction locations correct?
# plt.scatter(Pred[:q, 0, 0][~withinairfoil],
#             Pred[q:, 0, 1][~withinairfoil], marker = 'x')
# plt.plot(XB, YB)
# plt.show()
```

Kernel hyperparameters and covariance matrices

Set the variables `sigma` and `theta` to construct the covariance matrices OR opt for LOOCV hyperparameter tuning by setting `hypropt=1`.

In [10]:
```
# USER INPUTS
hypropt = 1;                                        # Flag to perform LOOCV hyperparame
sigma = 1.0;                                        # Default noise variance
theta = 1.0;                                        # Default lengthscale / correlation

# Exact observations
n = Obs.shape[0]                                    # True velocity observations.
ytrue = np.zeros(n)                                 # Full vector of observations.
ytrue[:int(n/2)] = Vx[mask];                        # vx obs first and then vy obs.
ytrue[int(n/2):n] = Vy[mask];

# Matrix U (coefficients for boundary condition)
U = Umat(nvects, p2)                                # normal vector components.
v = np.zeros(p2)                                    # RHS of DiffEqns.


# Matrix K
def Kmatfn(params):
    CovParam = lambda *Z: CovM(*Z, kernel=AnalyticalSqExpdiff2D, **params)
    K = CovParam(Obs);
    return K
```

In [11]:

```
##########################
# LOOCV optimization step
##########################
if hypropt == 1:
    bL = 0.2; bR = 0.3                                  # left and right bounds
    bounds = [bL, bR]                                   # To initialize theta (corre
    n_iter = 100
    loomsefn = lambda theta: LOOMSESK2D(theta, ytrue, Kmatfn, sigma = 1.0)
    thetaopt, optscore, history = adamopt(loomsefn, bounds, n_iter = n_iter, stoplo
    print(f'{thetaopt=}'); print(f'{optscore=:.4f}')
    sigmaopt = LOOVARSK2D(ytrue, Kmatfn, dict(theta = thetaopt,
                                              sigma = 1.0), nugget = 1e-6)
    print(f'{sigmaopt=:.2f}')
    plt.figure()
    if not np.sum(history==1e10) == 0:                   # To check IF the stopping
        stopindex = int(np.where(history==1e10)[0][0])  # WHERE the stopping criter
        plt.plot(range(stopindex - 1), history[:stopindex-1]); plt.title(f'Loss cur
    else:
        plt.plot(range(n_iter), history); plt.title(f'Loss curve with {thetaopt=},
else:
    print(f'Using the fixed kernel params (user inputs): {theta=}, {sigma=:.2f}')
    thetaopt = theta; sigmaopt = sigma

## Matrix K (optimal)
K = Kmatfn(dict(theta = thetaopt,                       # LOOCV Optimal Kplus matri
                    sigma = 1.0))
```

```
Iter 1/100 - LOOMSE: 0.000   lengthscale: 0.242
Iter 2/100 - LOOMSE: 0.000   lengthscale: 0.252
Iter 3/100 - LOOMSE: 0.000   lengthscale: 0.256
Iter 4/100 - LOOMSE: 0.000   lengthscale: 0.254
Iter 5/100 - LOOMSE: 0.000   lengthscale: 0.256
Iter 6/100 - LOOMSE: 0.000   lengthscale: 0.254
Iter 7/100 - LOOMSE: 0.000   lengthscale: 0.249
Iter 8/100 - LOOMSE: 0.000   lengthscale: 0.246
Iter 9/100 - LOOMSE: 0.000   lengthscale: 0.242
Iter 10/100 - LOOMSE: 0.000   lengthscale: 0.237
Iter 11/100 - LOOMSE: 0.000   lengthscale: 0.230
Iter 12/100 - LOOMSE: 0.000   lengthscale: 0.233
Iter 13/100 - LOOMSE: 0.000   lengthscale: 0.236
Iter 14/100 - LOOMSE: 0.000   lengthscale: 0.239
Iter 15/100 - LOOMSE: 0.000   lengthscale: 0.242
Iter 16/100 - LOOMSE: 0.000   lengthscale: 0.244
Iter 17/100 - LOOMSE: 0.000   lengthscale: 0.246
Iter 18/100 - LOOMSE: 0.000   lengthscale: 0.248
Iter 19/100 - LOOMSE: 0.000   lengthscale: 0.250
Iter 20/100 - LOOMSE: 0.000   lengthscale: 0.251
Iter 21/100 - LOOMSE: 0.000   lengthscale: 0.252
Iter 22/100 - LOOMSE: 0.000   lengthscale: 0.254
Iter 23/100 - LOOMSE: 0.000   lengthscale: 0.255
Iter 24/100 - LOOMSE: 0.000   lengthscale: 0.256
Iter 25/100 - LOOMSE: 0.000   lengthscale: 0.257
Iter 26/100 - LOOMSE: 0.000   lengthscale: 0.257
Iter 27/100 - LOOMSE: 0.000   lengthscale: 0.258
Iter 28/100 - LOOMSE: 0.000   lengthscale: 0.258
Iter 29/100 - LOOMSE: 0.000   lengthscale: 0.259
Iter 30/100 - LOOMSE: 0.000   lengthscale: 0.260
Iter 31/100 - LOOMSE: 0.000   lengthscale: 0.261
Iter 32/100 - LOOMSE: 0.000   lengthscale: 0.262
Iter 33/100 - LOOMSE: 0.000   lengthscale: 0.263
Iter 34/100 - LOOMSE: 0.000   lengthscale: 0.264
Iter 35/100 - LOOMSE: 0.000   lengthscale: 0.264
Iter 36/100 - LOOMSE: 0.000   lengthscale: 0.265
Iter 37/100 - LOOMSE: 0.000   lengthscale: 0.265
Iter 38/100 - LOOMSE: 0.000   lengthscale: 0.265
Iter 39/100 - LOOMSE: 0.000   lengthscale: 0.264
Iter 40/100 - LOOMSE: 0.000   lengthscale: 0.264
Iter 41/100 - LOOMSE: 0.000   lengthscale: 0.263
Iter 42/100 - LOOMSE: 0.000   lengthscale: 0.263
Iter 43/100 - LOOMSE: 0.000   lengthscale: 0.262
Iter 44/100 - LOOMSE: 0.000   lengthscale: 0.263
Iter 45/100 - LOOMSE: 0.000   lengthscale: 0.263
Iter 46/100 - LOOMSE: 0.000   lengthscale: 0.262
Iter 47/100 - LOOMSE: 0.000   lengthscale: 0.260
Iter 48/100 - LOOMSE: 0.000   lengthscale: 0.257
Iter 49/100 - LOOMSE: 0.000   lengthscale: 0.255
Iter 50/100 - LOOMSE: 0.000   lengthscale: 0.253
Early stopping: difference between, |iter 50 - iter 0| = 0.0000
Iter 51/100 - LOOMSE: 0.000   lengthscale: 0.252
thetaopt=np.float64(0.26491100230405557)
optscore=0.0000
sigma^2 opt. = 0.003766238986496914
sigmaopt=0.06
```



Final predictions

In [12]:

```
############################
## Simple Lagrangian Kriging: final prediction
############################
def LagKrig(Kinv, H, v, ytrue, U, **kwargs):
    '''
    LagKrig

    :param Kinv: K inverse
    :param H: H matrix
    :param v: RHS of constraints
    :param ytrue: True observations
    :param U: U matrix
    :param kwargs: Pass UTUinv

    Feel free to pass UTUinv as a keyword argument.
    '''
    if 'UTUinv' in kwargs:
        # print('Using U^T U inverse given')
        UTUinv = kwargs.get('UTUinv')
    else:
        # print('Computing U^T U inverse')
        UTU = U.T @ U
        I = np.eye(UTU.shape[0])
        UTUinv =  np.linalg.solve(UTU, I)
    HKZ = H.T @ Kinv @ ytrue                                # Simple Kriging prediction
    prediction = (U @ UTUinv @ (v - U.T @ HKZ)) + HKZ
    return prediction
```

```python
################################################
## Simple Lagrangian Kriging: Uncertainty Quantification
################################################
def LagVar(Zpred, Kinv, H, v, ytrue, U, **kwargs):
    '''
    MMSE prediction (Conditional variance approximation)

    :param Zpred: Prediction locations and resp. orders of derivatives.
    :param Kinv: K inverse
    :param H: Matrix H
    :param v: RHS of constraints
    :param ytrue: Observed y values
    :param U: Coefficient matrix
    :param kwargs: Extra

    Feel free to pass `UTUinv`, `lamda`, `gamma`, `thetaopt` and `sigmaopt` as a ke
    '''
    theta = 1.0; sigma = 1.0                            # Default. Pass the optimal
    if 'UTUinv' in kwargs:
        # print('Using U^T U inverse given')
        UTUinv = kwargs.get('UTUinv')
    else:
        # print('Computing U^T U inverse')
        UTU = U.T @ U
        I = np.eye(UTU.shape[0])
        UTUinv =  np.linalg.solve(UTU, I)               # (U^T U)^{-1}
    if 'gamma' in kwargs:
        # print('Using gamma value given')
        gamma = kwargs.get('gamma')
    else:
        # print('Computing gamma value')
        gamma = ytrue.T @ Kinv @ ytrue                  # Z^T K^{-1} Z, RKHS norm
    HKZ = H.T @ Kinv @ ytrue                            # H^T K^{-1} Z, Simple Krig
    if 'lamda' in kwargs:
        # print('Using lambda (Lagrange multipliers) values given')
        lamda = kwargs.get('lamda')
    else:
        # print('Computing lambda values')
        lamda = (1/gamma) * UTUinv @ (v - (U.T @ HKZ))  # Lagrange multipliers


    ## Please pass optimal kernel parameters
    if 'thetaopt' in kwargs:
        theta = kwargs.get('thetaopt')
    if 'sigmaopt' in kwargs:
        sigma = kwargs.get('sigmaopt')

    ## final variance equation
    Kstar = CovM(Zpred, kernel = AnalyticalSqExpdiff2D,
                        theta = theta,                  # Unconditional variance.
                        sigma = sigma)
    M1 = np.outer(ytrue, lamda) @ U.T
    M2 = (H + M1).T @ Kinv @ (M1 - H)                   # LK contribution
    Var = np.diag(Kstar + M2)
    BaseVar = 1e-5                                      # To make sure Conditional
    return np.sqrt(Var + BaseVar)
##############################################
```

In [13]:
```
## Matrix H
params = dict(theta = thetaopt, sigma = 1.0)
CovParam = lambda *Zvals: CovM(*Zvals, kernel = AnalyticalSqExpdiff2D, **params)
H = CovParam(Obs, B)                                          # boundary prediction

# Simple Lagrangian Kriging [vhat]
nugget = 1e-10                                                # small nugget for nu
I = np.eye(K.shape[0]); nI = nugget * I
Kinv = np.linalg.solve(K + nI, I)
yhat = LagKrig(Kinv, H, v, ytrue, U)                          # All predictions (al
vxhat, vyhat = yhat.reshape((2, p2),
                            order = 'F')
```


In [14]:
```
## Visualization true flow
plt.rcParams.update({'font.family': 'DejaVu Sans', 'font.size': 12})
widf = 1.5
plt.figure(figsize = (12, 10))
plt.cla()
quiverkwargs = dict(pivot = 'tail',
                    scale = 1/0.030,
                    width = 3.25/(widf*1e3),
                    clim = (0.6, 1.1))                                  # Colorbar
Q1 = plt.quiver(XX, YY,
                Vx, Vy,
                np.hypot(Vx, Vy),
                alpha = 1,
                **quiverkwargs)
plt.colorbar()
plt.plot(XB, YB,
         alpha = 0.5, c = 'grey', label='Obstacle')
plt.title(f'Exact flow')
# plt.xlim(-1,2)
# plt.ylim(-1.4, 1.4)
# if figsave == 1:
#     plt.savefig(IMGPATH+'AirfoilCK.pdf', dpi = 300, bbox_inches = 'tight', pad_in
plt.show()
```



In [15]:

```
## Visualization Lagrangian Kriging flow prediction
plt.figure(figsize = (12, 10))
plt.cla()
Q2 = plt.quiver(B[::2,0,0], B[::2,0,1],
                vxhat, vyhat,
                np.hypot(vxhat, vyhat),
                alpha = 1.0,
                **quiverkwargs)
# Q2 = plt.quiver(B[::2,0,0], B[::2,0,1],
#                 yhat[::2], yhat[1::2],
#                 np.hypot(yhat[::2], yhat[1::2]),
#                 alpha = 1.0,
#                 **quiverkwargs)
plt.colorbar()
Q1 = plt.quiver(XX[mask], YY[mask],
                Vx[mask], Vy[mask],
                # np.hypot(vwx[mask], vwy[mask]),
                # alpha = 0.5,
                color = 'red', alpha = 1,
                **quiverkwargs)
plt.quiverkey(Q1, 1.02, 1.05, 1, label='Observations', labelpos = 'E')
plt.quiverkey(Q2, 1.02, 1.03, 1, label='Predictions', labelpos = 'E')
plt.fill(XB, YB,
```

```
        alpha = 0.5, c = 'grey', label='Obstacle')
plt.title(f'Lagrangian Kriging: {thetaopt=}, {sigmaopt=:.4f}')
# plt.xlim(min(XX)-0.05, max(XX)+0.1)
# plt.ylim(min(YY)-0.1, max(YY)+0.1)
# if figsave == 1:
#     plt.savefig(IMGPATH+'AirfoilCK.pdf', dpi = 300, bbox_inches = 'tight', pad_in
plt.show()
```



Simple Kriging based interpolation step

In [16]:
```
# prediction points
q = XX.shape[0]                         # NUM prediction points.
Pred = np.zeros((q, 2, 2))              # initialize the prediction locations.

# Airfoil shape definition.
airfoilshape = Polygon(np.column_stack([XB, YB]))   # Defining a polygon based on t
airfoilcontains = lambda x, y: airfoilshape.contains(Point(x, y))   # Function to c

# Setting the right locations.
Pred[:,0,:] = np.column_stack([XX, YY])

# creating a mask to set predictions inside the airfoil to zero.
```

```
withinairfoil = np.array(list(map(airfoilcontains,
                                  XX,
                                  YY)))
```

In [17]:

```
# kernel hyperparameters
thetaInterpol = 1.0
sigmaInterpol = 1.0


# Grid prediction points.
PredOut = Pred[~withinairfoil]                                  # Prediction locations

TotObs = np.zeros((nobs + p2,                                   # Total observations lo
                   2, 2))                                       # Order of derivatives
TotObs[:nobs,0,:] = Obs[:nobs,0,:]                              # Original observation
TotObs[nobs:,0,:] = B[::2,0,:]                                  # Boundary prediction l
Vvect = np.vstack([*ytrue.reshape((-1, 2),                      # Adding an extra axis,
                            order='F').flatten(),
                   *yhat])                                      # Combined observations

## Interpolation K matrix
def Kinterpol(params):
    K = CovM(TotObs, kernel = AnalyticalSqExpdiff2D, **params)
    Kkron = np.kron(K, np.eye(2))                               # K matrix with zero cr
    return Kkron

if hypropt == 1:
    bL = 1.0; bR = 2.0                                          # left and right bounds
    bounds = [bL, bR]                                           # To initialize theta (
    n_iter = 1000
    loomsefn = lambda theta: LOOMSESK2D(theta, Vvect, Kinterpol, sigma = 1.0, nugge
    thetaopti, optscore, history = adamopt(loomsefn, bounds, n_iter = n_iter)
    print(f'{thetaopti=:.2f}'); print(f'{optscore=:.4f}')
    sigmaopti = LOOVARSK2D(Vvect, Kinterpol, dict(theta = thetaopti, sigma = 1.0),
    # plt.plot(range(n_iter), history); plt.show()              # To visualize LOOCV
    if not np.sum(history==1e10) == 0:                          # To check IF the sto
        stopindex = int(np.where(history==1e10)[0][0])          # WHERE the stopping
        plt.plot(range(stopindex - 1), history[:stopindex-1]); plt.title(f'Loss cur
    else:
        plt.plot(range(n_iter), history); plt.title(f'Loss curve with {thetaopti=},
    print(f'{sigmaopti=:.2f}')
else:
    print(f'Using the fixed kernel params (user inputs): {thetaInterpol=:.2f}, {sig
    thetaopti = thetaInterpol; sigmaopti = sigmaInterpol
```

```
Iter 1/1000 - LOOMSE: 0.006   lengthscale: 1.720
Iter 2/1000 - LOOMSE: 0.006   lengthscale: 1.710
Iter 3/1000 - LOOMSE: 0.006   lengthscale: 1.709
Iter 4/1000 - LOOMSE: 0.006   lengthscale: 1.705
Iter 5/1000 - LOOMSE: 0.006   lengthscale: 1.698
Iter 6/1000 - LOOMSE: 0.006   lengthscale: 1.696
Iter 7/1000 - LOOMSE: 0.006   lengthscale: 1.695
Iter 8/1000 - LOOMSE: 0.006   lengthscale: 1.694
Iter 9/1000 - LOOMSE: 0.006   lengthscale: 1.693
Iter 10/1000 - LOOMSE: 0.006   lengthscale: 1.696
Iter 11/1000 - LOOMSE: 0.006   lengthscale: 1.700
Iter 12/1000 - LOOMSE: 0.006   lengthscale: 1.703
Iter 13/1000 - LOOMSE: 0.006   lengthscale: 1.706
Iter 14/1000 - LOOMSE: 0.006   lengthscale: 1.709
Iter 15/1000 - LOOMSE: 0.006   lengthscale: 1.710
Iter 16/1000 - LOOMSE: 0.006   lengthscale: 1.711
Iter 17/1000 - LOOMSE: 0.006   lengthscale: 1.710
Iter 18/1000 - LOOMSE: 0.006   lengthscale: 1.709
Iter 19/1000 - LOOMSE: 0.006   lengthscale: 1.709
Iter 20/1000 - LOOMSE: 0.006   lengthscale: 1.708
Iter 21/1000 - LOOMSE: 0.006   lengthscale: 1.708
Iter 22/1000 - LOOMSE: 0.006   lengthscale: 1.707
Iter 23/1000 - LOOMSE: 0.006   lengthscale: 1.707
Iter 24/1000 - LOOMSE: 0.006   lengthscale: 1.707
Iter 25/1000 - LOOMSE: 0.006   lengthscale: 1.705
Iter 26/1000 - LOOMSE: 0.006   lengthscale: 1.703
Iter 27/1000 - LOOMSE: 0.006   lengthscale: 1.701
Iter 28/1000 - LOOMSE: 0.006   lengthscale: 1.700
Iter 29/1000 - LOOMSE: 0.006   lengthscale: 1.699
Iter 30/1000 - LOOMSE: 0.006   lengthscale: 1.699
Iter 31/1000 - LOOMSE: 0.006   lengthscale: 1.700
Iter 32/1000 - LOOMSE: 0.006   lengthscale: 1.699
Iter 33/1000 - LOOMSE: 0.006   lengthscale: 1.698
Iter 34/1000 - LOOMSE: 0.006   lengthscale: 1.697
Iter 35/1000 - LOOMSE: 0.006   lengthscale: 1.695
Iter 36/1000 - LOOMSE: 0.006   lengthscale: 1.692
Iter 37/1000 - LOOMSE: 0.006   lengthscale: 1.689
Iter 38/1000 - LOOMSE: 0.006   lengthscale: 1.687
Iter 39/1000 - LOOMSE: 0.006   lengthscale: 1.682
Iter 40/1000 - LOOMSE: 0.006   lengthscale: 1.678
Iter 41/1000 - LOOMSE: 0.006   lengthscale: 1.677
Iter 42/1000 - LOOMSE: 0.006   lengthscale: 1.675
Iter 43/1000 - LOOMSE: 0.006   lengthscale: 1.673
Iter 44/1000 - LOOMSE: 0.006   lengthscale: 1.671
Iter 45/1000 - LOOMSE: 0.006   lengthscale: 1.671
Iter 46/1000 - LOOMSE: 0.006   lengthscale: 1.672
Iter 47/1000 - LOOMSE: 0.006   lengthscale: 1.669
Iter 48/1000 - LOOMSE: 0.006   lengthscale: 1.667
Iter 49/1000 - LOOMSE: 0.006   lengthscale: 1.665
Iter 50/1000 - LOOMSE: 0.006   lengthscale: 1.662
Early stopping: difference between, |iter 50 - iter 0| = 0.0001
Iter 51/1000 - LOOMSE: 0.006   lengthscale: 1.658
thetaopti=1.66
optscore=0.0055
sigma^2 opt. = 7310.126168525763
sigmaopti=85.50
```




In [18]:
```
# TEST : Arrangement of the ytrue vector.
# ytrue.reshape((-1, 2),
#               order='F').flatten()
```

In [24]:
```
## Optimal interpolation matrices.
params = dict(theta = thetaopti, sigma = sigmaopti)          # Optimal params
Kkron = Kinterpol(params)
H = CovM(TotObs, PredOut, kernel = AnalyticalSqExpdiff2D, **params)
Hkron = np.kron(H, np.eye(2))

# Interpolated predictions
nugget = 1e-6
I = np.eye(Kkron.shape[0]); nI = nugget * I
Kkroninv = np.linalg.solve(Kkron + nI, I)
Vstarkron = Hkron.T @ Kkroninv @ Vvect                      # Simple Kriging predict
Vstarkron = Vstarkron.reshape(-1,2)                         # New axis indicating Vx
```

In [25]:
```
## Interpolated predictions
plt.figure(figsize = (12, 10))
plt.cla()
qout = int(PredOut.shape[0]/2)
Q2 = plt.quiver(PredOut[:,0,0], PredOut[:,0,1],
                Vstarkron[:,0], Vstarkron[:,1],
                np.hypot(Vstarkron[:,0], Vstarkron[:,1]),
                alpha = 1.0,
                **quiverkwargs)
# Q2 = plt.quiver(B[::2,0,0], B[::2,0,1],
#                 yhat[::2], yhat[1::2],
#                 np.hypot(yhat[::2], yhat[1::2]),
#                 alpha = 1.0,
#                 **quiverkwargs)
plt.colorbar()
Q1 = plt.quiver(XX[mask], YY[mask],
                Vx[mask], Vy[mask],
                # np.hypot(vwx[mask], vwy[mask]),
```

```
                # alpha = 0.5,
                color = 'red', alpha = 1,
                **quiverkwargs)
plt.quiverkey(Q1, 1.02, 1.05, 1, label='Observations', labelpos = 'E')
plt.quiverkey(Q2, 1.02, 1.03, 1, label='Predictions', labelpos = 'E')
plt.fill(XB, YB,
         alpha = 0.5, c = 'grey', label='Obstacle')
plt.title(f'Lagrangian Kriging (interpolated): {thetaopti=}, {sigmaopti=:.4f}')
# plt.xlim(min(XX)-0.05, max(XX)+0.1)
# plt.ylim(min(YY)-0.1, max(YY)+0.1)
# if figsave == 1:
#     plt.savefig(IMGPATH+'AirfoilCK.pdf', dpi = 300, bbox_inches = 'tight', pad_in
plt.show()
```



In [21]:
```
# min(np.diag(Kkron))/sigmaopti
```