Airfoil Simple Kriging

Load the NACA airfoil coordinates and predict. The coordinates should be arranged in one sense. Meaning, that `XB` and `YB` are either in a clockwise or anti-clockwise arrangement.

Exact solution

The true velocity is computed using the BEM code. GRID discretization used:

```
{python}
# Grid parameters
nGridX   = 30
# X-grid for streamlines and contours
nGridY   = 30
# Y-grid for streamlines and contours
xVals    = [min(XB)-0.5, max(XB)+0.5]
# X-grid extents [min, max]
yVals    = [min(YB)-0.2, max(YB)+0.2]
# Y-grid extents [min, max]
```

In [1]:
```
# imports
import numpy as np
import matplotlib.pyplot as plt
from shapely.geometry import Polygon, Point
# from scipy.interpolate import griddata
from matrices import CovM, CovFn
from covderivatives2D import AnalyticalSqExpdiff2D
from calibration import LOOMSESK2D, LOOVARSK2D, adamopt, Adam
import matplotlib.cm as cm
from matplotlib.colors import Normalize
```

```
Importing covderivatives.py
Importing covderivatives2D.py
```

In [2]:
```
# Image path to save the images.
IMGPATH = r'IMAGES/'

# load the NACA airfoil data
NACAname = r'0012'
XB, YB, nX, nY = np.loadtxt('data/NACA'+NACAname+'UIUCnormalvecs.dat',
                            unpack=True)
XX, YY, Vx, Vy = np.loadtxt('data/NACA'+NACAname+'BEMflow.dat',
                            unpack=True)
```

Defining relevant points in the extended design space.

- Observation points (`Obs`). $v_x \rightarrow$ `m = (1,0)` . $v_y \rightarrow$ `m = (0,1)` .
- Prediction points (`Pred`). `m = (1,0)` & `m = (0,1)` .

In [3]:
```
# USER INPUTS
## Observation locations with derivative orders.
nobs = 20                                   # number of observations (at i
nm = 20                                     # number of observations in th
UQFLAG = 1                                  # For uncertainty prediction
ostep = int(np.sqrt(XX.shape[0])/nobs)      # step size to select observat
mstep = int(np.sqrt(XX.shape[0])/nm)        # step size to select observat
```

In [4]:
```
# Observation locations
mask = np.zeros_like(XX, dtype = bool)      # mask to choose the right ob

for _ in np.where(XX==min(XX))[0][::ostep]:
    mask[_] = True;                         # observations at -infinity.
for _ in np.where(XX==max(XX))[0][::ostep]:
    mask[_] = True;                         # observations at +infinity.
for _ in np.where(YY==min(YY))[0][mstep::mstep]:
    mask[_] = True;                         # (upper) mid-domain observat
for _ in np.where(YY==max(YY))[0][mstep::mstep]:
    mask[_] = True;                         # (lower) mid-domain observat

nobs = np.sum(mask)                         # redefining nobs based on th
Obs = np.zeros((2*nobs, 2, 2))              # Observations of [Vx, Vy].

## Setting the appropriate locations.
Obs[:nobs, 0, 0] = XX[mask];
Obs[:nobs, 0, 1] = YY[mask]
Obs[nobs:, 0, :] = Obs[:nobs, 0, :]         # repeating the same observat

## Setting the right order of derivatives.
Obs[:nobs, 1, 0] = 1; Obs[nobs:, 1, 1] = 1  # m = (1,0) and m = (0,1)
```

In [5]:
```
# TEST : Is the `mask` vector properly defined?
# plt.scatter(XX[mask], YY[mask], marker = 'x')
# plt.quiver(XX[mask], YY[mask],
#            Vx[mask], Vy[mask])
# plt.show()
```

In [6]:
```
# prediction points
q = XX.shape[0]                         # NUM prediction points.
Pred = np.zeros((2*q, 2, 2))            # initialize the prediction location

# Airfoil shape definition.
airfoilshape = Polygon(np.column_stack([XB, YB]))   # Defining a polygon
airfoilcontains = lambda x, y: airfoilshape.contains(Point(x, y))   # Fun

# Setting the right locations.
Pred[:q, 0, :] = np.column_stack([XX, YY])
Pred[q:, 0, :] = Pred[:q, 0, :]

# Setting the right order of derivatives.
Pred[:q, 1, 0] = 1                          # m = (1,0)
Pred[q:, 1, 1] = 1                          # m = (0,1)

# creating a mask to set predictions inside the airfoil to zero.
withinairfoil = np.array(list(map(airfoilcontains,
                                  XX,
                                  YY)))
```

In [7]:
```
# TEST : Are the prediction locations correct?
# plt.scatter(Pred[:q, 0, 0][~withinairfoil],
#             Pred[q:, 0, 1][~withinairfoil], marker = 'x')
# plt.plot(XB, YB)
# plt.show()
```

Kernel hyperparameters and covariance matrices

Set the variables `sigma` and `theta` to construct the covariance matrices OR opt for LOOCV hyperparameter tuning by setting `hypropt=1`.

In [8]:
```
# USER INPUTS
hypropt = 1;                                        # Flag to perform LOOCV h
sigma = 1.0;                                        # Default noise variance
theta = 1.0;                                        # Default lengthscale / c


# Exact observations
n = Obs.shape[0]                                    # True velocity observati
ytrue = np.zeros(n)                                 # Full vector of observat
ytrue[:int(n/2)] = Vx[mask];                        # vx obs first and then v
ytrue[int(n/2):n] = Vy[mask];

# Matrix K
def Kmatfn(params):
    CovParam = lambda *Z: CovM(*Z, kernel=AnalyticalSqExpdiff2D, **params
    K = CovParam(Obs);
    return K
```

In [9]:
```
##########################
# LOOCV optimization step
##########################
if hypropt == 1:
    bL = 0.2; bR = 0.3                                  # left and right
    bounds = [bL, bR]                                   # To initialize t
    n_iter = 100
    loomsefn = lambda theta: LOOMSESK2D(theta, ytrue, Kmatfn, sigma = 1.0
    thetaopt, optscore, history = adamopt(loomsefn, bounds, n_iter = n_it
    print(f'{thetaopt=}'); print(f'{optscore=:.4f}')
    sigmaopt = LOOVARSK2D(ytrue, Kmatfn, dict(theta = thetaopt,
                                              sigma = 1.0), nugget = 1e
    print(f'{sigmaopt=:.2f}')
    plt.figure()
    if not np.sum(history==1e10) == 0:                  # To check IF the
        stopindex = int(np.where(history==1e10)[0][0])  # WHERE the stopp
        plt.plot(range(stopindex - 1), history[:stopindex-1]); plt.title(
    else:
        plt.plot(range(n_iter), history); plt.title(f'Loss curve with {th
    # plt.savefig(IMGPATH + 'lossAirfoilCK.pdf')
    # plt.show()      # To visualize LOOCV loss curve
else:
    print(f'Using the fixed kernel params (user inputs): {theta=}, {sigma
    thetaopt = theta; sigmaopt = sigma

## Matrix K (optimal)
K = Kmatfn(dict(theta = thetaopt,                       # LOOCV Optimal K
                    sigma = 1.0))
```

```
Iter 1/100 - LOOMSE: 0.000   lengthscale: 0.259
Iter 2/100 - LOOMSE: 0.000   lengthscale: 0.269
Iter 3/100 - LOOMSE: 0.000   lengthscale: 0.267
Iter 4/100 - LOOMSE: 0.000   lengthscale: 0.260
Iter 5/100 - LOOMSE: 0.000   lengthscale: 0.253
Iter 6/100 - LOOMSE: 0.000   lengthscale: 0.251
Iter 7/100 - LOOMSE: 0.000   lengthscale: 0.252
Iter 8/100 - LOOMSE: 0.000   lengthscale: 0.256
Iter 9/100 - LOOMSE: 0.000   lengthscale: 0.258
Iter 10/100 - LOOMSE: 0.000   lengthscale: 0.260
Iter 11/100 - LOOMSE: 0.000   lengthscale: 0.265
Iter 12/100 - LOOMSE: 0.000   lengthscale: 0.271
Iter 13/100 - LOOMSE: 0.000   lengthscale: 0.277
Iter 14/100 - LOOMSE: 0.000   lengthscale: 0.282
Iter 15/100 - LOOMSE: 0.000   lengthscale: 0.289
Iter 16/100 - LOOMSE: 0.000   lengthscale: 0.295
Iter 17/100 - LOOMSE: 0.000   lengthscale: 0.300
Iter 18/100 - LOOMSE: 0.000   lengthscale: 0.305
Iter 19/100 - LOOMSE: 0.000   lengthscale: 0.308
Iter 20/100 - LOOMSE: 0.000   lengthscale: 0.311
Iter 21/100 - LOOMSE: 0.000   lengthscale: 0.315
Iter 22/100 - LOOMSE: 0.000   lengthscale: 0.318
Iter 23/100 - LOOMSE: 0.000   lengthscale: 0.322
Iter 24/100 - LOOMSE: 0.000   lengthscale: 0.324
Iter 25/100 - LOOMSE: 0.000   lengthscale: 0.326
Iter 26/100 - LOOMSE: 0.000   lengthscale: 0.330
Iter 27/100 - LOOMSE: 0.000   lengthscale: 0.332
Iter 28/100 - LOOMSE: 0.000   lengthscale: 0.334
Iter 29/100 - LOOMSE: 0.000   lengthscale: 0.336
Iter 30/100 - LOOMSE: 0.000   lengthscale: 0.338
Iter 31/100 - LOOMSE: 0.000   lengthscale: 0.340
Iter 32/100 - LOOMSE: 0.000   lengthscale: 0.343
Iter 33/100 - LOOMSE: 0.000   lengthscale: 0.347
Iter 34/100 - LOOMSE: 0.000   lengthscale: 0.349
Iter 35/100 - LOOMSE: 0.000   lengthscale: 0.353
Iter 36/100 - LOOMSE: 0.000   lengthscale: 0.357
Iter 37/100 - LOOMSE: 0.000   lengthscale: 0.361
Iter 38/100 - LOOMSE: 0.000   lengthscale: 0.368
Iter 39/100 - LOOMSE: 0.000   lengthscale: 0.373
Iter 40/100 - LOOMSE: 0.000   lengthscale: 0.379
Iter 41/100 - LOOMSE: 0.000   lengthscale: 0.388
Iter 42/100 - LOOMSE: 0.000   lengthscale: 0.395
Iter 43/100 - LOOMSE: 0.000   lengthscale: 0.401
Iter 44/100 - LOOMSE: 0.000   lengthscale: 0.406
Iter 45/100 - LOOMSE: 0.000   lengthscale: 0.411
Iter 46/100 - LOOMSE: 0.000   lengthscale: 0.415
Iter 47/100 - LOOMSE: 0.000   lengthscale: 0.419
Iter 48/100 - LOOMSE: 0.000   lengthscale: 0.422
Iter 49/100 - LOOMSE: 0.000   lengthscale: 0.425
Iter 50/100 - LOOMSE: 0.000   lengthscale: 0.428
Early stopping: difference between, |iter 50 - iter 0| = 0.0000
Iter 51/100 - LOOMSE: 0.000   lengthscale: 0.431
thetaopt=np.float64(0.2888804311781113)
optscore=0.0000
sigma^2 opt. = 1.33244969937761
sigmaopt=1.15
```




Final predictions and UQ

In [10]:
```
## Matrix H
params = dict(theta = thetaopt, sigma = 1.0)
CovParam = lambda *Zvals: CovM(*Zvals, kernel = AnalyticalSqExpdiff2D, **
PredOut = np.vstack([Pred[:q][~withinairfoil],              # vx outside
                     Pred[q:][~withinairfoil]])            # vy outside
H = CovParam(Obs, PredOut)
```

In [11]:
```
# Simple Kriging [yhat]
# yhat = np.zeros(2*q)                                      # Prediction
qout = int(PredOut.shape[0]/2)
nugget = 1e-10                                              # small nugg
I = np.eye(K.shape[0]); nI = nugget * I
Kinv = np.linalg.solve(K + nI, I)
vxhat, vyhat = (H.T @ Kinv @ ytrue).reshape(2, qout)
# yhat = Hplus.T @ Kplusinv @ ytrue
```


In [12]:
```
## Visualization true flow
plt.rcParams.update({'font.family': 'DejaVu Sans', 'font.size': 12})
widf = 1.5
plt.figure(figsize = (12, 10))
plt.cla()
quiverkwargs = dict(pivot = 'tail',
                    scale = 1/0.030,
                    width = 3.25/(widf*1e3),
                    clim = (0.6, 1.1))                                  #
Q1 = plt.quiver(XX, YY,
                Vx, Vy,
                np.hypot(Vx, Vy),
                alpha = 1,
                **quiverkwargs)
plt.colorbar()
```

```
plt.plot(XB, YB,
         alpha = 0.5, c = 'grey', label='Obstacle')
plt.title(f'Exact flow')
# plt.xlim(-1,2)
# plt.ylim(-1.4, 1.4)
# if figsave == 1:
#     plt.savefig(IMGPATH+'AirfoilCK.pdf', dpi = 300, bbox_inches = 'tigh
plt.show()
```



In [13]:
```
## Visualization Co-Kriging flow prediction
plt.figure(figsize = (12, 10))
plt.cla()
Q2 = plt.quiver(PredOut[:qout, 0, 0], PredOut[:qout, 0, 1],
                vxhat, vyhat,
                np.hypot(vxhat, vyhat),
                alpha = 1.0,
                **quiverkwargs)
plt.colorbar()
Q1 = plt.quiver(XX[mask], YY[mask],
                Vx[mask], Vy[mask],
                color = 'red', alpha = 1,
                **quiverkwargs)
plt.quiverkey(Q1, 1.02, 1.05, 1, label='Observations', labelpos = 'E')
plt.quiverkey(Q2, 1.02, 1.03, 1, label='Predictions', labelpos = 'E')
plt.fill(XB, YB,
         alpha = 0.5, c = 'grey', label='Obstacle')
plt.title(f'Simple Kriging: {thetaopt=}, {sigmaopt=:.4f}')
# plt.xlim(min(XX)-0.05, max(XX)+0.1)
```

```
# plt.ylim(min(YY)-0.1, max(YY)+0.1)
# if figsave == 1:
#     plt.savefig(IMGPATH+'AirfoilCK.pdf', dpi = 300, bbox_inches = 'tigh
plt.show()
```



Uncertainty quantification.

In [14]:
```
if UQFLAG == 1:
    ## Uncertainty quantification: simple Kriging expression
    BaseVar = 1e-5                                          # To make sure C
    Kpred = CovParam(PredOut)                               # Unconditional
    CondVar = Kpred - (H.T @ Kinv @ H)                      # Minimal MSE
    CondVar[CondVar <= 0] = BaseVar                         # Replacing zero
    # CondVar += BaseVar                                      # Small quanti
    CondSigma = np.sqrt(sigmaopt**2 * np.diag(CondVar));
```

In [15]:
```
## Simple Kriging uncertainty in prediction.
## Generalized chi^2 distribtion. Quadratic form of two dependent gaussia
if UQFLAG == 1:
    CondVar = sigmaopt**2 * CondVar;
    CVxVx = np.diag(CondVar[:qout, :qout])                          # Var[V
    CVxVy = np.diag(CondVar[:qout, qout:])                          # Cov[V
    CVyVy = np.diag(CondVar[qout:, qout:])                          # Var[V
    ChiVar = np.zeros(qout)                                         # Chi^2
    for i in range(qout):
        Mu = np.array([vxhat[i],                                    # predi
```

```
                        vyhat[i]])                                          # predi
        Cov = np.array([[CVxVx[i], CVxVy[i]],                               # Cov m
                        [CVxVy[i], CVyVy[i]]])
        eigvect, eigmatrix = np.linalg.eigh(Cov)
        b = eigmatrix @ Mu
        ChiVar[i] = np.sum(2 * eigvect**2 * (1 + 2*b**2))                   # A der
                                                                            # A pap
    plt.figure(figsize = (12,10))
    plt.cla()
    UQ = np.zeros(XX.shape[0])                                              # initi
    UQ[~withinairfoil] = ChiVar                                             # Assig
    plt.contourf(XX.reshape(30, 30), YY.reshape(30,30),
                 2*np.sqrt(UQ).reshape(30, 30),)
                #  vmin = 0.0, vmax = 1.0)                                  # Same
    cnorm = Normalize(vmin = 0.0, vmax = 2.0)                               # To no
    plt.colorbar(cm.ScalarMappable(norm=cnorm), ax = plt.gca())
    # plt.clim(0.0, 0.01)
    # plt.colorbar()
    # plt.clim(0.0, 0.200)                                                  # Same
    plt.fill(XB, YB,
            alpha = 1, c = 'white', label='Obstacle')
    plt.title(f'Simple Kriging UQ: {thetaopt=}, {sigmaopt=:.4f}')
    # if figsave == 1:
    #     plt.savefig(IMGPATH+'FluidCKUQ.pdf', dpi = 300, bbox_inches = '
    plt.show()
```

