Sample Code Document

1. App.js

```
EXPLORER
JS SocketContext.js   JS Footer.js   .env   JS App.js X   JS NotificationDropdown.js
OPEN EDIT...
  JS SocketContext.js f...
  JS Footer.js food-deliv...
  .env food-delivery-a...
X JS App.js food-delivery-...
  JS NotificationDropd...
  JS notifications.js foo...
  .env.example food-...
  JS NotificationLog.js f...
SEAD_PROJECT
  food-delivery-app
    backend
    frontend
      build
      node_modules
      public
      src
        components
        context
        pages
        services
        JS App.js
food-delivery-app > frontend > src > JS App.js > ...
1  import { BrowserRouter as Router, Routes, Route } from 'react-router-dom';
2  import { useState, useEffect } from 'react';
3  import { Toaster } from 'react-hot-toast';
4  import { AuthProvider } from './context/AuthContext';
5  import { CartProvider } from './context/CartContext';
6  import { SocketProvider } from './context/SocketContext';
7  import Navbar from './components/Navbar';
8  import Footer from './components/Footer';
9  import ProtectedRoute from './components/ProtectedRoute';
10 import { getHotelStatus } from './services/api';
11
12 // Customer Pages
13 import Home from './pages/Home';
14 import Menu from './pages/Menu';
15 import FoodDetails from './pages/FoodDetails';
16 import Cart from './pages/Cart';
17 import Checkout from './pages/Checkout';
18 import OrderTracking from './pages/OrderTracking';
19 import Reservation from './pages/Reservation';
20 import MyReservations from './pages/MyReservations';
21 import Login from './pages/Login';
22
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS
```

2. Admindashboard.js

```
food-delivery-app > frontend > src > pages > admin > JS AdminDashboard.js > ...
1  import { useState, useEffect, useCallback } from 'react';
2  import { Link } from 'react-router-dom';
3  import { FiShoppingBag, FiDollarSign, FiCalendar, FiTrendingUp, FiWifi } from 'react-icons/fi';
4  import { getAnalytics, getReservations, getHotelStatus, updateHotelStatus } from '../../services/api';
5  import { useSocket } from '../../context/SocketContext';
6  import toast from 'react-hot-toast';
7
8  const AdminDashboard = () => {
9    const [analytics, setAnalytics] = useState(null);
10   const [reservationCount, setReservationCount] = useState(0);
11   const [loading, setLoading] = useState(true);
12   const [hotelOpen, setHotelOpen] = useState(true);
13   const [togglingStatus, setTogglingStatus] = useState(false);
14   const { on, off, connected } = useSocket();
15
16   const fetchData = async () => {
17     try {
18       const [analyticsRes, reservationsRes, statusRes] = await Promise.all([
19         getAnalytics(),
20         getReservations(),
21         getHotelStatus(),
22       ]);
```

3. OrderTracking.js

```
JS SocketContext.js   JS Footer.js   .env   JS NotificationDropdown.js   JS OrderTracking.js X   JS notifications.js   .env.examp
food-delivery-app > frontend > src > pages > JS OrderTracking.js > ...
1  import { useState, useEffect, useCallback } from 'react';
2  import { Link, useParams } from 'react-router-dom';
3  import { FiPackage, FiClock, FiCheck, FiTruck, FiWifi, FiWifiOff } from 'react-icons/fi';
4  import toast from 'react-hot-toast';
5  import { getOrders, getOrder } from '../services/api';
6  import { useSocket } from '../context/SocketContext';
7
8  const STATUS_STEPS = ['Pending', 'Preparing', 'Out for Delivery', 'Delivered'];
9  const STATUS_ICONS = { 'Pending': FiClock, 'Preparing': FiPackage, 'Out for Delivery': FiTruck, 'Delivered': FiCheck };
10 const STATUS_MESSAGES = {
11   'Pending': 'Your order is being confirmed...',
12   'Preparing': '👨‍🍳 Chefs are preparing your meal!',
13   'Out for Delivery': '🚚 Your order is on its way!',
14   'Delivered': '✅ Order delivered! Enjoy your meal!',
15 };
16
17 const OrderTracking = () => {
18   const { id } = useParams();
19   const { on, off, connected } = useSocket();
20   const [orders, setOrders] = useState([]);
21   const [selectedOrder, setSelectedOrder] = useState(null);
22   const [loading, setLoading] = useState(true);
```

4. FoodDetails.js

```
food-delivery-app > frontend > src > pages > JS FoodDetails.js > ...
1  import { useState, useEffect } from 'react';
2  import { useParams } from 'react-router-dom';
3  import { FiMinus, FiPlus, FiShoppingCart } from 'react-icons/fi';
4  import { getMenuItem } from '../services/api';
5  import { useCart } from '../context/CartContext';
6
7  const FoodDetails = () => {
8    const { id } = useParams();
9    const { addToCart } = useCart();
10   const [item, setItem] = useState(null);
11   const [loading, setLoading] = useState(true);
12   const [quantity, setQuantity] = useState(1);
13
14   useEffect(() => {
15     const fetch = async () => {
16       try {
17         const { data } = await getMenuItem(id);
18         setItem(data);
19       } catch (err) {
20         console.error(err);
21       } finally {
22         setLoading(false);
```