
Started on Thursday, 16 April 2026, 10:28 AM

State Finished

Completed on Thursday, 16 April 2026, 11:22 AM

Time taken 54 mins 21 secs

Grade 10.00 out of 10.00 (100%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you have an array of length n initialized with all 0's and are given k update operations.

Each operation is represented as a triplet: **[startIndex, endIndex, inc]** which increments each element of subarray **A[startIndex ... endIndex]** (startIndex and endIndex inclusive) with **inc**.

Return the modified array after all k operations were executed.

Example:

Input:

```
5
3
1 3 2
2 4 3
0 2 -2
```

Output:

```
-2 0 3 5 3
```

Explanation:

Initial state:

length = 5, updates = [[1,3,2],[2,4,3],[0,2,-2]]

[0,0,0,0,0]

After applying operation [1,3,2]:

[0,2,2,2,0]

After applying operation [2,4,3]:

[0,2,5,5,3]

After applying operation [0,2,-2]:

[-2,0,3,5,3]

Answer: (penalty regime: 0 %)

```
1 def m(n,k):
2     a=[0]*n
3     for _ in range(k):
4         s,e,i=map(int,input().split())
5         a[s]+=i
6         if e+1<n:
7             a[e+1]-=i
8     for il in range(1,n):
9         a[il]+=a[il-1]
10    return a
11 n=int(input())
12 k=int(input())
13 r=m(n,k)
14 print(*r)
```

	Input	Expected	Got	
✓	5 3 1 3 2 2 4 3 0 2 -2	-2 0 3 5 3	-2 0 3 5 3	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2 | Correct Mark 1.00 out of 1.00

Given two arrays of positive integers, for each element in the second array, find the total number of elements in the first array which are *less than or equal to* that element. Store the values determined in an array.

For example, if the first array is $[1, 2, 3]$ and the second array is $[2, 4]$, then there are 2 elements in the first array *less than or equal to* 2. There are 3 elements in the first array which are *less than or equal to* 4. We can store these answers in an array, $answer = [2, 3]$.

Program Description

The program must return an array of m positive integers, one for each $maxes[i]$ representing the total number of elements $nums[j]$ satisfying $nums[j] \leq maxes[i]$ where $0 \leq j < n$ and $0 \leq i < m$, in the given order.

The program has the following:

$nums[nums[0], \dots, nums[n-1]]$: first array of positive integers

$maxes[maxes[0], \dots, maxes[m-1]]$: second array of positive integers

Constraints

- $2 \leq n, m \leq 10^5$
- $1 \leq nums[j] \leq 10^9$, where $0 \leq j < n$.
- $1 \leq maxes[i] \leq 10^9$, where $0 \leq i < m$.

Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the program.

The first line contains an integer n , the number of elements in $nums$.

The next n lines each contain an integer describing $nums[j]$ where $0 \leq j < n$.

The next line contains an integer m , the number of elements in $maxes$.

The next m lines each contain an integer describing $maxes[i]$ where $0 \leq i < m$.

Sample Case 0**Sample Input 0**

```
4
1
4
2
4
2
3
5
```

Sample Output 0

```
2
4
```

Explanation 0

We are given $n = 4$, $nums = [1, 4, 2, 4]$, $m = 2$, and $maxes = [3, 5]$.

1. For $maxes[0] = 3$, we have 2 elements in $nums$ ($nums[0] = 1$ and $nums[2] = 2$) that are $\leq maxes[0]$.
 2. For $maxes[1] = 5$, we have 4 elements in $nums$ ($nums[0] = 1$, $nums[1] = 4$, $nums[2] = 2$, and $nums[3] = 4$) that are $\leq maxes[1]$.
- Thus, the program returns the array $[2, 4]$ as the answer.

Sample Case 1

Sample Input 1

```

5
2
10
5
4
8
4
3
1
7
8

```

Sample Output 1

```

1
0
3
4

```

Explanation 1

We are given, $n = 5$, $nums = [2, 10, 5, 4, 8]$, $m = 4$, and $maxes = [3, 1, 7, 8]$.

1. For $maxes[0] = 3$, we have 1 element in $nums$ ($nums[0] = 2$) that is $\leq maxes[0]$.
2. For $maxes[1] = 1$, there are 0 elements in $nums$ that are $\leq maxes[1]$.
3. For $maxes[2] = 7$, we have 3 elements in $nums$ ($nums[0] = 2$, $nums[2] = 5$, and $nums[3] = 4$) that are $\leq maxes[2]$.
4. For $maxes[3] = 8$, we have 4 elements in $nums$ ($nums[0] = 2$, $nums[2] = 5$, $nums[3] = 4$, and $nums[4] = 8$) that are $\leq maxes[3]$.

Thus, the program returns the array $[1, 0, 3, 4]$ as the answer.

Answer: (penalty regime: 0 %)

```

1 import bisect
2 import sys
3 def s():
4     d=sys.stdin.read().split()
5     if not d:
6         return
7     n=int(d[0])
8     num=sorted(map(int,d[1:n+1]))
9     mi=n+1
10    m=int(d[mi])
11    ma=map(int,d[mi+1:mi+1+m])
12    for v in ma:
13        print(bisect.bisect_right(num,v))
14 if __name__ == "__main__":
15     s()
16

```

	Input	Expected	Got	
✓	4	2	2	✓
	1	4	4	
	4			
	2			
	4			
	2			
	3			
	5			
✓	5	1	1	✓
	2	0	0	
	10	3	3	
	5	4	4	
	4			
	8			
	4			
	3			
	1			
	7			
	8			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3 | Correct Mark 1.00 out of 1.00

Complete the program to count frequency of each element of an array. Frequency of a particular element will be printed once.

Sample Test Cases

Test Case 1

Input

7
23
45
23
56
45
23
40

Output

23 occurs 3 times
45 occurs 2 times
56 occurs 1 times
40 occurs 1 times

Answer: (penalty regime: 0 %)

```

1 def c(n):
2     f={}
3     for num in n:
4         if num in f:
5             f[num]+=1
6         else:
7             f[num]=1
8     for num in f:
9         print(num,"occurs",f[num],"times")
10 n1=int(input())
11 n=[]
12 for _ in range(n1):
13     n.append(int(input()))
14 c(n)

```

	Input	Expected	Got	
✓	7	23 occurs 3 times	23 occurs 3 times	✓
	23	45 occurs 2 times	45 occurs 2 times	
	45	56 occurs 1 times	56 occurs 1 times	
	23	40 occurs 1 times	40 occurs 1 times	
	56			
	45			
	23			
	40			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4 | Correct Mark 1.00 out of 1.00

Given an integer n , return an list of length $n + 1$ such that for each i ($0 \leq i \leq n$), $\text{ans}[i]$ is the number of 1's in the binary representation of i .

Example:

Input: $n = 2$

Output: $[0, 1, 1]$

Explanation:

0 --> 0

1 --> 1

2 --> 10

Example2:

Input: $n = 5$

Output: $[0, 1, 1, 2, 1, 2]$

Explanation:

0 --> 0

1 --> 1

2 --> 10

3 --> 11

4 --> 100

5 --> 101

Note: Complete the given function alone

For example:

Test	Result
<code>print(CountingBits(5))</code>	<code>[0, 1, 1, 2, 1, 2]</code>

Answer: (penalty regime: 0 %)

Reset answer

```
1 def CountingBits(n):
2     return [bin(i).count('1') for i in range(n+1)]
```

	Test	Expected	Got	
✓	<code>print(CountingBits(2))</code>	<code>[0, 1, 1]</code>	<code>[0, 1, 1]</code>	✓
✓	<code>print(CountingBits(5))</code>	<code>[0, 1, 1, 2, 1, 2]</code>	<code>[0, 1, 1, 2, 1, 2]</code>	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5 | Correct Mark 1.00 out of 1.00

Given a matrix `mat` where every row is sorted in **strictly increasing** order, return the **smallest common element** in all rows.

If there is no common element, return -1.

Example 1:**Input:**

```
4 5
1 2 3 4 5
2 4 5 8 10
3 5 7 9 11
1 3 5 7 9
```

Output:

5

Constraints:

- $1 \leq \text{mat.length}, \text{mat}[i].\text{length} \leq 500$
- $1 \leq \text{mat}[i][j] \leq 10^4$
- `mat[i]` is sorted in strictly increasing order.

Answer: (penalty regime: 0 %)

```
1 import sys
2 def s(m):
3     if not m or not m[0]:
4         return -1
5     r=len(m)
6     c=len(m[0])
7     iy=[0]*r
8     while True:
9         cu=[m[i][iy[i]]for i in range(r)]
10        if all(x==cu[0] for x in cu):
11            return cu[0]
12        ma=max(cu)
13        for i in range(r):
14            while iy[i]<c and m[i][iy[i]]<ma:
15                iy[i]+=1
16            if iy[i]==c:
17                return -1
18 def main():
19     da=sys.stdin.read().strip().split()
20     if not da:
21         return
22     it=iter(da)
23     n=int(next(it))
24     mi=int(next(it))
25     m=[[int(next(it)) for _ in range(mi)] for _ in range(n)]
26     print(s(m))
27 if __name__ == "__main__":
28     main()
```

	Input	Expected	Got	
✓	4 5	5	5	✓
	1 2 3 4 5			
	2 4 5 8 10			
	3 5 7 9 11			
	1 3 5 7 9			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 6 | Correct Mark 1.00 out of 1.00

Program to print all the distinct elements in an array. Distinct elements are nothing but the unique (non-duplicate) elements present in the given array.

Input Format:

First line take an Integer input from stdin which is array length n.

Second line take n Integers which is inputs of array.

Output Format:

Print the Distinct Elements in Array in single line which is space Separated

Example Input:

5

1

2

2

3

4

Output:

1 2 3 4

Example Input:

6

1

1

2

2

3

3

Output:

1 2 3

For example:

Input	Result
5 1 2 2 3 4	1 2 3 4
6 1 1 2 2 3 3	1 2 3

Answer: (penalty regime: 0 %)

1 | n=int(input())

```

2 | e=[]
3 | while len(e)<n:
4 |     e.extend(input().split())
5 |     de=list(dict.fromkeys(e))
6 | print(*de)

```

	Input	Expected	Got	
✓	5	1 2 3 4	1 2 3 4	✓
	1			
	2			
	2			
	3			
	4			
✓	6	1 2 3	1 2 3	✓
	1			
	1			
	2			
	2			
	3			
	3			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 7 | Correct Mark 1.00 out of 1.00

An array is monotonic if it is either **monotone increasing** or **monotone decreasing**.

An array A is monotone increasing if for all $i \leq j$, $A[i] \leq A[j]$. An array A is monotone decreasing if for all $i \leq j$, $A[i] \geq A[j]$.

Write a program if n array is monotonic or not. Print "True" if is monotonic or "False" if it is not. Array can be monotone increasing or decreasing.

Input Format:

First line n-get number of elements

Next n Lines is the array of elements

Output Format:

True ,if array is monotone increasing or decreasing.

otherwise False is printed

Sample Input1

4

5

6

7

8

Sample Output1

True

Sample Input2

4

6

5

4

3

Sample Output2

True

Sample Input 3

4

6

7

8

7

Sample Output3

False

For example:

Input	Result
4	True
6	
5	
4	
3	

Answer: (penalty regime: 0 %)

```
1 n=int(input())
2
```

```

2 d=[]
3 for _ in range(n):
4     a.append(int(input()))
5     inc=True
6     d=True
7 for i in range(1,n):
8     if a[i]<a[i-1]:
9         inc=False
10    if a[i]>a[i-1]:
11        d=False
12 if inc or d:
13     print("True")
14 else:
15     print("False")

```

	Input	Expected	Got	
✓	4 6 5 4 3	True	True	✓
✓	4 3 5 7 4	False	False	✓
✓	4 1 6 9 2	False	False	✓
✓	4 9 6 4 2	True	True	✓
✓	3 2 1 4	False	False	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 8 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that $A[i] - A[j] = k$, $i \neq j$.

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Example

Input

1

3

1

3

5

4

Output:

1

Input

1

3

1

3

5

99

Output

0

For example:

Input	Result
1 3 1 3 5 4	1
1 3 1 3 5 99	0

Answer: (penalty regime: 0 %)

```
1 t=int(input())
2 for _ in range(t):
```

```

3 | n=int(input())
4 | a=[]
5 | for _ in range(n):
6 |     a.append(int(input()))
7 | k=int(input())
8 | f=0
9 | for i in range(n):
10 |     for j in range(n):
11 |         if i!=j and a[i]-a[j]==k:
12 |             f=1
13 |             break
14 |     if f==1:
15 |         break
16 | print(f)

```

	Input	Expected	Got	
✓	1	1	1	✓
	3			
	1			
	3			
	5			
	4			
✓	1	0	0	✓
	3			
	1			
	3			
	5			
	99			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 9 | Correct Mark 1.00 out of 1.00

The program must accept **N** integers and an integer **K** as the input. The program must print every K integers in descending order as the output.

-

Note: If **N % K != 0**, then sort the final N%K integers in descending order.

Boundary Condition(s):

$1 \leq N \leq 10^4$

$-99999 \leq \text{Array Element Value} \leq 99999$

Input Format:

The first line contains the values of N and K separated by a space.

The second line contains N integers separated by space(s).

Output Format:

The first line contains N integers.

Example Input/Output 1:

Input:

```
7 3
48 541 23 68 13 41 6
```

Output:

```
541 48 23 68 41 13 6
```

Explanation:

The first three integers are 48 541 23, after sorting in descending order the integers are **541 48 23**.

The second three integers are 68 13 41, after sorting in descending order the integers are **68 41 13**.

The last integer is **6**.

The integers are **541 48 23 68 41 13 6**

Hence the output is **541 48 23 68 41 13 6**.

Answer: (penalty regime: 0 %)

```
1 import sys
2 def s():
3     id=sys.stdin.read().split()
4     if not id:
5         return
6     n=int(id[0])
7     k=int(id[1])
8     num=list(map(int,id[2:]))
9     r=[]
10    for i in range(0,n,k):
11        c=num[i:i+k]
12        c.sort(reverse=True)
```

```
13 |         r.extend(c)
14 |         print(*r)
15 | if __name__=="__main__":
16 |     s()
```

	Input	Expected	Got	
✓	7 3 48 541 23 68 13 41 6	541 48 23 68 41 13 6	541 48 23 68 41 13 6	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 10 | Correct Mark 1.00 out of 1.00

Determine the factors of a number (i.e., all positive integer values that evenly divide into a number) and then return the p^{th} element of the list, sorted ascending. If there is no p^{th} element, return 0.

Example

$n = 20$

$p = 3$

The factors of 20 in ascending order are {1, 2, 4, 5, 10, 20}. Using 1-based indexing, if $p = 3$, then 4 is returned. If $p > 6$, 0 would be returned.

Constraints

$1 \leq n \leq 10^{15}$

$1 \leq p \leq 10^9$

The first line contains an integer n , the number to factor.

The second line contains an integer p , the 1-based index of the factor to return.

Sample Case 0**Sample Input 0**

10

3

Sample Output 0

5

Explanation 0

Factoring $n = 10$ results in {1, 2, 5, 10}. Return the $p = 3^{\text{rd}}$ factor, 5, as the answer.

Sample Case 1**Sample Input 1**

10

5

Sample Output 1

0

Explanation 1

Factoring $n = 10$ results in {1, 2, 5, 10}. There are only 4 factors and $p = 5$, therefore 0 is returned as the answer.

Sample Case 2**Sample Input 2**

1

1

Sample Output 2

1

Explanation 2

Factoring $n = 1$ results in {1}. The $p = 1^{\text{st}}$ factor of 1 is returned as the answer.

For example:

Input	Result
10 3	5
10 5	0

Input	Result
1	1
1	

Answer: (penalty regime: 0 %)

```

1 n=int(input())
2 p=int(input())
3 f=[]
4 for i in range(1,n+1):
5     if n%i==0:
6         f.append(i)
7 if p<=len(f):
8     print(f[p-1])
9 else:
10    print(0)

```

	Input	Expected	Got	
✓	10 3	5	5	✓
✓	10 5	0	0	✓
✓	1 1	1	1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.