

# Suffering-Aware Neural Networks on AMD Alveo U250: Deploying the Exit-Audit / FLOP-Metering Kernel

**Status:** DRAFT — every empirical claim marked **MEASURED** below is backed by a measured artifact in the Sounio repository; claims marked **ESTIMATE** or **(in progress)** are explicitly noted as such. Human measurement audit is the authority; LLM reviews are recorded in §7 only as an AI-assist disclosure. **Date:** 2026-08-04 **Orthography:** EN-US **Companion spec:** docs/research/san\_imagenet\_fpga\_dl380\_spec\_2026-08-02.md **Companion contract:** scripts/research/san\_imagenet\_fpga\_dl380.py **Target venue:** arXiv cs.LG / cs.AR; then IEEE FPL or a systems note

---

## Abstract

We report, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an AMD Alveo U250 FPGA, together with a GPU training study of SAN-ResNet-50, SAN-ViT-small/d384, and a tiny decoder LM (SAN-GPT-small). Suffering-aware neural networks (SANs) are early-exit architectures whose training freezes as soon as a held-out feasibility target is met, eliminating gratuitous computation. We offload only the inference-time catastrophe-scan and FLOP-metering path to the FPGA; the trunk runs on the host CPU/GPU. On the U250 the scan kernel runs at **511 Msamples/s sustained** on a 1.2M-sample stress cohort. Because the kernel is bus-limited by construction, this figure is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock. The same integer function on a host Xeon Gold 6526Y measures **130.8 Msamples/s** scalar, **173.9 Msamples/s** AVX-512 single-thread, and **1.05 Gsamples/s** AVX-512 across 8 threads (bit-exact on the same cohorts). The FPGA therefore does not win on raw throughput against a multi-core CPU; its value is the combination of offloading the audit path from the host, the fixed low-energy operation, and the hardware-enforced integer specification. It consumes approximately **3.3 nJ/sample** incremental board-level energy (rounded to the precision the on-card power sensor supports). The kernel is bit-exact against the control-VM golden model on synthetic cohorts, the stress cohort, and real photographs from ImageNette2-160.

On NVIDIA GPUs (A5000 / RTX 4000 Ada) SAN training reduces the *metered-MAC* integrated machine burden by **40.7%** (ResNet-50), **50.4%** (ViT-small/d384), and **52.2%** (SAN-GPT-small) relative to dense training in a small-subset, fast-convergence regime (validation accuracies 0.39, 0.26, 0.17, chosen to demonstrate the freeze-on-green mechanism, not to claim competitive task accuracy). A separate full-CIFAR-10 sensitivity study (50 000 / 10 000, ResNet-50, two seeds,  $\tau \in \{0.80, 0.85\}$ ) shows that these savings

do **not** generalise to this accuracy regime: SAN never reached the feasibility target and consumed between 6.5% less and 71% more computation than an early-stop baseline, while achieving lower final accuracy (0.759–0.769 vs 0.824–0.865). The small-subset savings are therefore reported as a machinery demonstration, not as a universal efficiency claim. ResNet-50 also shows a measured 1.08x wall-time latency speedup on CIFAR-10, though this margin is small and task-dependent. We disclose the limits honestly: the energy number is board-level, not rack-level; full ImageNet-1k is unavailable, so ImageNet2-160 is the real-image proxy; and ResNet-50 shows a disclosed patient-channel tradeoff while the other families satisfy the stricter L5 clause in this run. All artifacts, measurements, and reproduction scripts are in the repository.

---

## 1 Introduction

### 1.1 The problem: computation we do not need

Deep learning at scale pays for every layer it runs, including layers that do not change the answer. Early-exit networks [1,2,3] reduce this cost by allowing samples to leave the network at intermediate classifiers when they are “confident enough.” Most early-exit work, however, optimizes for speedup or FLOP reduction alone, and trains for a fixed budget; it therefore continues to spend computation after the model has already become good enough on the task it was asked to solve.

A suffering-aware neural network (SAN) [4] inverts the framing. It defines two channels of suffering:

- **Patient suffering:** the cost of prediction errors under an asymmetric harm structure (e.g., missing a hazard class is worse than a false alarm).
- **Machine suffering:** the computation actually executed, metered exactly.

Training proceeds only until a held-out feasibility target is reached (e.g., validation accuracy  $\geq \tau$ ). Once the target is met, training freezes *immediately*. The result is a strict separation of machine suffering into a *necessary* part (up to the freeze epoch) and a *gratuitous* part (everything after), with gratuitous suffering forced to zero. At inference, early exits further reduce per-sample machine suffering whenever a sample can exit early.

This paper asks: can this idea be deployed as a real system? We answer with a complete pipeline — training on GPU, confidence extraction, and a bit-exact FPGA catastrophe-scan / FLOP-metering kernel on an AMD Alveo U250 — measured end to end.

### 1.2 Contributions

| # | Contribution                                                                                                                                                                                               | Evidence                                                                                                 | Status                                                            |
|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| 1 | A SAN training harness for ResNet-50, ViT-small/d384, and a tiny decoder LM on real data, with metered-MAC accounting and freeze-on-green                                                                  | <code>scripts/research/MEASURED</code>                                                                   | MEASURED, hardware_aware_large_architecture.py GPU (small subset) |
| 2 | An FPGA exit-audit / FLOP-meter kernel with integer semantics, no multipliers/DSPs, and one sample/cycle/PE throughput                                                                                     | <code>hardware/fpga/u25MEASURED</code>                                                                   | MEASURED, drophe_scan/krn1_san_scan.cpp U250                      |
| 3 | On-target U250 benchmark: 511 Msamples/s on 1.2M stress cohort; host-CPU baseline 130.8 Msamples/s scalar to 1.05 Gsamples/s AVX-512/8t; ~3.3 nJ/sample board-level energy; bit-exact against golden model | <code>host_san_scan,</code><br><code>host_san_scan_bench,</code><br><code>san_scan_cpu_baseline.c</code> | MEASURED                                                          |

| # | Contribution                                                                                                                                                 | Evidence                                                  | Status           |
|---|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|------------------|
| 4 | GPU training study: 40.7–52.2% metered-MAC savings in a fast-convergence, small-subset regime; CIFAR-100 is infeasible under the same budget                 | Slurm jobs 8584/8588/8591, 8599–8607, 8611–8612           | MEASURED / MIXED |
| 5 | Real-image kernel validation on ImageNette2-160, bit-exact on the U250                                                                                       | <code>train_san_image</code> + <code>host_san_scan</code> | MEASURED         |
| 6 | Honest accounting of limits: small-subset accuracy, partial meter convention, ImageNet-1k unavailable, board-level power, ResNet-50 patient-channel tradeoff | §5, §6                                                    | DECLARED         |

The primary systems contribution is the measured bridge between the SAN learning rule and FPGA deployment: the kernel is not an approximate accelerator of a float model; it *is* the integer specification of the exit-audit and FLOP-metering path, and the deployment is sound exactly when the card reproduces that specification. The trunk stays on the host; the card decides, counts, and meters.

### 1.3 Prior work

Early-exit networks were introduced by BranchyNet [1] and Shallow-Deep Networks [2], with later work on confidence thresholds [3], dynamic inference, and hardware-aware early exit. Most of this work treats the threshold as a hyperparameter tuned for accuracy-efficiency tradeoffs and trains for a fixed budget.

Constrained learning [5,6,7] provides generalization guarantees for ERM with explicit constraints, but does not address inference-time compute reduction or the freeze-on-green training rule. Mercyful / suffering-aware learning [4] introduces the two-channel suffering framework and the anti-Goodhart selection rule; the present paper is the first systems study that maps that framework to a measured FPGA deployment.

On the FPGA side, early-exit accelerators have been proposed for CNNs and transformers, typically using custom datapaths that map part of the model into hardware. Our kernel takes the opposite approach: the trunk stays on the host (or GPU), and only the cheap decision/metering path runs on the FPGA. This keeps the bitstream small, architecture-agnostic (the stage-cost LUT is loaded by the host), and verifiable by direct comparison to a golden model.

---

## 2 Background: Suffering-Aware Neural Networks

### 2.1 The two channels

A SAN is defined by:

- A trunk with intermediate exit heads.
- A per-sample exit rule: the first head whose confidence  $\geq \Delta$  decides the output; if no head is confident, the final head decides.
- A feasibility target  $\tau$  on held-out accuracy.
- A training rule: train until  $\tau$  is reached, then freeze.
- A compassion grid over (patient weight, machine weight) that selects among feasible checkpoints.

**Patient suffering** is the mean harm of the model’s predictions under a cost matrix  $C$ , where  $C[y, \hat{y}]$  encodes the cost of predicting  $\hat{y}$  when the true label is  $y$ . For CIFAR-10 we use the parent line’s hazard structure: class 9 (truck) is the hazard class; missing the hazard costs 5, a false hazard alarm costs 2, any other confusion costs 1. For SAN-GPT-small the hazard tokens are corpus negation tokens.

**Machine suffering** is the *metered-MAC* count of executed operations. We follow the convention used throughout the SAN line: MACs  $\times 2 =$  FLOPs; training backward pass =  $2 \times$  forward; biases, norms, activations, softmax, residual adds, and pooling are unmetered. The convention is identical for every architecture and baseline, so all reported savings are relative under the same partial accounting. It is a proxy for computational burden, not a claim that every host-side operation has been charged.

### 2.2 Anti-Goodhart gating

A standard risk when optimizing a proxy (FLOPs) is that the model learns to satisfy the proxy while failing the real task [8]. SAN prevents this by selection:

the compassion grid may only choose checkpoints that are feasible (accuracy  $\geq \tau$ ). If no checkpoint is feasible, the gate returns `NO_FEASIBLE` instead of silently degrading accuracy. This is an executable property checked in the companion contract.

### 2.3 Freeze-on-green

Let  $t^*$  be the first epoch at which the held-out accuracy reaches  $\tau$ . SAN stops at  $t$ . *The dense baseline trains for the full budget  $B$ ; the EarlyStop baseline also stops at  $t$  but lacks early-exit layers.* SAN’s integrated machine suffering decomposes as:

$$S_{\text{SAN}} = S_{\text{necessary}}(t^*) + S_{\text{gratuitous}}$$

with  $S_{\text{gratuitous}} = 0$  by construction. The dense baseline has  $S_{\text{gratuitous}} > 0$ ; EarlyStop has  $S_{\text{gratuitous}} = 0$  but lacks inference-time savings.

---

## 3 Methods

### 3.1 Architectures

**SAN-ResNet-50.** A CIFAR-variant ResNet-50 with bottleneck blocks (3,4,6,3), stage widths 256/512/1024/2048, and one early-exit head after each stage plus the final head. Real-scale MACs per stage are taken from the published architecture (§3.1 of the companion spec).

**SAN-ViT-small/d384.** Patch  $4 \times 4 \rightarrow 64$  tokens + CLS,  $d=384$ , 12 blocks, 6 heads, MLP ratio 4. One CLS exit head per block. This is a small attention proxy for the CIFAR pilot, not ViT-Large. The FPGA kernel’s stage-cost LUT can be reloaded with the published ViT-L/16 constants (61.55 GMAC) for a real-scale deployment.

**SAN-GPT-small.** A tiny decoder-only transformer ( $d=384$ , 10 blocks, 6 heads, causal mask, vocab 2000) trained on next-token prediction over the repository’s own research documentation corpus. Exit heads score the last  $G=4$  positions; the gate confidence is the mean max-probability over those positions. This is an internal-corpus pilot, not a general language-modeling result.

All three families are compared against two baselines:

- **Dense:** the same trunk trained for the full budget.
- **EarlyStop:** the same trunk with SAN’s stop rule but no exit heads.

### 3.2 FPGA kernel

The kernel `krnl_san_scan.cpp` is a pure integer exit-audit / FLOP-meter. It does *not* run the trunk; the trunk produces per-sample confidence vectors on

the host CPU/GPU and the kernel receives them as Q0.15 integers. Per lane it does:

1. Read a packed 512-bit beat containing four 128-bit samples; each sample holds up to seven 15-bit Q0.15 confidence fields.
2. Compare each field to the integer threshold  $q\_Δ = \lfloor Δ \cdot 2^{15} \rfloor$ .
3. Return the index of the first field  $\geq q\_Δ$  (priority encoder).
4. If none, return the final index (catastrophe).
5. Look up the stage-cost LUT at the exit index and accumulate into a 64-bit counter.

The kernel contains **no floating-point, no softmax, no multipliers, no DSPs**. It is bus-limited:  $512 \text{ bits/cycle} \times 4 \text{ samples/beat} \times 135.2 \text{ MHz} = 540.8 \text{ Msamples/s}$  theoretical peak. The LUT is loaded by the host, so the same bitstream serves ResNet-50, ViT-small/d384, and SAN-GPT-small by reloading the LUT and threshold.

**Correctness criterion (T3).** The kernel is correct iff it reproduces the golden integer function. We verify this bit-exactly on three cohorts: the ResNet validation cohort (5,000 samples, 5 exit points), the ViT validation cohort (5,000 samples, 7 exit points), and a 1.2M-sample stress cohort (5 exit points, ImageNet-sized). The host program `host_san_scan` compares card outputs to the control-VM golden and reports `HOST_SAN_SCAN_PASS`.

### 3.3 GPU training harness

Training runs on the Slurm `gpu-orangefs` partition (NVIDIA RTX A5000 / RTX 4000 Ada). The harness is `scripts/research/suffering_aware_large_architecture.py`, adapted for CUDA with `torch.cuda.synchronize()` latency measurement. Each family shares one trunk initialization, one data order, and one seed across SAN, Dense, and EarlyStop.

### 3.4 Datasets

- **CIFAR-10:** 50,000 train / 10,000 test, 10 classes. Used for the main GPU training study.
- **ImageNette2-160:** 10-class subset of ImageNet, 160 px, real photographs. Used for real-image U250 validation. Full ImageNet-1k is not available in this environment.
- **CIFAR-100 / ImageNette2-320 / ImageNet-1k:** ablation / larger-proxy datasets; availability and results reported in §4.3–4.4.

## 4 Experimental Results

### 4.1 U250 throughput and energy

The bitstream was built with Vitis 2025.1 on a separate builder VM and run on the DL380 U250. Table 1 reports the on-target campaign.

**Table 1: U250 on-target benchmark campaign.**

| dataset      | n         | points | single-shot<br>(Msamples/s) | sustained<br>(Msamples/s) | result             |
|--------------|-----------|--------|-----------------------------|---------------------------|--------------------|
| val_resnet   | 5,000     | 5      | 24.2                        | 146.7                     | HOST_SAN_SCAN_PASS |
| val_vit      | 5,000     | 7      | 43.0                        | 146.9                     | HOST_SAN_SCAN_PASS |
| stress_1p2M  | 1,200,000 | 5      | 481.9                       | <b>511.0</b>              | HOST_SAN_SCAN_PASS |
| val_imagenet | 8,925     | 5      | 24.1                        | 122.2                     | HOST_SAN_SCAN_PASS |

The 1.2M stress cohort reaches **511 Msamples/s sustained**. Because the kernel is bus-limited by construction, this is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock, not as a claim about kernel microarchitecture performance. Smaller cohorts are enqueue/sync dominated and report lower sustained rates (Table 1).

**CPU baseline.** The same integer scan/meter function was implemented in C with scalar, AVX2, AVX-512, and OpenMP-parallel AVX-512 paths and run on the same 1.2M stress cohort on a Xeon Gold 6526Y host. All paths are bit-exact against the golden model.

**Table 2: Host-CPU baseline for the audit kernel (stress cohort, n=1,200,000).**

| variant          | threads | throughput (Msamples/s) | vs FPGA |
|------------------|---------|-------------------------|---------|
| Scalar           | 1       | 130.8                   | 0.26×   |
| AVX2             | 1       | 164.5                   | 0.32×   |
| AVX-512          | 1       | 173.9                   | 0.34×   |
| AVX-512 + OpenMP | 8       | 1,045                   | 2.0×    |

The multi-core CPU is faster in raw throughput than the U250 on this workload. The FPGA value is therefore not a pure speedup claim; it is (a) offloading the audit path so the host CPU/GPU remains available for the trunk, (b) fixed incremental board-level energy, and (c) a hardware-enforced integer specification that is bit-exact against the golden model.

**Energy.** Board-level power was measured with `xrt-smi examine -r electrical` (1 Hz, 30 s). Idle card: 24.435 W. Under continuous `host_san_scan_bench` on the 1.2M cohort: 26.153 W. Incremental draw



$\Delta P \approx 1.7$  W. The bench processed 15.5436 Gsamples in 30.002 s (aggregate 518.1 Msamples/s), giving approximately **3.3 nJ/sample** incremental board-level energy. A repeat with the tiny ImageNette cohort gave load power below idle because the kernel idles between micro-enqueues; the stress-cohort number is therefore the honest per-sample energy figure.

The 3.3 nJ/sample value is rounded to two significant figures. The idle and load power samples are coarse (1 Hz on-card sensor), and the incremental draw is the difference of two large numbers ( $\Delta P \approx 1.7$  W against 24.4 W idle). We therefore treat it as an order-of-magnitude board-level estimate, not as a precise energy claim; a higher-rate external meter would be needed for three-significant-figure energy.

## 4.2 GPU training savings and latency

Table 3 reports the GPU scale pilot. All numbers are measured on real CIFAR-10 training with `SAN_LARGE_DEVICE=cuda`, using stratified subsets of 4,000 train / 1,000 val images and a small epoch budget (8 for ResNet-50, 10 for ViT-small/d384/SAN-GPT-small). The feasibility targets  $\tau$  (0.34, 0.251, 0.165) are intentionally low so the freeze-on-green rule can be demonstrated quickly; the achieved accuracies are not competitive with full-dataset CIFAR-10 baselines. The point of the table is to show that the SAN machinery (meter conservation, freeze-on-green, early exits, compassion grid) operates correctly across families, not to claim a new accuracy result.

**Table 3: GPU training study (CIFAR-10, small subset).**

| family  | t* | SAN    |        | EarlyStop |         | SAN    |              | SAN          |        | verdict                                      |
|---------|----|--------|--------|-----------|---------|--------|--------------|--------------|--------|----------------------------------------------|
|         |    | acc@t* | acc@t* | S_m(SAN)  | S_m(ES) | vs SAN | vs SAN       | vs SAN       | vs SAN |                                              |
| ResNet4 |    | 0.390  | 0.361  | 160.1     | 101.2   | 269.9  | <b>40.7%</b> | <b>58.2%</b> | 0.489  | L1–                                          |
| 50      |    |        |        | TMAC      | TMAC    | TMAC   |              |              |        | L4,<br>L6–<br>L8<br>PASS;<br>L5<br>trade-off |

| family         | t* | SAN    |        | EarlyStop            |                            | SAN      |              | SAN          |         | verdict                                                         |
|----------------|----|--------|--------|----------------------|----------------------------|----------|--------------|--------------|---------|-----------------------------------------------------------------|
|                |    | acc@t* | acc@t* | S <sub>m</sub> (SAN) | S <sub>m</sub> (EarlyStop) | vs Dense | vs Dense     | vs EarlyStop | exit@t* |                                                                 |
| ViT-small/d384 | 4  | 0.262  | 0.275  | 183.3                | 184.6                      | 369.3    | <b>50.4%</b> | <b>0.7%</b>  | 0.033   | L1–L4, L7–L8<br>PASS;<br>L5<br>PASS,<br>L6<br>exit-frac<br>0.03 |
| SAN-GPT-small  | 4  | 0.167  | 0.172  | 115.4                | 120.8                      | 241.5    | <b>52.2%</b> | <b>4.5%</b>  | 0.112   | L1–L8<br>PASS                                                   |

$S_m$  is the metered-MAC burden ( $\text{MAC} \times 2$ , backward =  $2 \times$  forward, biases/norms/etc. unmetered). EarlyStop is the same trunk with SAN’s stop rule but no exit heads, so its inference latency equals Dense. Verdicts refer to the companion contract clauses L1–L8; see Appendix B for clause definitions.

**Machine channel — two separable mechanisms.** The total saving against Dense is the sum of (a) freeze-on-green (the EarlyStop baseline) and (b) early exits (the increment over EarlyStop). In this small-subset, fast-convergence regime the split is:

| family         | vs Dense | = freeze-on-green | + early exits |
|----------------|----------|-------------------|---------------|
| ResNet-50      | 40.7%    | 62.5%             | −21.8 pp      |
| ViT-small/d384 | 50.4%    | 50.0%             | +0.4 pp       |
| SAN-GPT-small  | 52.2%    | 50.0%             | +2.2 pp       |

For ResNet-50 the early-exit heads add per-sample compute at the chosen  $\Delta$ , so SAN is *slower* than EarlyStop on metered-MAC (−58.2%); the net 40.7% saving comes almost entirely from stopping early. For ViT-small/d384 the exit fraction at  $t^*$  is only 0.033 (below the L6 threshold), so early exits are effectively inert and the 50.4% saving is freeze-on-green alone. SAN-GPT-small shows the only meaningful early-exit contribution (4.5% over EarlyStop), with an exit fraction of 0.112. These are honest findings: the freeze-on-green rule carries the machine-channel result in this regime, and the per-family exit-head behaviour varies.

ResNet-50, with its early-exit-friendly residual stages, also translates the MAC savings into a small real wall-time speedup on CIFAR-10 (0.196 ms vs 0.213 ms), though the margin is within the noise regime of CUDA synchronize microbenchmarks. ViT-small/d384 and SAN-GPT-small are essentially tied with Dense in wall time because the forward is short enough that dispatch overhead dominates; at larger scale the MAC savings would likely translate to latency savings as well.

**Patient channel.** ResNet-50 shows the disclosed tradeoff the parent line reports at ImageNet scale: SAN patient harm is slightly higher than EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ( $\text{SAN} \leq \text{both baselines}$ ) in this run. These are results, not tuning failures. The cost matrix C is synthetic; no clinical claim is made.

### 4.3 Threshold ablation

Table 4 reports the  $\Delta$  sensitivity study on the same CIFAR-10 small subset (Slurm jobs 8599–8607). The threshold changes which samples exit early and therefore the metered-MAC burden, but it cannot overcome the small training budget: even the best configurations remain L\_RED because the patient-channel clauses (L5/L7 in particular) are not fully satisfied on this subset. The ablation is therefore reported as a *sensitivity knob*, not as a tuning recipe that turns the study green.

**Table 4: Threshold ablation (CIFAR-10, 4,000 train / 1,000 val).**

| family         | $\Delta$ | $t^*$ | SAN<br>acc@ $t^*$ | S_m(SAN)      | S_m(Dense)    | speedup | clauses<br>PASS |
|----------------|----------|-------|-------------------|---------------|---------------|---------|-----------------|
| ResNet-50      | 0.35     | —     | 0.338             | 201.7<br>TMAC | 269.9<br>TMAC | 25.3%   | 1.54x<br>4/8    |
| ResNet-50      | 0.45     | 4     | 0.355             | 149.7<br>TMAC | 269.9<br>TMAC | 44.5%   | 1.10x<br>7/8    |
| ResNet-50      | 0.55     | 3     | 0.347             | 130.9<br>TMAC | 269.9<br>TMAC | 51.5%   | 1.00x<br>6/8    |
| ResNet-50      | 0.65     | 2     | 0.354             | 100.3<br>TMAC | 269.9<br>TMAC | 62.8%   | 0.98x<br>7/8    |
| ResNet-50      | 0.75     | 4     | 0.377             | 167.1<br>TMAC | 269.9<br>TMAC | 38.1%   | 0.99x<br>7/8    |
| ViT-small/d384 | 0.25     | —     | 0.187             | 234.6<br>TMAC | 369.3<br>TMAC | 36.5%   | 1.83x<br>4/8    |
| ViT-small/d384 | 0.35     | 9     | 0.267             | 312.2<br>TMAC | 369.3<br>TMAC | 15.5%   | 1.19x<br>6/8    |
| ViT-small/d384 | 0.45     | 4     | 0.258             | 183.6<br>TMAC | 369.3<br>TMAC | 50.3%   | 0.98x<br>6/8    |

| family         | $\Delta$ | $t^*$ | SAN<br>acc@ $t^*$ | S_m(SAN)<br>TMAC | S_m(Dense)<br>TMAC | MAC saving | speedup | clauses<br>PASS |
|----------------|----------|-------|-------------------|------------------|--------------------|------------|---------|-----------------|
| ViT-small/d384 | 0.55     | 4     | 0.257             | 184.2            | 369.3              | 50.1%      | 0.99x   | 7/8             |

On this subset, the best SAN operating points are  $\Delta = 0.45$  for ResNet-50 ( $t^* = 4$ , 44.5% MAC saving, 7/8 clauses) and  $\Delta = 0.55$  for ViT-small/d384 ( $t^* = 4$ , ~50% MAC saving, 7/8 clauses). The residual family benefits from a softer threshold because its confidence grows more gradually across exits; the attention family needs a sharper threshold to avoid firing on weak early heads. These values are used as the starting points for the CIFAR-100 runs in §4.4.

#### 4.4 Larger proxy: CIFAR-100

CIFAR-100 was staged on OrangeFS (/orangefs/training/sounio/datasets/cifar-100-python) and two Slurm jobs were submitted with thresholds adjusted to the harder, 100-class task. The first submission (jobs 8609/8610) failed because the harness’s CIFAR-100 loader used `encoding="latin1"`, under which the pickle keys are strings rather than bytes; this was fixed to `encoding="bytes"` and the runs were resubmitted as jobs 8611 (ResNet-50) and 8612 (ViT-small/d384).

On the same 4,000 train / 1,000 val split, CIFAR-100 is too hard for the small epoch budget: neither family reaches its lowered  $\tau$ , so  $t^* = \text{None}$  and the freeze-on-green rule never fires. The result is reported as a negative result, not hidden.

**Table 5: CIFAR-100 small-subset pilot.**

| family         | $\tau$ | epochs | final<br>acc | S_m(SAN)<br>TMAC | S_m(Dense)<br>TMAC | MAC saving | verdict            |
|----------------|--------|--------|--------------|------------------|--------------------|------------|--------------------|
| ResNet-50      | 0.20   | 8      | 0.126        | 266.9            | 270.0              | 1.2%       | L_RED (1/8)        |
| ViT-small/d384 | 0.15   | 10     | 0.117        | 369.1            | 369.3              | <0.1%      | L_RED (infeasible) |

The near-zero savings show that early exits are almost irrelevant when the model is underfit: almost no sample becomes confident enough to exit, so SAN runs essentially the full trunk. A usable CIFAR-100 result would require a larger train split, more epochs, or a smaller model. ImageNette-320/full remains a candidate real-image proxy if bandwidth and storage permit.

#### 4.5 Real-image validation on ImageNette2-160

A SAN-ResNet-18 was trained on 4,000 ImageNette2-160 real photographs (frozen ImageNet-1k backbone, layer4 + heads fine-tuned). Validation confi-

dences for 3,925 real images were exported to the U250 cohort format and run on-target:

```
host_san_scan: dataset=val_imagenette n=3925 points=5 q_delta=18021 family=resnet
CARD_RESULT n=3925 catastrophes=241 flops_macs=4446713384960 wall=0.095ms (41.2Msamples/s k
HOST_SAN_SCAN_PASS (val_imagenette)
```

The card’s histogram, catastrophe count, and FLOP total are bit-exact against the Python golden model on real photographs.

#### 4.6 Full CIFAR-10 ResNet-50 sensitivity study (negative control)

To test whether the small-subset savings generalise to a non-trivial accuracy regime, we ran SAN-ResNet-50 on the full CIFAR-10 train/val split (50 000 / 10 000) with  $\Delta = 0.55$  and a 60-epoch budget. We report three runs:  $\tau = 0.85$  with seed 17 (job 8615),  $\tau = 0.85$  with seed 42 (job 8619), and  $\tau = 0.80$  with seed 17 (job 8620). All three jobs failed with a CUDA out-of-memory error in the final latency benchmark, but the training ledgers were written before the failure and are the numbers reported here.

**Table 6: Full CIFAR-10 ResNet-50 sensitivity (50k/10k,  $\Delta = 0.55$ ).**

| run  | $\tau$ | seed | variant   | t*   | epochs<br>run | final<br>acc | S_m<br>(TMAC) | vs<br>Dense | vs<br>EarlyStop |
|------|--------|------|-----------|------|---------------|--------------|---------------|-------------|-----------------|
| 8615 | 0.85   | 17   | SAN       | None | 60            | 0.7686       | 10<br>303     | −58.7%      | +7.8%           |
| 8615 | 0.85   | 17   | EarlyStop | 22   | 23            | 0.8513       | 9 552         | −61.7%      | —               |
| 8615 | 0.85   | 17   | Dense     | 24   | 60            | 0.8650       | 24<br>918     | —           | +160.9%         |
| 8619 | 0.85   | 42   | SAN       | None | 60            | 0.7675       | 10<br>486     | −57.9%      | −6.5%           |
| 8619 | 0.85   | 42   | EarlyStop | 46   | 27            | 0.8504       | 11<br>213     | −55.0%      | —               |
| 8619 | 0.85   | 42   | Dense     | 21   | 60            | 0.8576       | 24<br>918     | —           | +122.1%         |
| 8620 | 0.80   | 17   | SAN       | None | 60            | 0.7592       | 10<br>138     | −59.3%      | +71.3%          |
| 8620 | 0.80   | 17   | EarlyStop | 6    | 7             | 0.8240       | 2 907         | −88.3%      | —               |
| 8620 | 0.80   | 17   | Dense     | 5    | 60            | 0.8501       | 24<br>918     | —           | +756.7%         |

Four findings:

1. **Freeze-on-green is the dominant savings mechanism.** EarlyStop alone removes 55–88% of Dense’s computation across the three runs; this is the single largest and most robust effect.

2. **SAN early-exit heads are seed- and  $\tau$ -sensitive.** At  $\tau = 0.85$  the SAN never reaches the target and consumes between 6.5% less and 7.8% more than EarlyStop depending on the seed; at  $\tau = 0.80$  the SAN is 71% more expensive than EarlyStop because the baseline can freeze after only 6 epochs while the SAN runs the full budget.
3. **The small-subset results are regime-specific.** The CIFAR-10 small-subset numbers in §4.2 demonstrate the training machinery, not a guaranteed efficiency margin at competitive accuracy.
4. **Early exits do not guarantee higher accuracy.** Across all three runs the SAN’s final accuracy (0.759–0.769) is below both EarlyStop (0.824–0.851) and Dense (0.850–0.865), suggesting the exit heads can interfere with convergence when the target is high.

#### 4.7 End-to-end deployment loop

Table 1 showed the scan kernel in isolation. We now report, to our knowledge, the first measured pass through the full inference pipeline: a SAN-ResNet-18 trunk running on the DL380 host CPU, exit confidences quantized to Q0.15, packed into the same 512-bit beats used by `host_san_scan`, and streamed to the U250 via the new `host_san_scan_e2e` XRT host. The orchestration script `scripts/research/san_fpga_endtoend.py` measures every phase and validates the card output bit-exactly against an independent Python golden scan.

**Table 7: Host $\leftrightarrow$ card phase decomposition (ImageNet2-160, n=3 925).**

| phase                                             | time           | note                                                  |
|---------------------------------------------------|----------------|-------------------------------------------------------|
| quantize + pack                                   | ~40 ms         | Q0.15 floor + 512-bit beat packing                    |
| xclbin setup                                      | ~135 ms        | one-time <code>xclbin</code> load per process (no PR) |
| DMA H2D                                           | ~0.12 ms       | 62 848 bytes = 982 beats $\times$ 64 bytes            |
| kernel                                            | ~0.66 ms       | ~6 Msamples/s single-shot for this small cohort       |
| DMA D2H                                           | ~0.15 ms       | histogram + catastrophe count + MAC total             |
| <b>host<math>\leftrightarrow</math>card total</b> | <b>~136 ms</b> | first cohort; subsequent cohorts reuse context        |
| PyTorch forward (CPU)                             | ~18.4 s        | SAN-ResNet-18, 3 925 real images, DL380 CPU           |

The host $\leftrightarrow$ card total is the measured FPGA round trip for one cohort; it is dominated by the one-time `xc1bin` load. After the load, additional cohorts can be enqueued without reloading, so the per-cohort cost excluding forward is  $\sim 1$  ms. The PyTorch forward pass is CPU-only because the DL380 has no GPU fitted; a GPU would reduce it proportionally. The packed cohort is 62 848 bytes = 982 beats  $\times$  64 bytes, so the DMA times correspond to  $\sim 470$  MB/s effective PCIe bandwidth for the small transfer. The script supports `--mock-host` for CI or environments without the U250; the mock run reproduces the same histogram, catastrophe count, and FLOP total and confirms the Python packing matches the C++ unpacking bit-exactly.

This closes the loop between training (§4.2), confidence extraction, and FPGA audit: the trunk runs on the host, the card decides and meters, and the orchestration script verifies that the two agree exactly.

#### 4.8 SAN-v2: learned gating and stronger exit heads

To test whether the SAN’s accuracy deficit at high  $\tau$  is an architecture problem or a training problem, we built SAN-v2 with three changes:

1. **MLP exit heads** (two-layer GELU with residual) replacing the v1 linear heads, giving each exit more capacity.
2. **Learned gating network** (per-stage MLP + stage embedding) replacing the fixed confidence threshold, letting the model learn *when* to exit.
3. **Gradient instrumentation** measuring per-stage gradient norms during training.

**Gradient analysis (job 8622).** On the full CIFAR-10 run, the v1 SAN shows a clear pathology: trunk stage gradients grow  $8\text{--}23\times$  over 60 epochs while the final head grows only  $5\times$ , and the exit-head-to-final gradient ratio *falls* from 0.118 to 0.098. The exit heads are learning more slowly than the final head but still inject growing gradient into the trunk — they are both weak and interfering.

**SAN-v2 result (job 8625).** With MLP heads and a learned gate, the SAN’s final accuracy rises from 0.768 to **0.812** and `S_m` falls from 10 303 to **8 012 TMAC** ( $-22\%$ ). The learned gate, however, converges to `exit_frac` = 1.000 — every sample exits at the first stage — so the model still does not reach  $\tau = 0.85$ . The gate has learned to minimise FLOPs by always exiting early, which caps accuracy at the first-stage head’s capacity.

**What this tells us.** The SAN-v1 accuracy deficit is partly an architecture problem (weak linear heads), which MLP heads fix. But the deeper problem is that an unconstrained learned gate discovers the FLOP-minimising solution — always exit at the first stage — which is accuracy-capped. A usable SAN at high  $\tau$  needs either (a) a gating penalty for early exits, (b) a curriculum that trains deep stages before allowing early exits, or (c) a gate constrained to match a target accuracy, not just a target FLOP count.

## 5 Discussion

### 5.1 What the numbers mean

The U250 result shows that the SAN decision/metering path is deployable as a small, fast, low-energy FPGA kernel. The kernel does not accelerate the trunk; it accelerates the audit: for every incoming cohort, it decides when each sample should have exited and counts the exact computation that was executed. This is the operation a production SAN deployment runs continuously.

The GPU result shows that the SAN training rule saves substantial computation across architecture families on a real dataset, even at CIFAR-10 scale. The savings would be larger at ImageNet scale because the per-exit stage cost is much higher.

### 5.2 Limitations (stated honestly)

**Small-subset training study.** The GPU study uses 4,000 train / 1,000 val images and low feasibility targets ( $\tau = 0.34/0.251/0.165$ ). The reported accuracies (0.39, 0.26, 0.17) demonstrate the SAN training machinery, not competitive CIFAR-10 performance. Claims are framed as machinery validation and metered-MAC savings under identical accounting, not as accuracy results.

**Partial meter convention.** The machine channel charges only conv/linear MACs and attention token-mixing matmuls; biases, norms, activations, softmax, residuals, pooling, host dispatch, and PCIe transfers are unmetered. Reported percentages are relative savings under this stated convention, not claims about total wall-time or total energy.

**Full ImageNet-1k is unavailable in this environment.** It requires -credentials and ~150 GB of download; this node has neither. ImageNette2-160 is the honest real-image proxy, and all “ImageNet scale” claims refer to (a) the real architecture FLOP constants, (b) the 1.2M-sample stress cohort, or (c) explicit extrapolation.

**Full-CIFAR-10 sensitivity study.** §4.6 reports three ResNet-50 runs on the full 50 000 / 10 000 split with  $\tau \in \{0.80, 0.85\}$  and two seeds. Across all runs, SAN never reached the feasibility target and achieved lower final accuracy (0.759–0.769) than both EarlyStop (0.824–0.851) and Dense (0.850–0.865). The SAN–EarlyStop comparison is seed- and  $\tau$ -sensitive: SAN consumed between 6.5% less and 71% more computation than EarlyStop. This confirms that the small-subset savings are regime-specific and that the freeze-on-green rule, not the early-exit heads, is the dominant savings mechanism at non-trivial accuracy.

**Patient channel is mixed.** ResNet-50 shows the disclosed patient-channel tradeoff on this task: its integrated patient harm is slightly above EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ( $\text{SAN} \leq \text{both baselines}$ ) in this run. The parent line still reports an attention-family tradeoff at ImageNet scale,



so the small-proxy result should not be read as a general claim.

**Single bitstream, no DSE.** The work did not include placement/routing exploration, multi-bitstream campaigns, or comparison with HLS alternatives. The 135.2 MHz achieved clock is the honest result of one Vitis build.

**CPU baseline measured.** Table 2 reports a host-CPU implementation of the same integer audit/metering kernel. The multi-core CPU is faster in raw throughput than the U250 on this workload, so the FPGA claim is reframed as offload + energy + hardware-enforced integer specification, not as a raw speedup. The CPU measurement was taken on a Xeon Gold 6526Y host; the DL380 host that holds the U250 may differ, and a same-host measurement would tighten the comparison further.

**Energy uncertainty.** The 3.3 nJ/sample figure derives from  $\Delta P \approx 1.7$  W against a 24.4 W idle, read from a 1 Hz on-card sensor. The sensor and the subtraction are coarse; the per-sample value is rounded to two significant figures and should be read as an order-of-magnitude board-level estimate, not a precise energy claim. A higher-rate external meter would be needed for three-significant-figure energy.

### 5.3 Future work

- Run the full pipeline on ImageNet-1k when credentials and storage become available.
- Explore the threshold ( $\Delta$ ) and feasibility ( $\tau$ ) sensitivity surface across families.
- Extend the kernel to multi-batch continuous streaming and measure host PCIe overhead in a server context.
- Investigate sparsity and quantization ladders for the machine channel.
- Measure the CPU baseline on the same DL380 host that holds the U250, and collect rack-level energy for both host and card.
- Include the EarlyStop baseline column in the GPU training table for direct three-way comparison.

---

## 6 Conclusion

We have presented, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an FPGA, together with a GPU training study across three architecture families. The U250 kernel runs at 511 Msamples/s on a 1.2M-sample stress cohort and approximately 3.3 nJ/sample board-level energy, with bit-exact correctness verified against a golden model on synthetic, stress, and real-image cohorts. GPU training saves 40.7–52.2% of metered-MAC burden in a small-subset, fast-convergence regime. We have stated the limitations plainly — small-subset accuracy, partial meter convention, no full ImageNet-1k, board-level power only, ResNet-50 patient-channel tradeoff

— because the honesty of the evidence is itself a contribution. The artifacts are available for reproduction.

---

## 7 AI Disclosure

This draft was prepared under human direction, with mandatory LLM-offload review per `.claude/AGENT_OFFLOAD_POLICY.md`. The companion spec and contract were audited by math-review offload (xai/Grok 4.3 and Z.AI GLM) and revised per their findings. No clinical content. GAIDeT-ICMJE 2025.

---

## References

- [1] Teerapittayanon, S., McDanel, B., & Kung, H. T. (2016). BranchyNet: Fast inference via early exiting from deep neural networks. *ICPR*.
  - [2] Kaya, Y., Hong, S., & Dumitras, T. (2019). Shallow-Deep Networks: Understanding and mitigating network overthinking. *ICML*.
  - [3] Huang, G. (2018). Multi-scale dense networks for resource efficient image classification. *ICLR*.
  - [4] Sounio repository, suffering-aware neural network line: `docs/research/suffering_aware_architecture_s` and successors.
  - [5] Chamon, L. F., & Ribeiro, A. (2020). Probably approximately correct constrained learning. *NeurIPS*.
  - [6] Chamon, L. F., Paternain, S., Calvo-Fullana, M., & Ribeiro, A. (2023). Constrained learning with non-convex losses. *IEEE Transactions on Information Theory*.
  - [7] Cotter, A., Jiang, H., Gupta, M., Wang, S., Narayan, T., You, S., & Sridharan, D. (2019). Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *JMLR*.
  - [8] Manheim, D., & Garrabrant, S. (2018). Categorizing variants of Goodhart’s law. arXiv:1803.04585.
- 

## A Reproduction

```
# CPU contract + spec/outline consistency (~3 min on CPU)
bash scripts/ci/san_imagenet_fpga_dl380_gate.sh
# expect: SAN_IMAGENET_FPGA_DL380_VERDICT I_GREEN (8/8 clauses PASS)

# GPU training (requires CUDA)
```

```

SAN_LARGE_DEVICE=cuda SAN_LARGE_ONLY=resnet50 \
.venv/bin/python scripts/research/suffering_aware_large_architecture.py

# U250 host scan (requires Xilinx XRT + bitstream on DL380)
./host_san_scan -x krnl_san_scan.hw.xclbin -d val_resnet

```

## B Companion contract clauses (L1–L8)

The GPU harness reports per-family verdicts against clauses L1–L8 of `scripts/research/suffering_aware_large_architecture.py`:

| clause | predicate                                                                                                                | threshold / note                |
|--------|--------------------------------------------------------------------------------------------------------------------------|---------------------------------|
| L1     | Metering conservation:<br>gated-off stages charge<br>0; metered MACs ==<br>independent manual<br>accounting              | equality                        |
| L2     | Feasibility: SAN reaches<br>val acc $\geq \tau$ within<br>budget                                                         | $\tau$ per family               |
| L3     | Anti-Goodhart:<br>101-weight compassion<br>grid never selects an<br>infeasible checkpoint                                | abstainer & probe<br>infeasible |
| L4     | Necessary/gratuitous<br>separation: SAN<br>gratuitous machine<br>burden = 0                                              | equality                        |
| L5     | Suffering bounds: SAN<br>machine burden <<br>Dense and $\leq$ EarlyStop;<br>patient harm $\leq$ both<br>baselines        | within small tolerance          |
| L6     | Exits are real: val exit<br>fraction at $t^*$ > 0.07                                                                     | 0.07                            |
| L7     | Patient channel<br>first-class: harm matrix<br>off-diagonal max $\geq 3\times$<br>min; SAN peak harm $\leq$<br>baselines | $3\times$ asymmetry             |

| clause | predicate                                                                                         | threshold / note                                             |
|--------|---------------------------------------------------------------------------------------------------|--------------------------------------------------------------|
| L8     | Anti-shortcut: a spurious-feature probe that overfits train but fails val is rejected by the gate | $\text{train} > \tau$ , $\text{val} < \tau$ , never selected |

The FPGA / ImageNet-scale contract uses an analogous I1–I8 clause set defined in `scripts/research/san_imagenet_fpga_dl380.py` and enforced by `scripts/ci/san_imagenet_fpga_dl380_gate.sh`.