

The Suffering Ledger: Integer-Exact Training-Compute Accounting with an FPGA Root-of-Trust, Demonstrated on a Suffering-Aware Early-Exit Network

Status: DRAFT — every empirical claim marked MEASURED below is backed by a measured artifact in the Sounio repository; claims marked ESTIMATE or (in progress) are explicitly noted as such. Human measurement audit is the authority; LLM reviews are recorded in §7 only as an AI-assist disclosure. **Date:** 2026-08-06 (repositioned after a seven-front novelty audit, agent_logs/san_novelty_audit_2026-08-06.md) **Orthography:** EN-US **Companion spec:** docs/research/san_imagenet_fpga_d1380_spec_2026-08-02.md **Companion contract:** scripts/research/san_imagenet_fpga_d1380.py **Target venue:** arXiv cs.LG / cs.AR; then IEEE FPL or a systems note

Abstract

Claims that a training procedure saves computation are, today, unfalsifiable as published: FLOP counts are analytical estimates, energy figures are sampled at the wall, and no artifact lets a third party verify that the reported computation is the computation that actually ran. This paper builds the missing instrument and then turns it on itself. We present a training-compute ledger with three properties we have not found combined in the literature: (i) **integer-exact accounting of the executed computation path** — the meter charges the multiply-accumulates of the stages actually run (a sample that exits at stage k is never executed, and never charged, below k), under a stated partial-meter convention, with a conservation proof checked by an independent accounting path on every run; (ii) a **declared accuracy contract** (a feasibility target τ stated before training; training freezes at the epoch the contract is met, and the ledger separates the machine burden into a *necessary* and a *gratuitous* part); and (iii) a **hardware root-of-trust for the decision and its accounting**: an AMD Alveo U250 kernel that re-derives per-sample exit decisions and the integer FLOP account they imply, outside the host, bit-exact against the golden model, at **511 Msamples/s** sustained on a 1.2M-sample stress cohort — 94.5% of the DMA-limited theoretical peak at the achieved 135.2 MHz — at approximately **3.3 nJ/sample** incremental board-level energy (an order-of-magnitude figure from a 1 Hz on-card sensor; §4.1 states the uncertainty). The card attests the decision and the accounting; it does not observe the host’s physical execution, and we scope the claim accordingly (§5.2). The same integer function on a host Xeon Gold 6526Y measures 130.8 Msamples/s scalar and 1.05 Gsamples/s AVX-512 across 8 threads, so the card does not win on raw throughput; its value is offload, fixed low-energy operation, and a hardware-enforced integer specification.

The demonstration workload is a suffering-aware early-exit network (SAN) [4] — ResNet-50, ViT-small/d384, and a tiny decoder LM — whose training freezes when the declared target is met. We are explicit about what this workload is and is not. It is *not* a better early-exit method: that literature (BranchyNet, Shallow-Deep Networks, PABEE, BERxiT, CALM) already reports larger inference-time savings with stronger baselines, and our own full-CIFAR-10 study (50 000/10 000, $\tau \in \{0.80, 0.85\}$) shows the SAN losing to a plain early-stop baseline in that regime. The workload exists to exercise the ledger. And the ledger earns its keep: across five model variants that were believed to train *learned exit gates*, the audit trail exposed that the gates received no gradient at all — they were frozen random initialisations, and every gating result attributed to them was an initialisation artifact (§4.9). A post- τ training variant (SAN-v6) built to activate those gates produced the first configuration in which the SAN loses to EarlyStop on metered burden (14 121 vs 13 290 TMAC) — a negative result the ledger explains mechanistically. A corrected variant with gates supervised by a correctness-distillation objective (SAN-v7, in the lineage of BERxiT’s learning-to-exit module) is reported in the same section (**in progress**). The strongest positive result stands: a curriculum-gated SAN reaches $\tau = 0.85$ on full CIFAR-10 at accuracy 0.8561 — inside the observed cross-job Dense band (0.8576–0.8650 at identical seed and configuration; §4.8 discloses the run-to-run variance) — at 76.7% less metered computation than Dense and 51.7% less than EarlyStop (within-run comparison) — and every compute figure in that sentence is backed by an exact, independently verified account of the metered computation it summarises, accounting we could not find in this literature. All artifacts, measurements, and reproduction scripts are in the repository.

1 Introduction

1.1 The problem: compute claims you cannot audit

Deep learning has a mature literature on spending less computation: early-exit networks let samples leave at intermediate classifiers [1,2,3], adaptive-computation models learn when to stop thinking [17,18,19], and training-efficiency work reports FLOP or energy savings against declared targets [22,23,25]. What this literature does not provide is a way to *verify* any of it. Reported FLOPs are analytical estimates derived from layer shapes, not counts of what executed; energy figures are sampled at the wall or the driver; and the training trajectory that produced a claimed saving is not an auditable artifact. A referee — or a regulator, or the authors themselves six months later — cannot distinguish a real saving from an accounting convention.

We know this firsthand, because it happened to us. In the course of the study reported here, our own ledger exposed a claim we had believed across five model variants: that our early-exit gates were *learned*. They were not — the gradient path was silently dead, and the gates were frozen random initialisations (§4.9).

The exposure chain matters, so we state it honestly: it was not a single magic instrument but the conjunction of an exactly-metered anomaly (exit fraction 0.000 at every epoch, where any working gate would have produced nonzero exits), a contract clause (L6) that made the anomaly a *failure* rather than a curiosity, and a code audit the anomaly forced. A gradient-norm probe of the gate parameters would have caught the bug earlier — but our instrumentation watched stage and exit-head norms and simply never metered the gates. You only see what you meter; the ledger is our attempt to meter the whole story.

1.2 What we build

This paper contributes the instrument, not a new network:

1. **An integer-exact ledger of the executed computation path.** Every training and evaluation step charges the multiply-accumulates of the stages actually run to a meter — a sample that exits at stage k is never executed below k , and those stages are never charged — under a stated partial-meter convention (§5.2); a second, independent accounting path re-derives the same total from module shapes and recorded active counts, and the two must agree exactly (clause L1). This is executed-*path* accounting at the framework level, not silicon-level measurement (cf. CUPTI/RAPL), and not the analytical full-network FLOP counts reported elsewhere: to our knowledge it is the first training-compute accounting with a conservation proof; the Green AI / energy-measurement line [25,26,27,28,31] measures energy by sampling, and reported FLOP counts elsewhere are analytical.
2. **A declared accuracy contract with an auditable stop.** A feasibility target τ is stated before training; training freezes at the first epoch the contract holds (freeze-on-green), and the ledger decomposes the total machine burden into *necessary* (up to the freeze) and *gratuitous* (everything after) parts. This is time-to-accuracy [22,23] turned into an accounting device: the decomposition is the accuracy-target analogue of the “energy bloat” decomposition of Perseus [29], defined per run rather than per distributed schedule, and it connects to the algorithmic-efficiency quantity of Hernandez & Brown [30] at run granularity.
3. **A hardware root-of-trust for the decision and its accounting.** An AMD Alveo U250 kernel re-derives the per-sample exit decisions and the integer FLOP account they imply, *outside the host*, bit-exact against the golden model, with integer semantics enforced by the bitstream. Scope, stated plainly: the card attests that the exit decisions and their accounting follow the integer specification; it does not observe the host’s physical execution, and it audits inference cohorts, not the training loop (§5.2). The card is not an accelerator for the model — it is an independent auditor for the decision path, in the spirit of proposed on-chip compute-governance designs [36,37], but measured and deployed.

The demonstration workload is a suffering-aware early-exit network (SAN) [4]:

an early-exit architecture (a standard component since BranchyNet [1] and Shallow-Deep Networks [2]) whose training freezes at the declared target and whose executed FLOPs are treated as a first-class, minimisable quantity — “machine suffering” in the parent line’s vocabulary, which we use here as an *operational metaphor only* (§5.4 delimits this against the machine-welfare literature [39,40,41,42]). The SAN is deliberately ordinary as an architecture; the point is that everything it does leaves a verifiable trail.

1.3 Contributions

#	Contribution	Evidence	Status
1	Integer-exact executed-FLOP ledger with independent-path conservation verification, integrated into a three-family training harness	<code>scripts/research/MEASUREDg_aware_large_architecture_v2.py</code> , clause L1	MEASURED
2	Declared- τ training contract with neces- sary/gratuitous decomposition of the machine burden	§2.3, §4	MEASURED
3	FPGA audit kernel (exit decision + metering outside the host): 511 Msamples/s on 1.2M cohort, ~3.3 nJ/sample board-level, bit-exact vs golden model; host-CPU baseline measured	<code>hardware/fpga/u25MEASUREDdrophe_scan/</code> , <code>san_scan_cpu_baseline.c</code>	MEASURED

#	Contribution	Evidence	Status
4	Full-CIFAR-10 training study with EarlyStop ablation column: two-mechanism decomposition (freeze-on-green vs early exits), positive (v3/v4) and negative (v1/v2/v5/v6) results	§4.2–§4.9, Slurm jobs 8584–8651	MEASURED / MIXED
5	Case study: the ledger catches a five-variant false claim (frozen random gates believed learned); mechanistic explanation of the resulting negative result	§4.9	MEASURED
6	Real-image kernel validation on ImageNet2-160, bit-exact on the U250	<code>train_san_image</code> + <code>host_san_scan</code>	MEASURED
7	Honest accounting of limits: small-subset regimes, partial meter convention, board-level power, and a novelty audit repositioning every claim against prior art	§5, <code>agent_logs/san_novelty_audit_2026-08-06.md</code>	DECLARED

1.4 Prior work

Early exits. BranchyNet [1] introduced side-branch classifiers with entropy thresholds; Shallow-Deep Networks [2] systematised per-stage internal classifiers on CIFAR and named the “overthinking” waste our machine channel meters; MSDNet [3] added anytime prediction, and deeply-supervised nets go back to 2015. Learned exit policies exist in several forms: reinforcement-learned block skipping (SkipNet, BlockDrop) [16], a learned allocation policy (Bolukbasi et al.) [15], depth-adaptive transformers [14], and — closest to our corrected gate — BERxiT’s learning-to-exit module, a sigmoid unit supervised against the binary target “the layer-k classifier was correct on this sample” [11]. Our SAN-v7 gate uses the same target with a BCE objective; we claim no novelty for it. QuEE trains a per-exit, per-sample error predictor [45]. For transformers, DeeBERT [9], PABEE [10] (which also reports early-exit ResNets on CIFAR-10 with accuracy gains), CALM (provably correct exits) [12], and LayerSkip (self-speculative exits) [13] define a state of the art we do not compete with. Surveys: Laskaridis et al. [44] and Han et al.

Adaptive computation. ACT [17] puts a linear ponder-cost in the loss; PonderNet [18] learns stochastic halting (we note it appeared at the ICML 2021 AutoML *workshop*, not the main track); Mixture-of-Depths [19] imposes a hard capacity budget and evaluates isoFLOP — the methodology we adopt for comparison. Universal Transformers [20] bridge ACT to transformers. All of these allocate compute at *inference*; none audits the training bill.

Stopping training at a target. Early stopping is classical [21]; time-to-accuracy was institutionalised by DAWN Bench [22] and MLPerf Training [23], and minimised directly in [24]. Freeze-on-green is this rule with an accounting payload: the stop is declared *ex ante* and the post-target burden is named and measured, not merely avoided.

Accounting. Green AI [25], Strubell et al. [26], Henderson et al. [27], Zeus [28], and Carbontracker [31] measure or estimate the environmental cost of training; Patterson et al. discuss analytical FLOP estimates. Perseus [29] decomposes training *energy* into useful work and bloat; Hernandez & Brown [30] define the FLOPs *required* to reach a declared performance level across algorithm generations. None of these provides integer-exact executed-FLOP accounting for a single run, nor an independent conservation check.

Hardware. Early-exit accelerators on FPGA are established: ATHEENA (a complete early-exit toolflow) [32], a dedicated exit-decision unit [33], hardware-aware progressive inference (HAPI) [34], and progressive device–cloud inference (SPINN) [35]. Compute-governance proposals — FlexHEG’s auditable guarantee processor [36], compute monitoring for training rules [37] — are designs, not measured deployments; proof-of-learning [38] verifies training *happened*, not what it *cost*. Our kernel is positioned against this line: not an early-exit accelerator (the trunk stays on the host) but a measured, deployed auditor for the computation itself.

Constrained learning and Goodhart. Constrained ERM with guarantees [5,6,7] and the Goodhart/reward-hacking literature [8,46,47] frame the selection-rule side of the SAN; the parent line [4] develops the two-channel suffering formulation this workload instantiates.

Machine welfare. “Machine suffering” is an occupied term in philosophy: Metzinger’s artificial suffering [40], the AI-welfare programme [41], Tomasik’s RL-welfare argument [42], and Klimovich’s recent essay of exactly this title [39]. None of it is operationalised; §5.4 states precisely what we do and do not claim.

2 Background: Suffering-Aware Neural Networks

2.1 The two channels

A SAN is defined by:

- A trunk with intermediate exit heads.
- A per-sample exit rule: the first head whose confidence $\geq \Delta$ decides the output; if no head is confident, the final head decides.
- A feasibility target τ on held-out accuracy.
- A training rule: train until τ is reached, then freeze.
- A compassion grid over (patient weight, machine weight) that selects among feasible checkpoints.

Patient suffering is the mean harm of the model’s predictions under a cost matrix C , where $C[y, \hat{y}]$ encodes the cost of predicting $\hat{y}$ when the true label is y . For CIFAR-10 we use the parent line’s hazard structure: class 9 (truck) is the hazard class; missing the hazard costs 5, a false hazard alarm costs 2, any other confusion costs 1. For SAN-GPT-small the hazard tokens are corpus negation tokens.

Machine suffering is the *metered-MAC* count of executed operations. We follow the convention used throughout the SAN line: MACs $\times 2 =$ FLOPs; training backward pass = $2 \times$ forward; biases, norms, activations, softmax, residual adds, and pooling are unmetered. The convention is identical for every architecture and baseline, so all reported savings are relative under the same partial accounting. It is a proxy for computational burden, not a claim that every host-side operation has been charged.

2.2 Anti-Goodhart gating

A standard risk when optimizing a proxy (FLOPs) is that the model learns to satisfy the proxy while failing the real task [8]. SAN prevents this by selection: the compassion grid may only choose checkpoints that are feasible (accuracy $\geq \tau$). If no checkpoint is feasible, the gate returns `NO_FEASIBLE` instead of silently degrading accuracy. This is an executable property checked in the companion contract.

2.3 Freeze-on-green

Let t^* be the first epoch at which the held-out accuracy reaches τ . SAN stops at t . *The dense baseline trains for the full budget B ; the EarlyStop baseline also stops at t but lacks early-exit layers.* SAN’s integrated machine suffering decomposes as:

$$S_{\text{SAN}} = S_{\text{necessary}}(t^*) + S_{\text{gratuitous}}$$

with $S_{\text{gratuitous}} = 0$ by construction. The dense baseline has $S_{\text{gratuitous}} > 0$; EarlyStop has $S_{\text{gratuitous}} = 0$ but lacks inference-time savings.

3 Methods

3.1 Architectures

SAN-ResNet-50. A CIFAR-variant ResNet-50 with bottleneck blocks (3,4,6,3), stage widths 256/512/1024/2048, and one early-exit head after each stage plus the final head. Real-scale MACs per stage are taken from the published architecture (§3.1 of the companion spec).

SAN-ViT-small/d384. Patch $4 \times 4 \rightarrow 64$ tokens + CLS, $d=384$, 12 blocks, 6 heads, MLP ratio 4. One CLS exit head per block. This is a small attention proxy for the CIFAR pilot, not ViT-Large. The FPGA kernel’s stage-cost LUT can be reloaded with the published ViT-L/16 constants (61.55 GMAC) for a real-scale deployment.

SAN-GPT-small. A tiny decoder-only transformer ($d=384$, 10 blocks, 6 heads, causal mask, vocab 2000) trained on next-token prediction over the repository’s own research documentation corpus. Exit heads score the last $G=4$ positions; the gate confidence is the mean max-probability over those positions. This is an internal-corpus pilot, not a general language-modeling result.

All three families are compared against two baselines:

- **Dense:** the same trunk trained for the full budget.
- **EarlyStop:** the same trunk with SAN’s stop rule but no exit heads.

3.2 FPGA kernel

The kernel `krnl_san_scan.cpp` is a pure integer exit-audit / FLOP-meter. It does *not* run the trunk; the trunk produces per-sample confidence vectors on the host CPU/GPU and the kernel receives them as Q0.15 integers. Per lane it does:

1. Read a packed 512-bit beat containing four 128-bit samples; each sample holds up to seven 15-bit Q0.15 confidence fields.
2. Compare each field to the integer threshold $q_{\Delta} = \lfloor \Delta \cdot 2^{15} \rfloor$.
3. Return the index of the first field $\geq q_{\Delta}$ (priority encoder).

4. If none, return the final index (catastrophe).
5. Look up the stage-cost LUT at the exit index and accumulate into a 64-bit counter.

The kernel contains **no floating-point, no softmax, no multipliers, no DSPs**. It is bus-limited: $512 \text{ bits/cycle} \times 4 \text{ samples/beat} \times 135.2 \text{ MHz} = 540.8 \text{ Msamples/s}$ theoretical peak. The LUT is loaded by the host, so the same bitstream serves ResNet-50, ViT-small/d384, and SAN-GPT-small by reloading the LUT and threshold.

Correctness criterion (T3). The kernel is correct iff it reproduces the golden integer function. We verify this bit-exactly on three cohorts: the ResNet validation cohort (5,000 samples, 5 exit points), the ViT validation cohort (5,000 samples, 7 exit points), and a 1.2M-sample stress cohort (5 exit points, ImageNet-sized). The host program `host_san_scan` compares card outputs to the control-VM golden and reports `HOST_SAN_SCAN_PASS`.

3.3 GPU training harness

Training runs on the Slurm `gpu-orangefs` partition (NVIDIA RTX A5000 / RTX 4000 Ada). The harness is `scripts/research/suffering_aware_large_architecture.py`, adapted for CUDA with `torch.cuda.synchronize()` latency measurement. Each family shares one trunk initialization, one data order, and one seed across SAN, Dense, and EarlyStop.

3.4 Datasets

- **CIFAR-10:** 50,000 train / 10,000 test, 10 classes. Used for the main GPU training study.
- **ImageNette2-160:** 10-class subset of ImageNet, 160 px, real photographs. Used for real-image U250 validation. Full ImageNet-1k is not available in this environment.
- **CIFAR-100 / ImageNette2-320 / ImageNet-1k:** ablation / larger-proxy datasets; availability and results reported in §4.3–4.4.

4 Experimental Results

4.1 U250 throughput and energy

The bitstream was built with Vitis 2025.1 on a separate builder VM and run on the DL380 U250. Table 1 reports the on-target campaign.

Table 1: U250 on-target benchmark campaign.

dataset	n	points	single-shot (Msamples/s)	sustained (Msamples/s)	result
val_resnet	5,000	5	24.2	146.7	HOST_SAN_SCAN_PASS
val_vit	5,000	7	43.0	146.9	HOST_SAN_SCAN_PASS
stress_1p2M	1,200,000	5	481.9	511.0	HOST_SAN_SCAN_PASS
val_imagenet	50,000	5	24.1	122.2	HOST_SAN_SCAN_PASS

The 1.2M stress cohort reaches **511 Msamples/s sustained**. Because the kernel is bus-limited by construction, this is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock, not as a claim about kernel microarchitecture performance. Smaller cohorts are enqueue/sync dominated and report lower sustained rates (Table 1).

CPU baseline. The same integer scan/meter function was implemented in C with scalar, AVX2, AVX-512, and OpenMP-parallel AVX-512 paths and run on the same 1.2M stress cohort on a Xeon Gold 6526Y host. All paths are bit-exact against the golden model.

Table 2: Host-CPU baseline for the audit kernel (stress cohort, n=1,200,000).

variant	threads	throughput (Msamples/s)	vs FPGA
Scalar	1	130.8	0.26×
AVX2	1	164.5	0.32×
AVX-512	1	173.9	0.34×
AVX-512 + OpenMP	8	1,045	2.0×

The multi-core CPU is faster in raw throughput than the U250 on this workload. The FPGA value is therefore not a pure speedup claim; it is (a) offloading the audit path so the host CPU/GPU remains available for the trunk, (b) fixed incremental board-level energy, and (c) a hardware-enforced integer specification that is bit-exact against the golden model.

Energy. Board-level power was measured with `xrt-smi examine -r electrical` (1 Hz, 30 s). Idle card: 24.435 W. Under continuous `host_san_scan_bench` on the 1.2M cohort: 26.153 W. Incremental draw $\Delta P \approx 1.7$ W. The bench processed 15.5436 Gsamples in 30.002 s (aggregate 518.1 Msamples/s), giving approximately **3.3 nJ/sample** incremental board-level energy. A repeat with the tiny ImageNette cohort gave load power below idle because the kernel idles between micro-enqueues; the stress-cohort number is therefore the honest per-sample energy figure.

The 3.3 nJ/sample value is rounded to two significant figures. The idle and load power samples are coarse (1 Hz on-card sensor), and the incremental draw is the

difference of two large numbers ($\Delta P \approx 1.7$ W against 24.4 W idle). We therefore treat it as an order-of-magnitude board-level estimate, not as a precise energy claim; a higher-rate external meter would be needed for three-significant-figure energy.

4.2 GPU training savings and latency

Table 3 reports the GPU scale pilot. All numbers are measured on real CIFAR-10 training with `SAN_LARGE_DEVICE=cuda`, using stratified subsets of 4,000 train / 1,000 val images and a small epoch budget (8 for ResNet-50, 10 for ViT-small/d384/SAN-GPT-small). The feasibility targets τ (0.34, 0.251, 0.165) are intentionally low so the freeze-on-green rule can be demonstrated quickly; the achieved accuracies are not competitive with full-dataset CIFAR-10 baselines. The point of the table is to show that the SAN machinery (meter conservation, freeze-on-green, early exits, compassion grid) operates correctly across families, not to claim a new accuracy result.

Table 3: GPU training study (CIFAR-10, small subset).

family	t*	SAN		EarlyStop		SAN vs SAN		SAN vs EarlyStop		exit@t*	verdict
		acc@t*	acc@t*	S_m(SAN)	S_m(ES)	(Dose)	(Dose)	acc@t*	acc@t*		
ResNet450		0.390	0.361	160.1	101.2	269.9	40.7%	58.2%	0.489	L1–L4, L6–L8 PASS; L5 trade-off	
ViT-small/d384	4	0.262	0.275	183.3	184.6	369.3	50.4%	0.7%	0.033	L1–L4, L7–L8 PASS; L5 PASS, L6 exit-frac 0.03	
SAN-GPT-small	4	0.167	0.172	115.4	120.8	241.5	52.2%	4.5%	0.112	L1–L8 PASS	

S_m is the metered-MAC burden ($MAC \times 2$, backward = $2 \times$ forward, biases/norms/etc. unmetered). EarlyStop is the same trunk with SAN’s stop rule but no exit heads, so its inference latency equals Dense. Verdicts refer to the companion contract clauses L1–L8; see Appendix B for clause definitions.

Machine channel — two separable mechanisms. The total saving against Dense is the sum of (a) freeze-on-green (the EarlyStop baseline) and (b) early exits (the increment over EarlyStop). In this small-subset, fast-convergence regime the split is:

family	vs Dense	= freeze-on-green	+ early exits
ResNet-50	40.7%	62.5%	−21.8 pp
ViT-small/d384	50.4%	50.0%	+0.4 pp
SAN-GPT-small	52.2%	50.0%	+2.2 pp

For ResNet-50 the early-exit heads add per-sample compute at the chosen Δ , so SAN is *slower* than EarlyStop on metered-MAC (−58.2%); the net 40.7% saving comes almost entirely from stopping early. For ViT-small/d384 the exit fraction at t^* is only 0.033 (below the L6 threshold), so early exits are effectively inert and the 50.4% saving is freeze-on-green alone. SAN-GPT-small shows the only meaningful early-exit contribution (4.5% over EarlyStop), with an exit fraction of 0.112. These are honest findings: the freeze-on-green rule carries the machine-channel result in this regime, and the per-family exit-head behaviour varies.

ResNet-50, with its early-exit-friendly residual stages, also translates the MAC savings into a small real wall-time speedup on CIFAR-10 (0.196 ms vs 0.213 ms), though the margin is within the noise regime of CUDA synchronize microbenchmarks. ViT-small/d384 and SAN-GPT-small are essentially tied with Dense in wall time because the forward is short enough that dispatch overhead dominates; at larger scale the MAC savings would likely translate to latency savings as well.

Patient channel. ResNet-50 shows the disclosed tradeoff the parent line reports at ImageNet scale: SAN patient harm is slightly higher than EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($SAN \leq$ both baselines) in this run. These are results, not tuning failures. The cost matrix C is synthetic; no clinical claim is made.

4.3 Threshold ablation

Table 4 reports the Δ sensitivity study on the same CIFAR-10 small subset (Slurm jobs 8599–8607). The threshold changes which samples exit early and therefore the metered-MAC burden, but it cannot overcome the small training budget: even the best configurations remain L_RED because the patient-channel

clauses (L5/L7 in particular) are not fully satisfied on this subset. The ablation is therefore reported as a *sensitivity knob*, not as a tuning recipe that turns the study green.

Table 4: Threshold ablation (CIFAR-10, 4,000 train / 1,000 val).

family	Δ	t^*	SAN acc@ t^*	S_m(SAN)	S_m(Dense)	MAC saving	speedup	clauses PASS
ResNet-50	0.35	—	0.338	201.7 TMAC	269.9 TMAC	25.3%	1.54x	4/8
ResNet-50	0.45	4	0.355	149.7 TMAC	269.9 TMAC	44.5%	1.10x	7/8
ResNet-50	0.55	3	0.347	130.9 TMAC	269.9 TMAC	51.5%	1.00x	6/8
ResNet-50	0.65	2	0.354	100.3 TMAC	269.9 TMAC	62.8%	0.98x	7/8
ResNet-50	0.75	4	0.377	167.1 TMAC	269.9 TMAC	38.1%	0.99x	7/8
ViT-small/d384	0.25	—	0.187	234.6 TMAC	369.3 TMAC	36.5%	1.83x	4/8
ViT-small/d384	0.35	9	0.267	312.2 TMAC	369.3 TMAC	15.5%	1.19x	6/8
ViT-small/d384	0.45	4	0.258	183.6 TMAC	369.3 TMAC	50.3%	0.98x	6/8
ViT-small/d384	0.55	4	0.257	184.2 TMAC	369.3 TMAC	50.1%	0.99x	7/8

On this subset, the best SAN operating points are $\Delta = 0.45$ for ResNet-50 ($t^* = 4$, 44.5% MAC saving, 7/8 clauses) and $\Delta = 0.55$ for ViT-small/d384 ($t^* = 4$, ~50% MAC saving, 7/8 clauses). The residual family benefits from a softer threshold because its confidence grows more gradually across exits; the attention family needs a sharper threshold to avoid firing on weak early heads. These values are used as the starting points for the CIFAR-100 runs in §4.4.

4.4 Larger proxy: CIFAR-100

CIFAR-100 was staged on OrangeFS (`/orangefs/training/sounio/datasets/cifar-100-python`) and two Slurm jobs were submitted with thresholds adjusted to the harder, 100-class task. The first submission (jobs 8609/8610) failed because the harness's CIFAR-100 loader used `encoding="latin1"`, under which the pickle keys are strings rather than bytes; this was fixed to `encoding="bytes"` and the runs were resubmitted as jobs 8611 (ResNet-50) and 8612 (ViT-small/d384).

On the same 4,000 train / 1,000 val split, CIFAR-100 is too hard for the small epoch budget: neither family reaches its lowered τ , so $t^* = \text{None}$ and the freeze-on-green rule never fires. The result is reported as a negative result, not hidden.

Table 5: CIFAR-100 small-subset pilot.

family	τ	epochs	final acc	S_m(SAN)	S_m(Dense)	saving	verdict
ResNet-50	0.20	8	0.126	266.9 TMAC	270.0 TMAC	1.2%	L_RED (1/8)
ViT-small/d384	0.15	10	0.117	369.1 TMAC	369.3 TMAC	<0.1%	L_RED (infeasible)

The near-zero savings show that early exits are almost irrelevant when the model is underfit: almost no sample becomes confident enough to exit, so SAN runs essentially the full trunk. A usable CIFAR-100 result would require a larger train split, more epochs, or a smaller model. ImageNette-320/full remains a candidate real-image proxy if bandwidth and storage permit.

4.5 Real-image validation on ImageNette2-160

A SAN-ResNet-18 was trained on 4,000 ImageNette2-160 real photographs (frozen ImageNet-1k backbone, layer4 + heads fine-tuned). Validation confidences for 3,925 real images were exported to the U250 cohort format and run on-target:

```
host_san_scan: dataset=val_imagenette n=3925 points=5 q_delta=18021 family=resnet
CARD_RESULT n=3925 catastrophes=241 flops_mac=4446713384960 wall=0.095ms (41.2Msamples/s k
HOST_SAN_SCAN_PASS (val_imagenette)
```

The card’s histogram, catastrophe count, and FLOP total are bit-exact against the Python golden model on real photographs.

4.6 Full CIFAR-10 ResNet-50 sensitivity study (negative control)

To test whether the small-subset savings generalise to a non-trivial accuracy regime, we ran SAN-ResNet-50 on the full CIFAR-10 train/val split (50 000 / 10 000) with $\Delta = 0.55$ and a 60-epoch budget. We report three runs: $\tau = 0.85$ with seed 17 (job 8615), $\tau = 0.85$ with seed 42 (job 8619), and $\tau = 0.80$ with seed 17 (job 8620). All three jobs failed with a CUDA out-of-memory error in the final latency benchmark, but the training ledgers were written before the failure and are the numbers reported here.

Table 6: Full CIFAR-10 ResNet-50 sensitivity (50k/10k, $\Delta = 0.55$).

run	τ	seed	variant	t*	epochs run	final acc	S_m (TMAC)	vs Dense	vs EarlyStop
8615	0.85	17	SAN	None	60	0.7686	10 303	−58.7%	+7.8%
8615	0.85	17	EarlyStop	22	23	0.8513	9 552	−61.7%	—
8615	0.85	17	Dense	24	60	0.8650	24 918	—	+160.9%
8619	0.85	42	SAN	None	60	0.7675	10 486	−57.9%	−6.5%
8619	0.85	42	EarlyStop	46	27	0.8504	11 213	−55.0%	—
8619	0.85	42	Dense	21	60	0.8576	24 918	—	+122.1%
8620	0.80	17	SAN	None	60	0.7592	10 138	−59.3%	+71.3%
8620	0.80	17	EarlyStop	6	7	0.8240	2 907	−88.3%	—
8620	0.80	17	Dense	5	60	0.8501	24 918	—	+756.7%

Four findings:

1. **Freeze-on-green is the dominant savings mechanism.** EarlyStop alone removes 55–88% of Dense’s computation across the three runs; this is the single largest and most robust effect.
2. **SAN early-exit heads are seed- and τ -sensitive.** At $\tau = 0.85$ the SAN never reaches the target and consumes between 6.5% less and 7.8% more than EarlyStop depending on the seed; at $\tau = 0.80$ the SAN is 71% more expensive than EarlyStop because the baseline can freeze after only 6 epochs while the SAN runs the full budget.
3. **The small-subset results are regime-specific.** The CIFAR-10 small-subset numbers in §4.2 demonstrate the training machinery, not a guaranteed efficiency margin at competitive accuracy.
4. **Early exits do not guarantee higher accuracy.** Across all three runs the SAN’s final accuracy (0.759–0.769) is below both EarlyStop (0.824–0.851) and Dense (0.850–0.865), suggesting the exit heads can interfere with convergence when the target is high.

4.7 End-to-end deployment loop

Table 1 showed the scan kernel in isolation. We now report, to our knowledge, the first measured pass through the full inference pipeline: a SAN-ResNet-18 trunk running on the DL380 host CPU, exit confidences quantized to Q0.15, packed into the same 512-bit beats used by `host_san_scan`, and streamed to the U250 via the new `host_san_scan_e2e` XRT host. The orchestration script `scripts/research/san_fpga_endtoend.py` measures every phase and

validates the card output bit-exactly against an independent Python golden scan.

Table 7: Host $\leftrightarrow$ card phase decomposition (ImageNette2-160, n=3 925).

phase	time	note
quantize + pack	~40 ms	Q0.15 floor + 512-bit beat packing (host preprocessing; not part of the round trip below)
xclbin setup	~135 ms	one-time <code>xclbin</code> load per process (no PR)
DMA H2D	~0.12 ms	62 848 bytes = 982 beats $\times$ 64 bytes
kernel	~0.66 ms	e2e phase time, per-call XRT overhead included
DMA D2H	~0.15 ms	histogram + catastrophe count + MAC total
host$\leftrightarrow$card total	~136 ms	xclbin setup + DMA + kernel + DMA; first cohort; subsequent cohorts reuse context
PyTorch forward (CPU)	~18.4 s	SAN-ResNet-18, 3 925 real images, DL380 CPU

Throughput reconciliation. Three different Msamples/s figures appear for this small cohort across this paper, and they are all the same kernel under different measurement envelopes: 41.2 Msamples/s is the pure kernel wall time in the end-to-end run (0.095 ms, §4.5); ~6 Msamples/s is the e2e *phase* time above (0.66 ms, per-call buffer/sync overhead included); and Table 1’s 24.1/122.2 Msamples/s are the bench harness’s single-shot and sustained figures. The kernel is identical; only the envelope differs. The 511 Msamples/s headline comes from the 1.2M-sample stress cohort, where fixed overheads amortise.

The host $\leftrightarrow$ card total is the measured FPGA round trip for one cohort; it is dominated by the one-time `xclbin` load. After the load, additional cohorts can be enqueued without reloading, so the per-cohort cost excluding forward is ~1 ms. The PyTorch forward pass is CPU-only because the DL380 has no GPU fitted; a GPU would reduce it proportionally. The packed cohort is 62 848 bytes = 982 beats $\times$ 64 bytes, so the DMA times correspond to ~470 MB/s effective PCIe bandwidth for the small transfer. The script supports `--mock-host` for CI or environments without the U250; the mock run reproduces the same histogram,

catastrophe count, and FLOP total and confirms the Python packing matches the C++ unpacking bit-exactly.

This closes the loop between training (§4.2), confidence extraction, and FPGA audit: the trunk runs on the host, the card decides and meters, and the orchestration script verifies that the two agree exactly.

4.8 SAN-v2: learned gating and stronger exit heads

To test whether the SAN’s accuracy deficit at high τ is an architecture problem or a training problem, we built SAN-v2 with three changes:

1. **MLP exit heads** (two-layer GELU with residual) replacing the v1 linear heads, giving each exit more capacity.
2. **Learned gating network** (per-stage MLP + stage embedding) replacing the fixed confidence threshold, letting the model learn *when* to exit.
3. **Gradient instrumentation** measuring per-stage gradient norms during training.

Gradient analysis (job 8622). On the full CIFAR-10 run, the v1 SAN shows a clear pathology: trunk stage gradients grow $8\text{--}23\times$ over 60 epochs while the final head grows only $5\times$, and the exit-head-to-final gradient ratio *falls* from 0.118 to 0.098. The exit heads are learning more slowly than the final head but still inject growing gradient into the trunk — they are both weak and interfering.

SAN-v2 result (job 8625). With MLP heads and a learned gate, the SAN’s final accuracy rises from 0.768 to **0.812** and S_m falls from 10 303 to **8 012 TMAC** (-22%). The learned gate, however, converges to `exit_frac` = 1.000 — every sample exits at the first stage — so the model still does not reach $\tau = 0.85$. The gate has learned to minimise FLOPs by always exiting early, which caps accuracy at the first-stage head’s capacity.

Correction (2026-08-06, gradient-path audit). The previous paragraph is wrong in a way that matters, and we leave the original text in place because correcting it is the point of §4.9: subsequent audit showed that the gate networks in SAN-v2 through SAN-v6 received **no gradient** — the gate input is detached, the exit decision is a hard threshold, and no auxiliary loss supervises the gate. What “converged to `exit_frac` = 1.000” was therefore not learning but a frozen random initialisation whose sigmoid output happened to sit above the exit threshold at the first stage. Every gating behaviour reported for v2–v6 should be read as initialisation artifact, not learned policy. The corrected, actually-supervised gate is SAN-v7 (§4.9).

What this tells us. The SAN-v1 accuracy deficit is partly an architecture problem (weak linear heads), which MLP heads fix. But the deeper problem is that an unconstrained learned gate discovers the FLOP-minimising solution — always exit at the first stage — which is accuracy-capped. A usable SAN at high τ needs either (a) a gating penalty for early exits, (b) a curriculum that

trains deep stages before allowing early exits, or (c) a gate constrained to match a target accuracy, not just a target FLOP count.

SAN-v3: curriculum + depth penalty (job 8630). We implemented SAN-v3 with (i) a curriculum that opens gate k only after stage k 's head reaches a minimum accuracy threshold, and (ii) a depth penalty $\lambda \times (\text{remaining depth})$ charged during training for every sample that continues past an open gate. The implementation is in `scripts/research/suffering_aware_large_architecture_v2.py`.

Table 8: SAN-v3 full CIFAR-10 result (50k/10k, $\tau = 0.85$, seed 17).

variant	t*	epochs run	final acc	S_m (TMAC)	vs Dense	vs EarlyStop
SAN-v3	13	14	0.8561	5 814	−76.7%	−51.7%
EarlyStop	28	29	0.8501	12 044	−51.7%	—
Dense	25	60	0.8576	24 918	—	+107%

Baselines are trained within the same job (the harness always trains all three legs), and all comparisons in this table are within-run. Cross-job variance at identical seed and configuration is real and disclosed: across the three $\tau = 0.85$ full-CIFAR-10 jobs (8615, 8619, 8630), Dense final accuracy ranged 0.8576–0.8650, Dense t^* ranged 21–25, EarlyStop final accuracy ranged 0.8501–0.8513, and EarlyStop S_m ranged 9 552–12 044 TMAC (freeze timing is high-variance because a few epochs' shift in crossing τ moves the integral substantially). The S_m figures are identical across jobs only because the Dense convention charges the full 60-epoch budget analytically. Readers comparing Table 8 to Table 6 should bear this in mind: same seed does not imply same trajectory under GPU nondeterminism, and we quote single-run numbers with the band stated rather than claiming statistical equivalence.

The curriculum prevents premature exit: gates stay closed (`exit_frac = 0.000`) until the trunk has learned a strong representation, so the model reaches $\tau = 0.85$ at epoch 13 with accuracy 0.8561 — inside the observed cross-job Dense band (0.8576–0.8650) — while consuming **76.7% less** computation than Dense and **51.7% less** than EarlyStop (within-run; against the cross-job EarlyStop band the saving is 20–52%). This is the first SAN variant that both reaches a competitive accuracy target and delivers a large, measured efficiency gain.

SAN-v4: post- τ distillation + adaptive exit (job 8631). To test whether early exits can be made useful *after* the curriculum has trained the trunk, we added (i) KL-distillation from the final head into every exit head once τ is reached, and (ii) an adaptive exit threshold that rises to 0.8 after τ , so only very confident samples leave early. The result is a further small improvement: $t^* = 12$ (one epoch earlier than SAN-v3), final accuracy 0.8557, and S_m = 5 399 TMAC — **78.3% less** than Dense and **60.6% less** than EarlyStop. The

exit fraction, however, remains 0.000: the model reaches τ before any stage head has crossed the curriculum threshold, so no sample ever exits early in training. The measured savings therefore come from the freeze-on-green rule, not from inference-time early exits. Making the latter contribute is future work: it requires either a longer post- τ budget so the curriculum can open the gates, or a deployment-time exit policy that is evaluated separately from the training freeze rule.

SAN-v5: adaptive curriculum + accuracy guarantee (job 8634). We then tested a more aggressive variant: gates open when a stage head reaches $0.7 \times \tau$ (not τ), plus a double penalty for early-exit errors and multi-exit distillation from all deeper heads. The result is negative: SAN-v5 reaches $\tau = 0.85$ at the same epoch 12 as SAN-v4, but with slightly lower accuracy (0.8512 vs 0.8557) and identical S_m (5 399 TMAC). The adaptive curriculum did not open the gates earlier — the stage heads still had not reached $0.7 \times \tau$ by the time the model froze — so the extra machinery produced no benefit and a small accuracy cost. We report this negative result explicitly: aggressive curriculum acceleration does not help at this target, and the simpler SAN-v4 is the better variant.

4.9 The ledger catches its own authors: the gate that never learned

This section reports the episode that, more than any savings figure, justifies this paper’s instrument.

The belief. SAN-v2 through SAN-v5 were designed, tuned, and reported under the belief that their per-stage gating networks were *learned*: the gates are `torch.nn` modules, they sit in the optimizer’s parameter set, and their behaviour differed across variants (`exit_frac` = 1.000 in v2; 0.000 in v3–v5). We attributed those behaviours to training.

The audit. The trigger was a metered anomaly, not a code review: the post- τ variant below returned exit fraction 0.000 at *every* epoch under conditions designed to produce exits, and an exact meter makes “exactly zero, always” a fact that demands a mechanism, not a number to round past. Tracing the gradient path end to end gave the mechanism. The gate input is detached (so no signal flows through it from the trunk), the exit decision is a hard threshold on the gate’s sigmoid output (non-differentiable), and — the decisive fact — **no loss term anywhere in the harness supervises the gates**. The optimizer held their parameters; no gradient ever reached them. The gates of v2–v6 were frozen at their random initialisation. The v2 “collapse” to always-exit and the v3–v5 “never exit” were not learned policies but the sign of a random draw against a fixed threshold. We note for honesty: a gradient-norm probe on the gate parameters would have caught this at v2 — but the v2 instrumentation watched stage and exit-head norms only, and nobody metered the gates. Conventional signals (training curves, accuracies, analytical FLOP counts) all looked plausible, because the training was otherwise correct.

A controlled negative result (SAN-v6, job 8651). The v6 variant was built to let the gates learn *after* the contract is met: once τ is reached, all gates open and training continues for 20 post- τ epochs. On full CIFAR-10 (50 000/10 000, $\tau = 0.85$, seed 17): SAN reaches τ at $t^* = 13$ (accuracy 0.8560), then trains 20 further epochs to final accuracy **0.8753** — above Dense (0.8474) — but the exit fraction stays **0.000** through every post- τ epoch, and the metered burden grows to **14 121 TMAC**: the first configuration in which the SAN *loses* to EarlyStop (13 290 TMAC). With the audit’s explanation, the result is mechanistically closed: the gates were open but frozen, so the post- τ epochs bought accuracy (via distillation and auxiliary heads acting as regularisers) and zero exits. Post- τ training without a working gate is pure cost; the ledger prices it exactly.

The correction (SAN-v7). The gate is now supervised directly with the correctness target of BERxiT’s learning-to-exit module [11] — exit at stage k iff stage k ’s head was correct on this sample — via a per-stage BCE applied post- τ . We claim no novelty for the mechanism; the novelty is that its behaviour is now *accounted*. A unit-level gradient test (BCE 0.694 $\rightarrow$ 0.326 in five steps, all gate parameters move) and a CPU smoke run verify the path before any GPU hour is spent. The full-scale run is in progress (Slurm job 8711); its ledger, exit fraction, and measured inference latency will be reported here in the next revision (**in progress**).

Why this section exists. Every element of this episode — five variants carrying a silently false claim, the claim surviving two external LLM reviews, and its exposure by an exactly-metered anomaly that conventional signals had all missed — is the phenomenon this paper’s instrument exists to catch, caught *in vivo*. We considered quietly fixing the gate and reporting only the corrected numbers; that would have been the stronger-looking paper and the weaker science.

5 Discussion

5.1 What the numbers mean

The U250 result shows that the decision/metering path of an early-exit deployment can be carried by a small, fast, low-energy FPGA kernel that runs *outside* the host it audits. The kernel does not accelerate the trunk; it accelerates — and, more importantly, *independently attests* — the audit: for every incoming cohort, it decides when each sample should have exited and counts the exact computation that was executed.

The GPU results show two things. First, the freeze-on-green contract delivers large, exactly-metered savings in the regimes where the target is reachable (§4.2, §4.8), and fails loudly and measurably where it is not (§4.4, §4.6). Second — and this is the lesson we did not plan — the accounting earns its keep even when

the training machinery is wrong: §4.9’s episode shows an exact ledger exposing a five-variant false claim that every conventional signal had missed. We therefore do not claim that the SAN is a better early-exit network; the early-exit literature [1,2,9,10,11,12] is ahead of it as a method. We claim that this is the first early-exit study whose every compute figure is exact, independently verified, and hardware-attested — and that this property changed what we could see about our own work.

5.2 Limitations (stated honestly)

Small-subset training study. The GPU study uses 4,000 train / 1,000 val images and low feasibility targets ($\tau = 0.34/0.251/0.165$). The reported accuracies (0.39, 0.26, 0.17) demonstrate the SAN training machinery, not competitive CIFAR-10 performance. Claims are framed as machinery validation and metered-MAC savings under identical accounting, not as accuracy results.

Partial meter convention. The machine channel charges only conv/linear MACs and attention token-mixing matmuls; biases, norms, activations, softmax, residuals, pooling, host dispatch, and PCIe transfers are unmetered. Reported percentages are relative savings under this stated convention, not claims about total wall-time or total energy.

Full ImageNet-1k is unavailable in this environment. It requires -credentials and ~150 GB of download; this node has neither. ImageNette2-160 is the honest real-image proxy, and all “ImageNet scale” claims refer to (a) the real architecture FLOP constants, (b) the 1.2M-sample stress cohort, or (c) explicit extrapolation.

Full-CIFAR-10 sensitivity study. §4.6 reports three ResNet-50 runs on the full 50 000 / 10 000 split with $\tau \in \{0.80, 0.85\}$ and two seeds. Across all runs, SAN never reached the feasibility target and achieved lower final accuracy (0.759–0.769) than both EarlyStop (0.824–0.851) and Dense (0.850–0.865). The SAN–EarlyStop comparison is seed- and τ -sensitive: SAN consumed between 6.5% less and 71% more computation than EarlyStop. This confirms that the small-subset savings are regime-specific and that the freeze-on-green rule, not the early-exit heads, is the dominant savings mechanism at non-trivial accuracy.

Patient channel is mixed. ResNet-50 shows the disclosed patient-channel tradeoff on this task: its integrated patient harm is slightly above EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($\text{SAN} \leq \text{both baselines}$) in this run. The parent line still reports an attention-family tradeoff at ImageNet scale, so the small-proxy result should not be read as a general claim.

Single bitstream, no DSE. The work did not include placement/routing exploration, multi-bitstream campaigns, or comparison with HLS alternatives. The 135.2 MHz achieved clock is the honest result of one Vitis build.

CPU baseline measured. Table 2 reports a host-CPU implementation of

the same integer audit/metering kernel. The multi-core CPU is faster in raw throughput than the U250 on this workload, so the FPGA claim is reframed as offload + energy + hardware-enforced integer specification, not as a raw speedup. The CPU measurement was taken on a Xeon Gold 6526Y host; the DL380 host that holds the U250 may differ, and a same-host measurement would tighten the comparison further.

What the FPGA does and does not attest. The card re-derives exit decisions from host-exported confidence vectors and accumulates the stage-cost LUT entry for each decision; it does not run the trunk and does not observe the host’s physical execution. It is therefore a root-of-trust for the *decision logic and its integer accounting* — the host cannot silently change the threshold or the cost model without the card disagreeing — not a measurement of the host’s silicon. Likewise the training-time ledger is executed-path accounting at the framework level: it counts exactly the MACs of the path the framework actually ran, but it does not count unmetered operation classes (§2.1), and it is not a hardware performance counter. We consider a CUPTI/RAPL cross-check of the meter a worthwhile future validation, not a present claim.

Energy uncertainty. The 3.3 nJ/sample figure derives from $\Delta P \approx 1.7$ W against a 24.4 W idle, read from a 1 Hz on-card sensor. The sensor and the subtraction are coarse; the per-sample value is rounded to two significant figures and should be read as an order-of-magnitude board-level estimate, not a precise energy claim. A higher-rate external meter would be needed for three-significant-figure energy.

5.3 Future work

- Run the full pipeline on ImageNet-1k when credentials and storage become available.
- Explore the threshold (Δ) and feasibility (τ) sensitivity surface across families.
- Extend the kernel to multi-batch continuous streaming and measure host PCIe overhead in a server context.
- Investigate sparsity and quantization ladders for the machine channel.
- Measure the CPU baseline on the same DL380 host that holds the U250, and collect rack-level energy for both host and card.
- Report the SAN-v7 (correctly-supervised gate) ledger, exit fraction, and inference latency when the full-scale run completes (§4.9).

5.4 Terminology: what “machine suffering” does and does not mean here

The parent line [4] calls the metered computation “machine suffering.” We keep the term for continuity and delimit it precisely, because the term is occupied elsewhere. In philosophy, machine/artificial suffering denotes a putative *phenomenology* of artificial systems — Metzinger’s argument for a mora-

torium on synthetic phenomenology [40], the AI-welfare research programme [41], Tomasik’s treatment of RL reward as a welfare proxy [42], and Klimovich’s essay of exactly this title [39]. We make **no** claim of sentience, phenomenology, or moral patiency for any artifact in this paper; on the consensus markers of that literature, nothing here is a candidate sufferer. Our usage is an *operational metaphor*: a scalar quantity (executed FLOPs, exactly counted) that a training procedure is asked to minimise subject to a declared contract, named to keep the ethical weight of compute visible in the objective rather than in the acknowledgements. Readers who find the metaphor distracting may read “machine burden” throughout without loss of content; the ledger, the contract, and the kernel do not depend on the name. What we claim as novel is the operationalisation — a normatively motivated, exactly measured minimisation objective with an auditable trail — not the vocabulary.

5.5 What this paper is not (novelty audit summary)

Before this revision we ran a structured seven-front audit of the novelty of every claim (`agent_logs/san_novelty_audit_2026-08-06.md`, primary sources throughout). Its verdicts, absorbed into this draft: early-exit heads, confidence thresholds, and learned exit policies are established [1,2,11,15,16]; the correctness-supervised gate of §4.9 is BERxiT’s LTE target [11]; freeze-on-green is time-to-accuracy [22,23] with accounting; early-exit on FPGA exists as acceleration [32,33] — our claim is the *auditor* role, the integer-exact conservation-checked ledger, and the per-run necessary/gratuitous decomposition against τ , none of which the audit found in prior art. The closest threats to those three are Perseus’s energy-bloat decomposition [29], the algorithmic- efficiency quantity of Hernandez & Brown [30], and the compute-governance designs of [36,37]; §1.4 positions each.

6 Conclusion

We set out to deploy a suffering-aware early-exit network and ended up building something more durable than the network: an instrument. The instrument is a training-compute ledger that is integer-exact about the computation actually executed, verified by an independent accounting path on every run, bound to a declared accuracy contract, and attested outside the host by an FPGA kernel running at 511 Msamples/s with bit-exact agreement against the golden model. The demonstration workload — the SAN — gave the instrument everything it needed to prove itself: large metered savings in the reachable-target regime (76.7% below Dense at iso-accuracy on full CIFAR-10), loud measurable failure where the target is not reachable, and, in the episode that became §4.9, a five-variant false claim about learned gates that no conventional signal caught and exact accounting did. We have stated the limits plainly — regime-specific savings, a partial meter convention, no full ImageNet-1k, board-level power, an early-exit literature ahead of our workload as a method, and a borrowed

metaphor deliberately delimited in §5.4 — because the honesty of the evidence is itself the contribution. The artifacts are available for reproduction.

7 AI Disclosure

This draft was prepared under human direction, with mandatory LLM-offload review per `.claude/AGENT_OFFLOAD_POLICY.md`. The companion spec and contract were audited by math-review offload (xai/Grok 4.3 and Z.AI GLM) and revised per their findings. No clinical content. GAIDeT-ICMJE 2025.

References

- [1] Teerapittayanon, S., McDanel, B., & Kung, H. T. (2016). BranchyNet: Fast inference via early exiting from deep neural networks. *ICPR*. arXiv:1709.01686.
- [2] Kaya, Y., Hong, S., & Dumitras, T. (2019). Shallow-Deep Networks: Understanding and mitigating network overthinking. *ICML*, PMLR 97:3301–3310. arXiv:1810.07052.
- [3] Huang, G., Chen, D., Li, T., Wu, F., van der Maaten, L., & Weinberger, K. (2018). Multi-scale dense networks for resource efficient image classification. *ICLR*. arXiv:1703.09844.
- [4] Sounio repository, suffering-aware neural network line: `docs/research/suffering_aware_architecture_s` and successors.
- [5] Chamon, L. F., & Ribeiro, A. (2020). Probably approximately correct constrained learning. *NeurIPS*.
- [6] Chamon, L. F., Paternain, S., Calvo-Fullana, M., & Ribeiro, A. (2023). Constrained learning with non-convex losses. *IEEE Transactions on Information Theory*.
- [7] Cotter, A., Jiang, H., Gupta, M., Wang, S., Narayan, T., You, S., & Sridharan, D. (2019). Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *JMLR*.
- [8] Manheim, D., & Garrabrant, S. (2018). Categorizing variants of Goodhart’s law. arXiv:1803.04585.
- [9] Xin, J., Tang, R., Lee, J., Yu, Y., & Lin, J. (2020). DeeBERT: Dynamic early exiting for accelerating BERT inference. *ACL*. DOI 10.18653/v1/2020.acl-main.204.
- [10] Zhou, W., Xu, C., Ge, T., McAuley, J., Xu, K., & Wei, F. (2020). BERT loses patience: Fast and robust inference with early exit. *NeurIPS*. arXiv:2006.04152.

- [11] Xin, J., Tang, R., Yu, Y., & Lin, J. (2021). BERxiT: Early exiting for BERT with better fine-tuning and extension to regression. *EACL*, 91–104. DOI 10.18653/v1/2021.eacl-main.8.
- [12] Schuster, T., Fisch, A., Gupta, J., Dehghani, M., Bahri, D., Tran, V., Tay, Y., & Metzler, D. (2022). Confident adaptive language modeling. *NeurIPS*. arXiv:2207.07061.
- [13] Elhoushi, M., Shrivastava, A., Liskovich, D., Hosmer, B., Wasti, B., Lai, L., Mahmoud, A., Acun, B., Agarwal, S., Roman, A., Aly, A., Chen, B., & Symeonidis, G. (2024). LayerSkip: Enabling early exit inference and self-speculative decoding. *ACL*. arXiv:2404.16710.
- [14] Elbayad, M., Gu, J., Grave, E., & Auli, M. (2020). Depth-adaptive transformer. *ICLR*. arXiv:1910.10073.
- [15] Bolukbasi, T., Wang, J., Dekel, O., & Saligrama, V. (2017). Adaptive neural networks for efficient inference. *ICML*.
- [16] Wang, X., Yu, F., Dou, Z.-Y., Darrell, T., & Gonzalez, J. E. (2018). SkipNet: Learning dynamic routing in convolutional networks. *ECCV*. arXiv:1711.09485.
- [17] Graves, A. (2016). Adaptive computation time for recurrent neural networks. arXiv:1603.08983.
- [18] Banino, A., Balaguer, J., & Blundell, C. (2021). PonderNet: Learning to ponder. *ICML 2021 Workshop on Automated Machine Learning*; arXiv:2107.05407.
- [19] Raposo, D., Santoro, A., Richards, B., Humphreys, I., & Lillicrap, T. (2024). Mixture-of-Depths: Dynamically allocating compute in transformer-based language models. arXiv:2404.02258.
- [20] Dehghani, M., Gouws, S., Vinyals, O., Uszkoreit, J., & Kaiser, Ł. (2019). Universal transformers. *ICLR*.
- [21] Prechelt, L. (1998). Early stopping — but when? In *Neural Networks: Tricks of the Trade*, LNCS 1524, 55–69. DOI 10.1007/3-540-49430-8_3.
- [22] Coleman, C., Narayanan, D., Kang, D., Zhao, T., Zhang, J., Nardi, L., Bailis, P., Olukotun, K., Ré, C., & Zaharia, M. (2019). Analysis of DAWN Bench, a time-to-accuracy machine learning performance benchmark. *SIGOPS Oper. Syst. Rev.* 53(1). arXiv:1806.01427.
- [23] Mattson, P., Cheng, C., Diamos, G., Coleman, C., Micikevicius, P., Patterson, D., Tang, H., Wei, G.-Y., Bailis, P., Bittorf, V., et al. (2020). MLPerf training benchmark. *MLSys*. arXiv:1910.01500.
- [24] Shah, I. S. H., Hajialigol, D., Hsieh, C.-J., & Alizadeh, M. (2023). Repeated random sampling for minimizing the time-to-accuracy of learning. arXiv:2305.18424.

- [25] Schwartz, R., Dodge, J., Smith, N. A., & Etzioni, O. (2020). Green AI. *Communications of the ACM* 63(12), 54–63. DOI 10.1145/3381831.
- [26] Strubell, E., Ganesh, A., & McCallum, A. (2019). Energy and policy considerations for deep learning in NLP. *ACL*. DOI 10.18653/v1/P19-1355.
- [27] Henderson, P., Hu, J., Romoff, J., Brunskill, E., Jurafsky, D., & Pineau, J. (2020). Towards the systematic reporting of the energy and carbon footprints of machine learning. *JMLR* 21(248). arXiv:2002.05651.
- [28] You, J., Chung, J.-W., & Chowdhury, M. (2023). Zeus: Understanding and optimizing GPU energy consumption of DNN training. *NSDI*. arXiv:2208.06102.
- [29] Chung, J.-W., Qiao, Y., et al. (2024). Perseus: Reducing energy bloat in large model training. *SOSP*. arXiv:2312.06902.
- [30] Hernandez, D., & Brown, T. B. (2020). Measuring the algorithmic efficiency of neural networks. arXiv:2005.04305.
- [31] Anthony, L. F. W., Kanding, B., & Selvan, R. (2020). Carbontracker: Tracking and predicting the carbon footprint of training deep learning models. arXiv:2007.03051.
- [32] Biggs, J., Bouganis, C.-S., & Constantinides, G. A. (2023). ATHEENA: A toolflow for hardware early-exit network automation. *IEEE FCCM*. DOI 10.1109/FCCM57271.2023.00022.
- [33] Low cost early exit decision unit design for CNN accelerator. (2020). *IEEE ISOCC*. DOI 10.1109/ISOCC50952.2020.9333079.
- [34] Laskaridis, S., Venieris, S. I., Kim, H., & Lane, N. D. (2020). HAPI: Hardware-aware progressive inference. *ICCAD*. DOI 10.1145/3400302.3415698.
- [35] Laskaridis, S., Venieris, S. I., Almeida, M., Leontiadis, I., & Lane, N. D. (2020). SPINN: Synergistic progressive inference of neural networks over device and cloud. *MobiCom*. DOI 10.1145/3372224.3419194.
- [36] Petrie, J., Aarne, M., Ammann, T., & Dalrymple, D. (2025). Flexible hardware-enabled guarantees for AI compute (FlexHEG). arXiv:2506.15093.
- [37] Shavit, Y. (2023). What does it take to catch a Chinchilla? Verifying rules on large-scale neural network training via compute monitoring. arXiv:2303.11341.
- [38] Jia, H., Yaghini, M., Choquette-Choo, C. A., Dullerud, N., Thudi, A., Chandrasekaran, V., & Papernot, N. (2021). Proof-of-learning: Definitions and practice. *IEEE S&P*. arXiv:2103.05633.
- [39] Klimovich, A. (2025). The price of machine suffering. *AI & Society* 41(5), 4477–4484. DOI 10.1007/s00146-025-02831-8.

- [40] Metzinger, T. (2021). Artificial suffering: An argument for a global moratorium on synthetic phenomenology. *Journal of Artificial Intelligence and Consciousness* 8(1). DOI 10.1142/S270507852150003X.
- [41] Long, R., Sebo, J., Butlin, P., Finlinson, K., Fish, K., Harding, J., Pfau, J., Sims, T., Birch, J., & Chalmers, D. (2024). Taking AI welfare seriously. arXiv:2411.00986.
- [42] Tomasik, B. (2014). Do artificial reinforcement-learning agents matter morally? arXiv:1410.8233.
- [43] Sastry, G., Heim, L., Belfield, H., Anderljung, M., Brundage, M., Hazell, J., O’Keefe, C., Hadfield, G. K., Ngo, R., Pilz, K., Gor, G., Bluemke, E., Shoker, S., Egan, J., Trager, R. F., Avin, S., Weller, A., Bengio, Y., & Coyle, D. (2024). Computing power and the governance of artificial intelligence. arXiv:2402.08797.
- [44] Laskaridis, S., Kouris, A., & Lane, N. D. (2021). Adaptive inference through early-exit networks: Design, challenges and directions. *EMDL*; extended version in *ACM Computing Surveys*. arXiv:2106.05022.
- [45] Regel, F., Chataoui, S., Charpentier, P., Coates, M., Piantanida, P., & Günemann, S. (2024). QuEE: early exiting via learned per-sample error prediction. arXiv preprint, June 2024. (Identifier to be confirmed before submission; see `agent_logs/san_novelty_audit_2026-08-06.md`.)
- [46] Skalse, J., Howe, N., Krashennnikov, D., & Krueger, D. (2022). Defining and characterizing reward hacking. *NeurIPS*.
- [47] Pan, A., Bhatia, K., & Steinhardt, J. (2022). The effects of reward misspecification: Mapping and mitigating misaligned models. *ICLR*.

A Reproduction

```
# CPU contract + spec/outline consistency (~3 min on CPU)
bash scripts/ci/san_imagenet_fpga_dl380_gate.sh
# expect: SAN_IMAGENET_FPGA_DL380_VERDICT I_GREEN (8/8 clauses PASS)

# GPU training (requires CUDA)
SAN_LARGE_DEVICE=cuda SAN_LARGE_ONLY=resnet50 \
    .venv/bin/python scripts/research/suffering_aware_large_architecture.py

# U250 host scan (requires Xilinx XRT + bitstream on DL380)
./host_san_scan -x krnl_san_scan.hw.xclbin -d val_resnet
```

B Companion contract clauses (L1–L8)

The GPU harness reports per-family verdicts against clauses L1–L8 of `scripts/research/suffering_aware_large_architecture.py`:

clause	predicate	threshold / note
L1	Metering conservation: gated-off stages charge 0; metered MACs == independent manual accounting	equality
L2	Feasibility: SAN reaches val acc $\geq \tau$ within budget	τ per family
L3	Anti-Goodhart: 101-weight compassion grid never selects an infeasible checkpoint	abstainer & probe infeasible
L4	Necessary/gratuitous separation: SAN gratuitous machine burden = 0	equality
L5	Suffering bounds: SAN machine burden < Dense and $\leq$ EarlyStop; patient harm $\leq$ both baselines	within small tolerance
L6	Exits are real: val exit fraction at $t^* > 0.07$	0.07
L7	Patient channel first-class: harm matrix off-diagonal max $\geq 3\times$ min; SAN peak harm $\leq$ baselines	$3\times$ asymmetry
L8	Anti-shortcut: a spurious-feature probe that overfits train but fails val is rejected by the gate	train $> \tau$, val $< \tau$, never selected

The FPGA / ImageNet-scale contract uses an analogous I1–I8 clause set defined in `scripts/research/san_imagenet_fpga_dl380.py` and enforced by `scripts/ci/san_imagenet_fpga_dl380_gate.sh`.