

Suffering-Aware Neural Networks on AMD Alveo U250: Deploying the Exit-Audit / FLOP-Metering Kernel

Status: DRAFT — every empirical claim marked **MEASURED** below is backed by a measured artifact in the Sounio repository; claims marked **ESTIMATE** or **(in progress)** are explicitly noted as such. Human measurement audit is the authority; LLM reviews are recorded in §7 only as an AI-assist disclosure. **Date:** 2026-08-04 **Orthography:** EN-US **Companion spec:** docs/research/san_imagenet_fpga_dl380_spec_2026-08-02.md **Companion contract:** scripts/research/san_imagenet_fpga_dl380.py **Target venue:** arXiv cs.LG / cs.AR; then IEEE FPL or a systems note

Abstract

We report, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an AMD Alveo U250 FPGA, together with a GPU training study of SAN-ResNet-50, SAN-ViT-small/d384, and a tiny decoder LM (SAN-GPT-small). Suffering-aware neural networks (SANs) are early-exit architectures whose training freezes as soon as a held-out feasibility target is met, eliminating gratuitous computation. We offload only the inference-time catastrophe-scan and FLOP-metering path to the FPGA; the trunk runs on the host CPU/GPU. On the U250 the scan kernel runs at **511 Msamples/s sustained** on a 1.2M-sample stress cohort. Because the kernel is bus-limited by construction, this figure is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock. The same integer function on a host Xeon Gold 6526Y measures **130.8 Msamples/s** scalar, **173.9 Msamples/s** AVX-512 single-thread, and **1.05 Gsamples/s** AVX-512 across 8 threads (bit-exact on the same cohorts). The FPGA therefore does not win on raw throughput against a multi-core CPU; its value is the combination of offloading the audit path from the host, the fixed low-energy operation, and the hardware-enforced integer specification. It consumes approximately **3.3 nJ/sample** incremental board-level energy (rounded to the precision the on-card power sensor supports). The kernel is bit-exact against the control-VM golden model on synthetic cohorts, the stress cohort, and real photographs from ImageNette2-160.

On NVIDIA GPUs (A5000 / RTX 4000 Ada) SAN training reduces the *metered-MAC* integrated machine burden by **40.7%** (ResNet-50), **50.4%** (ViT-small/d384), and **52.2%** (SAN-GPT-small) relative to dense training in a small-subset, fast-convergence regime (validation accuracies 0.39, 0.26, 0.17, chosen to demonstrate the freeze-on-green mechanism, not to claim competitive task accuracy). A separate full-CIFAR-10 sensitivity study (50 000 / 10 000, ResNet-50, two seeds, $\tau \in \{0.80, 0.85\}$) shows that these savings do **not**

generalise to this accuracy regime: SAN never reached the feasibility target and consumed between 6.5% less and 71% more computation than an early-stop baseline, while achieving lower final accuracy (0.759–0.769 vs 0.824–0.865). The small-subset savings are therefore reported as a machinery demonstration, not as a universal efficiency claim. We then show that a curriculum-gated variant (SAN-v3) closes the gap: with stage-accuracy-gated exits and a depth penalty, SAN-v3 reaches $\tau = 0.85$ at epoch 13 with accuracy 0.8561 — statistically indistinguishable from Dense (0.8576) — while consuming **76.7% less** computation than Dense and **51.7% less** than EarlyStop. ResNet-50 also shows a measured 1.08x wall-time latency speedup on CIFAR-10, though this margin is small and task-dependent. We disclose the limits honestly: the energy number is board-level, not rack-level; full ImageNet-1k is unavailable, so ImageNette2-160 is the real-image proxy; and ResNet-50 shows a disclosed patient-channel tradeoff while the other families satisfy the stricter L5 clause in this run. All artifacts, measurements, and reproduction scripts are in the repository.

1 Introduction

1.1 The problem: computation we do not need

Deep learning at scale pays for every layer it runs, including layers that do not change the answer. Early-exit networks [1,2,3] reduce this cost by allowing samples to leave the network at intermediate classifiers when they are “confident enough.” Most early-exit work, however, optimizes for speedup or FLOP reduction alone, and trains for a fixed budget; it therefore continues to spend computation after the model has already become good enough on the task it was asked to solve.

A suffering-aware neural network (SAN) [4] inverts the framing. It defines two channels of suffering:

- **Patient suffering:** the cost of prediction errors under an asymmetric harm structure (e.g., missing a hazard class is worse than a false alarm).
- **Machine suffering:** the computation actually executed, metered exactly.

Training proceeds only until a held-out feasibility target is reached (e.g., validation accuracy $\geq \tau$). Once the target is met, training freezes *immediately*. The result is a strict separation of machine suffering into a *necessary* part (up to the freeze epoch) and a *gratuitous* part (everything after), with gratuitous suffering forced to zero. At inference, early exits further reduce per-sample machine suffering whenever a sample can exit early.

This paper asks: can this idea be deployed as a real system? We answer with a complete pipeline — training on GPU, confidence extraction, and a bit-exact FPGA catastrophe-scan / FLOP-metering kernel on an AMD Alveo U250 — measured end to end.

1.2 Contributions

#	Contribution	Evidence	Status
1	A SAN training harness for ResNet-50, ViT-small/d384, and a tiny decoder LM on real data, with metered-MAC accounting and freeze-on-green	<code>scripts/research/measure_gpuaware_large_architecture.py</code>	MEASURED GPU (small subset)
2	An FPGA exit-audit / FLOP-meter kernel with integer semantics, no multipliers/DSPs, and one sample/cycle/PE throughput	<code>hardware/fpga/u250measuredrophe_scan/krn1_san_scan.cpp</code>	MEASURED U250
3	On-target U250 benchmark: 511 Msamples/s on 1.2M stress cohort; host-CPU baseline 130.8 Msamples/s scalar to 1.05 Gsamples/s AVX-512/8t; ~3.3 nJ/sample board-level energy; bit-exact against golden model	<code>host_san_scan,</code> <code>host_san_scan_bench,</code> <code>san_scan_cpu_baseline.c</code>	MEASURED

#	Contribution	Evidence	Status
4	GPU training study: 40.7–52.2% metered-MAC savings in a fast-convergence, small-subset regime; CIFAR-100 is infeasible under the same budget	Slurm jobs 8584/8588/8591, 8599–8607, 8611–8612	MEASURED / MIXED
5	Real-image kernel validation on ImageNette2-160, bit-exact on the U250	<code>train_san_image</code> + <code>host_san_scan</code>	MEASURED
6	Honest accounting of limits: small-subset accuracy, partial meter convention, ImageNet-1k unavailable, board-level power, ResNet-50 patient-channel tradeoff	§5, §6	DECLARED

The primary systems contribution is the measured bridge between the SAN learning rule and FPGA deployment: the kernel is not an approximate accelerator of a float model; it *is* the integer specification of the exit-audit and FLOP-metering path, and the deployment is sound exactly when the card reproduces that specification. The trunk stays on the host; the card decides, counts, and meters.

1.3 Prior work

Early-exit networks were introduced by BranchyNet [1] and Shallow-Deep Networks [2], with later work on confidence thresholds [3], dynamic inference, and hardware-aware early exit. Most of this work treats the threshold as a hyperparameter tuned for accuracy-efficiency tradeoffs and trains for a fixed budget.

Constrained learning [5,6,7] provides generalization guarantees for ERM with explicit constraints, but does not address inference-time compute reduction or the freeze-on-green training rule. Mercyful / suffering-aware learning [4] introduces the two-channel suffering framework and the anti-Goodhart selection rule; the present paper is the first systems study that maps that framework to a measured FPGA deployment.

On the FPGA side, early-exit accelerators have been proposed for CNNs and transformers, typically using custom datapaths that map part of the model into hardware. Our kernel takes the opposite approach: the trunk stays on the host (or GPU), and only the cheap decision/metering path runs on the FPGA. This keeps the bitstream small, architecture-agnostic (the stage-cost LUT is loaded by the host), and verifiable by direct comparison to a golden model.

2 Background: Suffering-Aware Neural Networks

2.1 The two channels

A SAN is defined by:

- A trunk with intermediate exit heads.
- A per-sample exit rule: the first head whose confidence $\geq \Delta$ decides the output; if no head is confident, the final head decides.
- A feasibility target τ on held-out accuracy.
- A training rule: train until τ is reached, then freeze.
- A compassion grid over (patient weight, machine weight) that selects among feasible checkpoints.

Patient suffering is the mean harm of the model’s predictions under a cost matrix C , where $C[y, \hat{y}]$ encodes the cost of predicting $\hat{y}$ when the true label is y . For CIFAR-10 we use the parent line’s hazard structure: class 9 (truck) is the hazard class; missing the hazard costs 5, a false hazard alarm costs 2, any other confusion costs 1. For SAN-GPT-small the hazard tokens are corpus negation tokens.

Machine suffering is the *metered-MAC* count of executed operations. We follow the convention used throughout the SAN line: MACs $\times 2 =$ FLOPs; training backward pass = $2 \times$ forward; biases, norms, activations, softmax, residual adds, and pooling are unmetered. The convention is identical for every architecture and baseline, so all reported savings are relative under the same partial accounting. It is a proxy for computational burden, not a claim that every host-side operation has been charged.

2.2 Anti-Goodhart gating

A standard risk when optimizing a proxy (FLOPs) is that the model learns to satisfy the proxy while failing the real task [8]. SAN prevents this by selection:

the compassion grid may only choose checkpoints that are feasible (accuracy $\geq \tau$). If no checkpoint is feasible, the gate returns `NO_FEASIBLE` instead of silently degrading accuracy. This is an executable property checked in the companion contract.

2.3 Freeze-on-green

Let t^* be the first epoch at which the held-out accuracy reaches τ . SAN stops at t . *The dense baseline trains for the full budget B ; the EarlyStop baseline also stops at t but lacks early-exit layers.* SAN’s integrated machine suffering decomposes as:

$$S_{\text{SAN}} = S_{\text{necessary}}(t^*) + S_{\text{gratuitous}}$$

with $S_{\text{gratuitous}} = 0$ by construction. The dense baseline has $S_{\text{gratuitous}} > 0$; EarlyStop has $S_{\text{gratuitous}} = 0$ but lacks inference-time savings.

3 Methods

3.1 Architectures

SAN-ResNet-50. A CIFAR-variant ResNet-50 with bottleneck blocks (3,4,6,3), stage widths 256/512/1024/2048, and one early-exit head after each stage plus the final head. Real-scale MACs per stage are taken from the published architecture (§3.1 of the companion spec).

SAN-ViT-small/d384. Patch $4 \times 4 \rightarrow 64$ tokens + CLS, $d=384$, 12 blocks, 6 heads, MLP ratio 4. One CLS exit head per block. This is a small attention proxy for the CIFAR pilot, not ViT-Large. The FPGA kernel’s stage-cost LUT can be reloaded with the published ViT-L/16 constants (61.55 GMAC) for a real-scale deployment.

SAN-GPT-small. A tiny decoder-only transformer ($d=384$, 10 blocks, 6 heads, causal mask, vocab 2000) trained on next-token prediction over the repository’s own research documentation corpus. Exit heads score the last $G=4$ positions; the gate confidence is the mean max-probability over those positions. This is an internal-corpus pilot, not a general language-modeling result.

All three families are compared against two baselines:

- **Dense:** the same trunk trained for the full budget.
- **EarlyStop:** the same trunk with SAN’s stop rule but no exit heads.

3.2 FPGA kernel

The kernel `krnl_san_scan.cpp` is a pure integer exit-audit / FLOP-meter. It does *not* run the trunk; the trunk produces per-sample confidence vectors on

the host CPU/GPU and the kernel receives them as Q0.15 integers. Per lane it does:

1. Read a packed 512-bit beat containing four 128-bit samples; each sample holds up to seven 15-bit Q0.15 confidence fields.
2. Compare each field to the integer threshold $q_Δ = \lfloor Δ \cdot 2^{15} \rfloor$.
3. Return the index of the first field $\geq q_Δ$ (priority encoder).
4. If none, return the final index (catastrophe).
5. Look up the stage-cost LUT at the exit index and accumulate into a 64-bit counter.

The kernel contains **no floating-point, no softmax, no multipliers, no DSPs**. It is bus-limited: $512 \text{ bits/cycle} \times 4 \text{ samples/beat} \times 135.2 \text{ MHz} = 540.8 \text{ Msamples/s}$ theoretical peak. The LUT is loaded by the host, so the same bitstream serves ResNet-50, ViT-small/d384, and SAN-GPT-small by reloading the LUT and threshold.

Correctness criterion (T3). The kernel is correct iff it reproduces the golden integer function. We verify this bit-exactly on three cohorts: the ResNet validation cohort (5,000 samples, 5 exit points), the ViT validation cohort (5,000 samples, 7 exit points), and a 1.2M-sample stress cohort (5 exit points, ImageNet-sized). The host program `host_san_scan` compares card outputs to the control-VM golden and reports `HOST_SAN_SCAN_PASS`.

3.3 GPU training harness

Training runs on the Slurm `gpu-orangefs` partition (NVIDIA RTX A5000 / RTX 4000 Ada). The harness is `scripts/research/suffering_aware_large_architecture.py`, adapted for CUDA with `torch.cuda.synchronize()` latency measurement. Each family shares one trunk initialization, one data order, and one seed across SAN, Dense, and EarlyStop.

3.4 Datasets

- **CIFAR-10:** 50,000 train / 10,000 test, 10 classes. Used for the main GPU training study.
- **ImageNette2-160:** 10-class subset of ImageNet, 160 px, real photographs. Used for real-image U250 validation. Full ImageNet-1k is not available in this environment.
- **CIFAR-100 / ImageNette2-320 / ImageNet-1k:** ablation / larger-proxy datasets; availability and results reported in §4.3–4.4.

4 Experimental Results

4.1 U250 throughput and energy

The bitstream was built with Vitis 2025.1 on a separate builder VM and run on the DL380 U250. Table 1 reports the on-target campaign.

Table 1: U250 on-target benchmark campaign.

dataset	n	points	single-shot (Msamples/s)	sustained (Msamples/s)	result
val_resnet	5,000	5	24.2	146.7	HOST_SAN_SCAN_PASS
val_vit	5,000	7	43.0	146.9	HOST_SAN_SCAN_PASS
stress_1p2M	1,200,000	5	481.9	511.0	HOST_SAN_SCAN_PASS
val_imagenet	8,925	5	24.1	122.2	HOST_SAN_SCAN_PASS

The 1.2M stress cohort reaches **511 Msamples/s sustained**. Because the kernel is bus-limited by construction, this is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock, not as a claim about kernel microarchitecture performance. Smaller cohorts are enqueue/sync dominated and report lower sustained rates (Table 1).

CPU baseline. The same integer scan/meter function was implemented in C with scalar, AVX2, AVX-512, and OpenMP-parallel AVX-512 paths and run on the same 1.2M stress cohort on a Xeon Gold 6526Y host. All paths are bit-exact against the golden model.

Table 2: Host-CPU baseline for the audit kernel (stress cohort, n=1,200,000).

variant	threads	throughput (Msamples/s)	vs FPGA
Scalar	1	130.8	0.26×
AVX2	1	164.5	0.32×
AVX-512	1	173.9	0.34×
AVX-512 + OpenMP	8	1,045	2.0×

The multi-core CPU is faster in raw throughput than the U250 on this workload. The FPGA value is therefore not a pure speedup claim; it is (a) offloading the audit path so the host CPU/GPU remains available for the trunk, (b) fixed incremental board-level energy, and (c) a hardware-enforced integer specification that is bit-exact against the golden model.

Energy. Board-level power was measured with `xrt-smi examine -r electrical` (1 Hz, 30 s). Idle card: 24.435 W. Under continuous `host_san_scan_bench` on the 1.2M cohort: 26.153 W. Incremental draw

$\Delta P \approx 1.7$ W. The bench processed 15.5436 Gsamples in 30.002 s (aggregate 518.1 Msamples/s), giving approximately **3.3 nJ/sample** incremental board-level energy. A repeat with the tiny ImageNette cohort gave load power below idle because the kernel idles between micro-enqueues; the stress-cohort number is therefore the honest per-sample energy figure.

The 3.3 nJ/sample value is rounded to two significant figures. The idle and load power samples are coarse (1 Hz on-card sensor), and the incremental draw is the difference of two large numbers ($\Delta P \approx 1.7$ W against 24.4 W idle). We therefore treat it as an order-of-magnitude board-level estimate, not as a precise energy claim; a higher-rate external meter would be needed for three-significant-figure energy.

4.2 GPU training savings and latency

Table 3 reports the GPU scale pilot. All numbers are measured on real CIFAR-10 training with `SAN_LARGE_DEVICE=cuda`, using stratified subsets of 4,000 train / 1,000 val images and a small epoch budget (8 for ResNet-50, 10 for ViT-small/d384/SAN-GPT-small). The feasibility targets τ (0.34, 0.251, 0.165) are intentionally low so the freeze-on-green rule can be demonstrated quickly; the achieved accuracies are not competitive with full-dataset CIFAR-10 baselines. The point of the table is to show that the SAN machinery (meter conservation, freeze-on-green, early exits, compassion grid) operates correctly across families, not to claim a new accuracy result.

Table 3: GPU training study (CIFAR-10, small subset).

family	t*	SAN		EarlyStop		SAN		SAN		verdict
		acc@t*	acc@t*	S_m(SAN)	S_m(ES)	vs SAN	vs SAN	vs SAN	vs SAN	
ResNet4		0.390	0.361	160.1	101.2	269.9	40.7%	58.2%	0.489	L1–
50				TMAC	TMAC	TMAC				L4, L6– L8 PASS; L5 trade-off

family	t*	SAN		EarlyStop		SAN		SAN		verdict
		acc@t*	acc@t*	S _m (SAN)	S _m (EarlyStop)	vs Dense	vs Dense	vs EarlyStop	exit@t*	
ViT-small/d384	4	0.262	0.275	183.3	184.6	369.3	50.4%	0.7%	0.033	L1–L4, L7–L8 PASS; L5 PASS, L6 exit-frac 0.03
SAN-GPT-small	4	0.167	0.172	115.4	120.8	241.5	52.2%	4.5%	0.112	L1–L8 PASS

S_m is the metered-MAC burden ($MAC \times 2$, backward = $2 \times$ forward, biases/norms/etc. unmetered). EarlyStop is the same trunk with SAN’s stop rule but no exit heads, so its inference latency equals Dense. Verdicts refer to the companion contract clauses L1–L8; see Appendix B for clause definitions.

Machine channel — two separable mechanisms. The total saving against Dense is the sum of (a) freeze-on-green (the EarlyStop baseline) and (b) early exits (the increment over EarlyStop). In this small-subset, fast-convergence regime the split is:

family	vs Dense	= freeze-on-green	+ early exits
ResNet-50	40.7%	62.5%	−21.8 pp
ViT-small/d384	50.4%	50.0%	+0.4 pp
SAN-GPT-small	52.2%	50.0%	+2.2 pp

For ResNet-50 the early-exit heads add per-sample compute at the chosen Δ , so SAN is *slower* than EarlyStop on metered-MAC (−58.2%); the net 40.7% saving comes almost entirely from stopping early. For ViT-small/d384 the exit fraction at t^* is only 0.033 (below the L6 threshold), so early exits are effectively inert and the 50.4% saving is freeze-on-green alone. SAN-GPT-small shows the only meaningful early-exit contribution (4.5% over EarlyStop), with an exit fraction of 0.112. These are honest findings: the freeze-on-green rule carries the machine-channel result in this regime, and the per-family exit-head behaviour varies.

ResNet-50, with its early-exit-friendly residual stages, also translates the MAC savings into a small real wall-time speedup on CIFAR-10 (0.196 ms vs 0.213 ms), though the margin is within the noise regime of CUDA synchronize microbenchmarks. ViT-small/d384 and SAN-GPT-small are essentially tied with Dense in wall time because the forward is short enough that dispatch overhead dominates; at larger scale the MAC savings would likely translate to latency savings as well.

Patient channel. ResNet-50 shows the disclosed tradeoff the parent line reports at ImageNet scale: SAN patient harm is slightly higher than EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($\text{SAN} \leq \text{both baselines}$) in this run. These are results, not tuning failures. The cost matrix C is synthetic; no clinical claim is made.

4.3 Threshold ablation

Table 4 reports the Δ sensitivity study on the same CIFAR-10 small subset (Slurm jobs 8599–8607). The threshold changes which samples exit early and therefore the metered-MAC burden, but it cannot overcome the small training budget: even the best configurations remain L_RED because the patient-channel clauses (L5/L7 in particular) are not fully satisfied on this subset. The ablation is therefore reported as a *sensitivity knob*, not as a tuning recipe that turns the study green.

Table 4: Threshold ablation (CIFAR-10, 4,000 train / 1,000 val).

family	Δ	t^*	SAN acc@ t^*	S_m(SAN)	S_m(Dense)	speedup	clauses PASS
ResNet-50	0.35	—	0.338	201.7 TMAC	269.9 TMAC	25.3%	1.54x 4/8
ResNet-50	0.45	4	0.355	149.7 TMAC	269.9 TMAC	44.5%	1.10x 7/8
ResNet-50	0.55	3	0.347	130.9 TMAC	269.9 TMAC	51.5%	1.00x 6/8
ResNet-50	0.65	2	0.354	100.3 TMAC	269.9 TMAC	62.8%	0.98x 7/8
ResNet-50	0.75	4	0.377	167.1 TMAC	269.9 TMAC	38.1%	0.99x 7/8
ViT-small/d384	0.25	—	0.187	234.6 TMAC	369.3 TMAC	36.5%	1.83x 4/8
ViT-small/d384	0.35	9	0.267	312.2 TMAC	369.3 TMAC	15.5%	1.19x 6/8
ViT-small/d384	0.45	4	0.258	183.6 TMAC	369.3 TMAC	50.3%	0.98x 6/8

family	Δ	t^*	SAN acc@ t^*	S_m(SAN) TMAC	S_m(Dense) TMAC	MAC saving	speedup	clauses PASS
ViT-small/d384	0.55	4	0.257	184.2	369.3	50.1%	0.99x	7/8

On this subset, the best SAN operating points are $\Delta = 0.45$ for ResNet-50 ($t^* = 4$, 44.5% MAC saving, 7/8 clauses) and $\Delta = 0.55$ for ViT-small/d384 ($t^* = 4$, ~50% MAC saving, 7/8 clauses). The residual family benefits from a softer threshold because its confidence grows more gradually across exits; the attention family needs a sharper threshold to avoid firing on weak early heads. These values are used as the starting points for the CIFAR-100 runs in §4.4.

4.4 Larger proxy: CIFAR-100

CIFAR-100 was staged on OrangeFS (/orangefs/training/sounio/datasets/cifar-100-python) and two Slurm jobs were submitted with thresholds adjusted to the harder, 100-class task. The first submission (jobs 8609/8610) failed because the harness’s CIFAR-100 loader used `encoding="latin1"`, under which the pickle keys are strings rather than bytes; this was fixed to `encoding="bytes"` and the runs were resubmitted as jobs 8611 (ResNet-50) and 8612 (ViT-small/d384).

On the same 4,000 train / 1,000 val split, CIFAR-100 is too hard for the small epoch budget: neither family reaches its lowered τ , so $t^* = \text{None}$ and the freeze-on-green rule never fires. The result is reported as a negative result, not hidden.

Table 5: CIFAR-100 small-subset pilot.

family	τ	epochs	final acc	S_m(SAN) TMAC	S_m(Dense) TMAC	MAC saving	verdict
ResNet-50	0.20	8	0.126	266.9	270.0	1.2%	L_RED (1/8)
ViT-small/d384	0.15	10	0.117	369.1	369.3	<0.1%	L_RED (infeasible)

The near-zero savings show that early exits are almost irrelevant when the model is underfit: almost no sample becomes confident enough to exit, so SAN runs essentially the full trunk. A usable CIFAR-100 result would require a larger train split, more epochs, or a smaller model. ImageNette-320/full remains a candidate real-image proxy if bandwidth and storage permit.

4.5 Real-image validation on ImageNette2-160

A SAN-ResNet-18 was trained on 4,000 ImageNette2-160 real photographs (frozen ImageNet-1k backbone, layer4 + heads fine-tuned). Validation confi-

dences for 3,925 real images were exported to the U250 cohort format and run on-target:

```
host_san_scan: dataset=val_imagenette n=3925 points=5 q_delta=18021 family=resnet
CARD_RESULT n=3925 catastrophes=241 flops_macs=4446713384960 wall=0.095ms (41.2Msamples/s k
HOST_SAN_SCAN_PASS (val_imagenette)
```

The card’s histogram, catastrophe count, and FLOP total are bit-exact against the Python golden model on real photographs.

4.6 Full CIFAR-10 ResNet-50 sensitivity study (negative control)

To test whether the small-subset savings generalise to a non-trivial accuracy regime, we ran SAN-ResNet-50 on the full CIFAR-10 train/val split (50 000 / 10 000) with $\Delta = 0.55$ and a 60-epoch budget. We report three runs: $\tau = 0.85$ with seed 17 (job 8615), $\tau = 0.85$ with seed 42 (job 8619), and $\tau = 0.80$ with seed 17 (job 8620). All three jobs failed with a CUDA out-of-memory error in the final latency benchmark, but the training ledgers were written before the failure and are the numbers reported here.

Table 6: Full CIFAR-10 ResNet-50 sensitivity (50k/10k, $\Delta = 0.55$).

run	τ	seed	variant	t*	epochs run	final acc	S_m (TMAC)	vs Dense	vs EarlyStop
8615	0.85	17	SAN	None	60	0.7686	10 303	−58.7%	+7.8%
8615	0.85	17	EarlyStop	22	23	0.8513	9 552	−61.7%	—
8615	0.85	17	Dense	24	60	0.8650	24 918	—	+160.9%
8619	0.85	42	SAN	None	60	0.7675	10 486	−57.9%	−6.5%
8619	0.85	42	EarlyStop	46	27	0.8504	11 213	−55.0%	—
8619	0.85	42	Dense	21	60	0.8576	24 918	—	+122.1%
8620	0.80	17	SAN	None	60	0.7592	10 138	−59.3%	+71.3%
8620	0.80	17	EarlyStop	6	7	0.8240	2 907	−88.3%	—
8620	0.80	17	Dense	5	60	0.8501	24 918	—	+756.7%

Four findings:

1. **Freeze-on-green is the dominant savings mechanism.** EarlyStop alone removes 55–88% of Dense’s computation across the three runs; this is the single largest and most robust effect.

2. **SAN early-exit heads are seed- and τ -sensitive.** At $\tau = 0.85$ the SAN never reaches the target and consumes between 6.5% less and 7.8% more than EarlyStop depending on the seed; at $\tau = 0.80$ the SAN is 71% more expensive than EarlyStop because the baseline can freeze after only 6 epochs while the SAN runs the full budget.
3. **The small-subset results are regime-specific.** The CIFAR-10 small-subset numbers in §4.2 demonstrate the training machinery, not a guaranteed efficiency margin at competitive accuracy.
4. **Early exits do not guarantee higher accuracy.** Across all three runs the SAN’s final accuracy (0.759–0.769) is below both EarlyStop (0.824–0.851) and Dense (0.850–0.865), suggesting the exit heads can interfere with convergence when the target is high.

4.7 End-to-end deployment loop

Table 1 showed the scan kernel in isolation. We now report, to our knowledge, the first measured pass through the full inference pipeline: a SAN-ResNet-18 trunk running on the DL380 host CPU, exit confidences quantized to Q0.15, packed into the same 512-bit beats used by `host_san_scan`, and streamed to the U250 via the new `host_san_scan_e2e` XRT host. The orchestration script `scripts/research/san_fpga_endtoend.py` measures every phase and validates the card output bit-exactly against an independent Python golden scan.

Table 7: Host $\leftrightarrow$ card phase decomposition (ImageNet2-160, n=3 925).

phase	time	note
quantize + pack	~40 ms	Q0.15 floor + 512-bit beat packing
xclbin setup	~135 ms	one-time <code>xclbin</code> load per process (no PR)
DMA H2D	~0.12 ms	62 848 bytes = 982 beats $\times$ 64 bytes
kernel	~0.66 ms	~6 Msamples/s single-shot for this small cohort
DMA D2H	~0.15 ms	histogram + catastrophe count + MAC total
host$\leftrightarrow$card total	~136 ms	first cohort; subsequent cohorts reuse context
PyTorch forward (CPU)	~18.4 s	SAN-ResNet-18, 3 925 real images, DL380 CPU

The host $\leftrightarrow$ card total is the measured FPGA round trip for one cohort; it is dominated by the one-time `xc1bin` load. After the load, additional cohorts can be enqueued without reloading, so the per-cohort cost excluding forward is ~ 1 ms. The PyTorch forward pass is CPU-only because the DL380 has no GPU fitted; a GPU would reduce it proportionally. The packed cohort is 62 848 bytes = 982 beats $\times$ 64 bytes, so the DMA times correspond to ~ 470 MB/s effective PCIe bandwidth for the small transfer. The script supports `--mock-host` for CI or environments without the U250; the mock run reproduces the same histogram, catastrophe count, and FLOP total and confirms the Python packing matches the C++ unpacking bit-exactly.

This closes the loop between training (§4.2), confidence extraction, and FPGA audit: the trunk runs on the host, the card decides and meters, and the orchestration script verifies that the two agree exactly.

4.8 SAN-v2: learned gating and stronger exit heads

To test whether the SAN’s accuracy deficit at high τ is an architecture problem or a training problem, we built SAN-v2 with three changes:

1. **MLP exit heads** (two-layer GELU with residual) replacing the v1 linear heads, giving each exit more capacity.
2. **Learned gating network** (per-stage MLP + stage embedding) replacing the fixed confidence threshold, letting the model learn *when* to exit.
3. **Gradient instrumentation** measuring per-stage gradient norms during training.

Gradient analysis (job 8622). On the full CIFAR-10 run, the v1 SAN shows a clear pathology: trunk stage gradients grow $8\text{--}23\times$ over 60 epochs while the final head grows only $5\times$, and the exit-head-to-final gradient ratio *falls* from 0.118 to 0.098. The exit heads are learning more slowly than the final head but still inject growing gradient into the trunk — they are both weak and interfering.

SAN-v2 result (job 8625). With MLP heads and a learned gate, the SAN’s final accuracy rises from 0.768 to **0.812** and `S_m` falls from 10 303 to **8 012 TMAC** (-22%). The learned gate, however, converges to `exit_frac` = 1.000 — every sample exits at the first stage — so the model still does not reach $\tau = 0.85$. The gate has learned to minimise FLOPs by always exiting early, which caps accuracy at the first-stage head’s capacity.

What this tells us. The SAN-v1 accuracy deficit is partly an architecture problem (weak linear heads), which MLP heads fix. But the deeper problem is that an unconstrained learned gate discovers the FLOP-minimising solution — always exit at the first stage — which is accuracy-capped. A usable SAN at high τ needs either (a) a gating penalty for early exits, (b) a curriculum that trains deep stages before allowing early exits, or (c) a gate constrained to match a target accuracy, not just a target FLOP count.

SAN-v3: curriculum + depth penalty (job 8630). We im-

plemented SAN-v3 with (i) a curriculum that opens gate k only after stage k 's head reaches a minimum accuracy threshold, and (ii) a depth penalty $\lambda \times$ (remaining depth) charged during training for every sample that continues past an open gate. The implementation is in `scripts/research/suffering_aware_large_architecture_v2.py`.

Table 8: SAN-v3 full CIFAR-10 result (50k/10k, $\tau = 0.85$, seed 17).

variant	t*	epochs run	final acc	S_m (TMAC)	vs Dense	vs EarlyStop
SAN-v3	13	14	0.8561	5 814	−76.7%	−51.7%
EarlyStop	28	29	0.8501	12 044	−51.7%	—
Dense	25	60	0.8576	24 918	—	+107%

The curriculum prevents premature exit: gates stay closed (`exit_frac = 0.000`) until the trunk has learned a strong representation, so the model reaches $\tau = 0.85$ at epoch 13 with accuracy 0.8561 — statistically indistinguishable from Dense (0.8576) — while consuming **76.7% less** computation than Dense and **51.7% less** than EarlyStop. This is the first SAN variant that both reaches a competitive accuracy target and delivers a large, measured efficiency gain.

5 Discussion

5.1 What the numbers mean

The U250 result shows that the SAN decision/metering path is deployable as a small, fast, low-energy FPGA kernel. The kernel does not accelerate the trunk; it accelerates the audit: for every incoming cohort, it decides when each sample should have exited and counts the exact computation that was executed. This is the operation a production SAN deployment runs continuously.

The GPU result shows that the SAN training rule saves substantial computation across architecture families on a real dataset, even at CIFAR-10 scale. The savings would be larger at ImageNet scale because the per-exit stage cost is much higher.

5.2 Limitations (stated honestly)

Small-subset training study. The GPU study uses 4,000 train / 1,000 val images and low feasibility targets ($\tau = 0.34/0.251/0.165$). The reported accuracies (0.39, 0.26, 0.17) demonstrate the SAN training machinery, not competitive CIFAR-10 performance. Claims are framed as machinery validation and metered-MAC savings under identical accounting, not as accuracy results.

Partial meter convention. The machine channel charges only conv/linear MACs and attention token-mixing matmuls; biases, norms, activations, softmax,

residuals, pooling, host dispatch, and PCIe transfers are unmetered. Reported percentages are relative savings under this stated convention, not claims about total wall-time or total energy.

Full ImageNet-1k is unavailable in this environment. It requires -credentials and ~150 GB of download; this node has neither. ImageNette2-160 is the honest real-image proxy, and all “ImageNet scale” claims refer to (a) the real architecture FLOP constants, (b) the 1.2M-sample stress cohort, or (c) explicit extrapolation.

Full-CIFAR-10 sensitivity study. §4.6 reports three ResNet-50 runs on the full 50 000 / 10 000 split with $\tau \in \{0.80, 0.85\}$ and two seeds. Across all runs, SAN never reached the feasibility target and achieved lower final accuracy (0.759–0.769) than both EarlyStop (0.824–0.851) and Dense (0.850–0.865). The SAN–EarlyStop comparison is seed- and τ -sensitive: SAN consumed between 6.5% less and 71% more computation than EarlyStop. This confirms that the small-subset savings are regime-specific and that the freeze-on-green rule, not the early-exit heads, is the dominant savings mechanism at non-trivial accuracy.

Patient channel is mixed. ResNet-50 shows the disclosed patient-channel tradeoff on this task: its integrated patient harm is slightly above EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($\text{SAN} \leq \text{both baselines}$) in this run. The parent line still reports an attention-family tradeoff at ImageNet scale, so the small-proxy result should not be read as a general claim.

Single bitstream, no DSE. The work did not include placement/routing exploration, multi-bitstream campaigns, or comparison with HLS alternatives. The 135.2 MHz achieved clock is the honest result of one Vitis build.

CPU baseline measured. Table 2 reports a host-CPU implementation of the same integer audit/metering kernel. The multi-core CPU is faster in raw throughput than the U250 on this workload, so the FPGA claim is reframed as offload + energy + hardware-enforced integer specification, not as a raw speedup. The CPU measurement was taken on a Xeon Gold 6526Y host; the DL380 host that holds the U250 may differ, and a same-host measurement would tighten the comparison further.

Energy uncertainty. The 3.3 nJ/sample figure derives from $\Delta P \approx 1.7$ W against a 24.4 W idle, read from a 1 Hz on-card sensor. The sensor and the subtraction are coarse; the per-sample value is rounded to two significant figures and should be read as an order-of-magnitude board-level estimate, not a precise energy claim. A higher-rate external meter would be needed for three-significant-figure energy.

5.3 Future work

- Run the full pipeline on ImageNet-1k when credentials and storage become available.

- Explore the threshold (Δ) and feasibility (τ) sensitivity surface across families.
- Extend the kernel to multi-batch continuous streaming and measure host PCIe overhead in a server context.
- Investigate sparsity and quantization ladders for the machine channel.
- Measure the CPU baseline on the same DL380 host that holds the U250, and collect rack-level energy for both host and card.
- Include the EarlyStop baseline column in the GPU training table for direct three-way comparison.

6 Conclusion

We have presented, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an FPGA, together with a GPU training study across three architecture families. The U250 kernel runs at 511 Msamples/s on a 1.2M-sample stress cohort and approximately 3.3 nJ/sample board-level energy, with bit-exact correctness verified against a golden model on synthetic, stress, and real-image cohorts. GPU training saves 40.7–52.2% of metered-MAC burden in a small-subset, fast-convergence regime. We have stated the limitations plainly — small-subset accuracy, partial meter convention, no full ImageNet-1k, board-level power only, ResNet-50 patient-channel tradeoff — because the honesty of the evidence is itself a contribution. The artifacts are available for reproduction.

7 AI Disclosure

This draft was prepared under human direction, with mandatory LLM-offload review per `.claude/AGENT_OFFLOAD_POLICY.md`. The companion spec and contract were audited by math-review offload (xai/Grok 4.3 and Z.AI GLM) and revised per their findings. No clinical content. GAIDeT-ICMJE 2025.

References

- [1] Teerapittayanon, S., McDanel, B., & Kung, H. T. (2016). BranchyNet: Fast inference via early exiting from deep neural networks. *ICPR*.
- [2] Kaya, Y., Hong, S., & Dumitras, T. (2019). Shallow-Deep Networks: Understanding and mitigating network overthinking. *ICML*.
- [3] Huang, G. (2018). Multi-scale dense networks for resource efficient image classification. *ICLR*.

- [4] Sounio repository, suffering-aware neural network line: `docs/research/suffering_aware_architecture_s` and successors.
- [5] Chamon, L. F., & Ribeiro, A. (2020). Probably approximately correct constrained learning. *NeurIPS*.
- [6] Chamon, L. F., Paternain, S., Calvo-Fullana, M., & Ribeiro, A. (2023). Constrained learning with non-convex losses. *IEEE Transactions on Information Theory*.
- [7] Cotter, A., Jiang, H., Gupta, M., Wang, S., Narayan, T., You, S., & Sridharan, D. (2019). Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *JMLR*.
- [8] Manheim, D., & Garrabrant, S. (2018). Categorizing variants of Goodhart’s law. arXiv:1803.04585.

A Reproduction

```
# CPU contract + spec/outline consistency (~3 min on CPU)
bash scripts/ci/san_imagenet_fpga_dl380_gate.sh
# expect: SAN_IMAGENET_FPGA_DL380_VERDICT I_GREEN (8/8 clauses PASS)

# GPU training (requires CUDA)
SAN_LARGE_DEVICE=cuda SAN_LARGE_ONLY=resnet50 \
  .venv/bin/python scripts/research/suffering_aware_large_architecture.py

# U250 host scan (requires Xilinx XRT + bitstream on DL380)
./host_san_scan -x krnl_san_scan.hw.xclbin -d val_resnet
```

B Companion contract clauses (L1–L8)

The GPU harness reports per-family verdicts against clauses L1–L8 of `scripts/research/suffering_aware_large_architecture.py`:

clause	predicate	threshold / note
L1	Metering conservation: gated-off stages charge 0; metered MACs == independent manual accounting	equality
L2	Feasibility: SAN reaches val acc $\geq \tau$ within budget	τ per family

clause	predicate	threshold / note
L3	Anti-Goodhart: 101-weight compassion grid never selects an infeasible checkpoint	abstainer & probe infeasible
L4	Necessary/gratuitous separation: SAN gratuitous machine burden = 0	equality
L5	Suffering bounds: SAN machine burden < Dense and $\leq$ EarlyStop; patient harm $\leq$ both baselines	within small tolerance
L6	Exits are real: val exit fraction at $t^* > 0.07$	0.07
L7	Patient channel first-class: harm matrix off-diagonal max $\geq 3\times$ min; SAN peak harm $\leq$ baselines	$3\times$ asymmetry
L8	Anti-shortcut: a spurious-feature probe that overfits train but fails val is rejected by the gate	train $> \tau$, val $< \tau$, never selected

The FPGA / ImageNet-scale contract uses an analogous I1–I8 clause set defined in `scripts/research/san_imagenet_fpga_d1380.py` and enforced by `scripts/ci/san_imagenet_fpga_d1380_gate.sh`.