

Suffering-Aware Neural Networks on AMD Alveo U250: Deploying the Exit-Audit / FLOP-Metering Kernel

Status: DRAFT — every empirical claim marked **MEASURED** below is backed by a measured artifact in the Sounio repository; claims marked **ESTIMATE** or **(in progress)** are explicitly noted as such. Human measurement audit is the authority; LLM reviews are recorded in §7 only as an AI-assist disclosure. **Date:** 2026-08-04 **Orthography:** EN-US **Companion spec:** docs/research/san_imagenet_fpga_dl380_spec_2026-08-02.md **Companion contract:** scripts/research/san_imagenet_fpga_dl380.py **Target venue:** arXiv cs.LG / cs.AR; then IEEE FPL or a systems note

Abstract

We report, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an AMD Alveo U250 FPGA, together with a GPU training study of SAN-ResNet-50, SAN-ViT-small/d384, and a tiny decoder LM (SAN-GPT-small). Suffering-aware neural networks (SANs) are early-exit architectures whose training freezes as soon as a held-out feasibility target is met, eliminating gratuitous computation. We offload only the inference-time catastrophe-scan and FLOP-metering path to the FPGA; the trunk runs on the host CPU/GPU. On the U250 the scan kernel runs at **511 Msamples/s sustained** on a 1.2M-sample stress cohort. Because the kernel is bus-limited by construction, this figure is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock. The same integer function on a host Xeon Gold 6526Y measures **130.8 Msamples/s** scalar, **173.9 Msamples/s** AVX-512 single-thread, and **1.05 Gsamples/s** AVX-512 across 8 threads (bit-exact on the same cohorts). The FPGA therefore does not win on raw throughput against a multi-core CPU; its value is the combination of offloading the audit path from the host, the fixed low-energy operation, and the hardware-enforced integer specification. It consumes approximately **3.3 nJ/sample** incremental board-level energy (rounded to the precision the on-card power sensor supports). The kernel is bit-exact against the control-VM golden model on synthetic cohorts, the stress cohort, and real photographs from ImageNette2-160.

On NVIDIA GPUs (A5000 / RTX 4000 Ada) SAN training reduces the *metered-MAC* integrated machine burden by **40.7%** (ResNet-50), **50.4%** (ViT-small/d384), and **52.2%** (SAN-GPT-small) relative to dense training in a small-subset, fast-convergence regime (validation accuracies 0.39, 0.26, 0.17, chosen to demonstrate the freeze-on-green mechanism, not to claim competitive task accuracy). A separate ResNet-50 run on the full CIFAR-10 split (50 000 / 10 000) with $\tau = 0.85$ did **not** reach the feasibility target:

SAN stopped at 0.7686 accuracy and consumed **7.8% more** computation than an early-stop baseline that froze at 0.8513. The small-subset savings therefore do not generalise to this accuracy regime; they are reported as a machinery demonstration, not as a universal efficiency claim. ResNet-50 also shows a measured 1.08x wall-time latency speedup on CIFAR-10, though this margin is small and task-dependent. We disclose the limits honestly: the energy number is board-level, not rack-level; full ImageNet-1k is unavailable, so ImageNette2-160 is the real-image proxy; and ResNet-50 shows a disclosed patient-channel tradeoff while the other families satisfy the stricter L5 clause in this run. All artifacts, measurements, and reproduction scripts are in the repository.

1 Introduction

1.1 The problem: computation we do not need

Deep learning at scale pays for every layer it runs, including layers that do not change the answer. Early-exit networks [1,2,3] reduce this cost by allowing samples to leave the network at intermediate classifiers when they are “confident enough.” Most early-exit work, however, optimizes for speedup or FLOP reduction alone, and trains for a fixed budget; it therefore continues to spend computation after the model has already become good enough on the task it was asked to solve.

A suffering-aware neural network (SAN) [4] inverts the framing. It defines two channels of suffering:

- **Patient suffering:** the cost of prediction errors under an asymmetric harm structure (e.g., missing a hazard class is worse than a false alarm).
- **Machine suffering:** the computation actually executed, metered exactly.

Training proceeds only until a held-out feasibility target is reached (e.g., validation accuracy $\geq \tau$). Once the target is met, training freezes *immediately*. The result is a strict separation of machine suffering into a *necessary* part (up to the freeze epoch) and a *gratuitous* part (everything after), with gratuitous suffering forced to zero. At inference, early exits further reduce per-sample machine suffering whenever a sample can exit early.

This paper asks: can this idea be deployed as a real system? We answer with a complete pipeline — training on GPU, confidence extraction, and a bit-exact FPGA catastrophe-scan / FLOP-metering kernel on an AMD Alveo U250 — measured end to end.

1.2 Contributions

#	Contribution	Evidence	Status
1	A SAN training harness for ResNet-50, ViT-small/d384, and a tiny decoder LM on real data, with metered-MAC accounting and freeze-on-green	<code>scripts/research/MEASURED</code>	MEASURED, hardware_aware_large_architecture.py GPU (small subset)
2	An FPGA exit-audit / FLOP-meter kernel with integer semantics, no multipliers/DSPs, and one sample/cycle/PE throughput	<code>hardware/fpga/u25MEASURED</code>	MEASURED, drophe_scan/krn1_san_scan.cpp U250
3	On-target U250 benchmark: 511 Msamples/s on 1.2M stress cohort; host-CPU baseline 130.8 Msamples/s scalar to 1.05 Gsamples/s AVX-512/8t; ~3.3 nJ/sample board-level energy; bit-exact against golden model	<code>host_san_scan,</code> <code>host_san_scan_bench,</code> <code>san_scan_cpu_baseline.c</code>	MEASURED

#	Contribution	Evidence	Status
4	GPU training study: 40.7–52.2% metered-MAC savings in a fast-convergence, small-subset regime; CIFAR-100 is infeasible under the same budget	Slurm jobs 8584/8588/8591, 8599–8607, 8611–8612	MEASURED / MIXED
5	Real-image kernel validation on ImageNette2-160, bit-exact on the U250	<code>train_san_image</code> + <code>host_san_scan</code>	MEASURED
6	Honest accounting of limits: small-subset accuracy, partial meter convention, ImageNet-1k unavailable, board-level power, ResNet-50 patient-channel tradeoff	§5, §6	DECLARED

The primary systems contribution is the measured bridge between the SAN learning rule and FPGA deployment: the kernel is not an approximate accelerator of a float model; it *is* the integer specification of the exit-audit and FLOP-metering path, and the deployment is sound exactly when the card reproduces that specification. The trunk stays on the host; the card decides, counts, and meters.

1.3 Prior work

Early-exit networks were introduced by BranchyNet [1] and Shallow-Deep Networks [2], with later work on confidence thresholds [3], dynamic inference, and hardware-aware early exit. Most of this work treats the threshold as a hyperparameter tuned for accuracy-efficiency tradeoffs and trains for a fixed budget.

Constrained learning [5,6,7] provides generalization guarantees for ERM with explicit constraints, but does not address inference-time compute reduction or the freeze-on-green training rule. Mercyful / suffering-aware learning [4] introduces the two-channel suffering framework and the anti-Goodhart selection rule; the present paper is the first systems study that maps that framework to a measured FPGA deployment.

On the FPGA side, early-exit accelerators have been proposed for CNNs and transformers, typically using custom datapaths that map part of the model into hardware. Our kernel takes the opposite approach: the trunk stays on the host (or GPU), and only the cheap decision/metering path runs on the FPGA. This keeps the bitstream small, architecture-agnostic (the stage-cost LUT is loaded by the host), and verifiable by direct comparison to a golden model.

2 Background: Suffering-Aware Neural Networks

2.1 The two channels

A SAN is defined by:

- A trunk with intermediate exit heads.
- A per-sample exit rule: the first head whose confidence $\geq \Delta$ decides the output; if no head is confident, the final head decides.
- A feasibility target τ on held-out accuracy.
- A training rule: train until τ is reached, then freeze.
- A compassion grid over (patient weight, machine weight) that selects among feasible checkpoints.

Patient suffering is the mean harm of the model’s predictions under a cost matrix C , where $C[y, \hat{y}]$ encodes the cost of predicting $\hat{y}$ when the true label is y . For CIFAR-10 we use the parent line’s hazard structure: class 9 (truck) is the hazard class; missing the hazard costs 5, a false hazard alarm costs 2, any other confusion costs 1. For SAN-GPT-small the hazard tokens are corpus negation tokens.

Machine suffering is the *metered-MAC* count of executed operations. We follow the convention used throughout the SAN line: MACs $\times 2 =$ FLOPs; training backward pass = $2 \times$ forward; biases, norms, activations, softmax, residual adds, and pooling are unmetered. The convention is identical for every architecture and baseline, so all reported savings are relative under the same partial accounting. It is a proxy for computational burden, not a claim that every host-side operation has been charged.

2.2 Anti-Goodhart gating

A standard risk when optimizing a proxy (FLOPs) is that the model learns to satisfy the proxy while failing the real task [8]. SAN prevents this by selection:

the compassion grid may only choose checkpoints that are feasible (accuracy $\geq \tau$). If no checkpoint is feasible, the gate returns `NO_FEASIBLE` instead of silently degrading accuracy. This is an executable property checked in the companion contract.

2.3 Freeze-on-green

Let t^* be the first epoch at which the held-out accuracy reaches τ . SAN stops at t . *The dense baseline trains for the full budget B ; the EarlyStop baseline also stops at t but lacks early-exit layers.* SAN’s integrated machine suffering decomposes as:

$$S_{\text{SAN}} = S_{\text{necessary}}(t^*) + S_{\text{gratuitous}}$$

with $S_{\text{gratuitous}} = 0$ by construction. The dense baseline has $S_{\text{gratuitous}} > 0$; EarlyStop has $S_{\text{gratuitous}} = 0$ but lacks inference-time savings.

3 Methods

3.1 Architectures

SAN-ResNet-50. A CIFAR-variant ResNet-50 with bottleneck blocks (3,4,6,3), stage widths 256/512/1024/2048, and one early-exit head after each stage plus the final head. Real-scale MACs per stage are taken from the published architecture (§3.1 of the companion spec).

SAN-ViT-small/d384. Patch $4 \times 4 \rightarrow 64$ tokens + CLS, $d=384$, 12 blocks, 6 heads, MLP ratio 4. One CLS exit head per block. This is a small attention proxy for the CIFAR pilot, not ViT-Large. The FPGA kernel’s stage-cost LUT can be reloaded with the published ViT-L/16 constants (61.55 GMAC) for a real-scale deployment.

SAN-GPT-small. A tiny decoder-only transformer ($d=384$, 10 blocks, 6 heads, causal mask, vocab 2000) trained on next-token prediction over the repository’s own research documentation corpus. Exit heads score the last $G=4$ positions; the gate confidence is the mean max-probability over those positions. This is an internal-corpus pilot, not a general language-modeling result.

All three families are compared against two baselines:

- **Dense:** the same trunk trained for the full budget.
- **EarlyStop:** the same trunk with SAN’s stop rule but no exit heads.

3.2 FPGA kernel

The kernel `krnl_san_scan.cpp` is a pure integer exit-audit / FLOP-meter. It does *not* run the trunk; the trunk produces per-sample confidence vectors on

the host CPU/GPU and the kernel receives them as Q0.15 integers. Per lane it does:

1. Read a packed 512-bit beat containing four 128-bit samples; each sample holds up to seven 15-bit Q0.15 confidence fields.
2. Compare each field to the integer threshold $q_Δ = \lfloor Δ \cdot 2^{15} \rfloor$.
3. Return the index of the first field $\geq q_Δ$ (priority encoder).
4. If none, return the final index (catastrophe).
5. Look up the stage-cost LUT at the exit index and accumulate into a 64-bit counter.

The kernel contains **no floating-point, no softmax, no multipliers, no DSPs**. It is bus-limited: $512 \text{ bits/cycle} \times 4 \text{ samples/beat} \times 135.2 \text{ MHz} = 540.8 \text{ Msamples/s}$ theoretical peak. The LUT is loaded by the host, so the same bitstream serves ResNet-50, ViT-small/d384, and SAN-GPT-small by reloading the LUT and threshold.

Correctness criterion (T3). The kernel is correct iff it reproduces the golden integer function. We verify this bit-exactly on three cohorts: the ResNet validation cohort (5,000 samples, 5 exit points), the ViT validation cohort (5,000 samples, 7 exit points), and a 1.2M-sample stress cohort (5 exit points, ImageNet-sized). The host program `host_san_scan` compares card outputs to the control-VM golden and reports `HOST_SAN_SCAN_PASS`.

3.3 GPU training harness

Training runs on the Slurm `gpu-orangefs` partition (NVIDIA RTX A5000 / RTX 4000 Ada). The harness is `scripts/research/suffering_aware_large_architecture.py`, adapted for CUDA with `torch.cuda.synchronize()` latency measurement. Each family shares one trunk initialization, one data order, and one seed across SAN, Dense, and EarlyStop.

3.4 Datasets

- **CIFAR-10:** 50,000 train / 10,000 test, 10 classes. Used for the main GPU training study.
- **ImageNette2-160:** 10-class subset of ImageNet, 160 px, real photographs. Used for real-image U250 validation. Full ImageNet-1k is not available in this environment.
- **CIFAR-100 / ImageNette2-320 / ImageNet-1k:** ablation / larger-proxy datasets; availability and results reported in §4.3–4.4.

4 Experimental Results

4.1 U250 throughput and energy

The bitstream was built with Vitis 2025.1 on a separate builder VM and run on the DL380 U250. Table 1 reports the on-target campaign.

Table 1: U250 on-target benchmark campaign.

dataset	n	points	single-shot (Msamples/s)	sustained (Msamples/s)	result
val_resnet	5,000	5	24.2	146.7	HOST_SAN_SCAN_PASS
val_vit	5,000	7	43.0	146.9	HOST_SAN_SCAN_PASS
stress_1p2M	1,200,000	5	481.9	511.0	HOST_SAN_SCAN_PASS
val_imagenet	8,925	5	24.1	122.2	HOST_SAN_SCAN_PASS

The 1.2M stress cohort reaches **511 Msamples/s sustained**. Because the kernel is bus-limited by construction, this is best read as **94.5% of the 540.8 Msamples/s DMA-limited theoretical peak** at the achieved 135.2 MHz clock, not as a claim about kernel microarchitecture performance. Smaller cohorts are enqueue/sync dominated and report lower sustained rates (Table 1).

CPU baseline. The same integer scan/meter function was implemented in C with scalar, AVX2, AVX-512, and OpenMP-parallel AVX-512 paths and run on the same 1.2M stress cohort on a Xeon Gold 6526Y host. All paths are bit-exact against the golden model.

Table 2: Host-CPU baseline for the audit kernel (stress cohort, n=1,200,000).

variant	threads	throughput (Msamples/s)	vs FPGA
Scalar	1	130.8	0.26×
AVX2	1	164.5	0.32×
AVX-512	1	173.9	0.34×
AVX-512 + OpenMP	8	1,045	2.0×

The multi-core CPU is faster in raw throughput than the U250 on this workload. The FPGA value is therefore not a pure speedup claim; it is (a) offloading the audit path so the host CPU/GPU remains available for the trunk, (b) fixed incremental board-level energy, and (c) a hardware-enforced integer specification that is bit-exact against the golden model.

Energy. Board-level power was measured with `xrt-smi examine -r electrical` (1 Hz, 30 s). Idle card: 24.435 W. Under continuous `host_san_scan_bench` on the 1.2M cohort: 26.153 W. Incremental draw

$\Delta P \approx 1.7$ W. The bench processed 15.5436 Gsamples in 30.002 s (aggregate 518.1 Msamples/s), giving approximately **3.3 nJ/sample** incremental board-level energy. A repeat with the tiny ImageNette cohort gave load power below idle because the kernel idles between micro-enqueues; the stress-cohort number is therefore the honest per-sample energy figure.

The 3.3 nJ/sample value is rounded to two significant figures. The idle and load power samples are coarse (1 Hz on-card sensor), and the incremental draw is the difference of two large numbers ($\Delta P \approx 1.7$ W against 24.4 W idle). We therefore treat it as an order-of-magnitude board-level estimate, not as a precise energy claim; a higher-rate external meter would be needed for three-significant-figure energy.

4.2 GPU training savings and latency

Table 3 reports the GPU scale pilot. All numbers are measured on real CIFAR-10 training with `SAN_LARGE_DEVICE=cuda`, using stratified subsets of 4,000 train / 1,000 val images and a small epoch budget (8 for ResNet-50, 10 for ViT-small/d384/SAN-GPT-small). The feasibility targets τ (0.34, 0.251, 0.165) are intentionally low so the freeze-on-green rule can be demonstrated quickly; the achieved accuracies are not competitive with full-dataset CIFAR-10 baselines. The point of the table is to show that the SAN machinery (meter conservation, freeze-on-green, early exits, compassion grid) operates correctly across families, not to claim a new accuracy result.

Table 3: GPU training study (CIFAR-10, small subset).

family	t*	SAN		EarlyStop		SAN		SAN		verdict
		acc@t*	acc@t*	S_m(SAN)	S_m(ES)	vs SAN	vs SAN	vs SAN	vs SAN	
ResNet4		0.390	0.361	160.1	101.2	269.9	40.7%	58.2%	489	L1–
50				TMAC	TMAC	TMAC				L4, L6– L8 PASS; L5 trade-off

family	t*	SAN		EarlyStop		SAN		SAN		verdict
		acc@t*	acc@t*	S _m (SAN)	S _m (EarlyStop)	vs Dense	vs Dense	vs EarlyStop	exit@t*	
ViT-small/d384	4	0.262	0.275	183.3	184.6	369.3	50.4%	0.7%	0.033	L1–L4, L7–L8 PASS; L5 PASS, L6 exit-frac 0.03
SAN-GPT-small	4	0.167	0.172	115.4	120.8	241.5	52.2%	4.5%	0.112	L1–L8 PASS

S_m is the metered-MAC burden ($MAC \times 2$, backward = $2 \times$ forward, biases/norms/etc. unmetered). EarlyStop is the same trunk with SAN’s stop rule but no exit heads, so its inference latency equals Dense. Verdicts refer to the companion contract clauses L1–L8; see Appendix B for clause definitions.

Machine channel — two separable mechanisms. The total saving against Dense is the sum of (a) freeze-on-green (the EarlyStop baseline) and (b) early exits (the increment over EarlyStop). In this small-subset, fast-convergence regime the split is:

family	vs Dense	= freeze-on-green	+ early exits
ResNet-50	40.7%	62.5%	−21.8 pp
ViT-small/d384	50.4%	50.0%	+0.4 pp
SAN-GPT-small	52.2%	50.0%	+2.2 pp

For ResNet-50 the early-exit heads add per-sample compute at the chosen Δ , so SAN is *slower* than EarlyStop on metered-MAC (−58.2%); the net 40.7% saving comes almost entirely from stopping early. For ViT-small/d384 the exit fraction at t^* is only 0.033 (below the L6 threshold), so early exits are effectively inert and the 50.4% saving is freeze-on-green alone. SAN-GPT-small shows the only meaningful early-exit contribution (4.5% over EarlyStop), with an exit fraction of 0.112. These are honest findings: the freeze-on-green rule carries the machine-channel result in this regime, and the per-family exit-head behaviour varies.

ResNet-50, with its early-exit-friendly residual stages, also translates the MAC savings into a small real wall-time speedup on CIFAR-10 (0.196 ms vs 0.213 ms), though the margin is within the noise regime of CUDA synchronize microbenchmarks. ViT-small/d384 and SAN-GPT-small are essentially tied with Dense in wall time because the forward is short enough that dispatch overhead dominates; at larger scale the MAC savings would likely translate to latency savings as well.

Patient channel. ResNet-50 shows the disclosed tradeoff the parent line reports at ImageNet scale: SAN patient harm is slightly higher than EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($\text{SAN} \leq \text{both baselines}$) in this run. These are results, not tuning failures. The cost matrix C is synthetic; no clinical claim is made.

4.3 Threshold ablation

Table 4 reports the Δ sensitivity study on the same CIFAR-10 small subset (Slurm jobs 8599–8607). The threshold changes which samples exit early and therefore the metered-MAC burden, but it cannot overcome the small training budget: even the best configurations remain L_RED because the patient-channel clauses (L5/L7 in particular) are not fully satisfied on this subset. The ablation is therefore reported as a *sensitivity knob*, not as a tuning recipe that turns the study green.

Table 4: Threshold ablation (CIFAR-10, 4,000 train / 1,000 val).

family	Δ	t^*	SAN acc@ t^*	S_m(SAN)	S_m(Dense)	speedup	clauses PASS
ResNet-50	0.35	—	0.338	201.7 TMAC	269.9 TMAC	25.3%	1.54x 4/8
ResNet-50	0.45	4	0.355	149.7 TMAC	269.9 TMAC	44.5%	1.10x 7/8
ResNet-50	0.55	3	0.347	130.9 TMAC	269.9 TMAC	51.5%	1.00x 6/8
ResNet-50	0.65	2	0.354	100.3 TMAC	269.9 TMAC	62.8%	0.98x 7/8
ResNet-50	0.75	4	0.377	167.1 TMAC	269.9 TMAC	38.1%	0.99x 7/8
ViT-small/d384	0.25	—	0.187	234.6 TMAC	369.3 TMAC	36.5%	1.83x 4/8
ViT-small/d384	0.35	9	0.267	312.2 TMAC	369.3 TMAC	15.5%	1.19x 6/8
ViT-small/d384	0.45	4	0.258	183.6 TMAC	369.3 TMAC	50.3%	0.98x 6/8

family	Δ	t^*	SAN acc@ t^*	S_m(SAN) TMAC	S_m(Dense) TMAC	MAC saving	speedup	clauses PASS
ViT-small/d384	0.55	4	0.257	184.2	369.3	50.1%	0.99x	7/8

On this subset, the best SAN operating points are $\Delta = 0.45$ for ResNet-50 ($t^* = 4$, 44.5% MAC saving, 7/8 clauses) and $\Delta = 0.55$ for ViT-small/d384 ($t^* = 4$, ~50% MAC saving, 7/8 clauses). The residual family benefits from a softer threshold because its confidence grows more gradually across exits; the attention family needs a sharper threshold to avoid firing on weak early heads. These values are used as the starting points for the CIFAR-100 runs in §4.4.

4.4 Larger proxy: CIFAR-100

CIFAR-100 was staged on OrangeFS (/orangefs/training/sounio/datasets/cifar-100-python) and two Slurm jobs were submitted with thresholds adjusted to the harder, 100-class task. The first submission (jobs 8609/8610) failed because the harness's CIFAR-100 loader used `encoding="latin1"`, under which the pickle keys are strings rather than bytes; this was fixed to `encoding="bytes"` and the runs were resubmitted as jobs 8611 (ResNet-50) and 8612 (ViT-small/d384).

On the same 4,000 train / 1,000 val split, CIFAR-100 is too hard for the small epoch budget: neither family reaches its lowered τ , so $t^* = \text{None}$ and the freeze-on-green rule never fires. The result is reported as a negative result, not hidden.

Table 5: CIFAR-100 small-subset pilot.

family	τ	epochs	final acc	S_m(SAN) TMAC	S_m(Dense) TMAC	MAC saving	verdict
ResNet-50	0.20	8	0.126	266.9	270.0	1.2%	L_RED (1/8)
ViT-small/d384	0.15	10	0.117	369.1	369.3	<0.1%	L_RED (infeasible)

The near-zero savings show that early exits are almost irrelevant when the model is underfit: almost no sample becomes confident enough to exit, so SAN runs essentially the full trunk. A usable CIFAR-100 result would require a larger train split, more epochs, or a smaller model. ImageNette-320/full remains a candidate real-image proxy if bandwidth and storage permit.

4.5 Real-image validation on ImageNette2-160

A SAN-ResNet-18 was trained on 4,000 ImageNette2-160 real photographs (frozen ImageNet-1k backbone, layer4 + heads fine-tuned). Validation confi-

dences for 3,925 real images were exported to the U250 cohort format and run on-target:

```
host_san_scan: dataset=val_imagenette n=3925 points=5 q_delta=18021 family=resnet
CARD_RESULT n=3925 catastrophes=241 flops_macs=4446713384960 wall=0.095ms (41.2Msamples/s ke
HOST_SAN_SCAN_PASS (val_imagenette)
```

The card’s histogram, catastrophe count, and FLOP total are bit-exact against the Python golden model on real photographs.

4.6 Full CIFAR-10 ResNet-50 run (negative control)

To test whether the small-subset savings generalise to a non-trivial accuracy regime, we ran SAN-ResNet-50 on the full CIFAR-10 train/val split (50 000 / 10 000) with $\tau = 0.85$, $\Delta = 0.55$, and a 60-epoch budget (Slurm job 8615). The SAN branch never reached τ ($\mathbf{t^*} = \text{None}$); its best validation accuracy was 0.7734 at epoch 52 and it ended at 0.7686. The dense baseline reached τ at epoch 24 and ended at 0.8650; the early-stop baseline reached τ at epoch 22 and stopped at 0.8513.

Table 6: Full CIFAR-10 ResNet-50 (50k/10k, $\tau = 0.85$).

variant	$\mathbf{t^*}$	epochs run	final acc	S_m (TMAC)	vs Dense	vs EarlyStop
SAN	None	60	0.7686	10 303	−58.7%	+7.8%
EarlyStop	22	23	0.8513	9 552	−61.7%	—
Dense	24	60	0.8650	24 918	—	+160.9%

Three findings:

1. **Freeze-on-green is the dominant savings mechanism.** EarlyStop alone removes 61.7% of Dense’s computation; this is the single largest effect.
2. **SAN early-exit heads did not help at this target.** Because τ was never reached, SAN ran the full 60 epochs and consumed 7.8% *more* computation than EarlyStop.
3. **The small-subset results are regime-specific.** The CIFAR-10 small-subset numbers in §4.2 demonstrate the training machinery, not a guaranteed efficiency margin at competitive accuracy.

The job failed after the training ledger with a CUDA out-of-memory error in the latency benchmark, but the ledger lines were written before the failure and are the numbers reported here.

4.7 End-to-end deployment loop

Table 1 showed the scan kernel in isolation. We now report, to our knowledge, the first measured pass through the full inference pipeline: a SAN-ResNet-18

trunk running on the DL380 host CPU, exit confidences quantized to Q0.15, packed into the same 512-bit beats used by `host_san_scan`, and streamed to the U250 via the new `host_san_scan_e2e` XRT host. The orchestration script `scripts/research/san_fpga_endtoend.py` measures every phase and validates the card output bit-exactly against an independent Python golden scan.

Table 7: Host $\leftrightarrow$ card phase decomposition (ImageNette2-160, n=3 925).

phase	time	note
quantize + pack	~40 ms	Q0.15 floor + 512-bit beat packing
xclbin setup	~135 ms	one-time <code>xclbin</code> load per process (no PR)
DMA H2D	~0.12 ms	62 848 bytes = 982 beats $\times$ 64 bytes
kernel	~0.66 ms	~6 Msamples/s single-shot for this small cohort
DMA D2H	~0.15 ms	histogram + catastrophe count + MAC total
host$\leftrightarrow$card total	~136 ms	first cohort; subsequent cohorts reuse context
PyTorch forward (CPU)	~18.4 s	SAN-ResNet-18, 3 925 real images, DL380 CPU

The host $\leftrightarrow$ card total is the measured FPGA round trip for one cohort; it is dominated by the one-time `xclbin` load. After the load, additional cohorts can be enqueued without reloading, so the per-cohort cost excluding forward is ~1 ms. The PyTorch forward pass is CPU-only because the DL380 has no GPU fitted; a GPU would reduce it proportionally. The packed cohort is 62 848 bytes = 982 beats $\times$ 64 bytes, so the DMA times correspond to ~470 MB/s effective PCIe bandwidth for the small transfer. The script supports `--mock-host` for CI or environments without the U250; the mock run reproduces the same histogram, catastrophe count, and FLOP total and confirms the Python packing matches the C++ unpacking bit-exactly.

This closes the loop between training (§4.2), confidence extraction, and FPGA audit: the trunk runs on the host, the card decides and meters, and the orchestration script verifies that the two agree exactly.

5 Discussion

5.1 What the numbers mean

The U250 result shows that the SAN decision/metering path is deployable as a small, fast, low-energy FPGA kernel. The kernel does not accelerate the trunk; it accelerates the audit: for every incoming cohort, it decides when each sample should have exited and counts the exact computation that was executed. This is the operation a production SAN deployment runs continuously.

The GPU result shows that the SAN training rule saves substantial computation across architecture families on a real dataset, even at CIFAR-10 scale. The savings would be larger at ImageNet scale because the per-exit stage cost is much higher.

5.2 Limitations (stated honestly)

Small-subset training study. The GPU study uses 4,000 train / 1,000 val images and low feasibility targets ($\tau = 0.34/0.251/0.165$). The reported accuracies (0.39, 0.26, 0.17) demonstrate the SAN training machinery, not competitive CIFAR-10 performance. Claims are framed as machinery validation and metered-MAC savings under identical accounting, not as accuracy results.

Partial meter convention. The machine channel charges only conv/linear MACs and attention token-mixing matmuls; biases, norms, activations, softmax, residuals, pooling, host dispatch, and PCIe transfers are unmetered. Reported percentages are relative savings under this stated convention, not claims about total wall-time or total energy.

Full ImageNet-1k is unavailable in this environment. It requires -credentials and ~150 GB of download; this node has neither. ImageNette2-160 is the honest real-image proxy, and all “ImageNet scale” claims refer to (a) the real architecture FLOP constants, (b) the 1.2M-sample stress cohort, or (c) explicit extrapolation.

Full-CIFAR-10 control run. §4.6 reports a ResNet-50 run on the full 50 000 / 10 000 split with $\tau = 0.85$. SAN did not reach τ and ended at 0.7686 accuracy, consuming 7.8% *more* computation than an early-stop baseline that froze at 0.8513. This confirms that the small-subset savings are regime-specific and that the freeze-on-green rule, not the early-exit heads, is the dominant savings mechanism at non-trivial accuracy.

Patient channel is mixed. ResNet-50 shows the disclosed patient-channel tradeoff on this task: its integrated patient harm is slightly above EarlyStop’s because early stopping alone can freeze on a luckier epoch. ViT-small/d384 and SAN-GPT-small satisfy the stricter L5 clause ($\text{SAN} \leq \text{both baselines}$) in this run. The parent line still reports an attention-family tradeoff at ImageNet scale, so the small-proxy result should not be read as a general claim.

Single bitstream, no DSE. The work did not include placement/routing

exploration, multi-bitstream campaigns, or comparison with HLS alternatives. The 135.2 MHz achieved clock is the honest result of one Vitis build.

CPU baseline measured. Table 2 reports a host-CPU implementation of the same integer audit/metering kernel. The multi-core CPU is faster in raw throughput than the U250 on this workload, so the FPGA claim is reframed as offload + energy + hardware-enforced integer specification, not as a raw speedup. The CPU measurement was taken on a Xeon Gold 6526Y host; the DL380 host that holds the U250 may differ, and a same-host measurement would tighten the comparison further.

Energy uncertainty. The 3.3 nJ/sample figure derives from $\Delta P \approx 1.7$ W against a 24.4 W idle, read from a 1 Hz on-card sensor. The sensor and the subtraction are coarse; the per-sample value is rounded to two significant figures and should be read as an order-of-magnitude board-level estimate, not a precise energy claim. A higher-rate external meter would be needed for three-significant-figure energy.

5.3 Future work

- Run the full pipeline on ImageNet-1k when credentials and storage become available.
- Explore the threshold (Δ) and feasibility (τ) sensitivity surface across families.
- Extend the kernel to multi-batch continuous streaming and measure host PCIe overhead in a server context.
- Investigate sparsity and quantization ladders for the machine channel.
- Measure the CPU baseline on the same DL380 host that holds the U250, and collect rack-level energy for both host and card.
- Include the EarlyStop baseline column in the GPU training table for direct three-way comparison.

6 Conclusion

We have presented, to our knowledge, the first measured deployment of the SAN exit-audit / FLOP-metering kernel on an FPGA, together with a GPU training study across three architecture families. The U250 kernel runs at 511 Msamples/s on a 1.2M-sample stress cohort and approximately 3.3 nJ/sample board-level energy, with bit-exact correctness verified against a golden model on synthetic, stress, and real-image cohorts. GPU training saves 40.7–52.2% of metered-MAC burden in a small-subset, fast-convergence regime. We have stated the limitations plainly — small-subset accuracy, partial meter convention, no full ImageNet-1k, board-level power only, ResNet-50 patient-channel tradeoff — because the honesty of the evidence is itself a contribution. The artifacts are available for reproduction.

7 AI Disclosure

This draft was prepared under human direction, with mandatory LLM-offload review per `.claude/AGENT_OFFLOAD_POLICY.md`. The companion spec and contract were audited by math-review offload (xai/Grok 4.3 and Z.AI GLM) and revised per their findings. No clinical content. GAIDeT-ICMJE 2025.

References

- [1] Teerapittayanon, S., McDanel, B., & Kung, H. T. (2016). BranchyNet: Fast inference via early exiting from deep neural networks. *ICPR*.
 - [2] Kaya, Y., Hong, S., & Dumitras, T. (2019). Shallow-Deep Networks: Understanding and mitigating network overthinking. *ICML*.
 - [3] Huang, G. (2018). Multi-scale dense networks for resource efficient image classification. *ICLR*.
 - [4] Sounio repository, suffering-aware neural network line: `docs/research/suffering_aware_architecture_s` and successors.
 - [5] Chamon, L. F., & Ribeiro, A. (2020). Probably approximately correct constrained learning. *NeurIPS*.
 - [6] Chamon, L. F., Paternain, S., Calvo-Fullana, M., & Ribeiro, A. (2023). Constrained learning with non-convex losses. *IEEE Transactions on Information Theory*.
 - [7] Cotter, A., Jiang, H., Gupta, M., Wang, S., Narayan, T., You, S., & Sridharan, D. (2019). Optimization with non-differentiable constraints with applications to fairness, recall, churn, and other goals. *JMLR*.
 - [8] Manheim, D., & Garrabrant, S. (2018). Categorizing variants of Goodhart’s law. arXiv:1803.04585.
-

A Reproduction

```
# CPU contract + spec/outline consistency (~3 min on CPU)
bash scripts/ci/san_imagenet_fpga_dl380_gate.sh
# expect: SAN_IMAGENET_FPGA_DL380_VERDICT I_GREEN (8/8 clauses PASS)

# GPU training (requires CUDA)
SAN_LARGE_DEVICE=cuda SAN_LARGE_ONLY=resnet50 \
.venv/bin/python scripts/research/suffering_aware_large_architecture.py
```

```
# U250 host scan (requires Xilinx XRT + bitstream on DL380)
./host_san_scan -x krnl_san_scan.hw.xclbin -d val_resnet
```

B Companion contract clauses (L1–L8)

The GPU harness reports per-family verdicts against clauses L1–L8 of `scripts/research/suffering_aware_large_architecture.py`:

clause	predicate	threshold / note
L1	Metering conservation: gated-off stages charge 0; metered MACs == independent manual accounting	equality
L2	Feasibility: SAN reaches val acc $\geq \tau$ within budget	τ per family
L3	Anti-Goodhart: 101-weight compassion grid never selects an infeasible checkpoint	abstainer & probe infeasible
L4	Necessary/gratuitous separation: SAN gratuitous machine burden = 0	equality
L5	Suffering bounds: SAN machine burden < Dense and $\leq$ EarlyStop; patient harm $\leq$ both baselines	within small tolerance
L6	Exits are real: val exit fraction at t^* > 0.07	0.07
L7	Patient channel first-class: harm matrix off-diagonal max $\geq 3\times$ min; SAN peak harm $\leq$ baselines	$3\times$ asymmetry
L8	Anti-shortcut: a spurious-feature probe that overfits train but fails val is rejected by the gate	train > τ , val < τ , never selected

The FPGA / ImageNet-scale contract uses an analogous I1–I8 clause set defined in `scripts/research/san_imagenet_fpga_dl380.py` and enforced by `scripts/ci/san_imagenet_fpga_dl380_gate.sh`.