SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Adding Classes to a Package

Adam Spannbauer
Machine Learning Engineer at Eastman

Object oriented programming



Anatomy of a class

work_dir/my_package/my_class.py

```
# Define a minimal class with an attribute
class MyClass:

    """A minimal example class

    :param value: value to set as the ``attribute`` attribute
    :ivar attribute: contains the contents of ``value`` passed in init
    """


    # Method to create a new instance of MyClass
    def __init__(self, value):
        # Define attribute with the contents of the value param
        self.attribute = value
```

Using a class in a package

work_dir/my_package/__init__.py

```
from .my_class import MyClass
```

work_dir/my_script.py

```
import my_package

# Create instance of MyClass
my_instance = my_package.MyClass(value='class attribute value')

# Print out class attribute value
print(my_instance.attribute)

class attribute value
```

The self convention

work_dir/my_package/my_class.py

```
# Define a minimal class with an attribute
class MyClass:
    """A minimal example class

    :param value: value to set as the ``attribute`` attribute
    :ivar attribute: contains the contents of ``value`` passed in init
    """

    # Method to create a new instance of MyClass
    def __init__(self, value):
        # Define attribute with the contents of the value param
        self.attribute = value
```

Recall

```
my_instance = my_package.MyClass(value='class attribute value')
```

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Leveraging Classes

Adam Spannbauer
Machine Learning Engineer at Eastman

Extending Document class

```
class Document:
    def __init__(self, text):
        self.text = text
```



Current document class

```
class Document:
    def __init__(self, text):
        self.text = text
```



Revising __init__

```
class Document:
    def __init__(self, text):
        self.text = text
        self.tokens = self._tokenize()

doc = Document('test doc')
print(doc.tokens)
```

```
['test', 'doc']
```

Adding _tokenize() method

```
# Import function to perform tokenization
from .token_utils import tokenize

class Document:
    def __init__(self, text, token_regex=r'[a-zA-z]+'):
        self.text = text
        self.tokens = self._tokenize()

    def _tokenize(self):
        return tokenize(self.text)
```

Non-public methods

```
def __init__():
    ...
```



The risks of non-public methods

- Lack of documentation
- Unpredictability

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Classes and the DRY principle

Adam Spannbauer
Machine Learning Engineer at Eastman

Creating a SocialMedia Class

The DRY principle

The DRY principle

The DRY principle

The DRY principle

Intro to inheritance



Inheritance in Python



Inheritance in Python

```
# Import ParentClass object
from .parent_class import ParentClass


# Create a child class with inheritance
class ChildClass(ParentClass):
    def __init__(self):
        # Call parent's __init__ method
        ParentClass.__init__(self)

        # Add attribute unique to child class
        self.child_attribute = "I'm a child class attribute!"


# Create a ChildClass instance
child_class = ChildClass()
print(child_class.child_attribute)
print(child_class.parent_attribute)
```

```
I'm a child class attribute!
I'm a parent class attribute!
```

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Let's Practice

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Multilevel inheritance

Adam Spannbauer
Machine Learning Engineer at Eastman

Creating a Tweet class



Multilevel inheritance



Multilevel inheritance



Multiple inheritance



Multilevel inheritance and super

```
class Parent:
    def __init__(self):
        print("I'm a parent!")

class Child(Parent):
    def __init__(self):
        Parent.__init__()
        print("I'm a child!")

class SuperChild(Parent):
    def __init__(self):
        super().__init__()
        print("I'm a super child!")
```

Learn more about multiple inheritance & `super()`.

Multilevel inheritance and super

```
class Parent:
    def __init__(self):
        print("I'm a parent!")

class SuperChild(Parent):
    def __init__(self):
        super().__init__()
        print("I'm a super child!")

class Grandchild(SuperChild):
    def __init__(self):
        super().__init__()
        print("I'm a grandchild!")


grandchild = Grandchild()
```

```
I'm a parent!
I'm a super child!
I'm a grandchild!
```

Keeping track of inherited attributes

```
# Create an instance of SocialMedia
sm = SocialMedia('@DataCamp #DataScience #Python #sklearn')

# What methods does sm have?  ¯\_(ツ)_/¯
dir(sm)

['__class__', '__delattr__', '__dict__', '__dir__', '__doc__', '__eq__',
'__format__', '__ge__', '__getattribute__', '__gt__', '__hash__', '__init__',
'__init_subclass__', '__le__', '__lt__', '__module__', '__ne__', '__new__',
'__reduce__', '__reduce_ex__', '__repr__', '__setattr__', '__sizeof__',
'__str__', '__subclasshook__', '__weakref__', '_count_hashtags',
'_count_mentions', '_count_words', '_tokenize', 'hashtag_counts',
'mention_counts', 'text', 'tokens', 'word_counts']
```

SOFTWARE ENGINEERING FOR DATA SCIENTISTS IN PYTHON

Let's Practice