TCS | NQT

NATIONAL QUALIFIER TEST

PROGRAMMING LECTURE 2

CS

About Aditya Jain sir

1. Appeared for GATE during BTech and secured AIR 60 in GATE in very first attempt - City topper
2. Represented college as the first Google DSC Ambassador.
3. The only student from the batch to secure an internship at Amazon. (9+ CGPA)
4. Had offer from IIT Bombay and IISc Bangalore to join the Masters program
5. Joined IIT Bombay for my 2 year Masters program, specialization in Data Science
6. Published multiple research papers in well known conferences along with the team
7. Received the prestigious excellence in Research award from IIT Bombay for my Masters thesis
8. Completed my Masters with an overall GPA of 9.36/10
9. Joined Dream11 as a Data Scientist
10. Have mentored working professions in field of Data Science and Analytics 10K+ people
11. Have been mentoring GATE aspirants to secure a great rank in limited time
12. Have got around 27.5K followers on Linkedin where I share my insights and guide students and professionals.

Telegram Link for Aditya Jain sir:

https://t.me/AdityaSir_PW

Process :-

1) Problem Statement
2) Sample Test Cases.
3) Solve and Share approach on Telegram channel.
4) Suggestions
5) Lim Code (+ interview guidance)

[NAT]

#Q. Sort Colors

Problem Statement : Given an array nums with n objects colored red, white, or blue, sort them in-place so that objects of the same color are adjacent, with the colors in the order red, white, and blue.

We will use the integers 0, 1, and 2 to represent the color red, white, and blue, respectively.

You must solve this problem without using the library's sort function.

Example 1:

Input: nums = [2,0,2,1,1,0]

Output: [0,0,1,1,2,2]

Example 2:

Input: nums = [2,0,1]

Output: [0,1,2]

Constraints:

- n == nums.length

[NAT]

#Q. Remove duplicates from Sorted Array

Problem Statement: Given a sorted array arr[] of size n, the goal is to rearrange the array so that all distinct elements appear at the beginning in sorted order. Additionally, return the length of this distinct sorted subarray.

Note: The elements after the distinct ones can be in any order and hold any value, as they don't affect the result.

Examples

Example 1:

Input: arr[] = [2, 2, 2, 2, 2]

Output: [2]

Explanation: All the elements are 2, so only one instance of 2 is kept.

Example 2:

Input: arr[] = [1, 2, 2, 3, 4, 4, 4, 5, 5]

Output: [1, 2, 3, 4, 5]

Explanation: All distinct elements are extracted and placed at the beginning in sorted order.

Example 3:

Input: arr[] = [1, 2, 3]

Output: [1, 2, 3]

Explanation: No change is required as all elements are already distinct.

[MCQ]

#Q. Leaders in an array

Problem Statement : Given an array arr[] of size n, the task is to find all the Leaders in the array. An element is a Leader if it is greater than or equal to all the elements to its right side.

Note: The rightmost element is always a leader.

Examples

Example 1:

Input: arr[] = [16, 17, 4, 3, 5, 2]

Output: [17, 5, 2]

Explanation:

- 17 is greater than all the elements to its right [4, 3, 5, 2], so it is a leader.
- 5 is greater than all the elements to its right [2], so it is a leader.
- 2 has no elements to its right, so it is a leader.

Example 2:

Input: arr[] = [1, 2, 3, 4, 5, 2]

Output: [5, 2]

Explanation:

- 5 is greater than all the elements to its right [2], so it is a leader.
- 2 has no elements to its right, so it is a leader.

[NAT]

#Q. Missing and Repeating in an Array

Problem Statement : Given an unsorted array of size n, where the array elements are in the range 1 to n, one number from the set {1, 2, …, n} is missing, and one number occurs twice. The task is to find these two numbers. Examples

Example 1:

Input: arr[] = {3, 1, 3}

Output: 3, 2

Explanation:

- 3 occurs twice in the array.
- 2 is missing from the array.

Example 2:

Input: arr[] = {4, 3, 6, 2, 1, 1}

Output: 1, 5

Explanation:

[NAT]

#Q. Stock Buy and Sell – Max one Transaction Allowed

Problem Statement: Given an array prices[] of length N, representing the prices of stocks on different days, the task is to find the maximum profit possible by buying and selling the stocks on different days when at most one transaction is allowed.

Here, one transaction means one buy and one sell.

Note: The stock must be bought before being sold.

Examples

Example 1:

Input: prices[] = {7, 10, 1, 3, 6, 9, 2}

Output: 8

Explanation:

- Buy at 1 and sell at 9 to get a profit of 9 - 1 = 8.

Example 2:

Input: prices[] = {7, 6, 4, 3, 1}

Output: 0

Explanation:

- Since the array is sorted in decreasing order, no profit can be made.

Example 3:

Input: prices[] = {1, 3, 6, 9, 11}

Output: 10

Explanation:

- The array is sorted in increasing order, so we can make the maximum profit by buying at 1 and selling at 11, yielding a profit of 11 - 1 = 10.

[MCQ]

#Q. Stock Buy and Sell – Multiple Transaction Allowed

Problem Statement: Given an array prices[] of size n denoting the cost of stock on each day, the task is to find the maximum total profit if we can buy and sell the stocks any number of times.

Constraints:

- We can only sell a stock that we have previously bought.
  - We cannot hold multiple stocks at the same time (i.e., we must sell before buying again).

Examples

Example 1:

Input: prices[] = {100, 180, 260, 310, 40, 535, 695}

Output: 865

Explanation:

- Buy on Day 0 and Sell on Day 3 → 310 - 100 = 210
- Buy on Day 4 and Sell on Day 6 → 695 - 40 = 655
- Total Maximum Profit = 210 + 655 = 865

S B



Example 2:

Input: prices[] = {4, 2, 2, 2, 4}

Output: 2

Explanation:

- Buy on Day 3 and Sell on Day 4 → 4 - 2 = 2
- Total Maximum Profit = 2

Local maxima and local minima



[100, 180, 260, 310, 40, 535, 695]



Approach :-

$i = 1 \longrightarrow n-1$

if (a(i) > a(i-1))

profit += (a(i) - a(i-1))



profit = (d - a)



$[(b-a) + (c-b) + (d-c)]$

$b - a + c - b + d - c$

Same





[MCQ]

#Q. Product of Array Except Self

Problem Statement: Given an array arr[] of n integers, construct a product array res[] (of the same size) such that res[i] is equal to the product of all elements of arr[] except arr[i].

$0 \leq a_i \leq 1000$

Examples

Example 1:

Input: arr[] = [10, 3, 5, 6, 2]

Output: [180, 600, 360, 300, 900]

Explanation:

- res[0] = 3 * 5 * 6 * 2 = 180
- res[1] = 10 * 5 * 6 * 2 = 600
- res[2] = 10 * 3 * 6 * 2 = 360
- res[3] = 10 * 3 * 5 * 2 = 300
- res[4] = 10 * 3 * 5 * 6 = 900

Appr : a(i) ⟶

```
for( i=0 ⟶ n)
    res[i] = 1
    for(j = 0 ⟶ n)
        if( i != j )
        {
            res[i] *= a(j)
        }
```

Example 2:

Input: arr[] = [12, 0]

Output: [0, 12]

Explanation:

- res[0] = 0 (since any number multiplied by 0 is 0).
- res[1] = 12 (since all other elements except arr[1] are multiplied).

Approach :-

$A = [2, 3, 1, 4]$;

↓

$res = [12, 8, 24, 6]$

Logic :- $prod_all = 2 \times 3 \times 1 \times 4$

$$res(i) = \frac{prod_all}{a(i)}$$


2 - 3 - 1 - 4
2x3x1x4
2x3x1x4
2x3x1x4
2x3x1x4
1
3
1
4
3x1x4
2x1x4
2x3x4
2x3x1

Issue with above approach :






Count 0
A = [0 ... 0]
0
1
2
above logic
all elems 0 s
xor[ ]
[0 2 1 0 0]
[0 0 0 0 0]

zeroes = 1



[NAT]

#Q. Maximum Subarray Sum – Kadane's Algorithm

Problem Statement: Given an array arr[], the task is to find the subarray that has the maximum sum and return its sum.

Examples

Example 1:

Input: arr[] = {2, 3, -8, 7, -1, 2, 3}

Output: 11

Explanation: The subarray {7, -1, 2, 3} has the largest sum 11.

Example 2:

Input: arr[] = {-2, -4}

Output: -2

Explanation: The subarray {-2} has the largest sum -2.

Example 3:

Input: arr[] = {5, 4, 1, 7, 8}

Output: 25

Explanation: The subarray {5, 4, 1, 7, 8} has the largest sum 25.

[NAT]

#Q. Find Smallest Missing Positive Number

Problem Statement: Given an unsorted array arr[] containing both positive and negative elements, the task is to find the smallest positive number missing from the array.

Note: You can modify the original array.

Examples

Example 1:

Input: arr[] = {2, -3, 4, 1, 1, 7}

Output: 3

Explanation: The positive numbers in sorted order are {1, 2, 4, 7}. The smallest missing positive number is 3.

Example 2:

Input: arr[] = {5, 3, 2, 5, 1}

Output: 4

Explanation: The positive numbers in sorted order are {1, 2, 3, 5, 5}. The smallest missing positive number is 4.

Example 3:

Input: arr[] = {-8, 0, -1, -4, -3}

Output: 1

Explanation: There are no positive numbers in the array, so the smallest missing positive number is 1.



[NAT]

#Q. Third largest element in an array of distinct elements

Problem Statement: Given an array of n distinct integers, the task is to find the third largest element in the array.

Examples

Example 1:

Input: arr[] = {1, 14, 2, 16, 10, 20}

Output: 14

Explanation:

- Largest element: 20
- Second largest element: 16
- Third largest element: 14

Example 2:

Input: arr[] = {19, -10, 20, 14, 2, 16, 10}

Output: 16

Explanation:

Appr1 :- 1) Sort ⟶ asc order

A[] = { 1, 14, 2, 16, 10, 20 }



1)

2) third_largest = A[n-3]

Appr 2 :

```
max1 = a(0)
for (0 ⟶ n)
    max1 = max(max1, a(i))
```

```
min2 = int_min
for(i:0 ⟶ n)
{
    if(a(i) > max2 && a(i) < max1)
    {
        max2 = a(i)
    }
}
```

update

max3 = int_min

For (i = 0 ⟶ n)

{

if (a(i) > max3 && a(i) < max2)

{

max3 = a(i)

}

}



THANK - YOU