

HPC cluster Initiation

www.southgreen.fr

<https://southgreenplatform.github.io/trainings>





Emmanuelle Beyne
20% ETP

Aurore COMTE
20% ETP

Bruno GRANOUILAC
50% ETP

Valérie NOEL
25% ETP

Julie ORJUELA-BOUNIOU
25% ETP

Ndomassi TANDO
100% ETP

Christine TRANCHANT-DUBREUIL
20% ETP



Cluster certification in process

Provisioning of
softwares and HPC
ressources

Analysis software
and IS development

Plateau bioinformatique

Help and support
to IRD teams

Training to north
and South

- Request forms:

<https://itrop-glpi.ird.fr/plugins/formcreator/front/formlist.php>

- Accounts
- Softwares
- Projects

- Incidents: contact bioinfo@ird.fr

- Howtos:

<https://southgreenplatform.github.io/tutorials//cluster-itrop/hpchowto/>

- Slurm Tutorials:

<https://southgreenplatform.github.io/tutorials//cluster-itrop/Slurm/>




ARCHITECTURE

- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability

- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability



- A logical unit composed of several servers
- A powerful unique machine
- Allow to obtain high computing performance
- A bigger capacity storage
- More reliable
- A better resources availability





- **Master Node**
Handle resources and jobs priorities
- **Computing nodes**
Resources (CPU or RAM memory)

COMPUTING



- **Master Node**
Handle resources and jobs priorities
- **Computing nodes**
Resources (CPU or RAM memory)

STORAGE



- **NAS Server(s)**
Storage

- **1 Master Node**



bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet
- Connection :

```
ssh login@bioinfo-master.ird.fr
```

- **1 Master Node**




bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet
- Connection :

```
ssh login@bioinfo-master.ird.fr
```

- **27 computing nodes**



nodeX
X : 0..26

Role :

- Used by the master to execute jobs
- Not accessible from the Internet
- node0 to node26



Practice

Step 1: Connection, qhost

1

Go to the [Practice 1](#) of github

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation



Step 1
salloc/srun
ou sbatch


Partitions

Partitions	Use	RAM on nodes	Core on nodes
short	Short Jobs < 1 day (higher priority, interactive jobs)	48 to 64 GB	12 cores
normal	Short Jobs max 7 days	64 Go to 96 GB	12 to 24 cores
r900	Short Jobs max 7 days	32GB	16 cores /scratch 117GB
long	45 days >long jobs > 3 days	48 GB	12 to 24 cores
highmem	Jobs with more memory needs	144 GB	12 to 24 cores
supermem	Jobs with much more memory needs	1TB	40 cores
gpu	Need for analyses on GPU cores	192GB	24 cpus and 8 GPUs cores


- Partition to work on GPUs processors : basecalling, MiniOn etc..
- Restricted access to gpu_account group
- Request access with arguments to do here:

<https://itrop-gipi.ird.fr/plugins/formcreator/front/formlist.php>


How do I choose the partition?




How do I choose the partition?




How do I choose the partition?




How do I choose the partition?




How do I choose the partition?



How do I choose the partition?



How do I choose the partition?



- **1 Master node**



bioinfo-master.ird.fr

Role :

- Launch and prioritize jobs on computing nodes
- Accessible from the Internet

- **27 computing nodes**



nodeX

X : 0..26



Role :

- Used by the master to execute jobs
- Not accessible from the Internet

- **3 NAS servers**



bioinfo-nas.ird.fr
(nas)


bioinfo-nas2.ird.fr
(nas2)

bioinfo-nas3.ird.fr
(nas3)


Role :

- Store users data
- Accessible from the Internet
- To transfer data : *via filezilla or scp*

cluster i-Trop disk partitions




bioinfo-nas.ird.fr



bioinfo-nas2.ird.fr




bioinfo-nas3.ird.fr



bioinfo-master.ird.fr

**Virtual links to the
other servers
partitions**



27 nodes

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation

Step 1



Creation of
the analyses
folder in the
/scratch of
the node

Step 2
mkdir



Practice


Step 2:qrsh, partition

2

Go to the [Practice2](#) of the github



PC/MAC




direct transfer
via filezilla
forbidden



bioinfo-master.ird.fr
91.203.34.148

Data transfer on i-Trop cluster



Analyses steps of the cluster

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation

Step 1



Creation of
the analyses
folder in the
/scratch of
the node

Step 2



Data
transfer
from your
PC/MAC to
the nas
servers

Step 3



Copy your data from your PC/MAC to the nas serve if they are not on the cluster



Practice

Step 3: filezilla

3

Go to the [Practice3](#) of the github

- Copy between 2 remote servers :

```
scp -r source destination
```

- Syntax if the source is remote :

```
scp -r server_name:/path/file_to_copy local_folder
```

- Syntax if the destination is remote :

```
scp -r /path/file_to_copy server_name:/path/remote_folder
```

Ex: `scp -r nas:/home/tando/folder/ /scratch/tando/`

Analyses steps of the cluster

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation

Step 1



Creation of
the analyses
folder in the
/scratch of
the node

Step 2



Data
transfer
from your
PC/MAC to
the nas
servers

Step 3



Data
transfer
from the
nas servers
to the
/scratch of
the node

Step 4
scp



Practice

Step 4: scp to nodes

4

Go to the [Practice4](#) of the github

- Allow to choose the version of software you want to use
- 2 types of softwares :
 - bioinfo : includes all the bioinformatics softwares (example BEAST)
 - system : includes all the system softwares(example JAVA)
- Overcome the environment variables

➤ 5 types of commands :

- See the available modules :
`module avail`
- Obtain infos on a particular module:
`module whatis + module name`
- Load a module :
`module load + modulename`
- List the loaded module :
`module list`
- Unload a module :
`module unload + modulename`
- Unload all the modules :
`module purge`

Analyses steps of the cluster

Connection
to
bioinfo-mas
ter.ird.fr
and
resources
reservation

Step 1

Creation of
the analyses
folder in the
/scratch of
the node

Step 2

Data
transfer
from your
PC/MAC to
the nas
servers

Step 3

Data
transfer
from the
nas servers
to the
/scratch of
the node

Step 4

Load
softwares
with
modules
environment

Step 5
module




Practice

Step 5: module environment

5

Go to the [Practice5](#) of the github

Analyses steps of the cluster



- Load the software version to launch
- Launch the data analysis

```
$~ command <options> <arguments>
```

With *command*: the command to launch



Practice

Step6: launch the analysis

6

Go to the [Practice6](#) of the github

- Copy between 2 remote servers :

```
scp -r source destination
```


- Syntax if the source is remote :

```
scp -r server_name:/path/file_to_copy local_folder
```

- Syntax if the destination is remote :

```
scp -r /path/file_to_copy server_name:/path/remote_folder
```

Analyses steps of the cluster





Practice

Step 7: Retrieve the results


7

Go to the [Practice7](#) of the github

- Scratch= temporary spaces
- Verify that the copy is OK before
- Use rm command

```
cd /scratch  
rm -rf nom_rep
```

Analyses steps of the cluster





Practice

Step8: Data deletion

8

Go to the [Practice8](#) of the github

Scripts to visualize/delete données temporary data

- Scripts location: /opt/scripts/scratch-scripts
- Visualize data on scratches: scratch_use.sh

```
sh /opt/scripts/scratch-scripts/scratch_use.sh
```

- Delete data on scratches: clean_scratch.sh

```
sh /opt/scripts/scratch-scripts/clean_scratch.sh
```


Commande	Description	Exemple
<code>srun --time=0X:00 --pty bash -i</code>	Interactive way to connect to a node for X minutes	<code>srun --time=02:00:00 --pty bash -i</code> Connection for 2h
<code>salloc --time=0X:00</code>	Allocate one or several nodes for a later use	<code>salloc -N 2 --p short --time=05:00</code>
<code>sbatch</code>	Launch a analyses in background via a script	<code>sbatch script.sh</code>
<code>sinfo</code>	Informations on partitions	<code>sinfo</code>
<code>scancel</code>	Deletion of job with <job_id>	<code>scancel 1029</code>
<code>squeue</code>	Infos on all jobs	<code>squeue -u tando</code>
<code>scontrol show job <job_id></code>	Infos on the active job <job_id>	<code>scontrol show job 1029</code>

More infos here: <https://southgreenplatform.github.io/tutorials//cluster-itrop/Slurm/#part-2>

Options of sbatch, srun, salloc commands

Options	Description	Exemple
<code>--job-name=<name></code>	Name the job	<code>sbatch --job-name=tando_blast</code>
<code>-p <partition></code>	Choose a partition	<code>sbatch -p highmem</code>
<code>--odelist=<nodeX></code>	Choose a particular node	<code>sbatch -p normal --odelist=node14</code>
<code>-n <nb_tasks></code>	Launch several instance of a command	<code>srun -n 4</code>
<code>-c <nb_cpu_per_task></code>	Allocate the number of cpus per task	<code>srun -n 4 -c 2 hostname</code>
<code>--mail-user=<emailaddress></code>	Send a email	<code>sbatch --mail-user=ndomassi.tando@ird.fr</code>
<code>--mail-type=<event></code>	Send a email when : END: end of the job FAIL: abortion BEGIN: beginning of job ALL: all events	<code>sbatch ---mail-type=BEGIN</code>
<code>--workdir=[dir_name]</code>	Precise the working directory	<code>sbatch --workdir=/scratch/tando script.sh</code>

BONUS

LAUNCH A JOB

- Scheduler choose resources automatically
- Use up to 24 cores at the same time
- Possibility to configure this choice
- Jobs launch in background
 - possibility to turn off your PC/MAC
 - automatic results retrieving

Launch a batch job

- Execute a script via Slurm
- Use:

```
$~ sbatch script.sh
```

with `script.sh` : the name of the script

Options of sbatch, srun, salloc commands

Options	Description	Exemple
<code>--job-name=<name></code>	Name the job	<code>sbatch --job-name=tando_blast</code>
<code>-p <partition></code>	Choose a partition	<code>sbatch -p highmem</code>
<code>--nodelist=<nodeX></code>	Choose a particular node	<code>sbatch -p normal --nodelist=node14</code>
<code>-n <nb_tasks></code>	Launch several instance of a command	<code>srun -n 4</code>
<code>-c <nb_cpu_per_task></code>	Allocate the number of cpus per task	<code>srun -n 4 -c 2 hostname</code>
<code>--mail-user=<emailaddress></code>	Send a email	<code>sbatch --mail-user=ndomassi.tando@ird.fr</code>
<code>--mail-type=<event></code>	Send a email when : END: end of the job FAIL: abortion BEGIN: beginning of job ALL: all events	<code>sbatch ---mail-type=BEGIN</code>
<code>--workdir=[dir_name]</code>	Precise the working directory	<code>sbatch --workdir=/scratch/tando script.sh</code>

First part of the script (in green): sge execution options with the key word #SBATCH

```
#!/bin/bash
```

```
##### Configuration SLURM#####  
## Name of the job:  
#SBATCH --job-name=test  
## Name of the output file:  
#SBATCH --output=res.txt  
## Number of tasks  
#SBATCH --ntasks=1  
## Execution Time Limit  
#SBATCH --time=10:00  
#####
```


In the 2nd part of the script: the command to execute

```
#####Partie exécution des commandes #####
```

```
nom_variable1="valeur_variable1"  
nom_variable2="valeur_variable2"
```

```
sleep 30  
hostname
```



Practice

Launch a script with sbatch

9

Go to the [Practice9](#) of the github

Thank you to fill up the form at this URL:

<https://itrop-survey.ird.fr/index.php/562934?lang=fr>

If you use i-Trop Bioinformatics resources.

Thank you for citing with:

“The authors acknowledge the IRD itrop HPC (South Green Platform) at IRD montpellier
for providing HPC resources that have contributed to the
research results reported within this paper.

URL: <https://bioinfo.ird.fr/>- <http://www.southgreen.fr>”

- Include a budget for bioinformatics resources in your answer to projects funding
- A need in hard drives, renew machines etc...
- Available quotations
- Contact bioinfo@ird.fr : help, needs definition, quotations...

Thank you for your attention !



Le matériel pédagogique utilisé pour ces enseignements est mis à disposition selon les termes de la licence Creative Commons Attribution - Pas d'Utilisation Commerciale - Partage dans les Mêmes Conditions (BY-NC-SA) 4.0 International:

<http://creativecommons.org/licenses/by-nc-sa/4.0/>