

Team Number: _____ School & Team Name: _____

Student Names: _____

CHECK-IN (6 MINUTES TO SET UP AND TEST STRUCTURE)

1. _____	4.b.iii.3	Team's submitted Estimated Load Supported in grams (used as first tiebreaker)
2. _____	4.b.iii.4	Mass of Structure (in grams to the nearest 0.01 g or best precision available)
3. <u>T</u> <u>F</u>	2.b.	Eye protection is worn. (If F, Team gets participation points only)
Construction & Competition Parameters:		
T	F	2.a. Team enters only one Structure, designed and built by the team prior to the competition.
T	F	4.b.i. Once participants begin check-in, they do not leave or gain outside assistance, materials, or communication until testing is completed.
T	F	4.b.ii. No alterations to the structure are made once check-in begins.
T	F	2.c. Participants are able to answer questions regarding the construction & operation of the structure.
T	F	3.a. The structure is a single structure with no separate, loose, or detachable parts or pieces.
T	F	3.b. The structure is constructed of wood and bonded by adhesive with no other materials used.
T	F	3.c. The structure attaches to the testing wall by resting on the Mounting Bolt Assembly.
T	F	3.d. The structure supports only the Loading Block of the Loading Assembly which supports the balance of the Loading Assembly.
T	F	3.f. Division B: During competition testing, the Boomilever only touches the Testing Wall <u>inside</u> the Vertical Contact Width Lines. Division C: During competition testing, the Boomilever only touches the Testing Wall <u>outside</u> the Vertical Contact Width Lines.
T	F	3.e.i. The structure supports the Loading Assembly with the centerline of the chain being at least 40cm but no more than 45 cm when measured horizontally from the testing wall.
T	F	3.e.ii. The structure supports the Loading Assembly with the centerline of the chain being no more than 2.5 cm horizontally from either side of a perpendicular line extending from the centerline of the Testing Wall.
T	F	3.g. Prior to loading sand, the bottom of the Loading Block is supported above the horizontal plane extending from the centerline of the Mounting Bolt.
T	F	4.c.iii. Once loading of sand has begun, the Structure is not further adjusted.
T	F	4.c.iv. The bucket is only stabilized from movement by the tips of the Bucket Stabilizing Sticks.
4. <u>T</u> <u>F</u>	ALL CONSTRUCTION AND COMPETITION PARAMETERS ABOVE ARE MET (IF FALSE, TIER 2)	

TESTING

T	F	4.c.vii.	The structure fits on the test stand, is able to be loaded, supports the minimum load, and has no safety concerns. If F, put 0 in Box 6 (Load Supported).
5. Does the Boomilever meet the Base, Bonus, or neither criterion?			
Base		Base Option: 3.h.i. <u>Div B:</u> The Boomilever only touches the testing wall above the <u>20 cm</u> Horizontal Contact Depth Lines. <u>Div C:</u> The Boomilever only touches the testing wall above the <u>15 cm</u> Horizontal Contact Depth Lines.	
Bonus		Load Scored BONUS Option: 3.i.i <u>Div B:</u> The Boomilever only touches the testing wall above the <u>15 cm</u> Horizontal Contact Depth Line. <u>Div C:</u> The Boomilever only touches the testing wall above the <u>10 cm</u> Horizontal Contact Depth Line. Bonus points are awarded if: 3.i.i is met and the structure holds 15kg.	
None		None: Tier 2, Boomilever does not satisfy the Base Option or the Load Scored BONUS Option conditions.	

6. _____ 4.c.vi. **Load Supported:** mass of Loading Assembly, sand, bucket, in grams; up to 15,000 g. **If 0 is written, team gets participation points.**

5.a. **SCORE** = (_____ / _____) = _____
 Load Supported (g) + Bonus Structure Mass (g)

5.d. Tier 1: Meeting all construction and competition requirements
 Tier 2: NOT meeting any one or more of the construction and/or competition requirements.

7. T F General Rule: The team is disqualified. (Notify the team and their coach as soon as possible.)