Radiation Survey of Teletherapy and Brachytherapy Units

Date of experiment: 10 January 2026

Medical Physics Laboratory II

Name: Souvik Das

Roll No: 241126007

National Institute of Science Education and Research
Jatani, Odisha, India

Date of submission: January 26, 2026

Contents

1 Objective

- Radiation leakage measurement of telecobalt and brachytherapy units in source-off condition.
- Radiation protection survey of the Teletherapy and Brachytherapy installation.

2 Apparatus

- Radiation Survey Monitor
- Pocket Dosimeter

Radiation Survey Monitor: A radiation survey monitor is a portable device used to measure and detect ionizing radiation levels in various environments. It typically consists of a Geiger-Müller tube or scintillation detector that can detect different types of radiation, such as alpha, beta, gamma, and X-rays. The monitor provides real-time readings of radiation intensity, allowing users to assess potential radiation hazards and ensure safety in areas where radioactive materials are present.

Pocket Dosimeter: A pocket dosimeter is a small, portable device used to measure an individual's exposure to ionizing radiation over a period of time. It is typically worn on the person, such as on a lapel or pocket, and provides a direct reading of the accumulated radiation dose. Pocket dosimeters are commonly used by radiation workers to monitor their exposure and ensure it remains within safe limits.

3 Theory

4 Observation

5 Conclusion