

**Name: Sowanthari R P**

**Week 1 Assignment**

**1.What is an aggregate function in SQL? Give an example.**

An aggregate function in SQL performs a calculation on a set of values and returns a single value. Common aggregate functions include SUM(), COUNT(), AVG(), MIN(), and MAX().

**Example: SELECT AVG(salary) FROM employees;**

**2.How can you use the GROUP BY clause in combination with aggregate functions?**

The GROUP BY clause groups rows that have the same values in specified columns into aggregate data. Aggregate functions are then applied to each group.

**Example: SELECT department\_id, COUNT(\*) FROM employees GROUP BY department\_id;**

**3.Describe a scenario where atomicity is crucial for database operations.**

Atomicity is crucial in banking transactions, such as transferring money between accounts. Both the debit and credit operations must complete successfully, or neither should, to prevent data inconsistency and incorrect balances.

**4.Mention any 2 differences between OLAP and OLTP.**

- **Purpose:** OLTP (Online Transaction Processing) is designed for handling transactional data with many short online transactions. OLAP (Online Analytical Processing) is used for querying and analyzing large datasets for business intelligence.

- **Data Structure:** OLTP systems use normalized databases to optimize transaction processing. OLAP systems often use denormalized data structures (like star or snowflake schemas) to optimize query performance.

#### **5.How do you optimize an OLTP database for better performance?**

One common optimization technique is using indexes, which speed up data retrieval.

**CREATE INDEX idx\_employee\_name ON employees(name);**

#### **6.What are the different types of data encryption available in MSSQL?**

- **Transparent Data Encryption (TDE):** Encrypts data at rest, including backups and transaction log files.
- **Always Encrypted:** Protects sensitive data by encrypting data both in transit and at rest, even while in use.

#### **7.What is the main difference between SQL and NoSQL databases?**

SQL databases use structured, table-based schemas and typically support ACID properties, while NoSQL databases use various data models (document, key-value, wide-column, graph) and prioritize scalability and flexibility over strict schema constraints.

#### **8.How do you create a new schema in MSSQL?**

**CREATE SCHEMA schema\_name;**

This command creates a new schema named schema\_name.

#### **9.Describe the process of altering an existing table.**

The ALTER TABLE statement is used to add, modify, or delete columns and constraints in an existing table.

**ALTER TABLE employees ADD birthdate DATE;**

## 10.What is the difference between a VIEW and a TABLE in MSSQL?

- **VIEW:** A virtual table based on a SELECT query. It does not store data itself but provides a way to simplify complex queries and enhance security by restricting access to specific data.
- **TABLE:** A database object that stores data in rows and columns.

## 11.Explain how to create and manage indexes in a table.

Indexes improve query performance by allowing faster data retrieval.

- **Create Index:** CREATE INDEX idx\_column\_name ON table\_name(column\_name);
- **Drop Index:** DROP INDEX idx\_column\_name ON table\_name;

## 12.What are the most commonly used DML commands?

DML (Data Manipulation Language) commands include:

- SELECT - Retrieves data from tables.
- INSERT - Adds new rows to a table.
- UPDATE - Modifies existing data in a table.
- DELETE - Removes rows from a table.

## 13.How do you retrieve data from multiple tables using a JOIN?

JOINS combine rows from two or more tables based on a related column.

```
SELECT e.name, d.name FROM employees e JOIN departments d ON  
e.department_id = d.id;
```

## 14.Explain how relational algebra is used in SQL queries.

Relational algebra provides a theoretical foundation for SQL operations. It includes operations like selection, projection, union, and join, which correspond to SQL queries such as SELECT, WHERE, JOIN, etc.

**15.What are the implications of using complex queries in terms of performance?**

Complex queries can lead to increased computational resources, longer processing times, and potential inefficiencies. They can also make it difficult to optimize the query, resulting in slower response times, especially with large datasets.

**16.How does the HAVING clause differ from the WHERE clause when using aggregate functions? Can you use HAVING before GROUP BY in the SELECT statement?**

The WHERE clause filters rows before aggregation, while the HAVING clause filters groups after aggregation.

**SELECT department\_id, COUNT(\*) FROM employees GROUP BY department\_id  
HAVING COUNT(\*) > 10;**

The HAVING clause cannot be used before GROUP BY; it must follow GROUP BY.

**17.What are filters in SQL and how are they used in queries?**

Filters in SQL restrict the data returned by a query based on specific conditions, implemented using clauses like WHERE, HAVING, LIMIT, and OFFSET.

**18.How do you use the WHERE clause to filter data in MSSQL?**

The WHERE clause is used to specify conditions that must be met for rows to be selected.

**SELECT \* FROM employees WHERE department\_id = 5;**

**19.How can you combine multiple filter conditions using logical operators?**

**SELECT \* FROM employees WHERE department\_id = 5 AND salary > 50000;**

This query selects employees from department 5 with a salary greater than 50,000.

## **20.Explain the use of CASE statements for filtering data in a query.**

The CASE statement allows for conditional logic within SQL queries, enabling different outputs based on specified conditions.

**SELECT name, CASE WHEN salary < 50000 THEN 'Low' WHEN salary BETWEEN 50000 AND 100000 THEN 'Medium' ELSE 'High' END as salary\_range FROM employees;**

## **21.What are the different types of operators available in MSSQL?**

MSSQL supports various types of operators:

- **Arithmetic Operators:** +, -, \*, /, %
- **Comparison Operators:** =, !=, <>, >, <, >=, <=
- **Logical Operators:** AND, OR, NOT
- **Bitwise Operators:** &, |, ^, ~, <<, >>
- **String Operators:** + (concatenation)

## **22. How do arithmetic operators work in SQL?**

Arithmetic operators perform mathematical calculations on numeric data types.

**SELECT salary, salary + 5000 AS new\_salary FROM employees;**

## **23. Explain the use of LIKE operator with wildcards for pattern matching.**

The LIKE operator is used for pattern matching in strings. Wildcards % (matches zero or more characters) and \_ (matches a single character) are used.

**SELECT \* FROM employees WHERE name LIKE 'J%';** This finds employees whose names start with 'J'.

## **24. What is normalization and why is it important?**

Normalization is a process to organize database tables to reduce redundancy and improve data integrity. It involves dividing large tables into smaller ones and defining relationships between them.

## **25. Describe the basic normal forms. Hint: 1NF, 2NF, 3NF**

- **1NF (First Normal Form):** Ensures that each column contains atomic values, and each column contains only one type of data.
- **2NF (Second Normal Form):** Meets all requirements of 1NF and ensures that all non-key attributes are fully functionally dependent on the primary key.
- **3NF (Third Normal Form):** Meets all requirements of 2NF and ensures that no transitive dependency exists between non-key attributes.

## **26. Mention any one impact of normalization on database performance.**

Normalization can lead to increased complexity in queries, which may require joining multiple tables, potentially slowing down read performance.

## **27. What are indexes and why are they used?**

Indexes are database objects that improve data retrieval speed by providing a quick way to look up rows in a table based on the values of one or more columns.

## **28. How do you create a unique constraint on a table column?**

A unique constraint ensures that all values in a column are unique.

**ALTER TABLE employees ADD CONSTRAINT unique\_email UNIQUE (email);**

## **29. Explain the difference between clustered and non-clustered indexes.**

- **Clustered Index:** Determines the physical order of data in a table and can only have one per table.

- **Non-Clustered Index:** Contains a sorted list of pointers to the table rows and does not affect the physical order. A table can have multiple non-clustered indexes.

### **30. How would you optimize index usage in a highly transactional database?**

Regularly update statistics, use indexing strategies like covering indexes, avoid excessive indexing, and periodically rebuild or reorganize fragmented indexes.

### **31. What are the different types of joins available in MSSQL?**

- INNER JOIN
- LEFT JOIN (LEFT OUTER JOIN)
- RIGHT JOIN (RIGHT OUTER JOIN)
- FULL JOIN (FULL OUTER JOIN)
- CROSS JOIN
- SELF JOIN

### **32. Provide an example of a LEFT JOIN query.**

```
SELECT e.name, d.name FROM employees e LEFT JOIN departments d ON  
e.department_id = d.id;
```

### **33. Explain the concept of a self-join and when it might be used.**

A self-join is a regular join but the table is joined with itself. It is used to find related rows in the same table.

```
SELECT e1.EmployeeID, e1.Name AS EmployeeName, e2.Name AS ManagerName  
FROM Employees e1 JOIN Employees e2 ON e1.ManagerID = e2.EmployeeID;
```

### **34. How do you perform a full outer join and what is its significance?**

A full outer join returns all rows from both tables, with matching rows from both sides where available. If there is no match, NULLs are returned for non-matching rows.

```
SELECT a.column1, b.column2 FROM table1 a FULL OUTER JOIN table2 b ON  
a.common_column = b.common_column;
```

### **35. What is an alias in SQL and how is it used?**

An alias is a temporary name for a table or column used within a query for ease of reference.

```
SELECT e.name AS employee_name FROM employees e;
```

Here, e is an alias for the employees table, and employee\_name is an alias for the name column.

### **36. Give an example of using table aliases in a query.**

```
SELECT e.name, d.name FROM employees e JOIN departments d ON  
e.department_id = d.id;
```

In this query, e and d are aliases for the employees and departments tables, respectively.

### **37. How do you use column aliases in conjunction with aggregate functions?**

Column aliases can rename the result of an aggregate function for clarity.

```
SELECT department_id, COUNT(*) AS total_employees FROM employees GROUP  
BY department_id;
```

total\_employees is an alias for the count of employees in each department.



### **38. Explain the benefits of using aliases in complex queries.**

Aliases simplify complex queries by making them more readable and easier to manage, especially when dealing with long table or column names, or when performing self-joins.

### **39. What is the difference between joins and subqueries?**

- **Joins:** Combine columns from multiple tables into a single result set based on related columns.
- **Subqueries:** Nested queries used within another query to perform operations on data, often returning values to be used in the main query.

### **40. When would you prefer a subquery over a join?**

Subqueries are preferable when you need to isolate specific logic, especially if you need to use the result of the subquery as a condition or to return a single value.

### **41. Explain how correlated subqueries work with an example.**

A correlated subquery depends on the outer query for its values and is evaluated once for each row processed by the outer query.

```
SELECT e1.name FROM employees e1 WHERE e1.salary > (SELECT  
AVG(e2.salary) FROM employees e2 WHERE e2.department_id =  
e1.department_id);
```

### **42. Discuss the performance implications of using joins vs subqueries.**

Joins are generally more efficient and faster because they are often optimized by SQL engines, especially for large datasets. Subqueries can be less efficient, particularly correlated subqueries, which may require the inner query to run multiple times.

### **43. What are the different data types available in MSSQL?**

Common data types include:

- **Numeric:** INT, FLOAT, DECIMAL
- **String:** VARCHAR, CHAR, TEXT
- **Date and Time:** DATE, TIME, DATETIME
- **Binary:** BINARY, VARBINARY
- **Miscellaneous:** BIT, UNIQUEIDENTIFIER

### **44. How do you choose the appropriate data type for a column?**

Consider the nature of the data, its size, and performance requirements. For example, use INT for integers, VARCHAR for variable-length strings, and DATETIME for date and time data.

### **45. How do you handle data type conversions in queries?**

Data type conversions can be handled using the CAST or CONVERT functions.

```
SELECT CAST(salary AS VARCHAR(10)) FROM employees;
```

### **46. What is a correlated subquery?**

A correlated subquery is a subquery that references columns from the outer query, making it dependent on the outer query for its values.

### **47. What is a non-correlated subquery? Hint: Outer query checks the data from inner sub query**

A non-correlated subquery is independent of the outer query, meaning it can be run on its own. The outer query uses the result of the subquery.

```
SELECT name FROM employees WHERE department_id = (SELECT  
department_id FROM departments WHERE name = 'Sales');
```

#### **48. Explain how correlated subqueries can affect query performance.**

Correlated subqueries can significantly affect performance because the subquery is executed for each row processed by the outer query, potentially leading to multiple executions.

#### **49. What is TSQL and how does it extend standard SQL?**

TSQL (Transact-SQL) is an extension of SQL used in Microsoft SQL Server. It includes procedural programming, error handling, and transaction control capabilities, making it more powerful for complex operations.

#### **50. How do you create a stored procedure in MSSQL?**

```
CREATE PROCEDURE GetEmployeeDetails (@EmployeeID INT)
AS
BEGIN
    SELECT * FROM employees WHERE id = @EmployeeID;
END;
```

#### **51. Explain the difference between functions and procedures in MSSQL.**

- **Functions:** Return a single value or a table and are used in SQL statements like SELECT.
- **Procedures:** Perform actions, can return multiple results, and support control-of-flow constructs. They are called using the EXECUTE command.

#### **52. Describe the use of triggers and provide an example scenario.**

Triggers are special types of stored procedures that automatically execute or fire when certain events occur in a database. They can be used to enforce business rules, validate data, or synchronize tables.

### **Example Scenario:**

```
CREATE TRIGGER UpdateOrderTimestamp ON Orders
AFTER UPDATE
AS
BEGIN
    UPDATE Orders SET last_modified = GETDATE() WHERE OrderID =
        inserted.OrderID;
END;
```

### **53. What are the main differences between TSQL and PL/SQL?**

- **T-SQL (Transact-SQL)** is Microsoft's proprietary extension to SQL used in SQL Server. It includes procedural programming, local variables, and control-of-flow constructs.
- **PL/SQL (Procedural Language/SQL)** is Oracle's procedural extension to SQL. It also supports procedural programming, but with different syntax and capabilities, such as exception handling and cursors.

### **54. Describe a scenario where you would use the SUM aggregate function to calculate total sales for each month.**

```
SELECT MONTH(sale_date) AS Month, YEAR(sale_date) AS Year, SUM(amount) AS
TotalSales

FROM Sales

GROUP BY MONTH(sale_date), YEAR(sale_date);
```

### **55. You have a banking application where transactions must be all-or-nothing. Explain how you would implement atomicity to ensure this.**

```
BEGIN TRANSACTION;

BEGIN TRY
```

```
-- Perform operations

UPDATE Account SET balance = balance - 100 WHERE account_id = 1;

UPDATE Account SET balance = balance + 100 WHERE account_id = 2;

COMMIT;

END TRY

BEGIN CATCH

    ROLLBACK;

END CATCH;
```

**56. Imagine you are setting up a new database for an e-commerce website. How would you ensure that only authorized users have access to sensitive customer data?**

To ensure that only authorized users have access to sensitive customer data:

- Implement user authentication and authorization controls.
- Use roles and permissions to restrict access to sensitive data.
- Apply encryption to protect data both at rest and in transit.

**Example:**

```
-- Create a role

CREATE ROLE SensitiveDataAccess;

-- Grant select permission on sensitive data

GRANT SELECT ON Customers TO SensitiveDataAccess;

-- Assign role to a user

EXEC sp_addrolemember 'SensitiveDataAccess', 'username';
```

**57. A large retail company needs a high-performing OLTP system for processing sales and an OLAP system for analyzing sales data. Explain how you would design and optimize these systems.**

- **OLTP (Online Transaction Processing) System:** Focus on high-speed transactions and reliability. Design a normalized schema to minimize redundancy, and use indexing to speed up query performance.
- **OLAP (Online Analytical Processing) System:** Optimize for complex queries and data analysis. Use a star schema or snowflake schema to facilitate efficient querying, and implement aggregation tables to speed up reporting and analysis.

**58. What is authentication vs authorization?**

- **Authentication** is the process of verifying the identity of a user or system (e.g., through usernames and passwords).
- **Authorization** determines what an authenticated user is allowed to do (e.g., what resources or operations they can access).

**59. You need to create a new table with columns for EmployeeID, Name, Position, and Salary. Write the SQL statement to create this table. Add unique constraint, primary key accordingly.**

```
CREATE TABLE Employees (  
    EmployeeID INT PRIMARY KEY,  
    Name VARCHAR(100),  
    Position VARCHAR(50),  
    Salary DECIMAL(10, 2) UNIQUE  
);
```

**60. A table needs to be altered to add a new column Email, but only if it doesn't already exist. Write the SQL statement to achieve this.**

```
IF NOT EXISTS (SELECT * FROM INFORMATION_SCHEMA.COLUMNS
```

```
WHERE TABLE_NAME = 'YourTable' AND COLUMN_NAME = 'Email')  
  
BEGIN  
  
    ALTER TABLE YourTable ADD Email VARCHAR(255);  
  
END
```

**61. What is a Composite Key?**

A composite key is a combination of two or more columns in a table that uniquely identifies a row in that table. It is used when a single column is not sufficient to uniquely identify records.

**62. Write a query to update the Salary column in the Employees table, increasing all salaries by 10%.**

```
UPDATE Employees SET Salary = Salary * 1.10;
```

**63. You need to retrieve data from the Orders and Customers tables to find all orders placed by customers from a specific city. Write the query.**

```
SELECT Orders.* FROM Orders  
INNER JOIN Customers ON Orders.CustomerID = Customers.CustomerID  
WHERE Customers.City = 'SpecificCity';
```

**64. Write a query to find the average Salary in the Employees table, grouped by Department.**

```
SELECT DepartmentID, AVG(Salary) AS AverageSalary  
FROM Employees  
GROUP BY DepartmentID;
```

**65. Describe a scenario where you would use the RANK function to assign ranks to employees based on their sales performance.**

The RANK function is used to rank employees based on their sales performance to identify top performers. For example, if you have a Sales table with columns for

EmployeeID and TotalSales, you can use RANK to assign ranks based on the total sales amount.

```
SELECT EmployeeID, SalesAmount,  
RANK() OVER (ORDER BY SalesAmount DESC) AS SalesRank  
FROM Sales;
```

**66. Write a query to filter out all products from the Products table that have a Price greater than rs.100.**

```
SELECT * FROM Products WHERE Price > 100;
```

**67. Explain how you would use the CASE statement to filter data based on multiple conditions, such as categorizing products into different price ranges.**

The CASE statement can be used to create new categories based on conditions. For example:

```
SELECT ProductID, ProductName,  
CASE  
    WHEN Price < 50 THEN 'Low'  
    WHEN Price BETWEEN 50 AND 100 THEN 'Medium'  
    ELSE 'High'  
END AS PriceCategory  
FROM Products;
```

**68. Write a query to find all employees whose Name starts with the letter 'A'.**

```
SELECT * FROM Employees WHERE Name LIKE 'A%';
```

**69. A denormalized database is causing performance issues. Describe the steps you would take to normalize it and improve performance till 3NF.**

- **First Normal Form (1NF):** Ensure that each column contains only atomic values, and each row is unique.



- **Second Normal Form (2NF):** Remove partial dependencies, ensuring all non-key attributes are fully dependent on the primary key.
- **Third Normal Form (3NF):** Remove transitive dependencies, ensuring that non-key attributes are only dependent on the primary key.

**70. Write a SQL statement to create an index on the Email column of the Users table.**

```
CREATE INDEX idx_email ON Users (Email);
```

**71. Write a query to perform an inner join between the Orders and Customers tables to retrieve all orders along with customer names.**

```
SELECT Orders.OrderID, Customers.CustomerName FROM Orders
INNER JOIN Customers ON Orders.CustomerID = Customers.CustomerID;
```

**72. Describe a scenario where a full outer join would be necessary, and provide a query example.**

A full outer join is useful when you need to retrieve all records from both tables, even if there is no match. For example, to find all products and all orders, including those without corresponding data:

```
SELECT Products.ProductName, Orders.OrderID FROM Products
FULL OUTER JOIN Orders ON Products.ProductID = Orders.ProductID;
```

**73. Write a query using table aliases to simplify a complex join between three tables: Orders, Customers, and Products.**

```
SELECT o.OrderID, c.CustomerName, p.ProductName FROM Orders AS o
INNER JOIN Customers AS c ON o.CustomerID = c.CustomerID
INNER JOIN Products AS p ON o.ProductID = p.ProductID;
```

**74. Explain how column aliases can be used in a query with aggregate functions to make the results more readable.**

Column aliases make query results easier to understand by providing meaningful names to the output columns. For example:

```
SELECT AVG(Salary) AS AverageSalary FROM Employees;
```

Here, AverageSalary is a column alias for the result of the AVG(Salary) function.

**75. Provide a scenario where a subquery would be more appropriate than a join, and write the corresponding query.**

Subqueries are useful when you need to filter results based on an aggregated value. For example, to find employees who earn more than the average salary:

```
SELECT EmployeeID, Name, Salary FROM Employees  
WHERE Salary > (SELECT AVG(Salary) FROM Employees);
```

**76. Compare the performance implications of using a join versus a subquery for retrieving data from large tables.**

- **Join:** Often more efficient for retrieving related data from multiple tables in a single query.
- **Subquery:** Can be less efficient, especially if used in the WHERE clause, as it may result in multiple executions of the subquery.

**77. Describe a scenario where using a DATETIME data type would be essential, and explain how you would store and retrieve this data.**

A DATETIME data type is essential for recording timestamps of transactions or events. For example, in a transaction table, you might store the date and time of each transaction:

```
CREATE TABLE Transactions (  
    TransactionID INT PRIMARY KEY,
```

```
TransactionDate DATETIME,  
Amount DECIMAL(10, 2)  
);
```

To retrieve transactions from a specific date range:

```
SELECT * FROM Transactions  
WHERE TransactionDate BETWEEN '2024-01-01' AND '2024-12-31';
```

**78. Explain how you would handle data type conversions when importing data from a CSV file with mixed data types.**

You would:

- Identify the correct data types for each column.
- Use tools or scripts to convert data types during the import process.
- Validate and clean the data before importing to ensure compatibility with the database schema.

**79. Write a query using a correlated subquery to find all employees who have a salary higher than the average salary in their department.**

```
SELECT EmployeeID, Name, Salary FROM Employees e1  
WHERE Salary > (SELECT AVG(Salary) FROM Employees e2  
WHERE e1.DepartmentID = e2.DepartmentID);
```

**80. Explain how non-correlated subqueries can be optimized for better performance compared to correlated subqueries.**

Non-correlated subqueries are executed once and the result is used multiple times, which is often more efficient than correlated subqueries that execute for each row in the outer query. Optimizing non-correlated subqueries involves indexing the columns used in the subquery to speed up execution.

**81. Write a simple stored procedure to insert a new record into the Employees table.**

```
CREATE PROCEDURE AddEmployee
```

```
    @EmployeeID INT,
```

```
    @Name VARCHAR(100),
```

```
    @Position VARCHAR(50),
```

```
    @Salary DECIMAL(10, 2)
```

```
AS
```

```
BEGIN
```

```
    INSERT INTO Employees (EmployeeID, Name, Position, Salary)
```

```
    VALUES (@EmployeeID, @Name, @Position, @Salary);
```

```
END;
```

**82. Describe a scenario where you would use a trigger to enforce business rules.**

```
CREATE TRIGGER CheckSalary
```

```
ON Employees
```

```
AFTER INSERT, UPDATE
```

```
AS
```

```
BEGIN
```

```
    IF EXISTS (
```

```
        SELECT 1
```

```
        FROM Employees e
```

```
        JOIN Employees m ON e.ManagerID = m.EmployeeID
```

```
        WHERE e.Salary > m.Salary
```

```
    )
```

```
BEGIN
```

```
        RAISERROR ('Employee salary cannot exceed manager salary.', 16, 1);  
    ROLLBACK;  
END  
END;
```

**83. Mention any 2 common security measures to protect a SQL Server database.**

- **Encryption:** Encrypt sensitive data both at rest and in transit.
- **Access Control:** Implement strict user roles and permissions to limit access to sensitive data.

**84. How do you create a user and assign roles in MSSQL?**

```
-- Create a new user  
CREATE LOGIN newUser WITH PASSWORD = 'password123';  
CREATE USER newUser FOR LOGIN newUser;  
  
-- Assign roles  
EXEC sp_addrolemember 'db_datareader', 'newUser';  
EXEC sp_addrolemember 'db_datawriter', 'newUser';
```

**85. Explain how encryption can be implemented for data at rest in MSSQL.**

Encryption for data at rest can be implemented using **Transparent Data Encryption (TDE)**, which encrypts the entire database and log files.

To enable TDE:

```
-- Create a master key  
CREATE MASTER KEY ENCRYPTION BY PASSWORD = 'YourStrongPassword';  
  
-- Create a certificate  
CREATE CERTIFICATE MyCertificate
```

```
WITH SUBJECT = 'My Database Encryption Certificate';  
-- Create a database encryption key  
CREATE DATABASE ENCRYPTION KEY  
WITH ALGORITHM = AES_256  
ENCRYPTION BY SERVER CERTIFICATE MyCertificate;  
-- Enable encryption  
ALTER DATABASE YourDatabase  
SET ENCRYPTION ON;
```