## **Shop API - User Module aaDocumentation**

#### **Overview**

This documentation provides an overview of the User module endpoints for the Shop API. The User module includes functionalities such as user registration, login, deletion, and retrieval of orders. All endpoints that require authentication use JWT tokens.

Base URL

http://sp-rest.vercel.app/

### User

## **Endpoints**

### **User Registration**

- → POST /user/signup
  - ◆ This endpoint allows a new user to register.
  - ◆ Request:
    - Method: POSTURL: /user/signup
    - Headers: Content-Type: application/json
    - Body: json

{ "email": "user@example.com", "password": "user password" }

### **User Login**

- POST /user/login
  - o This endpoint allows a user to log in and receive a JWT token.
  - Request:
    - Method: POSTURL: /user/login
    - Headers: Content-Type: application/json
    - Body json :

```
{ "email": "user@example.com", "password": "user_password" }
```

#### **Delete User**

- DELETE /user/
  - This endpoint allows for the deletion of a user account.
  - o Request:

Method: DELETEURL: /user/userID

Headers:

Content-Type: application/jsonAuthorization: Bearer jwt token

Params:

■ userID: The ID of the user to be deleted.

# **Product**

#### **Get All Products**

- GET /product
  - This endpoint retrieves all products.
  - Request:

Method: GETURL: /productHeaders: None

#### **Create a Product**

- → POST /product
  - ◆ This endpoint allows a new product to be created.
  - ◆ Request:

Method: POSTURL: /product

Headers:

Authorization: Bearer jwt\_tokenContent-Type: multipart/form-data

### Body: Form data:

o name (String): The name of the product

o price (Number): The price of the product

o productImage (File): The image file of the product

## **Get a Specific Product**

GET /product/:productID

o This endpoint retrieves a specific product by ID.

Request:

Method: GET

■ URL: /product/:productID

■ Headers: None

# **Update a Product**

PATCH /product/:productID

This endpoint updates a product by ID.

Request:

■ Method: PATCH

■ URL: /product/:productID

Headers:

Authorization: Bearer jwt\_tokenContent-Type: application/json

#### **Delete a Product**

DELETE /product/:productID

o This endpoint deletes a product by ID.

Request:

■ Method: DELETE

■ URL: /product/:productID

Headers:

Authorization: Bearer jwt\_tokenContent-Type: application/json

## **Orders**

#### Create an Order

POST / orders

This endpoint allows a new order to be created.

### Request:

Method: POSTURL: /ordersHeaders:

Authorization: Bearer jwt\_tokenContent-Type: application/json

Body: json

{ "productID": "product\_id", "quantity": 1 }

#### **Get All Orders**

- GET /orders
  - o This endpoint retrieves all orders.
  - Request:

Method: GETURL: /ordersHeaders:

Authorization: Bearer jwt\_token

### Get a Specific Order

- GET /order/:orderID
  - This endpoint retrieves a specific order by ID.
  - Request:

■ Method: GET

■ URL: /orders/:orderID

Headers:

■ Authorization: Bearer jwt\_token

## **Delete an Order**

- DELETE /orders/
  - o This endpoint deletes a specific order by ID.
  - Request:

Method: DELETEURL: /orders/

■ Headers:

■ Authorization: Bearer jwt\_token