



System Verification and Validation Plan for RoCam

Team #3, SpaceY

Zifan Si

Jianqing Liu

Mike Chen

Xiaotian Lou

March 9, 2026

Revision History

Date	Version	Notes
2025-10-21	1.0	Initial Draft
2025-10-23	2.0	Revised on section 3
2025-10-26	3.0	Revised on section 3 based on TA and peer feedback
2025-10-27	4.0	Added system tests
2026-03-04	5.0	Scope limited to unit testing and stakeholder (McMaster Rocketry Team) review only; removed supervisor, classmate, task-based inspection, field testing
2026-03-05	6.0	Added unit testing plan
2026-04-05	7.0	Rev 1: Removed template comments; added unit test summary section; fixed typos and grammar; updated traceability matrices; addressed TA and peer feedback; added test environment details and timing requirements per peer review

Contents

1	Symbols, Abbreviations, and Acronyms	iv
2	General Information	1
2.1	Summary	1
2.2	Objectives	1
2.3	In-Scope Objectives	2
2.4	Out-of-Scope Objectives	2
2.5	Extras	2
2.6	Relevant Documentation	3
3	Plan	3
3.1	Verification and Validation Team	4
3.2	SRS Verification	4
3.2.1	Functional and Non-Functional Requirement Review	4
3.2.2	Stakeholder Review	4
3.2.3	Constraints and Scope of Work Review	4
3.3	Design Verification	5
3.4	Verification and Validation Plan Verification	7
3.5	Implementation Verification	8
3.6	Automated Testing and Verification Tools	9
3.7	Software Validation	10
4	System Tests	11
4.1	Tests for Functional Requirements	11
4.1.1	Area of Testing: Video Acquisition and Output	11
4.1.2	Area of Testing: Recording	13
4.1.3	Area of Testing: Tracking	14
4.1.4	Field Testing (Out of Scope)	16
4.2	Tests for Nonfunctional Requirements	16
4.2.1	UI Walkthrough	16
4.2.2	Code and Documentation Walkthrough	19
4.2.3	Error Handling and Logging	19
4.2.4	Field Testing (Out of Scope)	20
4.3	Traceability Between Test Cases and Requirements	22
5	Unit Test Description	22
5.1	Unit Test Summary	22
5.2	Unit Testing Scope	24
5.3	Tests for Functional Requirements	25
5.3.1	Module: State Management (mState)	25
5.3.2	Module: API Gateway (mAPI)	27
5.3.3	Module: Recording Database (mRecord)	28
5.3.4	Module: Gimbal Abstraction (mGimbal)	29

5.3.5	Module: Tracking (mTrack)	30
5.3.6	Module: CV Process Management (mCVManagement)	31
5.3.7	Module: Live Video Process Management (mVideoManagement)	32
5.3.8	Module: Transcode API (mAPI)	33
5.3.9	Module: Transcode Process (mTranscode)	34
5.3.10	Module: CV Process (mCV)	35
5.3.11	Module: Common IPC (Shared Modules)	35
5.3.12	Module: Common IPC Buffer	36
5.3.13	Module: Common Watchdog	37
5.3.14	Module: Preview (mPreview)	37
5.3.15	Module: Manual Control (mManual)	38
5.3.16	Module: Recording Management (mRecordMng)	38
5.3.17	Module: Configuration (mConfig)	40
5.3.18	Module: API Client (Network Layer)	40
5.3.19	Module: Rocam Provider (React Context)	41
5.3.20	Module: Utility Formatters	42
5.3.21	Module: Internationalization (i18n)	43
5.3.22	Module: Application Routing (App)	43
5.4	Tests for Nonfunctional Requirements	44
5.4.1	Module: State Management (mState)	44
5.4.2	Module: API Gateway (mAPI)	44
5.4.3	Module: SSE (Server-Sent Events)	45
5.4.4	Module: IPC Buffer	45
5.4.5	Module: CV Process Management (mCVManagement)	46
5.4.6	Module: Recording Database (mRecord)	46
5.4.7	Module: Watchdog	46
5.4.8	Module: System Status (mStatus)	47
5.4.9	Module: Common Utils	47
5.4.10	Module: Recording-Only State Management	48
5.4.11	Module: Main Entry Point	49
5.4.12	Module: Utility Formatters	50
5.4.13	Module: UI Components	51
5.5	Traceability Between Test Cases and Modules	51
6	Appendix	56
6.1	User Survey Questions	56

1 Symbols, Abbreviations, and Acronyms

symbol	description
YOLO	You Only Look Once – an existing object detection model
CNN	Convolutional Neural Network
Jetson	abbreviation for specifically Jetson Nano Orin, which is the proposed board for this project
STM32	abbreviation for specifically STM32 microcontroller, which is the proposed microcontroller

This Verification and Validation (V&V) plan outlines how the RoCam project will demonstrate that the system is built correctly (verification) and fits stakeholder needs (validation). It anchors testing to the SRS, architecture (MG), and detailed design (MIS), ensuring every requirement is traceable where possible. **Unit testing and system testing are performed;** only field testing is out of scope. Verification relies on structured internal reviews and checklists, plus unit tests and system tests, to confirm functional behavior and safety assumptions. Validation is limited to a planned review with the McMaster Rocketry Team (stakeholders) to collect feedback; no task-based inspection, classmate review, or supervisor validation is conducted. Roles and responsibilities are assigned to team members only, with feedback from the rocketry team captured and tracked. Priorities emphasize correctness, performance, reliability, and safety; lower-priority or out-of-scope items (e.g., exhaustive usability studies, independent verification of third-party components, and field testing) are noted to keep the plan feasible. The document concludes with traceability tables, a unit test summary, and appendices for parameters and optional surveys—forming a clear, practical roadmap for the evidence of quality that can be gathered under these constraints.

2 General Information

2.1 Summary

The RoCam system is a ground-based camera and gimbal assembly designed to autonomously track model rockets during launch and flight. It utilizes a high-resolution camera coupled with a motorized gimbal to maintain visual lock on the rocket, providing real-time data and video feed. The system consists of a STM32 based motion controller that interfaces with the physical gimbal; a Jetson compute module that processes the camera feed; and a react frontend that displays the video preview and allows the user to control the gimbal. The primary purpose of RoCam is to replace the traditional unreliable manual tracking methods with an automated solution to produce high-quality flight data and video footage. To better assist model rocket teams across Canada to conduct successful launches by providing an affordable and reliable system that can be easily track rocket launch movements.

2.2 Objectives

The primary objective of this Verification and Validation V&V Plan is to establish confidence in the correctness, performance, and reliability of the RoCam system by ensuring that all verification and validation activities are thorough, traceable, and aligned with project requirements. The plan emphasizes unit testing, system testing, and internal review to confirm that functional and performance criteria are addressed where possible, with improvements tracked through GitHub Issues. Validation focuses on a planned review with the McMaster Rocketry Team (stakeholders) to collect feedback; no field testing or supervisor validation is performed. These qualities—correctness, performance, reliability, and traceability—are fundamental to the success of the V&V process, ensuring that the RoCam system is both technically sound and operationally dependable. Certain objectives, such as independent verification of third-party hardware and extended usability testing, are excluded due to scope

and resource limitations, with reliance placed on manufacturer and stakeholder validation.

2.3 In-Scope Objectives

Verification and validation efforts will prioritize the following qualities:

- **Correctness:** Ensure the reliability of tracking and control algorithms through testing and validation.
- **Performance:** Achieve real-time processing of 1080p 60 fps video and maintain minimal gimbal control latency.
- **Safety:** Guarantee that the system operates safely under assumed conditions, with fail-safe mechanisms.

2.4 Out-of-Scope Objectives

The following objectives are excluded from this project due to time, budget, and resource constraints:

- **Field Testing:** Live rocket launches, hardware field conditions, and external reviewer validation at launch sites are out of scope.
- **Third-Party Component Verification:** External hardware such as the gimbal controller and camera are assumed to perform according to their manufacturer specifications.
- **Scalability Beyond Small-Scale Rockets:** Tracking a bullet or extremely difficult targets beyond a model rocket is outside the scope of this project.

By defining these priorities and exclusions, the RoCam project ensures that available effort is directed toward validating the most critical system qualities: **performance, accuracy, and operational safety**.

2.5 Extras

Beyond the core objectives, the RoCam project includes several extras that enhance its quality and usability:

- **STM32 control circuit design:** Development of a custom control circuit to interface the gimbal actuators with the host computer, enabling precise motion control and feedback sensing.
- **User Instructional Video:** Creation of a short instructional video demonstrating system setup, calibration, and operation to support new users and ensure safe deployment.

These extras aim to improve the overall usability, accessibility, and documentation quality of the final deliverable, reinforcing RoCam's emphasis on practical integration between computer vision software, mechanical control, and end-user experience.

2.6 Relevant Documentation

Software Requirements Specification (SRS Vision-Guided Tracker Team (2025c)):

The SRS document serves as an outline for the VnV plan. The SRS document contains specific functional and non-functional requirements, performance criteria, and constraints. The SRS document also contains detailed stakeholder roles and scope of the work. Aligning the VnV plan with the SRS document ensures that all specified requirements are adequately verified and validated.

Software Architecture MG (MG Vision-Guided Tracker Team (2025a)) The MG document provides details of our system architecture. To effectively design tests to validate and verify the system, it is important to understand the architecture and functionality of each module.

Software Detailed Design Document (MIS Vision-Guided Tracker Team (2025b)):

The MIS document provides detailed design of our system. It provides critical information about the implementation details, including data structures, algorithms, and interfaces. This document is essential for efficient test design to specific modules.

3 Plan

This section outlines the overall Verification and Validation (V&V) plan for the **RoCam** project. It defines the structure, responsibilities, and methods used to verify that the system meets its functional and non-functional requirements and to validate that it fulfills stakeholder needs. The section covers the verification of the SRS, design, and implementation via internal reviews, unit testing, and system testing, as well as the validation strategy through a planned stakeholder review with the McMaster Rocketry Team (no field testing). Its purpose is to provide a clear, organized framework ensuring that all aspects of RoCam are systematically tested, reviewed, and proven reliable before final deployment.

3.1 Verification and Validation Team

Table 1: Verification and Validation Team Responsibilities

Name	Role	V&V Responsibilities
Zifan Si	Front End Interface Tester	Responsible for verifying and validating the usability and functionality of the react frontend interface. Ensure usability, robustness of frontend features.
Jianqing Liu	Team Lead	Conduct system validation. Validate the functionality and performance of the system against requirements and use cases. Validate system design and functionality.
Mike Chen	CV Tester	Verify and validate computer vision pipeline performance, including object detection and tracking accuracy.
Xiaotian Lou	Test automation developer	Implement automated testing frameworks in all software components. Implement API tests across different modules.

3.2 SRS Verification

The SRS verification will focus on verifying whether the system design satisfies all functional and non-functional requirements, stakeholder needs, scope of work, and constraints specified. The SRS verification will be conducted through the following steps:

3.2.1 Functional and Non-Functional Requirement Review

Since the design verification will evaluate in detail whether the system aligns with the functional and non-functional requirements, the SRS verification will focus on verifying the system design as a whole against the requirements. It will be implemented as system tests in the final stages of development.

3.2.2 Stakeholder Review

Since our team leader is the control team lead of the McMaster Rocketry Team, he serves as the primary reviewer of the system design and implementation and acts as the communication bridge between the team and the stakeholders.

3.2.3 Constraints and Scope of Work Review

Several internal review sessions will be conducted to ensure that our system design and implementation are within the defined scope of work and constraints specified in the SRS document.

Table 2: SRS Verification Checklist

Phase	Verification Activities
Functional & Non-Functional Requirement Review	☐ Review all requirements against current system design ☐ Create automated system tests for functional requirements ☐ Measure performance, safety, and reliability against non-functional requirements ☐ Record test results and address any failed cases ☐ Update traceability matrix after verification
Stakeholder Review	☐ Present verified results and collect feedback ☐ Document required changes based on feedback ☐ Obtain stakeholder confirmation or approval
Constraints & Scope of Work Review	☐ Verify implementation stays within project scope ☐ Check compliance with all technical and safety constraints ☐ Review design against timeline and budget limits ☐ Update records if scope or constraints change
System Verification	☐ Conduct system tests covering all system components ☐ Validate full system behavior against SRS requirements ☐ Log and resolve all system test issues ☐ Prepare final verification report for stakeholder review
Safety Review	☐ Review safety requirements against Hazard Analysis

3.3 Design Verification

The design verification process for the **RoCam** project ensures that the proposed architecture, algorithms, and hardware interfaces satisfy all functional and non-functional requirements before implementation. Design verification activities will be conducted through structured design reviews, peer evaluations, and the use of detailed verification checklists. The goal is to confirm that the design meets the intended performance, reliability, and safety objectives defined in the SRS.

Verification Plan

The design verification will proceed through internal review only (no classmate or supervisor review, due to contact and resource limitations):

1. **Internal Design Review:** Each subsystem (computer vision, control, and UI) will undergo an internal review by all four team members (Zifan Si, Jianqing Liu, Mike Chen, Xiaotian Lou). All members must agree on the designed architecture, algorithms, and interfaces. Interfaces must be clearly defined for scalability.

Verification Artifacts

Design verification will produce the following artifacts:

- Verified design diagrams and interface specifications.
- Internal review notes and agreed-upon design decisions.
- Updated design documents reflecting corrections and improvements.
- Completed design verification checklists (Table 3).

Design Verification Checklist

Table 3 will be used during design reviews to ensure completeness and consistency across all modules:

Table 3: Design Verification Checklist

Phase	Verification Activities
Internal Design Review	☐ Review subsystem architectures (vision, control, UI) with all team members ☐ Confirm APIs that are agreed upon ☐ Verify all module interfaces are clearly defined and documented in code ☐ Ensure design supports scalability and modularity ☐ Record review comments and update design diagrams
Verification Artifacts	☐ Store verified design diagrams and updated interface specifications ☐ Archive internal review notes and design decisions ☐ Maintain a design document in the project repository ☐ Complete and file the final design verification checklist

By following this structured verification plan and checklist, the team ensures that the RoCam design is both technically sound and fully aligned with its performance and safety goals prior to implementation.

3.4 Verification and Validation Plan Verification

The verification of the verification and validation (VnV) plan for the **RoCam** project will be verified through internal review and unit testing only. Each iteration of feedback and improvements will be tracked with GitHub Issues. The focus of the verification plan is to ensure functionality and performance metrics are adequately covered in design where possible.

For the validation plan, the only validation activity is a planned review with the McMaster Rocketry Team (stakeholders) to collect feedback. No field tests or supervisor validation are performed; unit testing and system testing are conducted.

Table 4: RoCam Verification and Validation (V&V) Checklist

Phase	Actionable Verification and Validation Activities
Verification Plan Review	☐ Conduct internal reviews of the V&V plan with team ☐ Ensure functionality and performance metrics are fully covered ☐ Track feedback and revisions using GitHub Issues ☐ Confirm all review comments are resolved before approval
Automated Verification Testing	☐ Develop automated tests for vision, control, and UI components ☐ Verify software behavior under simulated conditions ☐ Record test results and compare against performance criteria ☐ Update test scripts based on identified defects or regressions
Continuous Monitoring	☐ Review unit test outcomes after each iteration ☐ Maintain test evidence and validation summaries in repository ☐ Update the V&V plan to reflect system improvements and new unit test cases

3.5 Implementation Verification

The implementation verification for the **RoCam** project ensures that the developed software and integrated hardware components correctly realize the verified design. This phase confirms that the implemented system satisfies the functional and non-functional requirements defined in the SRS through a combination of structured testing, static verification, and peer review.

Dynamic Verification

Due to resource and contact limitations, **only field testing** is out of scope. Unit testing and system testing are performed.

- **Unit Testing:** Each software module (vision processing, gimbal control, data recording, and UI management) will undergo unit testing to verify functional correctness in isolation. This is the only form of dynamic testing conducted.

Out of scope: Field testing is not performed due to the constraints noted in this plan.

Static Verification

Static verification will be performed throughout the implementation phase to ensure that the codebase meets quality, safety, and maintainability standards before execution. Planned techniques include:

- **Code Walkthroughs:** Internal code walkthroughs where each subsystem lead presents core implementation logic and design decisions to the team, enabling identification of potential design or coding issues.
- **Code Inspection:** Team members will review each other's pull requests prior to merging into the main branch. Reviews will focus on coding standard compliance, potential logic errors, exception handling, and safety-critical sections that align with the Hazard Analysis (e.g., gimbal actuation and state transitions).
- **Static Analysis Tools:** Where applicable (e.g., on the frontend), static analysis may be used to detect common implementation defects. Results will be logged and reviewed as part of the verification record.
- **Documentation Review:** The team will verify that all inline comments, module-level documentation, and API references are consistent with the design specification and user documentation requirements.

Together, these verification activities ensure that the RoCam implementation is thoroughly tested, statically verified, and validated against both its design and real-world performance expectations.

3.6 Automated Testing and Verification Tools

The RoCam project adopts a structured automated testing approach that prioritizes maintainability, integration compatibility, and developer productivity. The selection of testing frameworks was guided by three key criteria: (1) **language and runtime fit**, ensuring each tool aligns with its respective language and runtime; (2) **ease of automation**, to integrate smoothly with CI/CD pipelines; and (3) **scalability**, so that test coverage can expand as the project evolves. These principles ensure a consistent and reliable testing environment across frontend and end-to-end validation stages.

Each subsystem of RoCam employs unit testing and coverage tools appropriate to its implementation language. The frontend (React/TypeScript) uses a unit testing framework and coverage reporting suited to that stack. System-level and Web UI testing, where in scope, use tooling that can coordinate frontend and hardware layers. Specific frameworks are chosen to support CI/CD integration and to allow test coverage to scale as the project evolves.

Code Coverage and Reporting Plan:

Coverage analysis is conducted using tools that provide line, branch, and function-level metrics for each language stack, with results suitable for unified tracking and CI integration.

Linters and Formatters:

To maintain coding standards and prevent stylistic or logical errors, RoCam enforces consistent linting and formatting on the frontend:

- **Frontend (TypeScript):** Uses **ESLint** and **Prettier** to maintain uniform style rules and detect syntax or logical inconsistencies.

3.7 Software Validation

Software validation confirms that **RoCam** satisfies stakeholder needs and accurately implements the intended use cases (“building the right system”). Validation complements verification and is referenced to the SRS goals and stakeholder roles.

Stakeholder Review (McMaster Rocketry Team)

Validation is limited to a planned review with the McMaster Rocketry Team (stakeholders). The following is **in scope**:

- **Stakeholder Review Session:** A scheduled review with the McMaster Rocketry Team to present the current system (or design/SRS), discuss scope, priorities, and acceptance criteria, and collect feedback. Revisions to the plan or implementation will be made based on their feedback.

Out of scope (not conducted): Task-based inspection by stakeholders, classmate or peer review, supervisor validation, Rev 0/supervisor demo, and formal user (operator) sessions. These are excluded due to contact and resource limitations.

External Data and Bench Validation

- **Reference Footage:** Where live launches are unavailable, public model-rocket videos and internally recorded dry-runs are used to validate detection/tracking logic and reacquisition behavior.
- **Synthetic Scenarios:** Scripted clips with occlusion/smoke/backlight and varying apparent rocket sizes validate robustness claims prior to field tests.

Acceptance and Traceability

- **Acceptance Criteria:** Derived from the SRS (e.g., sustained 1080p 60 fps I/O, end-to-end latency ≤ 120 ms, successful tracking through nominal flight phases, recording with angle overlays).
- **Traceability:** Validation tests map to SRS goals and stakeholder needs; a table links each validation activity to the corresponding SRS item(s) and planned evidence (videos, logs, checklists).

If no suitable external datasets are available for certain scenarios, this limitation will be stated explicitly; validation in this plan relies on the planned stakeholder review with the McMaster Rocketry Team and, where applicable, unit testing and internal review only. This section also references the SRS verification section for consistency checks between validated behaviors and specified requirements.

4 System Tests

Scope note: Due to resource and contact limitations, **only field testing** is out of scope. Unit tests and system tests described in this section are executed. Evidence of correctness comes from unit tests, system tests, and the planned stakeholder review with the McMaster Rocketry Team.

4.1 Tests for Functional Requirements

The following manual tests are designed to evaluate the robustness of the Tracking Camera System. Each test includes its initial state, input, expected output, justification (test case derivation), and procedure. Tests are organized by functional area. The intent is to verify compliance with the functional requirements (FR) while deliberately stressing the system to expose edge cases.

4.1.1 Area of Testing: Video Acquisition and Output

test-acquire-frame: Camera Frames are Acquired at Startup

- **Control:** Manual
- **Initial State:** System powered off; camera connected; HDMI monitor attached.
- **Input:** Power on the system and allow it to fully initialize.
- **Expected Output:** Within 10s of boot, logs show that the camera is acquiring frames.
- **Test Case Derivation:** The system's operation depends on a valid video feed.
- **How Test Will Be Performed:** Boot the device; observe the program logs.

test-disconnect-camera: Camera Disconnect During Operation

- **Control:** Manual
- **Initial State:** System initialized; preview and HDMI output active.
- **Input:** Physically disconnect the camera from the system.
- **Expected Output:** On disconnect, the UI and HDMI output show a clear error message; no crash.
- **Test Case Derivation:** When the camera is disconnected, the system should gracefully handle the loss without crashing. And it should notify the operator that the camera is disconnected.
- **How Test Will Be Performed:** Disconnect the camera from the system; observe the UI and HDMI output for error messages.

`test-hdmi-output`: HDMI Output with Info Overlay

- **Control:** Manual
- **Initial State:** System initialized; idle state; preview and HDMI output active.
- **Input:** Move the gimbal manually through the UI.
- **Expected Output:** HDMI shows 1080p60 camera feed with a text overlay of current pan/tilt angles.
- **Test Case Derivation:** The system should be able to display the current camera feed and the pan/tilt angles for the viewers
- **How Test Will Be Performed:** Move the gimbal manually, and visually verify overlay values change smoothly and match commanded motion

`test-disconnect-hdmi`: HDMI Disconnect

- **Control:** Manual
- **Initial State:** System initialized; preview and HDMI output active.
- **Input:** Physically disconnect the HDMI cable.
- **Expected Output:** On disconnect, the UI shows a clear error message; no crash.
- **Test Case Derivation:** When the HDMI cable is disconnected, the system should gracefully handle the loss without crashing. And it should notify the operator that the HDMI cable is disconnected.
- **How Test Will Be Performed:** Disconnect the HDMI cable from the system; observe the UI for error messages.

`test-preview-real-time`: Preview with Real-Time Info

- **Control:** Manual
- **Initial State:** System initialized; idle state; preview and HDMI output active.
- **Input:** Move the gimbal manually through the UI.
- **Expected Output:** Preview in the UI updates fluidly (target ≥ 15 fps) and displays current pan/tilt angles.
- **Test Case Derivation:** The system should allow the camera operator to see the current pan/tilt angles and HDMI output in real-time.
- **How Test Will Be Performed:** Move the gimbal manually, and visually verify the preview in the UI updates fluidly and displays the current pan/tilt angles.

test-network-disconnect: Network Disconnect While Viewing UI

- **Control:** Manual
- **Initial State:** System initialized; preview and HDMI output active.
- **Input:** Disconnect the system from the network for 30s; reconnect.
- **Expected Output:** The system keeps functioning as normal without network; UI shows a clear error message; upon reconnection, the UI session restores automatically within 5s without reboot; no data loss or crash.
- **Test Case Derivation:** The system needs to be resilient against transient network failures in field conditions.
- **How Test Will Be Performed:** Manually disconnect and connect the system from the network; observe the UI for error messages.

4.1.2 Area of Testing: Recording

test-recording: Start and Stop Recording

- **Control:** Manual
- **Initial State:** System initialized; idle state; sufficient disk space.
- **Input:** Press "Start Recording", wait 10s, then press "Stop Recording".
- **Expected Output:** A 10 second 1080p60 video file is created and saved to the disk.
- **Test Case Derivation:** The system should be able to start and stop recording.
- **How Test Will Be Performed:** Press "Start Recording", wait 10s, then press "Stop Recording".

test-disk-full: Disk Full Behavior During Recording

- **Control:** Manual
- **Initial State:** System initialized; idle state; storage nearly full (simulate by filling disk leaving < 1min recording capacity).
- **Input:** Start recording and allow disk to fill.
- **Expected Output:** UI shows a clear "Storage Full" alert **within 2 seconds** of exhaustion; current recording is stopped and the file is saved to the disk; no crash.
- **Test Case Derivation:** The system should be able to handle storage exhaustion gracefully.
- **How Test Will Be Performed:** Fill the disk with data until it is nearly full; start recording; observe the UI for the "Storage Full" alert; check the disk for the saved file.

`test-manage-recordings`: List and Download Recordings

- **Control:** Manual
- **Initial State:** At least two prior recordings exist.
- **Input:** Open recordings list; download the latest file and an older file; delete a small test clip.
- **Expected Output:** List shows correct entries (name, timestamp, duration); downloads succeed; delete removes the selected item only.
- **Test Case Derivation:** The system should be able to list, delete, and download recordings.
- **How Test Will Be Performed:** Open the recordings list; download the latest file and an older file; delete a small test clip; check the list for the correct entries; check the disk for the saved files.

4.1.3 Area of Testing: Tracking

`test-manual-control`: Manual Gimbal Control in Idle

- **Control:** Manual
- **Initial State:** System initialized; idle state; preview and HDMI output active.
- **Input:** Issue manual pan and tilt commands via UI.
- **Expected Output:** The gimbal follows commands smoothly.
- **Test Case Derivation:** The operator should be able to manually control the gimbal in idle state.
- **How Test Will Be Performed:** Issue manual pan and tilt commands via UI; observe the gimbal movement.

`test-transition-to-tracking`: Transition to Tracking When Rocket Detected

- **Control:** Manual
- **Initial State:** System initialized; idle state; preview and HDMI output active.
- **Input:** Arm the system via UI, and waving a model rocket in front of the camera.
- **Expected Output:** The system transitions to tracking state as soon as the rocket is detected; the UI shows the system is in tracking state
- **Test Case Derivation:** The system should be able to transition to tracking state when a rocket is detected.
- **How Test Will Be Performed:** Arm the system via UI, and waving a model rocket in front of the camera; observe the UI for the system to transition to tracking state.

test-tracking: Keep Rocket in Frame While Tracking

- **Control:** Manual
- **Initial State:** System initialized; tracking state; preview and HDMI output active.
- **Input:** Wave a model rocket (approx. 30 cm length) at 1–3 m distance from the camera in an indoor lab environment with standard overhead lighting. Move the target at moderate speed (approx. 0.5–1 m/s lateral) across the camera’s field of view.
- **Expected Output:** Gimbal should continuously adjust its position to keep the rocket within the center 80% of the frame for the duration of the test (minimum 10s of sustained tracking).
- **Test Case Derivation:** The system should be able to keep the rocket in the frame while tracking. This test verifies FR-7.
- **How Test Will Be Performed:** In a controlled indoor environment, wave the model rocket at the specified distance and speed in front of the camera; observe the gimbal movement tracks the target; observe the preview in the UI to confirm the rocket stays in frame.

test-return-to-idle: Return to Idle When Rocket is Lost

- **Control:** Manual
- **Initial State:** System initialized; tracking state; preview and HDMI output active.
- **Input:** Occlude the model rocket.
- **Expected Output:** Within 2s of sustained loss, system transitions to idle state; ceases autonomous gimbal commands; UI indicates ”target lost”.
- **Test Case Derivation:** The system should be able to return to idle state when the rocket is lost.
- **How Test Will Be Performed:** Occlude the model rocket; observe the UI for the system to transition to idle state.

test-exit-gimbal-range: Rocket Exits Gimbal Range

- **Control:** Manual
- **Initial State:** System initialized; tracking state; preview and HDMI output active.
- **Input:** Move the model rocket outside of the gimbal’s range of motion.
- **Expected Output:** The gimbal moves until it reaches its mechanical limit, then stops moving further; no errors or warnings are presented to the user; system remains responsive.

- **Test Case Derivation:** The system must safely handle objects that leave the gimbal's range without faulting or reporting spurious errors.
- **How Test Will Be Performed:** Move the model rocket outside of the gimbal's range of motion; observe the gimbal reaches its mechanical end and stops; verify that no error messages appear in the UI and that all other system functions remain operational.

4.1.4 Field Testing (Out of Scope)

Field testing is **out of scope** for this project due to resource and contact limitations. The following is retained for reference only.

If field testing were to be conducted, it would be done by the McMaster Rocketry Team (client), who would be provided with the manual and would operate the system at a model rocket launch event. The development team would be present to assist. After the event, the client could fill out a survey (Appendix 6.2). Under the current plan, no field testing is performed; unit testing, system testing, and a planned stakeholder review with the rocketry team are conducted.

4.2 Tests for Nonfunctional Requirements

4.2.1 UI Walkthrough

The UI walkthrough will be conducted by the capstone team members themselves before the field test.

test-consistent-units: Consistent and Changeable Units

- **Type:** Manual
- **Initial State:** System initialized; idle state; preview and HDMI output active.
- **Input/Condition:** Go through the UI twice, once with metric units, once with imperial units.
- **Output/Result:** The units are consistent and changeable.
- **How Test Will Be Performed:** The capstone team members will go through the UI twice, once with metric units, once with imperial units; observe the units in the UI.

test-bilingual-ui: Bilingual UI

- **Type:** Manual
- **Initial State:** System initialized; language = English.
- **Input/Condition:** Switch UI language to French and back; navigate all UI sections, dialogs, and toasts.

- **Output/Result:** All visible strings/localized assets appear in the selected language; no truncation/overflow; no mixed-language strings; hotkeys remain functional; date/time/number formats localize correctly.
- **How Test Will Be Performed:** Perform a complete UI walkthrough in French; capture screenshots of each page/dialog; switch back to English and repeat spot checks.

test-immediate-ui-feedback: Immediate UI Feedback

- **Type:** Manual
- **Initial State:** System idle; UI ready.
- **Input/Condition:** Trigger representative actions: button press, toggle, menu selection, starting/stopping recording, arming/disarming, opening settings.
- **Output/Result:** A visible confirmation (pressed state, spinner, toast, label change) appears within 0.2s for each action.
- **How Test Will Be Performed:** Observe the UI while performing each action

test-visual-indicators: Rely on Visual Indicators

- **Type:** Manual
- **Initial State:** System initialized; speakers muted or disconnected.
- **Input/Condition:** Trigger statuses/alerts: armed, tracking, target lost, storage low/full, network disconnect, device error.
- **Output/Result:** Every status/alert is presented visually (icons, colors, banners, toasts) without relying on sound; no action-critical info is audio-only.
- **How Test Will Be Performed:** With audio disabled, induce each state/fault; verify a visible indicator appears and remains long enough to be noticed.

test-confirmation-prompts: Confirmation Prompts for Safety-Critical Actions

- **Type:** Manual
- **Initial State:** System idle; gimbal powered.
- **Input/Condition:** Attempt potentially hazardous actions: force home while tracking, hard stop, high-speed slew, firmware update during armed state, factory reset.
- **Output/Result:** A blocking confirmation dialog appears for each action; dialog text states the specific risk and outcome; default action is “Cancel”; action proceeds only after explicit confirmation.

- **How Test Will Be Performed:** Trigger each action; capture screenshots of the prompt; verify risk wording is specific (not generic); verify no motion/change occurs until “Confirm” is pressed.

`test-manual-idle-mode`: Manual Idle Mode / Override

- **Type:** Manual
- **Initial State:** System armed or tracking.
- **Input/Condition:** Press “Idle” (or equivalent) control while tracking.
- **Output/Result:** System transitions to idle within 1 s; autonomous commands cease; manual controls become available; status clearly shows “Idle.”
- **How Test Will Be Performed:** Enter tracking, then invoke manual idle; observe immediate cessation of gimbal motion; verify state banner change and manual jog controls responsiveness.

`test-no-collection-pii`: No Collection of PII

- **Type:** Manual
- **Initial State:** System initialized; default configuration.
- **Input/Condition:** Inspect all settings, logs, exported files, filenames/paths, and network-configurable fields.
- **Output/Result:** No fields request or store personal identifiers (names, emails, phone numbers, precise home addresses, faces with identity tags); logs contain only technical data; telemetry excludes PII.
- **How Test Will Be Performed:** Open each settings and log panel; download logs/recordings; inspect metadata (EXIF/JSON/CSV) for PII keys; verify any optional labels are device/session IDs, not personal data.

`test-color-vision-deficiency`: Color-Vision Deficiency Accessibility

- **Type:** Manual
- **Initial State:** System initialized; all status indicators visible.
- **Input/Condition:** Review all status/alert states (normal, armed, tracking, warning, error) and interactive controls (enabled/disabled) under simulated Protanopia/Deutanopia/Tritanopia or printed CVD reference swatches.
- **Output/Result:** Each state is distinguishable without relying on hue alone (uses shape, text labels, patterns, or contrast); contrast ratio $\geq 4.5:1$ for text/icons against background.

- **How Test Will Be Performed:** Cycle UI through all states; verify distinct icon shapes/labels; optionally view via a CVD simulator; record pass/fail with screenshots; confirm tooltips/textual labels exist for each color state.

4.2.2 Code and Documentation Walkthrough

`test-manual-arm-mode`: Manual Arm Mode Only

- **Type:** Static
- **Initial State:** N/A
- **Input/Condition:** Inspect all state transition code and configuration defaults.
- **Output/Result:** The system only enters armed mode when explicitly commanded by the user, never automatically.
- **How Test Will Be Performed:** Review code for all references to the armed state, verify guards require user input.

`test-gimbal-interface`: Gimbal Interface Documentation Review

- **Type:** Static
- **Initial State:** N/A
- **Input/Condition:** Review the interface specification with the client, including command set, telemetry, timing, and safety notes.
- **Output/Result:** The client confirms the interface documentation is complete, clear, and suitable for supporting multiple gimbal systems.
- **How Test Will Be Performed:** Conduct a walkthrough meeting with the client, check all required topics against a prepared checklist.

4.2.3 Error Handling and Logging

`test-report-errors`: Report All Errors to the User

- **Type:** Manual
- **Initial State:** System initialized and idle.
- **Input/Condition:** Manually trigger hardware, communication, and software faults.
- **Output/Result:** Each error generates a visible and descriptive message on the user interface **within 2 seconds** of fault occurrence.
- **How Test Will Be Performed:** Disconnect devices, kill processes, and simulate faults while observing the UI for clear error reporting. Time the interval between fault injection and the appearance of the error notification; verify it does not exceed 2 s.

test-stop-immediately: Stop Immediately on Unrecoverable Error

- **Type:** Manual
- **Initial State:** System operating in tracking mode.
- **Input/Condition:** Introduce a fatal condition such as gimbal communication loss or corrupted control process.
- **Output/Result:** The system stops all automated operations and transitions to a safe idle state **within 0.5 seconds** of the unrecoverable fault.
- **How Test Will Be Performed:** Disconnect the gimbal or crash the tracking process; time the interval until motion ceases and the system reaches idle state; verify that the interval does not exceed 0.5 s and that a clear unrecoverable error message is displayed.

test-validate-commands: Validate All Commands

- **Type:** Manual
- **Initial State:** System idle.
- **Input/Condition:** Enter invalid or out-of-range user commands through the UI or API.
- **Output/Result:** The system rejects invalid commands and displays a validation error without sending them to the gimbal.
- **How Test Will Be Performed:** Attempt to send commands beyond gimbal limits or in unsupported formats and confirm that they are blocked with clear feedback.

test-log-operations: Log All Operations

- **Type:** Manual
- **Initial State:** System initialized and user logged in.
- **Input/Condition:** Perform a series of user operations such as arming, tracking, and recording.
- **Output/Result:** Each action is logged with a timestamp and operation details in the system log.
- **How Test Will Be Performed:** After the field test, review the log file to confirm all actions and timestamps are recorded accurately.

4.2.4 Field Testing (Out of Scope)

Field testing and user surveys are out of scope; unit testing, system testing, and the stakeholder review are performed.

test-user-survey: User Survey (Out of Scope)

- **Type:** Static (out of scope)
- **Initial State:** N/A
- **Input/Condition:** N/A
- **Output/Result:** Completed user survey.
- **How Test Will Be Performed:** Not performed. If field testing were in scope, the client would fill out the survey after the field test. Under the current plan, unit testing, system testing, and stakeholder review are conducted.

4.3 Traceability Between Test Cases and Requirements

Test ID	Requirements
test-acquire-frame	FR-1, SLR-2
test-disconnect-camera	FR-1
test-hdmi-output	FR-8, FR-9, INT-1, SLR-3
test-disconnect-hdmi	FR-8
test-preview-real-time	FR-10
test-network-disconnect	FR-10
test-recording	FR-11
test-disk-full	FR-11
test-manage-recordings	FR-12
test-manual-control	FR-2, FR-6
test-transition-to-tracking	FR-3, FR-4
test-tracking	FR-2, FR-3, FR-7
test-return-to-idle	FR-5
test-exit-gimbal-range	FR-2, FR-7
test-consistent-units	EZ-1, PI-1
test-bilingual-ui	PI-2
test-immediate-ui-feedback	EZ-2
test-visual-indicators	EZ-3
test-confirmation-prompts	EZ-4, UPR-3
test-manual-idle-mode	SCR-1
test-no-collection-pii	LR-1
test-color-vision-deficiency	AR-1
test-manual-arm-mode	SCR-4
test-gimbal-interface	INT-2
test-report-errors	RFR-1
test-stop-immediately	RFR-2
test-validate-commands	IR-1
test-log-operations	AUR-1

5 Unit Test Description

5.1 Unit Test Summary

This subsection provides an overview of the unit testing approach, frameworks, module coverage, and expected coverage targets for the RoCam project.

Testing Approach

Unit testing follows a bottom-up strategy: each leaf module identified in the Module Guide ([MG Vision-Guided Tracker Team \(2025a\)](#)) is tested in isolation before integration. Tests are designed to verify functional correctness, boundary conditions, error handling, and key nonfunctional attributes (performance, robustness, thread safety). External dependencies (hardware, third-party SDKs) are replaced by mocks or stubs so that tests are deterministic and repeatable.

Frameworks and Tooling

- **Backend (Python) – pytest:** All backend modules running on the Jetson are tested with `pytest`. Fixtures provide reusable mocked dependencies (gimbal, database, IPC connections). Coverage is measured with `pytest-cov`, producing line, statement, and branch metrics.
- **Frontend (React/TypeScript) – Vitest:** All frontend UI modules are tested with `Vitest` (a Vite-native test runner compatible with the Jest API). Component tests use `@testing-library/react` for DOM assertions. Coverage is measured with Vitest’s built-in V8 provider, producing line, statement, branch, and function metrics.
- **CI Integration:** Both test suites run automatically on every pull request targeting `main` via GitHub Actions. All tests must pass before a pull request can be merged.

Modules Covered

- **Backend (18 modules):** State Management, API Gateway, Recording Database, Gimbal Abstraction, Tracking, CV Process Management, Live Video Process Management, Transcode API, Transcode Process, CV Process, Common IPC, Common IPC Buffer, Common Watchdog, System Status, Common Utils, Recording-Only State Management, Main Entry Point, and SSE.
- **Frontend (10 module groups):** Preview, Manual Control, Recording Management, Configuration, API Client, Rocam Provider, Utility Formatters, Internationalization, App Routing, and individual UI Components (Navbar, SystemStatusCard, ControlsCard).

Out-of-Scope Modules

The following modules are excluded from unit testing because they wrap third-party or hardware-specific libraries:

- Video Stream Abstraction (Nvidia Deepstream SDK)
- Serial Abstraction (`pyserial`)
- System Status hardware queries (`jetson-stats`)

Coverage Targets

The project targets a minimum of **80% line coverage** for both backend and frontend codebases. Achieved coverage at the time of the VnV Report is:

- Backend: 88% line coverage, 81.4% branch coverage (313 tests passed)
- Frontend: 85.57% line coverage, 70.35% branch coverage (168 tests passed)

Branch coverage is lower because some defensive paths (e.g., hardware error branches, rare race conditions) are difficult to trigger in a mocked environment. These paths are partially addressed by system tests and manual walkthroughs.

5.2 Unit Testing Scope

The RoCam system unit testing covers all leaf modules implemented by the project team. The following modules are within the scope of unit testing:

- **Backend (Jetson) Modules:**
 - `mState` (State Management Module)
 - `mAPI` (API Gateway Module)
 - `mRecord` (Recording Database Module)
 - `mGimbal` (Gimbal Abstraction Module)
 - `mTrack` (Tracking Module)
 - `mCVManagement` (CV Process Management Module)
 - `mVideoManagement` (Live Video Process Management Module)
 - `mTranscodeManagement` (Transcode Process Management Module)
 - `mCV` (CV Process Module)
 - `mVideo` (Live Video Process Module)
 - `mTranscode` (Transcode Process Module)
 - Common utilities (IPC, IPC Buffer, Watchdog, System Status, Utils)
- **Frontend (UI) Modules:**
 - `mPreview` (Preview Module)
 - `mManual` (Manual Control Module)
 - `mRecordMng` (Recording Management Module)
 - `mConfig` (Configuration Module)
 - API client and network layer
 - Utility formatters and internationalization

Out of Scope:

- **mStream** (Video Stream Abstraction Module) — Implemented by Nvidia Deepstream SDK (third-party)
- **mSerial** (Serial Abstraction Module) — Implemented by pyserial library (third-party)
- **mStatus** (System Status Module) — Hardware-dependent library (jetson-stats)
- Hardware-specific system tests (require actual Jetson hardware)

The unit testing strategy employs pytest for Python backend modules and Vitest for TypeScript frontend modules. Tests are designed to verify functional correctness, edge case handling, and error conditions for each module in isolation, with external dependencies mocked appropriately.

5.3 Tests for Functional Requirements

Unit tests for functional requirements verify that each module correctly implements its specified behavior. Tests are organized by module, with references to the MIS and MG documents where applicable. All tests are automated and implemented using pytest (Python backend) or Vitest (TypeScript frontend).

5.3.1 Module: State Management (mState)

The State Management module handles system state transitions, manual gimbal control, recording operations, and status aggregation. Tests verify state machine behavior, command validation, and data management.

1. `test-state-management-arm-disarm`

Type: Functional, Dynamic, Automatic

Initial State: StateManagement instance with mocked dependencies

Input: Call `arm()` and `disarm()` methods

Output: Internal armed flag set appropriately; gimbal LED commands issued

Test Case Derivation: Verifies FR-4 (arming/disarming functionality) and that state transitions trigger correct hardware responses

How test will be performed: Automated via `test_state_management_class.py::TestArmDisarm`

2. `test-state-management-manual-move`

Type: Functional, Dynamic, Automatic

Initial State: Disarmed system with gimbal at known position

Input: `manual_move()` with directions up/down/left/right

Output: Gimbal `set_deg()` called with correctly adjusted angles

Test Case Derivation: Verifies FR-2 (manual control) and FR-6 (manual control only when disarmed)

How test will be performed: Automated via `test_state_management_class.py::TestManualMove`

3. `test-state-management-manual-move-clamped`

Type: Functional, Dynamic, Automatic

Initial State: Disarmed system with gimbal near limits

Input: `manual_move()` commands that would exceed gimbal limits

Output: Angles clamped to valid ranges (tilt 0-90°, pan -45° to 45°)

Test Case Derivation: Verifies IR-1 (command validation and clamping)

How test will be performed: Automated via `test_state_management_class.py::TestManualMove`

4. `test-state-management-recording`

Type: Functional, Dynamic, Automatic

Initial State: System with mocked database and CV process

Input: `start_recording()` and `stop_recording()` calls

Output: Recording allocated in database; CV process notified; recording ID tracked

Test Case Derivation: Verifies FR-11 (recording start/stop functionality)

How test will be performed: Automated via `test_state_management_class.py::TestRecording`

5. `test-state-management-download-pause`

Type: Functional, Dynamic, Automatic

Initial State: Active recording session

Input: `on_download_start()` and `on_download_end()` calls during recording

Output: CV pipeline paused on first download, resumed after last download ends

Test Case Derivation: Verifies correct pipeline management during recording downloads

How test will be performed: Automated via `test_state_management_class.py::TestDownloadHandlers`

6. `test-bounding-box-collection`

Type: Functional, Dynamic, Automatic

Initial State: Empty `BoundingBoxCollection`

Input: Sequential `CVData` with bounding boxes and timestamps

Output: Correct bbox retrieval within 40ms window; latest valid bbox returned; max 10 entries enforced

Test Case Derivation: Verifies data structure behavior for tracking data management
How test will be performed: Automated via test_state_management.py

5.3.2 Module: API Gateway (mAPI)

The API Gateway module provides REST endpoints for UI communication. Tests verify endpoint behavior, request validation, and proper delegation to StateManagement.

1. [test-api-endpoints-exist](#)

Type: Functional, Dynamic, Automatic

Initial State: Flask test client with mocked StateManagement

Input: HTTP requests to /api/arm, /api/disarm, /api/manual_move, /api/manual_move_to, /api/recordings/start, /api/recordings/stop

Output: HTTP 200 responses; correct methods called on StateManagement

Test Case Derivation: Verifies FR-6, FR-10, FR-11 (API endpoints for control and recording)

How test will be performed: Automated via test_api.py and test_api_gateway.py

2. [test-api-recordings-crud](#)

Type: Functional, Dynamic, Automatic

Initial State: Flask test client with mocked database

Input: GET /api/recordings, PATCH /api/recordings/{id}, DELETE /api/recordings/{id}

Output: Recording list returned; rename and delete operations delegated to database

Test Case Derivation: Verifies FR-12 (recording management)

How test will be performed: Automated via test_api.py::TestRecordingsList, TestRecordingsRename, TestRecordingsDelete

3. [test-api-validation](#)

Type: Functional, Dynamic, Automatic

Initial State: Flask test client

Input: PATCH /api/recordings/{id} with missing or invalid new_name

Output: HTTP 400 Bad Request with appropriate error message

Test Case Derivation: Verifies IR-1 (input validation)

How test will be performed: Automated via test_api.py::TestRecordingsRename

5.3.3 Module: Recording Database (mRecord)

The Recording Database module manages recording metadata, file storage, and retrieval operations.

1. `test-database-allocate`

Type: Functional, Dynamic, Automatic

Initial State: Empty temporary directory

Input: `allocate_recording()` call

Output: Recording directory created with `meta.json`; `RecordingInfo` returned with valid paths

Test Case Derivation: Verifies FR-11 (recording allocation)

How test will be performed: Automated via `test_database.py::TestAllocateRecording`

2. `test-database-list-recordings`

Type: Functional, Dynamic, Automatic

Initial State: Database with multiple recordings

Input: `list_all_recordings()` call

Output: Sorted list of `RecordingInfo` objects (newest first)

Test Case Derivation: Verifies FR-12 (recording listing)

How test will be performed: Automated via `test_database.py::TestListAllRecordings`

3. `test-database-rename-delete`

Type: Functional, Dynamic, Automatic

Initial State: Database with existing recording

Input: `rename_recording()` and `delete_recording()` calls

Output: `meta.json` updated with new name; directory removed on delete

Test Case Derivation: Verifies FR-12 (recording renaming and deletion)

How test will be performed: Automated via `test_database.py::TestRenameRecording`, `TestDeleteRecording`

4. `test-database-path-traversal-protection`

Type: Functional, Dynamic, Automatic

Initial State: Database with validation enabled

Input: Recording IDs containing path traversal patterns (`../etc/passwd`)

Output: ValueError raised; no filesystem access outside base path

Test Case Derivation: Verifies security requirement for path validation

How test will be performed: Automated via test_database.py::TestValidateId

5. [test-database-space-usage](#)

Type: Functional, Dynamic, Automatic

Initial State: Mocked disk usage

Input: space_usage_bytes() and recording_duration_left_s() calls

Output: Correct used/total bytes; estimated recording duration based on free space

Test Case Derivation: Verifies FR-10 (storage status reporting)

How test will be performed: Automated via test_database.py::TestSpaceUsage

5.3.4 Module: Gimbal Abstraction (mGimbal)

The Gimbal Abstraction module handles serial communication with the gimbal hardware.

1. [test-gimbal-crc8](#)

Type: Functional, Dynamic, Automatic

Initial State: GimbalSerial instance

Input: Various byte sequences for CRC calculation

Output: Correct CRC-8 values; consistent results; valid byte range (0-255)

Test Case Derivation: Verifies communication protocol integrity

How test will be performed: Automated via test_gimbal.py::TestCrc8Smbus

2. [test-gimbal-packet-construction](#)

Type: Functional, Dynamic, Automatic

Initial State: GimbalSerial with mocked serial port

Input: create_request_data() with various request IDs and payloads

Output: Properly formatted packets with CRC at byte 0, request ID at byte 1

Test Case Derivation: Verifies INT-2 (gimbal protocol implementation)

How test will be performed: Automated via test_gimbal.py::TestCreateRequestData

3. [test-gimbal-angle-commands](#)

Type: Functional, Dynamic, Automatic

Initial State: GimbalSerial with mocked serial port returning ACK

Input: `set_deg(tilt, pan)` and `get_deg()` calls

Output: True on success; correct angle values parsed from response

Test Case Derivation: Verifies FR-2, FR-6, FR-7 (gimbal angle control)

How test will be performed: Automated via `test_gimbal.py::TestSetDeg`, `TestGetDeg`

4. `test-gimbal-led-control`

Type: Functional, Dynamic, Automatic

Initial State: GimbalSerial with mocked serial port

Input: `set_arm_led(True/False)` and `set_status_led(True/False)`

Output: True on success; serial write called with correct packets

Test Case Derivation: Verifies visual feedback control for armed status

How test will be performed: Automated via `test_gimbal.py::TestLedCommands`

5. `test-gimbal-info-query`

Type: Functional, Dynamic, Automatic

Initial State: GimbalSerial with mocked response

Input: `gimbal_info()` call

Output: Tilt range, pan range, and focal length range parsed correctly

Test Case Derivation: Verifies gimbal capability detection

How test will be performed: Automated via `test_gimbal.py::TestGimbalInfo`

5.3.5 Module: Tracking (`mTrack`)

The Tracking module implements the control law for automatic rocket tracking.

1. `test-tracking-queue-behavior`

Type: Functional, Dynamic, Automatic

Initial State: Tracking instance with mocked gimbal

Input: Sequential `on_detection()` calls with bounding box coordinates

Output: Detections queued; oldest dropped when queue full; None accepted

Test Case Derivation: Verifies FR-3, FR-7 (tracking queue management)

How test will be performed: Automated via `test_tracking.py::TestOnDetection`

2. [test-tracking-worker-control-law](#)

Type: Functional, Dynamic, Automatic

Initial State: Tracking instance with mocked gimbal at known position

Input: Detection coordinates off-center from frame

Output: `gimbal.set_deg()` called with corrected angles based on proportional control

Test Case Derivation: Verifies FR-7 (tracking control law)

How test will be performed: Automated via `test_tracking.py::TestWorkerControlLaw`

3. [test-tracking-angle-clamping](#)

Type: Functional, Dynamic, Automatic

Initial State: Tracking instance with mocked gimbal near angle limits

Input: Detection that would push angles beyond valid range

Output: New angles clamped to valid tilt/pan ranges

Test Case Derivation: Verifies IR-1 (tracking command validation)

How test will be performed: Automated via `test_tracking.py::TestWorkerControlLaw`

4. [test-tracking-stop](#)

Type: Functional, Dynamic, Automatic

Initial State: Running Tracking instance

Input: `stop()` call

Output: Stop event set; worker thread joined successfully

Test Case Derivation: Verifies clean shutdown of tracking thread

How test will be performed: Automated via `test_tracking.py::TestStop`

5.3.6 Module: CV Process Management (`mCVManagement`)

The CV Process Management module handles the lifecycle and IPC with the CV worker process.

1. [test-cv-management-osd-send](#)

Type: Functional, Dynamic, Automatic

Initial State: `CVProcessManagement` with open IPC connection

Input: `send_osd_data()` with `OSDData`

Output: Data sent over IPC; exceptions swallowed safely

Test Case Derivation: Verifies FR-10 (OSD data transmission to CV process)

How test will be performed: Automated via `test_cv_process_mgmt.py::TestSendOsdData`

2. `test-cv-management-recording-commands`

Type: Functional, Dynamic, Automatic

Initial State: CVProcessManagement with open IPC connection

Input: `start_recording()` with RecordingInfo; `stop_recording()`

Output: Recording info sent; StopRecording sentinel sent

Test Case Derivation: Verifies FR-11 (recording command relay to CV process)

How test will be performed: Automated via `test_cv_process_mgmt.py::TestRecordingCommands`

3. `test-cv-management-pause-resume`

Type: Functional, Dynamic, Automatic

Initial State: CVProcessManagement with active process

Input: `pause_pipeline()` and `resume_pipeline()` calls

Output: Process terminated on pause; resume event set on resume

Test Case Derivation: Verifies pipeline control for download operations

How test will be performed: Automated via `test_cv_process_mgmt.py::TestPauseResume`

4. `test-cv-management-recv-loop`

Type: Functional, Dynamic, Automatic

Initial State: CVProcessManagement with mocked connection

Input: Simulated CVData and PreviewData via recv loop

Output: Callbacks dispatched correctly; connection closed on EOF

Test Case Derivation: Verifies data flow from CV process to control process

How test will be performed: Automated via `test_cv_process_mgmt.py::TestRecvLoop`

5.3.7 Module: Live Video Process Management (mVideoManagement)

The Live Video Process Management module supervises the live video output process.

1. `test-livestream-construction`

Type: Functional, Dynamic, Automatic

Initial State: System ready for process management

Input: LivestreamProcessManagement instantiation

Output: Daemon thread started for process supervision

Test Case Derivation: Verifies FR-8, FR-9 (live video process lifecycle)

How test will be performed: Automated via test_livestream_mgmt.py

2. [test-livestream-process-loop](#)

Type: Functional, Dynamic, Automatic

Initial State: LivestreamProcessManagement instance

Input: Simulated process loop iteration

Output: subprocess.Popen called with livestream command; process monitored

Test Case Derivation: Verifies live video process supervision

How test will be performed: Automated via test_livestream_mgmt.py

5.3.8 Module: Transcode API (mAPI)

The Transcode API provides endpoints for stabilized video preview and download.

1. [test-transcode-routes-404](#)

Type: Functional, Dynamic, Automatic

Initial State: Flask app with transcode routes registered; recording not found

Input: GET /api/recordings/{id}/preview-stabilized and /download-stabilized

Output: HTTP 404 when recording not found

Test Case Derivation: Verifies FR-12 (proper error handling for missing recordings)

How test will be performed: Automated via test_transcode_api.py::TestTranscodeRoutes

2. [test-transcode-streaming](#)

Type: Functional, Dynamic, Automatic

Initial State: Flask app with valid recording

Input: GET preview-stabilized or download-stabilized with valid recording ID

Output: HTTP 200 with video/webm content type; on_download_start/end called

Test Case Derivation: Verifies FR-12 (stabilized video streaming)

How test will be performed: Automated via test_transcode_api.py::TestTranscodeRoutes

3. [test-transcode-pipe-cleanup](#)

Type: Functional, Dynamic, Automatic

Initial State: Named pipe exists on filesystem

Input: `_cleanup_pipe()` call

Output: Pipe file removed; no error if pipe missing; `OSError` swallowed

Test Case Derivation: Verifies resource cleanup for transcode operations

How test will be performed: Automated via `test_transcode_api.py::TestCleanupPipe`

5.3.9 Module: Transcode Process (`mTranscode`)

The Transcode Process module handles offline video transcoding with stabilization.

1. `test-transcode-read-log`

Type: Functional, Dynamic, Automatic

Initial State: `TranscodeProcess` instance with mocked `GStreamer`

Input: JSONL log file with OSD entries

Output: List of `OSDData` objects parsed correctly; invalid lines skipped

Test Case Derivation: Verifies FR-12 (log parsing for overlay generation)

How test will be performed: Automated via `test_transcode_main.py::TestTranscodeProcessReadLog`

2. `test-transcode-shader-probe`

Type: Functional, Dynamic, Automatic

Initial State: `TranscodeProcess` with OSD data list

Input: Shader probe calls with various PTS values

Output: Correct OSD data selected; pointer advanced appropriately for preview vs download modes

Test Case Derivation: Verifies overlay synchronization with video frames

How test will be performed: Automated via `test_transcode_main.py::TestTranscodeProcessShaderProbe`

3. `test-transcode-bus-call`

Type: Functional, Dynamic, Automatic

Initial State: `TranscodeProcess` with mocked `GStreamer` bus

Input: EOS, WARNING, and ERROR messages

Output: Loop quit on EOS and ERROR; continued on WARNING

Test Case Derivation: Verifies proper `GStreamer` pipeline event handling

How test will be performed: Automated via `test_transcode_main.py::TestTranscodeProcessBusCall`

5.3.10 Module: CV Process (mCV)

The CV Process module handles video acquisition, object detection, and recording.

1. `test-cv-format-time`

Type: Functional, Dynamic, Automatic

Initial State: CV process utilities loaded

Input: Millisecond timestamps

Output: Human-readable formatted time strings with milliseconds

Test Case Derivation: Verifies utility function for timestamp formatting in overlays

How test will be performed: Automated via `test_cv_main.py::TestFormatTime`

2. `test-cv-update-osd`

Type: Functional, Dynamic, Automatic

Initial State: Mocked GStreamer osd and shader elements

Input: OSDData with gimbal angles, GPS coordinates, IP addresses

Output: Text property set with formatted OSD; shader uniforms updated

Test Case Derivation: Verifies FR-8, FR-9, FR-10 (OSD overlay generation)

How test will be performed: Automated via `test_cv_main.py::TestUpdateOsd`

5.3.11 Module: Common IPC (Shared Modules)

The Common IPC module provides data structures and communication utilities.

1. `test-bounding-box-center`

Type: Functional, Dynamic, Automatic

Initial State: BoundingBox instance

Input: Various bounding box coordinates

Output: Correct center point (cx, cy) calculated

Test Case Derivation: Verifies geometry calculations for tracking

How test will be performed: Automated via `test_ipc.py::TestBoundingBoxCenter`

2. `test-bounding-box-rotate-90`

Type: Functional, Dynamic, Automatic

Initial State: BoundingBox instance

Input: Bounding box for 90-degree rotated frame

Output: Correctly transformed bounding box

Test Case Derivation: Verifies coordinate transformation for rotated camera

How test will be performed: Automated via `test_ipc.py::TestBoundingBoxRotate90`

3. `test-dataclass-construction`

Type: Functional, Dynamic, Automatic

Initial State: IPC module loaded

Input: Construction of `CVData`, `OSDDData`, `PreviewData`, `RecordingInfo`, `StopRecording`

Output: Objects created with correct field values

Test Case Derivation: Verifies data structure integrity

How test will be performed: Automated via `test_ipc.py::TestDataclasses`

5.3.12 Module: Common IPC Buffer

The IPC Buffer module provides shared memory circular buffer for high-throughput video data.

1. `test-ipc-buffer-sender`

Type: Functional, Dynamic, Automatic

Initial State: `IPCBufferSender` with mocked shared memory

Input: `send()` calls with fixed-size payloads

Output: Head advanced; data written at correct offset; returns `False` when full

Test Case Derivation: Verifies efficient video frame buffering

How test will be performed: Automated via `test_ipc_buffer.py::TestIPCBufferSender`

2. `test-ipc-buffer-receiver`

Type: Functional, Dynamic, Automatic

Initial State: `IPCBufferReceiver` with mocked shared memory containing data

Input: `receive()` calls with various head/tail positions

Output: Data retrieved correctly; tail advanced; overrun handled gracefully

Test Case Derivation: Verifies reliable video frame retrieval

How test will be performed: Automated via `test_ipc_buffer.py::TestIPCBufferReceiver`

5.3.13 Module: Common Watchdog

The Watchdog module provides timeout-based process monitoring.

1. [test-watchdog-refresh](#)

Type: Functional, Dynamic, Automatic

Initial State: Watchdog instance with timeout and callback

Input: refresh() calls

Output: Timer created and started; previous timer cancelled

Test Case Derivation: Verifies RFR-2 (watchdog functionality for process monitoring)

How test will be performed: Automated via test_watchdog.py::TestWatchdogRefresh

2. [test-watchdog-clear](#)

Type: Functional, Dynamic, Automatic

Initial State: Watchdog with active timer

Input: clear() call

Output: Timer cancelled; reference cleared; idempotent when no timer

Test Case Derivation: Verifies safe watchdog shutdown

How test will be performed: Automated via test_watchdog.py::TestWatchdogClear

5.3.14 Module: Preview (mPreview)

The Preview module displays live video feed in the UI.

1. [test-control-page-render](#)

Type: Functional, Dynamic, Automatic

Initial State: React component with mocked dependencies

Input: Various status states (null, with/without preview, armed/disarmed, recording)

Output: Preview image rendered when available; spinner shown when loading; REC/ARMED indicators displayed correctly

Test Case Derivation: Verifies FR-10 (real-time preview display)

How test will be performed: Automated via test_pages/control.test.tsx

2. [test-control-page-bbox-overlay](#)

Type: Functional, Dynamic, Automatic

Initial State: Control page with status containing bbox

Input: Status with bounding box coordinates and confidence
Output: Bounding box overlay rendered with confidence value
Test Case Derivation: Verifies FR-3 (detection visualization)
How test will be performed: Automated via test_pages/control.test.tsx

5.3.15 Module: Manual Control (mManual)

The Manual Control module provides UI for gimbal control.

1. [test-controls-card-render](#)

Type: Functional, Dynamic, Automatic
Initial State: ControlsCard component with mocked API
Input: Various system states (armed/disarmed)
Output: Directional controls rendered; manual move API called on interaction
Test Case Derivation: Verifies FR-2, FR-6 (manual gimbal control UI)
How test will be performed: Automated via test_components/ControlsCard.test.tsx

2. [test-control-page-drag](#)

Type: Functional, Dynamic, Automatic
Initial State: Control page in disarmed mode
Input: Pointer drag gestures on preview area
Output: manualMoveTo API called with calculated tilt/pan values
Test Case Derivation: Verifies FR-2 (intuitive manual control)
How test will be performed: Automated via test_pages/control.test.tsx

5.3.16 Module: Recording Management (mRecordMng)

The Recording Management module provides UI for listing, renaming, deleting, and previewing recordings.

1. [test-recordings-page-loading](#)

Type: Functional, Dynamic, Automatic
Initial State: Recordings page mounted
Input: API loading state
Output: Loading spinner displayed
Test Case Derivation: Verifies UI feedback during data fetch
How test will be performed: Automated via test_pages/recordings.test.tsx

2. `test-recordings-page-empty`

Type: Functional, Dynamic, Automatic

Initial State: Recordings page with empty list

Input: API returns empty recordings array

Output: “No recordings” message displayed

Test Case Derivation: Verifies FR-12 (empty state handling)

How test will be performed: Automated via `test_pages/recordings.test.tsx`

3. `test-recordings-page-list`

Type: Functional, Dynamic, Automatic

Initial State: Recordings page with sample data

Input: API returns list of recordings

Output: Recording names rendered; dates and durations formatted

Test Case Derivation: Verifies FR-12 (recording listing)

How test will be performed: Automated via `test_pages/recordings.test.tsx`

4. `test-recordings-delete`

Type: Functional, Dynamic, Automatic

Initial State: Recordings page with sample recording

Input: Delete button clicked with confirmation

Output: `deleteRecording` API called with correct ID

Test Case Derivation: Verifies FR-12 (recording deletion with confirmation)

How test will be performed: Automated via `test_pages/recordings.test.tsx`

5. `test-recordings-rename`

Type: Functional, Dynamic, Automatic

Initial State: Recordings page with editable name

Input: Name changed and blurred (or Escape pressed)

Output: `renameRecording` API called with new name; cancelled on Escape

Test Case Derivation: Verifies FR-12 (recording renaming)

How test will be performed: Automated via `test_pages/recordings.test.tsx`

5.3.17 Module: Configuration (mConfig)

The Configuration module provides UI for system settings.

1. [test-language-selector](#)

Type: Functional, Dynamic, Automatic

Initial State: LanguageSelector component

Input: Language selection change

Output: Language atom updated; i18n activated

Test Case Derivation: Verifies PI-2, EZ-4 (language configuration)

How test will be performed: Automated via test_components/LanguageSelector.test.tsx

2. [test-configuration-menu](#)

Type: Functional, Dynamic, Automatic

Initial State: ConfigurationMenu component

Input: Settings changes (temperature unit, drag sensitivity, invert drag)

Output: Setting atoms updated with new values

Test Case Derivation: Verifies UPR-1, UPR-3 (user preference configuration)

How test will be performed: Automated via test_components/ConfigurationMenu.test.tsx

5.3.18 Module: API Client (Network Layer)

The API Client module provides HTTP communication with the backend.

1. [test-api-client-urls](#)

Type: Functional, Dynamic, Automatic

Initial State: ApiClient instance

Input: Base URL configuration

Output: Correct endpoint URLs generated for status stream, recordings, previews

Test Case Derivation: Verifies FR-10, FR-12 (API endpoint construction)

How test will be performed: Automated via test_network/api.test.ts

2. [test-api-client-automatic-discovery](#)

Type: Functional, Dynamic, Automatic

Initial State: Network with multiple potential server URLs

Input: createAutomatic() with probe URLs

Output: Client created with first responding URL; throws if all fail

Test Case Derivation: Verifies SCR-3 (automatic server discovery)

How test will be performed: Automated via test_network/api.test.ts

3. test-api-client-methods

Type: Functional, Dynamic, Automatic

Initial State: ApiClient with mocked fetch

Input: manualMove(), arm(), disarm(), startRecording(), stopRecording(), listRecordings(), renameRecording(), deleteRecording()

Output: Correct HTTP methods and URLs; proper request bodies; ApiError thrown on failure

Test Case Derivation: Verifies FR-2, FR-6, FR-10, FR-11, FR-12 (API operations)

How test will be performed: Automated via test_network/api.test.ts

5.3.19 Module: Rocam Provider (React Context)

The Rocam Provider module manages API client instance and global state for React components.

1. test-rocam-provider-initialization

Type: Functional, Dynamic, Automatic

Initial State: RocamProvider component with mocked createAutomatic

Input: Provider mounted with children

Output: API client created; status polling started; loading state managed

Test Case Derivation: Verifies FR-10 (provider initializes API connection on mount)

How test will be performed: Automated via test_network/rocamProvider.test.tsx

2. test-rocam-provider-error-handling

Type: Nonfunctional, Robustness, Automatic

Initial State: RocamProvider with mocked API that fails to connect

Input: API initialization failure

Output: Error state set; error message displayed; component doesn't crash

Test Case Derivation: Verifies RFR-1 (graceful handling of connection failures)

How test will be performed: Automated via test_network/rocamProvider.test.tsx

3. [test-rocam-provider-polling](#)

Type: Functional, Dynamic, Automatic

Initial State: RocamProvider with mocked API client

Input: Status stream events and polling intervals

Output: Status state updated; polling continues with proper cleanup on unmount

Test Case Derivation: Verifies FR-10 (real-time status updates via SSE)

How test will be performed: Automated via `test_network/rocamProvider.test.tsx`

4. [test-use-rocam-hook](#)

Type: Functional, Dynamic, Automatic

Initial State: Component wrapped in RocamProvider

Input: `useRocam()` hook called

Output: API client and status accessible to consuming components

Test Case Derivation: Verifies React context API exposes required values

How test will be performed: Automated via `test_network/rocamProvider.test.tsx`

5.3.20 Module: Utility Formatters

The Utility Formatters module provides data formatting functions.

1. [test-formatters-degrees](#)

Type: Functional, Dynamic, Automatic

Initial State: Formatter functions loaded

Input: Various numeric values for degrees, FPS, percentages

Output: Correctly formatted strings with appropriate precision and units

Test Case Derivation: Verifies PI-1 (intuitive value display)

How test will be performed: Automated via `test_utils/formatters.test.ts`

2. [test-formatters-temperature](#)

Type: Functional, Dynamic, Automatic

Initial State: Formatter functions loaded

Input: Celsius temperatures; Fahrenheit unit preference

Output: Correct conversion and formatting with degree symbol

Test Case Derivation: Verifies temperature display in both units

How test will be performed: Automated via `test_utils/formatters.test.ts`

3. [test-formatters-bytes](#)

Type: Functional, Dynamic, Automatic

Initial State: Formatter functions loaded

Input: Byte counts of various magnitudes

Output: Human-readable sizes (B, KB, MB, GB)

Test Case Derivation: Verifies FR-10 (storage display)

How test will be performed: Automated via test_utils/formatters.test.ts

4. [test-formatters-duration](#)

Type: Functional, Dynamic, Automatic

Initial State: Formatter functions loaded

Input: Millisecond durations

Output: Formatted HH:MM:SS or relative time strings

Test Case Derivation: Verifies FR-12 (recording duration display)

How test will be performed: Automated via test_utils/formatters.test.ts

5.3.21 Module: Internationalization (i18n)

The Internationalization module provides multi-language support.

1. [test-i18n-activation](#)

Type: Functional, Dynamic, Automatic

Initial State: i18n module with mocked linguist

Input: dynamicActivate() with locale string

Output: Messages loaded; i18n activated with correct locale

Test Case Derivation: Verifies PI-2 (language switching)

How test will be performed: Automated via test_i18n.test.ts

5.3.22 Module: Application Routing (App)

The App module handles page routing and navigation.

1. [test-app-routing](#)

Type: Functional, Dynamic, Automatic

Initial State: App component with MemoryRouter

Input: Navigation to / and /recordings routes

Output: Correct page components rendered; unknown paths redirect to /

Test Case Derivation: Verifies EZ-1 (navigation between pages)

How test will be performed: Automated via test_App.test.tsx

5.4 Tests for Nonfunctional Requirements

Unit tests for nonfunctional requirements verify performance characteristics, reliability, and quality attributes of individual modules. These tests focus on measurable behaviors such as timing, resource usage, error handling, and robustness.

5.4.1 Module: State Management (mState)

1. [test-state-status-performance](#)

Type: Nonfunctional, Performance, Automatic

Initial State: StateManagement with mocked dependencies and cached metrics

Input: status() called repeatedly

Output: Status returned within milliseconds; cached values returned without recalculation

Test Case Derivation: Verifies SLR-2, SLR-3 (status query performance for real-time monitoring)

How test will be performed: Automated via test_state_management_class.py::TestStatus

2. [test-state-error-handling](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: StateManagement with mocked components that may raise exceptions

Input: Various operations with components configured to raise exceptions

Output: Operations fail gracefully; no unhandled exceptions propagate

Test Case Derivation: Verifies RFR-1 (error handling for robustness)

How test will be performed: Automated via test_state_management_class.py

5.4.2 Module: API Gateway (mAPI)

1. [test-api-error-responses](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: Flask test client

Input: Invalid JSON, missing required fields, malformed requests

Output: HTTP 400 with descriptive error messages; no server crashes
Test Case Derivation: Verifies RFR-1 (API error handling and feedback)
How test will be performed: Automated via `test_api.py::TestRecordingsRename`

5.4.3 Module: SSE (Server-Sent Events)

1. `test-sse-broadcast-performance`

Type: Nonfunctional, Performance, Automatic
Initial State: MessageAnnouncer with multiple listeners registered
Input: Rapid announce() calls with status updates
Output: All listeners receive messages; full queues drop messages silently (no blocking)
Test Case Derivation: Verifies SLR-3, RFR-4 (real-time status streaming without back-pressure)
How test will be performed: Automated via `test_sse.py::TestMessageAnnouncer`

2. `test-sse-thread-safety`

Type: Nonfunctional, Robustness, Automatic
Initial State: MessageAnnouncer with concurrent operations
Input: Simultaneous listen(), remove(), and announce() from multiple threads
Output: No race conditions; all operations complete safely
Test Case Derivation: Verifies thread safety for concurrent UI connections
How test will be performed: Automated via `test_sse.py::TestMessageAnnouncer`

5.4.4 Module: IPC Buffer

1. `test-ipc-buffer-overflow-handling`

Type: Nonfunctional, Robustness, Automatic
Initial State: IPCBufferReceiver with head significantly ahead of tail (overflow condition)
Input: receive() call during overflow
Output: Tail advanced to catch up; data retrieved without corruption
Test Case Derivation: Verifies RFR-4 (graceful handling of producer/consumer rate mismatch)
How test will be performed: Automated via `test_ipc_buffer.py::TestIPCBufferReceiver`

2. [test-ipc-buffer-memory-safety](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: IPCBuffer with various head/tail positions including edge cases

Input: Operations at buffer boundaries

Output: No out-of-bounds access; proper ring buffer wrapping

Test Case Derivation: Verifies memory safety for shared video data

How test will be performed: Automated via test_ipc_buffer.py

5.4.5 Module: CV Process Management (mCVManagement)

1. [test-cv-management-exception-safety](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: CVProcessManagement with connection in various states

Input: Operations during broken pipe, EOF, and other error conditions

Output: Exceptions caught and swallowed; component continues operating

Test Case Derivation: Verifies RFR-2 (fault tolerance for process communication)

How test will be performed: Automated via test_cv_process_mgmt.py::TestExceptionHandling

5.4.6 Module: Recording Database (mRecord)

1. [test-database-error-handling](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: Database with simulated filesystem errors

Input: Operations with mocked os/path functions raising OSError

Output: Graceful degradation; sensible defaults returned; exceptions handled

Test Case Derivation: Verifies RFR-1, CR-1 (error handling and data integrity)

How test will be performed: Automated via test_database.py::TestGetSizeBytes

5.4.7 Module: Watchdog

1. [test-watchdog-timeout-accuracy](#)

Type: Nonfunctional, Performance, Automatic

Initial State: Watchdog with specific timeout value

Input: refresh() calls at various intervals

Output: Timer created with correct timeout; callback triggered after timeout
Test Case Derivation: Verifies PAR-1 (timing accuracy for process monitoring)
How test will be performed: Automated via test_watchdog.py

5.4.8 Module: System Status (mStatus)

1. [test-system-status-caching](#)

Type: Nonfunctional, Performance, Automatic
Initial State: SystemStatusMonitor with mocked jtop
Input: Multiple getter calls between updates
Output: Cached values returned immediately; no redundant hardware queries
Test Case Derivation: Verifies SLR-2, SLR-3 (efficient status monitoring)
How test will be performed: Automated via test_system_status.py

2. [test-system-status-callback-updates](#)

Type: Nonfunctional, Correctness, Automatic
Initial State: SystemStatusMonitor with initial readings
Input: jtop callback with updated sensor values
Output: All cached metrics updated to new values
Test Case Derivation: Verifies EZ-3 (accurate system telemetry)
How test will be performed: Automated via test_system_status.py::TestSystemStatusMonitor

5.4.9 Module: Common Utils

The Utils module provides network and scheduling utilities.

1. [test-ip4-addresses](#)

Type: Functional, Dynamic, Automatic
Initial State: Utils module with mocked netifaces
Input: Network interface configurations with various IPv4 addresses
Output: List of IP addresses extracted correctly; empty list when no interfaces
Test Case Derivation: Verifies FR-10 (device IP address reporting for UI)
How test will be performed: Automated via test_utils.py::TestIp4Addresses

2. [test-scheduler-validation](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: Scheduler functions with mocked OS calls

Input: Various priority values (valid and invalid) for FIFO, OTHER, and BATCH schedulers

Output: ValueError raised for out-of-range priorities; successful calls for valid values

Test Case Derivation: Verifies PAR-1 (process scheduling priority validation)

How test will be performed: Automated via `test_utils.py::TestSchedulerValidation`

5.4.10 Module: Recording-Only State Management

The Recording-Only State Management module provides a limited state management implementation for recording management mode.

1. [test-state-management-recording-only-noops](#)

Type: Functional, Dynamic, Automatic

Initial State: `StateManagementRecordingManagementOnly` instance

Input: Calls to `arm()`, `disarm()`, `manual_move()`, `manual_move_to()`, `start_recording()`, `stop_recording()`

Output: All operations are no-ops (do not raise exceptions)

Test Case Derivation: Verifies that recording-only mode safely ignores control operations

How test will be performed: Automated via `test_state_management_recording_only.py::TestStateManagementRecordingOnlyNoops`

2. [test-state-management-recording-only-status](#)

Type: Functional, Dynamic, Automatic

Initial State: `StateManagementRecordingManagementOnly` with mocked database and system status

Input: `status()` call

Output: `StatusResponse` with `is_recording=False`, `armed=False`, system metrics populated

Test Case Derivation: Verifies FR-10 (status reporting in recording-only mode)

How test will be performed: Automated via `test_state_management_recording_only.py::TestStateManagementRecordingOnlyStatus`

3. `test-control-process-main-entry`

Type: Functional, Dynamic, Automatic

Initial State: Mocked StateManagement and threading

Input: `run_control_process()` and `run_recording_management()` calls

Output: API thread started and joined; StateManagement instantiated

Test Case Derivation: Verifies control process entry points initialize correctly

How test will be performed: Automated via `test_state_management_recording_only.py::TestControlPro`

5.4.11 Module: Main Entry Point

The Main Entry Point module handles command-line dispatch to different process modes.

1. `test-main-dispatch-control`

Type: Functional, Dynamic, Automatic

Initial State: Mocked `sys.argv` with no arguments

Input: Default execution (no command line args)

Output: `run_control_process()` called

Test Case Derivation: Verifies default mode launches control process

How test will be performed: Automated via `test_main_entry.py::TestMainDispatch`

2. `test-main-dispatch-cv`

Type: Functional, Dynamic, Automatic

Initial State: Mocked `sys.argv` with `["cv"]` argument

Input: CV process launch command

Output: `run_cv_process()` called

Test Case Derivation: Verifies FR-3 (CV process launch)

How test will be performed: Automated via `test_main_entry.py::TestMainDispatch`

3. `test-main-dispatch-livestream`

Type: Functional, Dynamic, Automatic

Initial State: Mocked `sys.argv` with `["livestream"]` argument

Input: Livestream process launch command

Output: `run_livestream_process()` called

Test Case Derivation: Verifies FR-8, FR-9 (live video process launch)

How test will be performed: Automated via `test_main_entry.py::TestMainDispatch`

4. [test-main-dispatch-transcode](#)

Type: Functional, Dynamic, Automatic

Initial State: Mocked sys.argv with ["download-stabilized"] or ["preview-stabilized"] arguments

Input: Transcode process launch command with video and log paths

Output: start_transcode_process() called with correct mode and paths

Test Case Derivation: Verifies FR-12 (transcode process launch for recording stabilization)

How test will be performed: Automated via test_main_entry.py::TestMainDispatch

5. [test-main-dispatch-unknown](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: Mocked sys.argv with unknown command

Input: Unknown command line argument

Output: System exits with code 1

Test Case Derivation: Verifies proper error handling for invalid commands

How test will be performed: Automated via test_main_entry.py::TestMainDispatch

5.4.12 Module: Utility Formatters

1. [test-formatters-edge-cases](#)

Type: Nonfunctional, Robustness, Automatic

Initial State: Formatter functions loaded

Input: Edge values (null, undefined, negative, zero, very large numbers)

Output: Sensible defaults; no crashes; formatted output for all inputs

Test Case Derivation: Verifies RFR-1 (robustness against unexpected data)

How test will be performed: Automated via test_utils/formatters.test.ts

2. [test-formatters-internationalization](#)

Type: Nonfunctional, Internationalization, Automatic

Initial State: Formatters with various locale considerations

Input: Values requiring locale-specific formatting

Output: Consistent formatting regardless of system locale

Test Case Derivation: Verifies PI-2 (consistent international display)

How test will be performed: Automated via test_utils/formatters.test.ts

5.4.13 Module: UI Components

1. `test-ui-loading-states`

Type: Nonfunctional, Usability, Automatic

Initial State: Components with loading/null states

Input: Null or undefined data

Output: Loading spinners or placeholder content; no crashes

Test Case Derivation: Verifies EZ-2 (immediate feedback for pending operations)

How test will be performed: Automated via component test files (e.g., `test_pages/control.test.tsx`)

2. `test-ui-error-handling`

Type: Nonfunctional, Robustness, Automatic

Initial State: Components with mocked API that returns errors

Input: API errors, network failures, malformed responses

Output: Graceful error display; component remains interactive

Test Case Derivation: Verifies RFR-1 (UI error resilience)

How test will be performed: Automated via component test files

5.5 Traceability Between Test Cases and Modules

The following tables provide traceability between unit test cases and the modules defined in the Module Guide (MG). Each test case verifies specific functionality of its corresponding module, ensuring that all implemented leaf modules have adequate test coverage.

Table 5: Traceability Between Unit Test Cases and Backend Modules

Module	Unit Test Cases
mState (State Management)	<code>test-state-management-arm-disarm;</code> <code>test-state-management-manual-move;</code> <code>test-state-management-manual-move-clamped;</code> <code>test-state-management-recording;</code> <code>test-state-management-download-pause;</code> <code>test-state-status-performance;</code> <code>test-state-error-handling</code>
mAPI (API Gateway)	<code>test-api-endpoints-exist;</code> <code>test-api-recordings-crud;</code> <code>test-api-validation;</code> <code>test-api-error-responses</code>

Continued on next page

Table 5 – Continued from previous page

Module	Unit Test Cases
mRecord (Recording Database)	test-database-allocate; test-database-list-recordings; test-database-rename-delete; test-database-path-traversal-protection; test-database-space-usage; test-database-error-handling
mGimbal (Gimbal Abstraction)	test-gimbal-crc8; test-gimbal-packet-construction; test-gimbal-angle-commands; test-gimbal-led-control; test-gimbal-info-query
mTrack (Tracking)	test-tracking-queue-behavior; test-tracking-worker-control-law; test-tracking-angle-clamping; test-tracking-stop
mCVManagement (CV Process Management)	test-cv-management-osd-send; test-cv-management-recording-commands; test-cv-management-pause-resume; test-cv-management-recv-loop; test-cv-management-exception-safety
mVideoManagement (Live Video Management)	test-livestream-construction; test-livestream-process-loop
mTranscodeManagement (Transcode Management)	test-transcode-read-log; test-transcode-shader-probe; test-transcode-bus-call
mTranscode (Transcode Process)	test-transcode-read-log; test-transcode-shader-probe; test-transcode-bus-call
mCV (CV Process)	test-cv-format-time; test-cv-update-osd
mVideo (Live Video Process)	test-livestream-construction; test-livestream-process-loop
Common IPC	test-bounding-box-center; test-bounding-box-rotate-90; test-dataclass-construction
Common IPC Buffer	test-ipc-buffer-sender; test-ipc-buffer-receiver; test-ipc-buffer-overflow-handling; test-ipc-buffer-memory-safety
Common Watchdog	test-watchdog-refresh; test-watchdog-clear; test-watchdog-timeout-accuracy

Continued on next page

Table 5 – Continued from previous page

Module	Unit Test Cases
Common System Status	<code>test-system-status-caching</code> ; <code>test-system-status-callback-updates</code>
Common Utils	<code>test-ip4-addresses</code> ; <code>test-scheduler-validation</code>
Recording-Only State Management	<code>test-state-management-recording-only-noops</code> ; <code>test-state-management-recording-only-status</code> ; <code>test-control-process-main-entry</code>
Main Entry Point	<code>test-main-dispatch-control</code> ; <code>test-main-dispatch-cv</code> ; <code>test-main-dispatch-livestream</code> ; <code>test-main-dispatch-transcode</code> ; <code>test-main-dispatch-unknown</code>
Transcode API (mAPI)	<code>test-transcode-routes-404</code> ; <code>test-transcode-streaming</code> ; <code>test-transcode-pipe-cleanup</code>
SSE (mAPI)	<code>test-sse-broadcast-performance</code> ; <code>test-sse-thread-safety</code>

Table 6: Traceability Between Unit Test Cases and Frontend Modules

Module	Unit Test Cases
mPreview (Preview)	<code>test-control-page-render</code> ; <code>test-control-page-bbox-overlay</code>
mManual (Manual Control)	<code>test-controls-card-render</code> ; <code>test-control-page-drag</code>
mRecordMng (Recording Management)	<code>test-recordings-page-loading</code> ; <code>test-recordings-page-empty</code> ; <code>test-recordings-page-list</code> ; <code>test-recordings-delete</code> ; <code>test-recordings-rename</code>
mConfig (Configuration)	<code>test-language-selector</code> ; <code>test-configuration-menu</code>
API Client	<code>test-api-client-urls</code> ; <code>test-api-client-automatic-discovery</code> ; <code>test-api-client-methods</code>
Rocam Provider	<code>test-rocam-provider-initialization</code> ; <code>test-rocam-provider-error-handling</code> ; <code>test-rocam-provider-polling</code> ; <code>test-use-rocam-hook</code>
Utility Formatters	<code>test-formatters-degrees</code> ; <code>test-formatters-temperature</code> ; <code>test-formatters-bytes</code> ; <code>test-formatters-duration</code> ; <code>test-formatters-edge-cases</code> ; <code>test-formatters-internationalization</code>
Internationalization	<code>test-i18n-activation</code>
App (Routing)	<code>test-app-routing</code>
UI Components (Individual)	<code>test-system-status-card</code> ; <code>test-navbar</code> ; <code>test-controls-card</code> ; <code>test-language-selector</code> ; <code>test-configuration-menu</code> ; <code>test-ui-loading-states</code> ; <code>test-ui-error-handling</code>

Note: The following modules are listed in MG but are not verified by unit tests (as documented in the Unit Testing Scope section):

- **mStream** (Video Stream Abstraction) — Third-party library (Nvidia Deepstream SDK)
- **mSerial** (Serial Abstraction) — Third-party library (pyserial)
- **mStatus** (System Status Module) — Hardware-dependent library (jetson-stats)

Container modules (**mJetson**, **mControl**, **mUI**) are also not directly tested as they are organizational constructs; their leaf modules are tested individually.

References

- Vision-Guided Tracker Team. Software architecture (module guide), 2025a. Project document, this repository.
- Vision-Guided Tracker Team. Software detailed design (module interface specification), 2025b. Project document, this repository.
- Vision-Guided Tracker Team. Software requirements specification, 2025c. Project document, this repository.

6 Appendix

6.1 User Survey Questions

Please answer each question based on your experience during the field test. For questions rated on a scale, circle the number that best reflects your opinion: 1 = Strongly Disagree, 2 = Disagree, 3 = Neutral, 4 = Agree, 5 = Strongly Agree.

User Interface

1. The interface was readable and easy to see outdoors. (1 2 3 4 5)
2. The interface looked professional and well-designed. (1 2 3 4 5)
3. The important information was immediately visible on the screen. (1 2 3 4 5)
4. No unnecessary or confusing information was shown. (1 2 3 4 5)
5. The system was easy to learn and operate after a short time. (1 2 3 4 5)
6. The terms and labels used in the interface were clear and understandable. (1 2 3 4 5)

System Performance

1. The tracking footage was stable and smooth. (1 2 3 4 5)
2. The tracking system maintained lock on the rocket reliably. (1 2 3 4 5)
3. The system operated as expected without major errors. (1 2 3 4 5)
4. Once armed, the system operated fully autonomously. (1 2 3 4 5)
5. I was able to fully operate and monitor the system remotely. (1 2 3 4 5)

User Experience and Feedback

1. Were any colors, symbols, or content elements disrespectful or inappropriate to you?
(Please describe if applicable)

2. What improvements would you suggest for future versions of RoCam?

Appendix — Reflection

The information in this section will be used to evaluate the team members on the graduate attribute of Lifelong Learning.

The purpose of reflection questions is to give you a chance to assess your own learning and that of your group as a whole, and to find ways to improve in the future. Reflection is an important part of the learning process. Reflection is also an essential component of a successful software development process.

Reflections are most interesting and useful when they're honest, even if the stories they tell are imperfect. You will be marked based on your depth of thought and analysis, and not based on the content of the reflections themselves. Thus, for full marks we encourage you to answer openly and honestly and to avoid simply writing "what you think the evaluator wants to hear."

Please answer the following questions. Some questions can be answered on the team level, but where appropriate, each team member should write their own response:

1. What went well while writing this deliverable?
2. What pain points did you experience during this deliverable, and how did you resolve them?
3. What knowledge and skills will the team collectively need to acquire to successfully complete the verification and validation of your project? Examples of possible knowledge and skills include dynamic testing knowledge, static testing knowledge, specific tool usage, Valgrind etc. You should look to identify at least one item for each team member.
4. For each of the knowledge areas and skills identified in the previous question, what are at least two approaches to acquiring the knowledge or mastering the skill? Of the identified approaches, which will each team member pursue, and why did they make this choice?

Jianqing Liu

1. **What went well:** I was responsible for the Part 4 of this deliverable, focusing on all the system tests. I think it was really easy to come up with all the test cases because We already completed the SRS.
2. **Pain points and resolution:** I think some of the test cases are very verbose. For some of the tests, how test will be performed is just the same as the input and output condition of the test case.

Mike Chen

1. **What went well:** I contributed primarily to Part 3 of this deliverable, focusing on the verification and validation plan and the automation tools section. The structure

and clarity of this part improved substantially after integrating team and stakeholder feedback. I ensured that each verification activity was directly tied to the SRS and our test framework.

2. **Pain points and resolution:** I initially faced several issues with GitHub CI configuration—some commits overwrote teammates’ work and caused LaTeX compilation failures. I resolved these by restoring the affected commits, redesigning the YAML workflows, and setting up branch protection rules. Revisions based on feedback also required extensive reformatting to achieve consistency across sections.
3. **Knowledge and skills to acquire:** I plan to improve my skills in CI/CD automation and verification planning, particularly integrating automated builds, test execution, and documentation generation through GitHub Actions.
4. **Approaches to acquire skills:** I will (1) study advanced GitHub Actions pipelines from open-source projects and (2) create a smaller test repository to simulate multi-stage verification workflows. I selected the second approach because it provides hands-on experience with merge control, build automation, and verification feedback integration.

Frank

1. **What went well:** I contributed to both Part 2 and Part 3 of the deliverable, ensuring that the design and verification sections were fully aligned with the SRS. My work focused on refining the test structure, verifying requirement traceability, and improving the flow between verification items and their corresponding system requirements.
2. **Pain points and resolution:** The main challenge was maintaining consistent terminology and depth of explanation between sections written by different team members. To resolve this, I reviewed the SRS and cross-checked every requirement reference to ensure correctness and coherence across parts.
3. **Knowledge and skills to acquire:** I plan to strengthen my knowledge of requirements traceability and automated testing frameworks to improve coverage and maintain consistency with system goals.
4. **Approaches to acquire skills:** I will (1) review documentation on structured traceability mapping and (2) develop example UI and system tests that link directly to specific SRS requirements. I chose the second approach because applying traceability in practice will reinforce both documentation and test alignment.

Xiaotian Lou

1. **What went well:** I focused mainly on Part 2 of the deliverable, organizing the SRS and design verification sections. The verification checklists and phase structure improved document readability and made the review process more systematic.

2. **Pain points and resolution:** The primary difficulty was harmonizing writing styles and section formatting across contributors. I standardized tables, checklists, and layout conventions to produce a consistent and professional presentation.
3. **Knowledge and skills to acquire:** I aim to gain more experience in formal verification documentation and structured validation reporting to improve the traceability and completeness of future deliverables.
4. **Approaches to acquire skills:** I will (1) study professional verification and validation templates from engineering projects and (2) apply checklist-based verification methods in upcoming development stages. I selected the first approach to strengthen my understanding of documentation standards and best practices.