Advanced Science Letters
E-ISSN:1936-7317

Facial Emotion Recognition Using Convolutional Neural Netwoks(CNN)

D.Spandana[1], Dr.M.C.Raju[2], P.Madhurima[3], M.Manya[4], P.Uma[5]
[1,3-5]B.Tech Student, Department of ECE, VNR VJIET, Hyderabad, Telangana, India.
[2]Associate Professor, Department of ECE, VNR VJIET, Hyderabad, Telangana, India.
raju_mc@vnrvjiet.in

Abstract:-*Facial feeling acknowledgement is a subject of incredible enthusiasm for the fields of PC vision, man-made conscious- ness and gaming to advertising and human services. The principle objective of this paper is to group feelings on human appearances. Despite the fact that FER can be led utilizing numerous sensors however this paper plans to chip away at Convolutional Neural Networks(CNN) since they work better for picture acknowledgement errands since they can catch spatial highlights of the information pictures because of the accessibility of enormous number of channels. Our model comprises of four convolutional layers,3 max pooling layers and 2 completely associated layers. Using 4 layer CNN, the model accomplished an exact- ness of 63.2% in 50 epochs.*

I. Introduction

Scientists and engineers thought of artificially intelligent systems that can mentally and physically be equivalent to humans since the development of computers. The expansion of computational force has prompted quick learning machines, and gigantic measure of information is provided by web for preparing. These two improvements have prompted the exploration on keen self-learning frameworks, with neural systems.

People as a rule speak with one another either by speech, emotions or gestures. They are significant in human correspondence.

One potential application for this lies in the zone of surveillance and conduct investigation by law enforcement. Moreover such systems are utilized in advanced cameras to consequently take pictures when the client smiles. The most encouraging applications include the humanization of artificial intelligent systems. PCs can follow the psychological condition of the client, robots can respond upon this and act suitably. Emotion recognition along these lines assumes a key-job in improving human machine cooperation.

II. Literature review

For the advancement of a framework that can recognize feelings through facial expressions, a lot of research has been done in the past. In addition to that, several public challenges were also conducted to promote progress in this field.

In more recent work, Yu and Zhang utilized an ensemble of CNN and achieved a 61.2% accuracy. They utilized information enlargement during preparing and testing so as to improve execution. They proposed information perturbation and voting method to increase the performance. They likewise utilized stochastic pooling layers rather than max pooling layers. Their technique positioned second in the EmotiW2015 challenge.

Mollahosseini et al proposed a system which comprises of a solitary CNN layer dependent on Inception engineering on the information which comprised various presented and naturalistic images. They likewise contrasted they got accuracy with AlexNet on the equivalent datasets.

Ming Li et al proposed a model which involves two convolutional neural networks. The first is set up with outward appearance databases and the second is a Deep ID system to recognize

features. These two systems are consolidated together which is fed to fully connected layers. This model was assessed on two datasets in particular FER+ dataset and CK+ dataset. For 200 epochs the model was prepared and accomplished a precision of 0.71 for FER2013 dataset and 0.99 for CK+ dataset.

Tan et al proposed a model to arrange a group picture into emotions, for example, positive or nonpartisan or negative. His model involves the use of two convolutional neural networks. The principal framework relies upon pack pictures and the second is on singular pictures. This model has accomplished an exactness of 80.9.

To take care of the facial emotion acknowledgement issue numerous works have been finished by the utilization of a mix of numerous datasets. In this paper,FER-2013 dataset was picked to perceive various kinds of emotions.

III. Theoretical Background

Convolution Neural Network:

A Convolutional neural system is a sort of neural system that contains convolution layers which does errands performing convolution.

Convolution is only a mathematical estimation between the two quantities to deliver a third quantity. In this, the picture isn't considered as pixels, yet rather it is considered as numbers speaking to the pixel esteem.

PC just observes the grid of numbers. Convolution activities happen on these numbers. We utilize both convolution layers and fully connected layers.

Each node is associated with each other neuron in fully connected layer. In standard feedforward neural systems these layers are utilized. The contrast between the fully connected layers and convolution layer is that the convolutional layers are not associated with each neuron. Over the confined regions associations are made. A sliding window is moved over the picture. The size of window is known as the kernel or the filter. They are fundamentally used to perceive designs in the information.

For each filter, there are properties to consider, mostly stride and padding. Stride essentially speaks to each progression of the convolution activity that is by knowing what number of number of pixels the window moves over. In padding, to expand the size of the picture we include invalid pixels. Invalid pixels are only the pixels with zero worth. On the off chance if we have a picture of 5 x 5 and a window with a 3 x 3 filter, a stride of 1 and no padding and the yield of the convolutional layer will be a 3 x3 picture. This procedure is called as pooling.

For this situation, max pooling is utilized. From each sliding window most extreme yield will be taken and that is put in the yield matrix.

For image recognition mostly convolution is utilized rather than feed forward system. The explanation is that it exploits spatial region and it likewise permits to diminish the quantity of parameters in a system. The idea of pooling is utilized in convolution neural system to decrease the quantity of parameters by down sampling. There are numerous uses of CNN like mechanical autonomy, utilized in vehicles however it is for the most part utilized in image recognition.

IV. Experimental Setup

Here it tells how much amount of data was used for training and testing, how preprocessing takes place and the design of the model.

4.1.1. Dataset

Neural systems, particularly profound neural systems, will in general perform better when bigger measures of preparing informational collection is available.

The Facial Expression dataset FER-2013 was utilized. This dataset was introduced in the ICML 2013 Challenges in Representation Learning. This dataset contains 35,887 pictures having the basic articulations, for example, Happy, Sad, Angry, Disgusted, Fearful, Surprised and Neutral. Each image is a viewpoint with respect to an issue which is taken from the wild and remarked on to one of the seven explanations.



Fig1:Graph between Accuracy and number of test images used per class

4.1.2. Pre-Processing

The dataset involved different pictures represented to as strings of 2304 space isolated numbers which were at that point changed over to a 48 * 48 cross section. Each number addressed a pixel value.

The first information of 35,886 pictures was part into a preparing set of 28,708 pictures and a testing set of 7,177 pictures a 80 : 20 split. With regards to profound learning, information is the greatest factor. The greater the preparation set, the better the yield. Remembering that, having a testing set of 20% of the absolute pictures might be viewed as unreasonable. For case, Mollahosseini et al. separated their 275k picture dataset into 60% for preparing, 20% for testing and 20% for approval.

4.1.3. Model

The model structured comprises of four two-dimensional convolutional layers, three max pooling layers and two fully connected layers. Max pooling chooses the most extreme incentive from each group of neurons. This diminishes the spatial components of the yield exhibit. The contribution to the model is a pre-handled picture of size 48 * 48.This model likewise uses dropout so as to limit overfitting.

The system comprises of two convolutional layers with a filter size of 32 and 64 individually. This is trailed by a maximum pooling layer with pool size 2 * 2. At that point a dropout of rate 0.25 is applied to limit overfitting. This is trailed by a convolutional layer with a filtersize of 128 which at that point is trailed by max pooling layer. Another convolutional layer with filter size of 128 follows this. Again max pooling is performed with a dropout pace of 0.25.To convert the got yield into a one dimensional vector,the yield from the past layers was flattened.A fully connected layer is then utilized alongside an extra dropout of rate 0.5.Finally,a fully connected layer with a softmax initiation work characterizes the yield layer.



Fig2:Convolutional neural networks

The size of the kernel likewise knows as filter is set to 3 * 3 for all Convolutional layers. Each max pooling layer utilized is two dimensional with a pool size 2 * 2. This lessens the size of the yield of each layer to half. All the Convolutional layers utilized a rectified linear unit which is an initiation capacity to build the non-linearity. The softmax activation function was utilized in the yield layer to create likelihood of every feeling.

V. Testing

The dataset was at first part into a 80% preparing set and 20% preparing set. During the period of testing, each trained system is being stacked and taken care of the whole testing set with one picture at a time. This will be an- other picture which the model had never ob- served. The picture taken by the model was preprocessed similarly as point by point in preprocessing. So the model doesn't have a clue about the right yield and

predicts it dependent on the own training. It endeavors to characterize the picture dependent on the information it procured by preparing and characteristics of the picture itself.

Therefore towards the end it gives a list of characterized feeling probabilities for each picture. The most noteworthy likelihood feeling will at that point be contrasted with the pictures to check the exact number of expectations. It basically checks the quantity of tests where the model precisely anticipated and divides it by the complete number of test all together in the preparation set. So here the testing set contains an aggregate of 7177 pictures.

VI. Result

At last, a small tool was built up that took information from the webcam, detected faces, prepared them and took care of as a contribution to the model. It was discovered that the model accurately anticipated practically all occurrences of happiness, fearful, sadness, neutral and most cases of surprise though the feelings anger and disgust were never anticipated. In fact, the emotions, for example, anger and fear would in general blend in with each other. Hence, during the testing, it was seen that the model had the option to identify faces and foresee their feelings immediately.

Fig3:Screenshot of Live Module



Fig 4: Screenshot of Live Module

Fig 5: Screenshot of Live Module

VII. Conclusion and Future Work

We built up a model to categorize outward appearances into one of seven emotions by utilizing the FER-2013 dataset and assessed the performance. The accuracy we got is 63.7%.The outcomes shown that CNNs are equipped for learning facial attributes and improving facial feeling acknowledgment.

In future, an in-depth examination of the most anticipated feelings may prompt significantly more realizable and exact system. In order to get an ideal framework further preparing tests will be certainly be required to foresee the troublesome feeling, for example, disgust.

In future this model could be utilized in numerous applications, for example, marketing, video game industry and healthcare. This can

likewise be utilized in the vehicles to recognize driver's inactiveness. In expansion to these, it can utilized in shopping centers and super markets and to give feedback.

References

[1] Zhiding Yu & Cha Zhang. (2015). Image based Static Facial Expression Recognition with Multiple Deep Network Learning. Proceedings of the 2015 ACM on International Conference on Multimodal Interaction . 435442.

[2]Abhinav Dhall, Roland Goecke, Simon Lucey, and Tom Gedeon. (2011). Static Facial Expressions in Tough Conditions: Data, Evaluation Protocol And Benchmark, First IEEE International Workshop on Benchmarking Facial Image Analysis Technologies BeFIT, IEEE International Conference on Computer Vision ICCV2011, Barcelona, Spain, 6-13 November 2011.

[3]A. Mollahosseini, D. Chan and M. H. Mahoor. (2016). Going deeper in facial expression recognition using deep neural networks. 2016 IEEE Winter Conference on Applications of Computer Vision (WACV), Lake Placid, NY, 1-10.

[4] Chollet, Franc¸ois and others (2015). Keras: https://keras.io/

[5]A. Krizhevsky, I. Sutskever, and G. E. Hinton. (2012). Imagenet classification with deep convolutional neural networks. Advances in neural information processing systems, 10971105.

[6] P. Khorrami, T. Paine, and T. Huang, "Do Deep Neural Networks Learn Facial Action Units When Doing Expression Recognition?" in IEEE International Conference on Computer Vision (ICCV) Workshops, 2015, pp. 19–27.

[7] N. Srivastava, G. Hinton, A. Krizhevsky, I. Sutskever, and R. Salakhutdinov, "Dropout: A simple way to prevent neural networks from overfitting," The Journal of Machine Learning Research, vol. 15, no. 1, pp. 1929–1958, 2014.

[8]S. Ioffe and C. Szegedy, "Batch Normalization: Accelerating Deep Network Training by Reducing Internal Covariate Shift," CoRR, vol. 1502, 2015.