Requirements:

OS: Ubuntu 22.04 Python: 3.10.12

In Ubuntu Software:

Arduino

Terminator (sudo apt install terminator) Brave (Optional, browser without adds)

Install pip:

sudo apt install python3-pip

Install VS Code:

sudo snap install code -classic

Install VS Code Extensions:

ROS – Developer has to be Microsoft

Python – Developer has to be Microsoft

Turn on auto save: File -> Auto Save OR File -> Preferences -> Settings → (Write "auto save") ->

Select afterDelay

Install Dynamixel Wizard:

https://emanual.robotis.com/docs/en/software/dynamixel/dynamixel wizard2/

Install Git and configure:

https://www.digitalocean.com/community/tutorials/how-to-install-git-on-ubuntu-22-04

To create a github SSH authentication key follow this tutorial, but DO NOT PUT PASSWORD:

Hit Enter when asked for password:

https://www.youtube.com/watch?v=WgZIv5HI44o

Install NVIDIA drivers:

https://www.cherryservers.com/blog/install-cuda-ubuntu

(Follow until step 5)

Arduino Libraries:

Sketch → Include Libraries → Manage Libraries

Adafruit NeoPixel

Install ROS2 humble:

https://docs.ros.org/en/humble/Installation/Ubuntu-Install-Debians.html

Follow Tutorials (include ROS2 installation):

https://www.youtube.com/playlist?list=PLLSegLrePWgJudpPUof4-nVFHGkB62Izy

This tutorial includes a lot more than intalling ROS2 and subs and pubs examples, it does:

- adds ws sources to ~/.bashrc

To work with UFACTORY xArm 6:

- https://www.ufactory.cc/ufactory-studio/
- Download Linux

To install realsense-viewer:

Follow the following link until the part that states: "Uninstalling the packages" https://github.com/IntelRealSense/librealsense/blob/master/doc/distribution_linux.md

To install librealsenseand some more necessary libraries:

First follow these instructions:

https://dev.intelrealsense.com/docs/compiling-librealsense-for-linux-ubuntu-guide
Then follow the "Step 3: Install Intel® RealSense™ ROS2 wrapper":
https://github.com/IntelRealSense/realsense-ros/blob/ros2-development/README.md

Please check ANEX to see possible errors during COLCON BUILD:

To save vídeos for dataset:

- sudo apt-get install ffmpeg x264 libx264-dev

pip install keras pip install tensorflow

- ros2 run charmie_debug save_videos_for_dataset
- vídeo is saved at home directory with date: "2024-07-04 00-14-19charmie.avi"
- to put in roboflow we must convert using ffmpeg to mp4 using:

 ffmpeg -i 2024-07-04 00-14-19charmie.avi 2024-07-04_00-14-19_charmie.mp4

PACKAGES:

```
low level:
              pip install pyserial
       ps4_controller:
              pip install pyPS4Controller
       neck dynamixel:
              pip install dynamixel-sdk
       xarm:
              Follow steps in: https://github.com/xArm-Developer/xarm_ros2/tree/humble?
tab=readme-ov-file
              sudo apt install ros-foxy-xacro ros-foxy-joint-state-publisher-gui
              sudo apt install ros-foxy-gazebo-ros-pkgs
              sudo apt install ros-foxy-ros2-control ros-foxy-ros2-controllers ros-foxy-gazebo-
ros2-control
       yolos:
              pip install ultralytics
              to get the characteristics in yolo_pose:
```

audio:

receptionist:

pip install face_recognition

debug_visual:

python3 -m pip install pygame-widgets

speakers novos:

- pip install TTS
- export PATH=\$PATH:/home/utilizador/.local/bin (so tts commands can be used in terminal)
- pip install pydub
- (editar depois install espeak)
- pip install pygame

Possible ROS2 Errors:

.....

When doing colcon build after creating the first package:

"/usr/lib/python3/dist-packages/setuptools/command/install.py:34: SetuptoolsDeprecationWarning: setup.py install is deprecated. Use build and pip and other standards-based tools. warnings.warn(

---'

pip3 list | grep setuptools

pip3 install setuptools==58.2.0

pip3 list | grep setuptools

If you have error such as the following when doing colcon build:

Finished <<< charmie_point_cloud [10.3s]

--- stderr: charmie restaurant

/home/charmie/.local/lib/python3.10/site-packages/setuptools/command/easy_install.py:157: EasyInstallDeprecationWarning: easy_install command is deprecated. Use build and pip and other standards-based tools.

warnings.warn(

It means that you have the wrong version of setuptools. For ROS a specific version must be installed: setup tools version 58.2.0 (last version to work with ros2 python packages without any warnings)

pip install setuptools==58.2.0 (all above versions do not work)

Please check for more info:

https://answers.ros.org/question/396439/setuptoolsdeprecationwarning-setuppy-install-is-deprecated-use-build-and-pip-and-other-standards-based-tools/

when doing colcon build realsense packages (on charmie_ws) it might get some erros related with gazebo, install gazebo using:

The error indicates that your workspace depends on the <code>gazebo_ros</code> package, but it is either not installed or not properly sourced in your environment. Here's how to resolve this issue:

1. Install the gazebo_ros Package

gazebo_ros is part of the ROS 2 Humble distribution. Install it by running:

```
sudo apt update
sudo apt install ros-humble-gazebo-ros-pkgs
```

2. Verify the Package Installation

Check if gazebo_ros is installed:

ros2 pkg list | grep gazebo_ros

You should see gazebo_ros and related packages listed.

3. Set CMAKE PREFIX PATH if Needed

If you installed gazebo_ros but CMake still cannot find it, manually set the CMAKE_PREFIX_PATH to include the installation directory of gazebo_ros.

Add this to your ~/.bashrc or run it in your terminal:

export CMAKE_PREFIX_PATH=\$CMAKE_PREFIX_PATH:/opt/ros/humble

Then source your .bashrc:

source ~/.bashrc

--- stderr: xarm_controller CMake Error at CMakeLists.txt:38 (find_package): By not providing "Findhardware_interface.cmake" in CMAKE_MODULE_PATH this project has asked CMake to find a package configuration file provided by "hardware_interface", but CMake did not find one. Could not find a package configuration file provided by "hardware_interface" with any of the following names: hardware_interfaceConfig.cmake hardware_interface-config.cmake Add the installation prefix of "hardware_interface" to CMAKE_PREFIX_PATH or set "hardware_interface_DIR" to a directory containing one of the above files. If "hardware_interface" provides a separate development package or SDK, be sure it has been installed.

1. Install ros-humble-ros2-control

The hardware_interface package is provided by the ros2_control framework. Install it using:

sudo apt update sudo apt install ros-humble-ros2-control ros-humble-ros2-controllers

The display FACE on CHARMIE does not map the input touchscreen to the display. What happens is that when you click on the display touchscreen it is like you are pressing with the mouse but on the PC screen an not on the display. To use to display CHARMIE face you have to change from: Ubuntu on Wayland to Ubuntu on Xorg. Wayland handles input devices and outputs differently, and currently does not provide an official xinput-like way to map touchscreen input to specific displays.

The test this switch you can do:

- **Log out** of your current session (don't restart just log out).
- On the **login screen**, click your **username**.
- Before entering your password, in the **bottom-right corner** of the screen is a **gear icon**
- It appears **after** you select your user, and **before** you type your password.
- Click the **gear icon** a small menu will pop up.
- Choose "Ubuntu on Xorg" or "Ubuntu (X11)".
- Now type your password and log in.

However if you restart the PC it goes back to Ubuntu on Wayland. To make this a definitive change you have to do the following:

You can **force GDM to always start Xorg** instead of Wayland by editing its config file:

sudo nano /etc/gdm3/custom.conf

Then **uncomment** (remove #) or set this line:

WaylandEnable=false

This tells GDM to **disable Wayland entirely**, so it always boots into Xorg for every user.

After saving (Ctrl+O), reboot.

Now it will **default to Xorg**, and your touchscreen mapping will always work.

Now run charmie face to test if you can press the face and it detects.

To check the id (device_id) of the display touchscreen, you can run:

xinput list

And to check the name (output_name) of the display touchscreen you can run:

xrandr

In sum after you switch to Ubuntu on Xorg you have to run the following command:

xinput map-to-output <device id> <output name>

For exmaple in Tiago's PC it is:

xinput map-to-output 10 DP-1-2

I think the device_id may change from PC to PC but the output_name is the same.

The face_display already does this subprocess automatically to map the input touchscreen. So you only need to make sure you are on Ubuntu on Xorg.

Links for new team members:

RoboCup@Home official website:

https://athome.robocup.org/

RoboCup@Home official Github:

https://github.com/RoboCupAtHome/

Rulebook Link:

https://robocupathome.github.io/RuleBook/rulebook/master.pdf

CHARMIE Project Github:

https://github.com/SparkRibeiro21/charmie ws

CHARMIE Dataset:

 $\frac{https://github.com/SparkRibeiro21/charmie\ ws/blob/main/objects/LAR\ objects/LAR\%20Dataset\ \%20Objects.pdf}$

Requirements nos vossos Pcs:

OS: Ubuntu 22.04 LTS (Aconselho vivamente que façam dualboot, máquina virtual vai dar erros no ROS)

ROS2: Humble

Para instalarem ROS2, aconselho a seguirem este set de tutoriais, eles instalam também o VSCode que é o interface que usamos para programar o robô, portanto é só seguir estes tutoriais. Além disso nestes tutoriais também vos explicam bem as bases todas que vão precisar de ROS2.

https://www.youtube.com/playlist?list=PLLSegLrePWgJudpPUof4-nVFHGkB62lzy

Arm (UFACTORY xArm 6): <u>xArm Humble Repo</u> To setup the arm in your workspace, please follow the preparation steps on the xArm Humble repository. (Isto vemos depois, para já podem ir analisar as características do braço)

Terminator Keyboard Shortcuts:

Split Vertically	Ctrl + Shift + O
Split Horizontally	Ctrl + Shift + E
Switch Next Terminal	Ctrl + Shift + N
Switch Previous Terminal	Ctrl + Shift + P
New Tab	Ctrl + Shift + T
Next Tab	Ctrl + Tab
Previous Tab	Ctrl + Shift + Tab
Сору	Ctrl + Shift + C
Paste	Ctrl + Shift + V
Zoom In	Ctrl + +
Zoom Out	Ctrl + -
Reset Zoom	Ctrl + 0
Fullscreen Mode	F11
Close Terminal	Ctrl + Shift + W