●登录 😯

下一页》

免费高级进阶



授课模式:在线直播+课 后视频,从零基础到中 高级开发工程师





Read More



赞---个

Created at July 25, 2018 11:32 AM

流逝的仲夏夜之梦 Created at 5 hours ago

教程确实过时了,和aiohttp官方文档不一样

至部讨论 每 回复

app.make_handler()这个方法用不了,改用APPrunner 咕咕111111 created at May 11, 2019 12:10 AM, Last updated at May 11, 2019 12:14 AM

app.make_handler()这个方法用不了,改用APPrunner,虽然我没看懂,但是官方替换是这样得,有大神解析嘛,代码能正常运行。

 $import\ asynciofrom\ aiohttp\ import\ webasync\ def\ index(request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)\ Index\ h1)',\ content_type='text/html',\ charset='utf-8') async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)\ Index\ h1)',\ content_type='text/html',\ charset='utf-8') async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)\ Index\ h1)',\ content_type='text/html',\ charset='utf-8') async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' async\ def\ hello\ (request): \qquad await\ asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (body=b'\ h1)' asyncio.\ sleep\ (0.5) \qquad return\ web.\ Response\ (0.5) \qquad return\$ await asyncio.sleep(0.5) text = '\h1\rightarrow hello, \%s!\langle h1\rightarrow match_info['name'] return web. Response(body=text. encode("utf-8"))async def init(): app = web. Application() app. router. add_get("/", i ndex) app.router.add_get('/hello/{name}', hello) runner = web.AppRunner(app) # app.make_handler()这个方法用不了,改用APPrunner,虽然我没看懂,但是官方替换是这样得 await runner.setup() site = web.T CPSite(runner, '127.0.0.1', 8000) await site.start() print('Server started at http://127.0.0.1:8000...') return siteloop = asyncio.get_event_loop()loop.run_until_complete(init())loop.run_forever()



Created at May 11, 2019 12:14 AM

https://aiohttp.readthedocs.io/en/stable/web_advanced.html#aiohttp-web-app-runners



DanboDanbo created at October 29, 2018 2:33 PM, Last updated at April 13, 2019 10:22 PM

from aiohttp import web 导入这个会报这个错 This inspection detects names that should resolve but don't. Due to dynamic dispatch and duck typing, this is possible in a limited but useful number of cases. Top-level and class-level items are supported better than instance items.



Created at April 13, 2019 10:22 PM

你需要导入alohttp-webpack包



打卡——第15天 ny12348 created at April 4, 2019 12:42 PM, Last updated at April 4, 2019 12:42 PM