ROBUS°

INDUSTRIAL

SELEST LED FLOOD LIGHT 200W, 300W, IP65





Weight (kg):









OPERATING VOLTAGE



3.88

FEATURES

respectively

rating of IK07

installation CONSTRUCTION



Tempered glass diffuser



PRODUCT INFORMATION DOCUMENT

 Full range providing energy efficient, low maintenance replacement for metal halide and halogen floodlights up to 1500W/6000W

 Switch on the back of luminaire allows switching colour temperature between

 Equipped with self regulating valve to prevent moisture condensation
 Tempered glass providing high impact

• Pre-drilled, angled mounting bracket with

180° adjustable angle for fast and simple

• Powder-coated die cast aluminium housing


Steel bracket and stainless steel screws

3000K, 4000K and 5000K



6.2

RST200CCT3-04 RST300CCT3-04 Comparable to: 1000W metal halide/4000W halogen 1500W metal halide/6000W halogen Total Power (W): 197.9/194.3/198.6 290.8/289.7/295.1 Total Light Output (lm): 28310/31520/29410 42010/46580/43680 Total Emergency Light Output (lm): NΑ Efficacy (lm/cctW): 143/162/148 142/161/148 Lux at 1m (lux): 10240/11320/10490 15210/16670/15520 Emergency Lux at 1m (lux): NΑ NΑ IP: 65 65 Operation Temperature (°C) -20 ≤ Ta ≤ +50 -20 ≤ Ta ≤ +50 **Inrush Current:** 37.6A/ 35us 60A/ 50ns 3000/4000/5000 CCT (K): 3000/4000/5000 RG Value: 0 n Rated Life to L70B50 (Hrs): 30000 30000 390x305x58 480x384x63 Dimensions LxWxH (mm):



Product is certified to all the relevant standards.

Please contact our technical department for market specific compliances.




Diagram for RST300CCT3-04 in 4000K. Other diagrams available on request

PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000
UK: TEL: 0800 973 220
AUS: TEL: +61 7 3890 5444
NZ: TEL: +64 03 668 5285

WEB: ROBUS.COM WEB: ROBUS.COM WEB: ROBUS.COM.AU WEB: ROBUSLED.CO.NZ