

# Additional Function Of Saturation

The data except this specification conform to those of IMX287.

---

### Description

The additional function of saturation which sets saturation level wider is described in this document.

---

### Features

- ◆ Additional function of saturation
- ◆ Support mode
  - All pixel scan mode

CHINA DAHENG GROUP, INC.  
Internal use only

Sony Semiconductor Solutions Corporation reserves the right to change products and specifications without prior notice.  
This information does not convey any license by any implication or otherwise under any patents or other right.  
Application circuits shown, if any, are typical examples illustrating the operation of the devices. Sony Semiconductor Solutions Corporation cannot assume responsibility for any problems arising out of the use of these circuits.

---

**Contents**

|  |   |
|--|---|
| Description-----                                       | 1 |
| Features-----  | 1 |
| Register Map-----                                      | 3 |
| Description of Additional Function of Saturation ----- | 4 |
| Revision History-----                                  | 5 |

CHINA DAHENG GROUP, INC.  
Internal use only

---

## Register Map

The register map for Additional function of saturation is shown below. Set this via Standby mode.  
Please refer to the product specification for register setup other than those list.

Registers corresponding to Chip ID = 02h in Write mode. (I2C:30\*\*h)

| Address | Bit | Register name | Description                                     | Default Value after reset |
|---------|-----|---------------|---|---------------------------|
| 0Dh     | [6] | SAT_CNT       | 0h: Normal mode<br>1h: Additional function mode | 0h                        |

CHINA DAHENG GROUP, INC.  
Internal use only

## Description of Additional Function of Saturation

By using this additional function of saturation, image sensor characteristics are changed as shown below.




Image of output at Additional Function of Saturation (12bit)

Note) 1 Digit = 0.2445 mV (12bit, Normal mode) becomes 1 Digit = 0.4890 mV (12bit, Additional function mode)

---

**Revision History**

| Version | Date           | Page | Remarks   |
|---------|----------------|------|---|
| Rev.0.1 | 9 – Dec. – 16  | –    | First Edition   |
| Rev.0.2 | 10 – Feb. – 17 | 1    | Add:<br>Preliminary   |
|         |                | 4    | Correction:<br>The value of output of the figure. (full count : 4096=>4094) |
| Rev.1.0 | 6 – Oct. – 17  | –    | First Edition (Official Version)  |

CHINA DAHENG GROUP, INC.  
Internal use only