Python: Lesson #3 Functions... Again

By: Marc Geffroy

What was covered last lesson?

- What is a function.
- Why we use functions.
- The syntax of functions
  - Defining a function.
  - Calling a function.
- Variable scope and lifetime.
- Parameters/arguments (typing).
- Return values.

Example code:

- Defining a function.
- Refactoring large code section into functions.

week2.py > main

```python
def greet(AName: str, msg=' welcome!'):
    '''
        This is a function to greet someone
    '''
    return 'Hello, ' + AName + msg

def main():
    name = 'Marc'
    greetMessage = greet(name, ' thank you for your contribution.')

    print(greetMessage)

if __name__ == '__main__':
    main()
```

Maintainability Through Functions

- Functions increase maintainability and reusability.
- We cannot have an entire application in a single file.
- MODULES!!!!!!
- Modules are python files consisting of python code.
- Modules can consist of classes, functions and/or variables.
- There is no hard set rules in Python around modules ie no IDE errors, warnings or hints.
  - It's up to programmers to mind their manners.

Module Syntax #1

Setting up a module:

- Ensure a relevant name for the file ie ‘Greetings.py’.
- Ensure that the path to the module can be found.
- Define some python code inside the file.
- Hint: Keep related code in a module. Create additional modules as needed

“Greetings.py”

```
def greetGuest():
        print(‘Hello, how do you do?’)

def greetFriend(AName):
        print(‘Hey ’ + AName + ‘, how you buddy?’)

def greetMother():
        print(‘Hello Mother dearest’)

def greetEnemy():
        print(‘Hmmmph…’)
```

Module Syntax #2

Using a module:

- To use a module, you have to import the module file using the import keyword.
- You can also use the 'from…import…' to only import specific attributes from the module.
- To use/call a module's attribute you use dot notation (Object Oriented calling language) in the following syntax:
  - *module_name.module_attribute*

```
import Greetings

myFriend= 'Trevor'
Greetings.greetFriend(myFriend)

>>> Hey Trevor, how you buddy?
```

```
From Greetings import greetEnemy

greetEnemy()

>>> Hmmmph…
```

ASCII

What is ASCII? American Standard Code for Information Interchange

- ASCII is a character encoding used between computers on the internet.
- ASCII was developed in the 60s.
- ASCII uses 7 bits to encode 128 characters
  - 0-9
  - a-z
  - A-Z
  - Special characters.

Decimal - Binary - Octal - Hex – ASCII Conversion Chart

Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII	Decimal	Binary	Octal	Hex	ASCII
0	00000000	000	00	NUL	32	00100000	040	20	SP	64	01000000	100	40	@	96	01100000	140	60	`
1	00000001	001	01	SOH	33	00100001	041	21	!	65	01000001	101	41	A	97	01100001	141	61	a
2	00000010	002	02	STX	34	00100010	042	22	“	66	01000010	102	42	B	98	01100010	142	62	b
3	00000011	003	03	ETX	35	00100011	043	23	#	67	01000011	103	43	C	99	01100011	143	63	c
4	00000100	004	04	EOT	36	00100100	044	24	$	68	01000100	104	44	D	100	01100100	144	64	d
5	00000101	005	05	ENQ	37	00100101	045	25	%	69	01000101	105	45	E	101	01100101	145	65	e
6	00000110	006	06	ACK	38	00100110	046	26	&	70	01000110	106	46	F	102	01100110	146	66	f
7	00000111	007	07	BEL	39	00100111	047	27	‘	71	01000111	107	47	G	103	01100111	147	67	g
8	00001000	010	08	BS	40	00101000	050	28	(	72	01001000	110	48	H	104	01101000	150	68	h
9	00001001	011	09	HT	41	00101001	051	29	)	73	01001001	111	49	I	105	01101001	151	69	i
10	00001010	012	0A	LF	42	00101010	052	2A	*	74	01001010	112	4A	J	106	01101010	152	6A	j
11	00001011	013	0B	VT	43	00101011	053	2B	+	75	01001011	113	4B	K	107	01101011	153	6B	k
12	00001100	014	0C	FF	44	00101100	054	2C	,	76	01001100	114	4C	L	108	01101100	154	6C	l
13	00001101	015	0D	CR	45	00101101	055	2D	-	77	01001101	115	4D	M	109	01101101	155	6D	m
14	00001110	016	0E	SO	46	00101110	056	2E	.	78	01001110	116	4E	N	110	01101110	156	6E	n
15	00001111	017	0F	SI	47	00101111	057	2F	/	79	01001111	117	4F	O	111	01101111	157	6F	o
16	00010000	020	10	DLE	48	00110000	060	30	0	80	01010000	120	50	P	112	01110000	160	70	p
17	00010001	021	11	DC1	49	00110001	061	31	1	81	01010001	121	51	Q	113	01110001	161	71	q
18	00010010	022	12	DC2	50	00110010	062	32	2	82	01010010	122	52	R	114	01110010	162	72	r
19	00010011	023	13	DC3	51	00110011	063	33	3	83	01010011	123	53	S	115	01110011	163	73	s
20	00010100	024	14	DC4	52	00110100	064	34	4	84	01010100	124	54	T	116	01110100	164	74	t
21	00010101	025	15	NAK	53	00110101	065	35	5	85	01010101	125	55	U	117	01110101	165	75	u
22	00010110	026	16	SYN	54	00110110	066	36	6	86	01010110	126	56	V	118	01110110	166	76	v
23	00010111	027	17	ETB	55	00110111	067	37	7	87	01010111	127	57	W	119	01110111	167	77	w
24	00011000	030	18	CAN	56	00111000	070	38	8	88	01011000	130	58	X	120	01111000	170	78	x
25	00011001	031	19	EM	57	00111001	071	39	9	89	01011001	131	59	Y	121	01111001	171	79	y
26	00011010	032	1A	SUB	58	00111010	072	3A	:	90	01011010	132	5A	Z	122	01111010	172	7A	z
27	00011011	033	1B	ESC	59	00111011	073	3B	;	91	01011011	133	5B	[	123	01111011	173	7B	{
28	00011100	034	1C	FS	60	00111100	074	3C	<	92	01011100	134	5C	\	124	01111100	174	7C	|
29	00011101	035	1D	GS	61	00111101	075	3D	=	93	01011101	135	5D	]	125	01111101	175	7D	}
30	00011110	036	1E	RS	62	00111110	076	3E	>	94	01011110	136	5E	^	126	01111110	176	7E	~
31	00011111	037	1F	US	63	00111111	077	3F	?	95	01011111	137	5F	_	127	01111111	177	7F	DEL