



#### **MODAL DECOMPOSITION**

**Pattern detection** Reconstruction **Prediction** 

**HOSVD** 

**HODMD** 

ModelFLOWs

**Data Repairing** 

**Superresolution** 

**HODMD** 

**DEEP LEARNING** 

**Pattern detection** 

**Autoencoders** 

Reconstruction

**Superresolution** 

**Full DL** 

**Prediction** 

Hybrid





























### Motivation



Deep Learning combined with singular value decomposition to reconstruct databases in fluid dynamics

P. Díaz<sup>1</sup>, A. Corrochano<sup>1</sup>, M. López-Martín<sup>2</sup> and S. Le Clainche<sup>1</sup>

<sup>1</sup> E.T.S.I. Aeronáutica y del Espacio, Universidad Politécnica de Madrid, Spain
<sup>2</sup> E.T.S.I.T., Universidad de Valladolid, Valladolid, Spain
https://doi.org/10.48550/arXiv.2305.08832



Reconstruction of fluid dynamics databases from few points.

For example, an Atmospheric Boundary Layer (ABL) database.














# Methodology

















# Database & Data preparation

2D Flow past a cylinder at Re = 100





















#### **Superresolution**


## Database & Data preparation

Snapshots Tensor = 
$$\{N_v, N_x, N_y, N_t\}$$
 
$$\begin{cases} - & N_v = 3 \\ - & N_x = 449 \\ - & N_y = 199 \\ - & N_t = 150 \end{cases}$$



Downsampled Tensor = 
$$\{N_v, N_x, N_y, N_t\}$$
 
$$\begin{cases} - & N_v = 3 \\ - & N_x' = 15 \\ - & N_y' = 7 \\ - & N_t = 150 \end{cases}$$

















### Calibration

Hyperparameters		Value	Typical values
Training size	$p_{train}$	121	≤ 80%
Batch size	$N_{batch}$	23	4, 8, 16
Epochs number	$N_{epoch}$	500	100, 200, 500
Activation function	AF	relu	linear, elu, sigmoid
Loss function	$l_f$	MSE	_
Learning rate	$l_r$	$10^{-3}$	$10^{-2}$ , $10^{-3}$ , $10^{-4}$
















#### Superresolution

### Results

















```
Thanks for
watching! Visit us
on:
http://modelflows.e
S
```