Diameter of a Binary Tree



= 3

(1)



= 6

→ longest path bet 2 nodes

→ path does not need to pass via root



max lh + rh

N


mani = 0
root
find Man (node)
{
if (root == null)
return;
lh = findLeftH (node → left)
rh = findRightH (node → right)
mani = max (mani, lh + rh);
findMan (node → left)
findMan (node → right)
}
1
2
3
4
6
5
7
9
8
O(N) x O(N) = O(N²)



mani = 0 1 2

⇒ 6

```
int findMan(node, mani)
{
    if (node == null)
        return 0;

    lh = findMan(node->left, mani);
    rh = findMan(node->right, mani);
    mani = max(mani, lh+rh);
    return 1 + max(lh, rh);
}
```

lh: 5, rh: 3

Java • Autocomplete

```java
/**
 * Definition for a binary tree node.
 * public class TreeNode {
 *     int val;
 *     TreeNode left;
 *     TreeNode right;
 *     TreeNode() {}
 *     TreeNode(int val) { this.val = val; }
 *     TreeNode(int val, TreeNode left, TreeNode right) {
 *         this.val = val;
 *         this.left = left;
 *         this.right = right;
 *     }
 * }
 */
public class Solution {
    public int diameterOfBinaryTree(TreeNode root) {
        int[] diameter = new int[1];
        height(root, diameter);
        return diameter[0];
    }

    private int height(TreeNode node, int[] diameter) {
        if (node == null) {
            return 0;
        }
        int lh = height(node.left, diameter);
        int rh = height(node.right, diameter);
        diameter[0] = Math.max(diameter[0], lh + rh);
        return 1 + Math.max(lh, rh);
    }
}
```

TUF