

Spatial Clustering Algorithm Survey

Baskin, Sean Reinsmidt, Eric
xpq514@mocs.utc.edu first2.last2@xxxxx.com

Sidella, Pallavi
p.s@mocs.utc.edu

November 8, 2012

1 Introduction

1.1 Open Source

2 Asymptotic Evaluation

2.1 Generalized Search Tree

2.2 DBSCAN

Algorithm 1 The DBSCAN spatial clustering algorithm

```
1: procedure DBSCAN( $D, \epsilon, MinPts$ )                       $\triangleright D$  set of points is unclassified
2:    $clusterID = 0$ 
3:   for  $i \leftarrow 1, n$  do
4:      $p \leftarrow D[i]$ 
5:      $p.visited \leftarrow true$                                        $\triangleright$  Mark  $p$  as visited
6:     if  $p.clusterID = UNCLASSIFIED$  then
7:       if EXPANDCLUSTER( $D, p, clusterID, \epsilon, MinPts$ ) then
8:          $clusterID \leftarrow nextID(clusterID)$ 
9:       end if
10:    end if
11:  end for
12: end procedure

13: procedure EXPANDCLUSTER
14: end procedure
```

Algorithm 2 BIRCH

1: **procedure** BIRCH
2: **end procedure**

2.3 BIRCH

2.4 Fuzzy K-Means

3 Empirical Evaluation

3.1 Testing Environment

To maintain the reproducibility of our results the authors decided to implement the empirical analysis using entirely open-source software.

3.2 Results

4 Discussion and Conclusion