

Arm® Cortex®-M23
32-bit Microcontroller

M251/M252/M254/M256/M258 Series
CMSIS BSP
Revision History

The information described in this document is the exclusive intellectual property of Nuvoton Technology Corporation and shall not be reproduced without permission from Nuvoton.

Nuvoton is providing this document only for reference purposes of NuMicro microcontroller and microprocessor based system design. Nuvoton assumes no responsibility for errors or omissions.

All data and specifications are subject to change without notice.

For additional information or questions, please contact: Nuvoton Technology Corporation.

www.nuvoton.com

Revision 3.02.002 (Released 2022-3-15)

- Library
 - LCDLib: Synchronized with NuTool-LCDView tool.
 - TKLib: Improved anti-noise capability.
- Sample code
 - DAC_GroupMode, EADC_BPWM_Trigger, EADC_PDMA_BPWM_Trigger: Added.
 - LCD_Blinking and LCD_Pixel_OnOff: Used default Charge Pump setting.
 - LCD samples: Used new LCDLib.
 - NK_M258KG_LCD_TK: Added.
- Tool
 - NuSenadj_MP: Updated.

Revision 3.02.001 (Released 2021-1-20)

- Supported CRYPTO.
- Peripheral header
 - dac_reg.h: Fixed DAC_CTL_GRPEN_Msk.
 - lcd_reg.h: Updated base on TRM.
 - tk_reg.h: Supported up to 24 keys.
- Standard driver
 - Improved infinite loop prevention with timeout counter and error code.
 - BPWM: BPWM_ConfigCaptureChannel and BPWM_ConfigOutputChannel fixed wrong clock for chips without PLL.
 - CLK: CLK_EnableSysTick correctly used external reference clock.
 - DAC: DAC_SetDelayTime fixed calculation overflow issue.
 - GPIO: PF15 added.
 - LCD
 - LCD_GET_CHARGE_TIME and LCD_WAVEFORM_TYPE fixed.
 - LCD_SET_CONTINUOUS_FRAME and LCD_SET_NULL_FRAME_TIME removed.
 - LCD_SET_PAUSE_TIME and LCD_SET_PAUSE_TYPE added.
 - PWM: PWM_ConfigCaptureChannel and PWM_ConfigOutputChannel fixed wrong clock for chips without PLL.
 - RTC: RTC_Open added return value.
 - SCUART: SCUART_Write added return value.
 - SPI: Supported SPI1.
 - TIMER: TIMER_Delay and TIMER_ResetCounter added return value.

- TK: Supported up to 24 keys.
- Library
 - TKLib: Supported up to 24 keys.
- Sample code
 - EADC_Timer_Trigger: Fixed wrong timer period.
 - I2C samples: Removed redundant code.
 - ISP_I2C, ISP_RS485, ISP_UART: Added GCC project.
 - ISP_MSC: Added.
 - SPI_HalfDuplex, SPI_PDMA_LoopTest: QSPI0 replaced with USPI0.
 - USB HID samples: Unified INT_IN interval.
 - USB_Mass_Storage_CDR0M: Fixed Linux and Mac compatibility issue.
- Tool
 - NuSenadj: Updated.

Revision 3.01.002 (Released 2021-6-25)

- system_M251.h: __HXT and __LXT added redefinition check.
- Peripheral header
 - psio_reg.h: A reserved member added to GNCT_T structure.
- Standard driver
 - SYS: PF.15 MFP added.
- Library
 - LCDLib
 - Fixed display flicker.
 - Variable legality check for LCD print and putchar.
 - TKLib
 - Added all key calibration for power-down mode, store address scan, and store pin selection to Flash.
 - Decreased parameters Flash size.
 - Fixed reference CB overflow, power-on fine tune.
- Sample code
 - BPWM_Capture: Replaced PWM0 channel 0 with Timer0.
 - I2C and USCI_I2C samples: Enabled schmitt trigger of I²C pins.
 - ISP_HID, ISP_I2C, ISP_RS485, ISP_UART: Enabled GPIO and Systick clocks.
 - NuMaker-M258KE: Supported CKO shielding, default calibration parameters, and null frame in power-down mode.
 - SPI_SlaveFIFOModelINT, USCI_SPI_SlaveModelINT: Added.
 - TIMER_FreeCountingMode: Saved the first captured data.

- UART_Wakeup: Provided more wake-up methods.
- USB_D_Audio_Codec: Refactored.
- USB_D_MassStorage_CDROM: Removed 2 KB file size limitation.
- USB_D_VCOM samples: Fixed potential UART Tx FIFO overflow issue.
- USB_D_VCOM_DaulPort: Fixed power-down blocked issue and wrong baud rate issue.
- Tool
 - NuSenadj: Moved to TK subfolder.
 - NuSenadj_MP: Added.

Revision 3.01.001 (Released 2020-11-16)

- Supported M254/M256/M258 series.
- Peripheral header
 - lcd_reg.h, tk_reg.h: Added.
 - eadc_reg.h: EADC_T.OFFSETCAL, EADC_CTL_CALEN_Msk, EADC_CTL_CALEN_Pos, EADC_OFFSETCAL_OFFSETCANCEL_Msk, and EADC_OFFSETCAL_OFFSETCANCEL_Pos removed.
- Standard driver
 - retarget.c: Fixed program terminated issue with optimization level 0 of Arm Compiler 6.
 - EADC
 - EADC_ENABLE_CMP0, EADC_ENABLE_CMP1, EADC_ENABLE_CMP2, and EADC_ENABLE_CMP3 fixed bits overwritten issue.
 - EADC_DISABLE_OFFSETCANCEL and EADC_ENABLE_OFFSETCANCEL removed.
 - LCD, TK: added.
 - QSPI: QSPI_DISABLE_TX_RX_PDMA and QSPI_TRIGGER_TX_RX_PDMA added.
 - SPI: SPI_DISABLE_TX_RX_PDMA and SPI_TRIGGER_TX_RX_PDMA added.
 - SYS: SYS_SetPowerLevel improved power level switch stability.
 - USCI-SPI: USPI_DISABLE_TX_RX_PDMA and USPI_TRIGGER_TX_RX_PDMA added.
 - USCI-UART: UART_PDMA_DISABLE and UART_PDMA_ENABLE added.
- Library
 - LCDLib, TKLib: Added.
- Sample code
 - EADC_BandGapCalculateAVDD, LCD_Blinking, LCD_Pixel_OnOff,

LCD_Print_Text, NK_M258KE_LCD_TK, USBD_BC12_HID_Mouse: Added.

- EADC_OffsetCancel: Removed.
- GPIO samples: Enabled GPIO clock.
- PDMA_BasicMode: Fixed miss word alignment.
- USBD_Audio_Codec: Fixed noise and I²C timeout.
- USBD_VCOM_DualPort: Fixed only one VCOM port in Linux.

Revision 3.00.005 (Released 2020-6-10)

- Added Apache-2.0 license declaration.
- Standard driver
 - retarget.c: SendChar fixed uninitialized pointer.
 - TIMER: TIMER_SET_OPMODE added.
 - UART: UART_DEGLITCH_DISABLE, UART_DEGLITCH_ENABLE, UART_PDMA_DISABLE, and UART_PDMA_ENABLE added.
 - USCI-UART: UART_DEGLITCH_DISABLE and UART_DEGLITCH_ENABLE added.
- Sample code
 - CLK_ClockDetector: HCLK clock source used HXT instead of PLL.
 - GPIO_SingleCycleIO, I2C_SMBus, MPU, SYS_PowerDownMode, Sys_PowerMode, USBD_CCID: Added.
 - QSPI_DualMode_Flash, QSPI_QualMode_Flash, SPI_Flash: Fixed the 256th byte written issue.

Revision 3.00.004 (Released 2019-12-31)

- Removed CRYPTO.
- Standard driver
 - retarget.c: _write and SendChar_ToUART fixed '\r' issue.
 - CRC: CRC_SET_WDATA_LEN added.
 - FMC
 - FMC_Write128 added note to run in SRAM instead of inline function.
 - FMC_WriteConfig fixed return value.
 - SYS: Replaced SYS_PLCTL_PLSEL_PL2 with SYS_PLCTL_PLSEL_PL3.
 - TIMER_PWM: TPWM_ConfigOutputFreqAndDuty fixed wrong configuration for 1 Hz.
- Sample code
 - FMC_MultiWordProgram: Used FMC driver API.
 - I2C_Wakeup_Slave: Improved wakeup robustness.
 - ISP_DFU: Added.

- UART_LIN, UART_SingleWire: Fixed '\r' issue.
- USBBD samples: Improved USB compatibility.

Revision 3.00.003 (Released 2019-8-30)

- M251.h: Included core_cm23.h instead of core_armv8mbl.h.
- Peripheral header
 - clk_reg.h, rtc_reg.h: Updated base on TRM.
- Standard driver
 - I2C: I2C_SetSlaveAddr and I2C_SetSlaveAddrMask supported 10-bit slave address and error handling for new transfer.
 - TIMER
 - TIMER_GetModuleClock used correct PCLK.
 - TIMER_Open fixed return value.
 - TIMER_PWM
 - TPWM_ClearWakeupFlag, TPWM_DisableTrigger, TPWM_DisableWakeup, TPWM_EnableTrigger, TPWM_EnableWakeup, TPWM_GetWakeupFlag, TPWM_CLEAR_TRG_DAC_STATUS, TPWM_CLEAR_TRG_PDMA_STATUS, TPWM_GET_TRG_DAC_STATUS, and TPWM_GET_TRG_PDMA_STATUS added.
 - TPWM_OUTPUT_TOGGLE, TPWM_OUTPUT_NOTHING, TPWM_OUTPUT_LOW, TPWM_OUTPUT_HIGH, TPWM_CLKSRC_HXT, TPWM_CLKSRC_LXT, TPWM_CLKSRC_PCLK, TPWM_CLKSRC_TX, TPWM_CLKSRC_LIRC, and TPWM_CLKSRC_HIRC removed.
 - USCI_SPI: USPI_SET_SS_HIGH fixed implementation.
- Library
 - SmartcardLib: SCLIB_CheckCDEvent_ByVar added.
- Sample code
 - EADC_BandGap: Showed voltage result and modified extern sample time for band-gap.
 - FMC_ExecInSRAM: Added GCC project.
 - I2C_Master_PDMA, I2C_PDMA, I2C_Slave_PDMA: Replaced with I2C_PDMA_TRX.
 - ISP samples, QSPI_Slave3Wire, SPI_HalfDuplex: Added.
 - SC_ReadATR, SC_ReadSimPhoneBook: Added software card detection.
 - UART_TxRx_Function: Fixed data lost.
 - USBBD samples: Fixed potential issue.
 - USCI_SPI_Loopback, USCI_SPI_MasterMode, USCI_SPI_SlaveMode: Added using GPIO pin instead of SS pin.

Revision 3.00.002 (Released 2019-2-22)

- system_M251.c: Set flash access cycle to 0x03.
- Standard driver
 - CLK: CLK_SET_PCLK_DIVIDER removed.
- Sample code
 - Used other clock source instead of HXT.
 - SYS_TrimHIRC: Added auto trim disable.
 - USBD_Audio_Codec: Cleared buffer before play / record.

Revision 3.00.001 (Released 2018-12-25)

- Initial release.

Important Notice

Nuvoton Products are neither intended nor warranted for usage in systems or equipment, any malfunction or failure of which may cause loss of human life, bodily injury or severe property damage. Such applications are deemed, "Insecure Usage".

Insecure usage includes, but is not limited to: equipment for surgical implementation, atomic energy control instruments, airplane or spaceship instruments, the control or operation of dynamic, brake or safety systems designed for vehicular use, traffic signal instruments, all types of safety devices, and other applications intended to support or sustain life.

All Insecure Usage shall be made at customer's risk, and in the event that third parties lay claims to Nuvoton as a result of customer's Insecure Usage, customer shall indemnify the damages and liabilities thus incurred by Nuvoton.

*Please note that all data and specifications are subject to change without notice.
All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.*