Cat Spacer

Short manual . free and open source (AGPL-3.0-or-later) . github.com/SpeakingColors

Cat Spacer is a spectral sidechain ducker. Instead of ducking the whole sound, it listens to the sidechain (for example a vocal or kick) and cuts only the frequencies in your main track where the sidechain is loud, so both can sit in the same mix. No threshold is needed: it follows the loudest sidechain bands.

Quick start

- Put Cat Spacer on the sound you want to carve (a lead or pad) and route the sound that should stay clear (vocal, kick) to its sidechain input in your DAW.
- Raise Amount until the gaps appear in the display; the cut curve shows what is being removed.
- Use Low cut and High cut to limit the range that is affected, and Max cut to set the deepest cut.
- Use Audition to hear only what is being removed, Freeze to hold the current sidechain shape.

How the window works

- Each knob sits directly under the display it changes; the displays react to the knobs and the knobs react to the displays.
- Meters show the real signal in dB with a dB scale: input and output on the far right.
- Hover a control for about one second to see an info bubble. Turn bubbles off with the round i button in the header.
- The Limiter switch in the header adds a safety limiter at the output (useful while experimenting).
- Presets are in the header; the dice picks random settings (some controls are excluded on purpose).

Controls

Spectrum and cut

Amount	0 to 100 % default 50 %	Amount: how much the main sound is turned down in the bands where the sidechain is loud. 0 = nothing, 100 = full.
Low cut	20 to 20000 Hz default 20 Hz	Low cut: sidechain content below this frequency does not trigger any ducking (stops a kick from carving the whole mix, for example).
High cut	20 to 20000 Hz default 20000 Hz	High cut: sidechain content above this frequency does not trigger any ducking.
Max cut	3 to 36 dB default 18 dB	Max cut: the deepest reduction any band can get at 100 % amount.
Floor	10 to 70 dB default 40 dB	Floor: how far below the loudest sidechain band a band can be and still cause ducking. Lower = only the strongest bands duck, higher = more bands duck.

Timing

Latency	Choice: Ultra 256, Low 512, Normal 1024, High 2048 (default Low 512)	Latency: the delay this plugin adds (the host compensates). Ultra 256 is about 6 ms, Low 512 about 11 ms, Normal 1024 about 21 ms, High 2048 about 43 ms. Shorter = tighter timing but less precise at low frequencies; longer = cleaner and more exact in the bass.
Attack	1 to 300 ms default 20 ms	Attack: how fast the ducking engages when the sidechain gets loud.
Release	10 to 2000 ms default 160 ms	Release: how long the ducking takes to let go after the sidechain stops. Short = pumping, long = smooth.

Stereo

Stereo mode	Choice: L/R / M/S (default L/R)	Stereo mode: L/R ducks left and right, M/S ducks mid and side.
Freeze	Choice: Off / On (default Off)	Freeze: holds the current sidechain curve so it keeps carving the same gaps (a static EQ taken from the sidechain).
Audition	Choice: Off / On (default Off)	Audition: listen to the sidechain as the plugin hears it (after low and high cut). Useful for setting the cuts.
Pan	-100 to 100 default 0	Pan: moves the effect toward one side. Left of centre applies less to the right channel, right of centre applies less to the left (or to side instead of mid in M/S).
Mix	0 to 100 % default 100 %	Mix: dry/wet blend of the ducked signal.

Recommendations

• Lead under a vocal: Amount 50 to 70, Attack 5 to 20 ms, Release 100 to 200 ms, Low cut 150 Hz, High cut 8 kHz.
• Pad under a kick: Release shorter (60 to 120 ms), Max cut 8 to 12 dB.
• Keep Floor above 0 if the carving sounds hollow; lower Mix to blend with the untouched sound.
• Latency: Low 512, Normal 1024, High 2048 samples. Use Low while playing live, High for the cleanest cut when mixing.

Install and use

• Windows: run the installer (.exe). macOS: open the installer (.pkg or .dmg). Linux: install the Flatpak with `flatpak install --user` and the .flatpak file, or copy the .vst3 folder to ~/.vst3.
• Everything works offline. Rescan plugins in your DAW, then look for the plugin under SpeakingColors.
• Report problems or ideas on the GitHub page of the plugin. Free to use, copy and change under the AGPL-3.0-or-later licence.