





# The Dog Ate My Homework...

(re)Building a PowerShell Module for the New BloodHound



SadProcessor

**SpecterOps** 








Some say

I love the Captain...







Some say

I dream in Graphs...







Others say

I'm just a PowerShell Bad Boy...







I can neither confirm nor deny any of these statements...





# whoami

- SadProcessor Walter Legowski
- Born FR / Home NL / Father x3
- ERNW / FalconForce / SpecterOps
- PowerShell all the Things!!
- Dog Whisperer Handbook
- CypherDog / WatchDog / ZipHound BHQlib / FalconHound







- SadProcessor Walter Legowski
- Born FR / Home NL / Father x3
- ERNW / FalconForce / SpecterOps
- PowerShell all the Things!!
- Dog Whisperer Handbook
- CypherDog / WatchDog / ZipHound BHQlib / FalconHound





# whoami

- SadProcessor Walter Legowski
- Born FR / Home NL / Father x3
- ERNW / FalconForce / SpecterOps
- PowerShell all the Things!!
- Dog Whisperer Handbook
- PowerShell BloodHound Operator





# **Agenda**

- Intro
- Old BloodHound vs. New BloodHound
- New BloodHound REST API
- PowerShell BloodHound Operator
- What Next...
- Q&A







#### Old BloodHound vs. New BloodHound




# Old vs. New – Components















### Old vs. New – Components: Old BloodHound







### Old vs. New – Components: Old BloodHound











































### Old vs. New – Feature Comparison

FEATURE	LEGACY	COMMUNITY	
Easy Install	×	<b>✓</b>	
User Management	n/a	<b>✓</b>	
Secure Authentication	×	•	
Custom Queries via REST API	<b>✓</b>	*	
Data Ingestion via REST API	×	<b>✓</b>	
Other Actions via REST API	×	<b>✓</b>	



## Old vs. New – Feature Comparison

FEATURE	LEGACY	COMMUNITY
Easy Install	×	<b>✓</b>
User Management	n/a	•
Secure Authentication	×	<b>*</b>
Custom Queries via REST API	<b>✓</b>	*
Data Ingestion via REST API	×	<b>*</b>
Other Actions via REST API	×	<b>✓</b>
ADCS Attack Paths	×	<b>✓</b>







### New BloodHound REST API






#### BloodHound REST API – Overview

- Exposes all functionalities of UI
- Follows OpenAPI specs
- Secure Authentication
- Shared BHCE / BHE structure
- Endpoints: BHCE=142 / BHE=195
- Explorable in UI







### BloodHound REST API – Roles & Permissions

Authority	Permission	Read- Only	Upload- Only	User	Power User	Admin
Арр	ReadAppConfig			<b>*</b>		
Арр	WriteAppConfig					
Auth	CreateToken			<b>*</b>		
Auth	ManageAppConfig					
Auth	ManageProviders					
Auth	ManageSelf					
Auth	ManageUsers					<b>*</b>
GraphDB	Read					<b>*</b>
GraphDB	Write				<b>*</b>	<b>*</b>
Saved_Queries	Read					<b>*</b>
Saved_Queries	Write			<b>*</b>		
Clients	Manage				<b>*</b>	<b>*</b>
Clients	Read			<b>*</b>		
Clients	Taskings					
Collection	ManageJobs				<b>*</b>	
Risks	GenerateReport			<b>*</b>		
Risks	ManageRisks				<b>*</b>	<b>*</b>

Access to API endpoints is determined by role and associated permissions in the application

BHE only



#### BloodHound REST API – Authentication

- Uses TokenID + TokenKey (incl. User Token Lifecycle)
- Each request must be signed
- 3x HMAC SHA256
- Signature = [Hash:(((TokenKey x Operation) x Timestamp) x Body)].ToBase64
- Headers must include TokenID, Signature and Timestamp
- Server validates signature against request



#### BloodHound REST API – Authentication

```
# Signature
                                                                             PowerShell
$Timestamp = [Datetime]::utcnow.tostring('o')
           = [Text.Encoding]::UTF8.GetBytes($TokenKey)
$KeyByte
           = [Text.Encoding]::UTF8.GetBytes("$Method/$URI")
$OpByte
$DateByte = [Text.Encoding]::UTF8.GetBytes(-join $Timestamp[0..12])
$BodyByte = [Text.Encoding]::UTF8.GetBytes("$Body")
           = [Security.Cryptography.HMACSHA256]::new($KeyByte).ComputeHash($OpByte)
$HMAC
$HMAC
           = [Security.Cryptography.HMACSHA256]::new($HMAC).ComputeHash($DateByte)
$HMAC
           = [Security.Cryptography.HMACSHA256]::new($HMAC).ComputeHash($BodyByte)
           = [Convert]::ToBase64String($HMAC)
$Sign
# Headers
$Headers = @{
    Authorization = "BHESignature $TokenID"
    Signature
                  = $Sign
    RequestDate = $Timestamp
```



### PowerShell BloodHound Operator



#### BloodHound Operator – Features

- PowerShell Cmdlets for the BloodHound REST API (50+)
- Verb-BHNoun Syntax / Pipeline Input / Output Objects / Tab-Completion / ...
- All application features are accessible
- Allows for scripted deployments
- Allows for full Ingest-Query-Analyze automation (DIY)
- Experimental: Multiple sessions



#### BloodHound Operator – Disclaimer


- Still a Work-In-Progress...
- ADCS / BHE endpoints not included yet
- Some things will change = Break
- Provided as Gist for beta testers / No Support (feedback via BH Slack)
- Not an official SpecterOps tool
- Use at your own risks...





# DEMO

BloodHound Operator – Basic Usage





What's Next?









# **O**ToDo






- Add ADCS / BugFix / Docs
- Add BHE functionalities
- Format as proper Module
- Publish to PS Gallery
- Present at PSConfEU



# ToDo



- Add ADCS / BugFix / Docs
- Add BHE functionalities
- Format as proper Module
- Publish to PS Gallery
- Present at PSConfEU





- Download Gist
- Test-drive
- Feedback via BH Slack
- Wait for release
- Automate all the things...










CptJesus will be signing autographs in the lobby later this afternoon...

Come and get yours!







# Thank you

Catch me in the lobby if you want to chat... Enjoy the rest of SO-CON!





