



# Synced User Attack Path Analysis w/ BloodHound

Permalink to this deck: <https://bit.ly/46Xjzjw>



# About Us



## Andy Robbins

Product Architect at SpecterOps

Co-creator of BloodHound

@\_wald0



## Cody Thomas

Senior Software Engineer at SpecterOps

Creator of Mythic

@its\_a\_feature\_

# Microsoft Hybrid Identity

**Admins can sync users with two Microsoft technologies:**

## **Entra Connect**

- ✓ Supports user synchronization
- ✓ Supports password hash sync
- ✓ Supports password writeback

## **Entra Cloud Sync**

- ✓ Supports user synchronization
- ✓ Supports password hash sync
- ✓ Supports password writeback

<https://learn.microsoft.com/en-us/entra/identity/hybrid/cloud-sync/what-is-cloud-sync#comparison-between-microsoft-entra-connect-and-cloud-sync>

# Why this matters



## **Cross-platform attack paths**

User synchronization can enable attack paths that traverse identity and compute platforms



## **Synced users, synced risk**

The security posture of one platform will affect the posture of the other.



## **Implicit, obscure trust**

Entra user sync attack paths can expose on-prem Active Directory forests that do not explicitly trust one another.



# Two New Edges




## SyncedToEntraUser


- May reveal attack paths from on-prem AD users to their synchronized Entra users.
- Potentially abusable due to identical passwords, federated authentication, or artifacts left behind by single sign-on.




## SyncedToADUser

- May reveal attack paths from Entra users to their synchronized on-prem AD users.
- Potentially abusable due to password write-back or cloud kerberos trust.











# Demo




Attack Path Step 1:  
Get execution as on-prem user.


Attack Path Step 2:  
Steal a token for the Entra user from the system  
used by the on-prem Active Directory user.



**Attack Path Step 3:**  
Add a new credential to the “IAM Automation”  
application registration object.




**Attack Path Step 4:**  
Authenticate as the “IAM Automation” service principal.




**Attack Path Step 5:**  
Promote the “IAM Automation” service principal to  
Global Admin.






Attack Path Step 6 (part 1):  
Get updated token with new roles from step 5.  
Create a new user and grant it the “Password Administrator” role.



Attack Path Step 6 (part 2):  
Reset the password for the Entra user  
“DMCGUIRE”, which will be written back  
to the on-prem AD user “DMCGUIRE”.




**Attack Path Step 7:**  
Authenticate as the on-prem AD user “DMCGUIRE”,  
add ourselves to the Domain Admins group.

# What should defenders do?



## Identify risky attack paths


- Most synced user relationships are harmless.
- Some synced user relationships create immense risk.





# On-Prem AD Domain


# Entra ID Tenant



## On-Prem AD Domain



## Entra ID Tenant



Synced

Synced

Synced

Synced


Synced

Synced

Synced

# On-Prem AD Domain

# Entra ID Tenant




—

Q SEARCH

◆ PATHFINDING

</> CYPHER





```
1 MATCH p = (:User)-
  [:SyncedToEntraUser]->(:AZUser)
2 RETURN p
```


Save Query


? Help


▶ Run



























































































































































































SEARCH PATHFINDING CYPHER



```
1 MATCH p = (:User)-  
  [:SyncedToEntraUser]->(:AZUser)-  
  [:AZHasRole]->(:AZRole)  
2 RETURN p
```

Save Query

? Help

Run

### Pre-built Searches

ACTIVE DIRECTORY

AZURE

CUSTOM SEARCHES


#### Cross Platform Attack Paths

On-Prem Users synced to Entra Users with Entra Admin Roles (direct)

On-Prem Users synced to Entra Users with Entra Admin Roles (group delegated)

On-Prem Users synced to Entra Users with Azure RM Roles (direct)

On-Prem Users synced to Entra Users with Azure RM Roles (group delegated)







SEARCH PATHFINDING CYPHER



```
1 MATCH p = (:User)-  
  [:SyncedToEntraUser]->(:AZUser)-  
  [:AZOwns]->(:AZBase)  
2 RETURN p
```

Save Query

Help

Run

### Pre-built Searches

ACTIVE DIRECTORY

AZURE

CUSTOM SEARCHES


#### Cross Platform Attack Paths

On-Prem Users synced to Entra Users with Azure RM Roles (direct)

On-Prem Users synced to Entra Users with Azure RM Roles (group delegated)

On-Prem Users synced to Entra Users that Own Entra Objects

On-Prem Users synced to Entra Users with Entra Group Membership



# What should defenders do?



## Identify risky attack paths

- Most synced user relationships are harmless.
- Some synced user relationships create immense risk.



## Eliminate the attack paths that you can

- An ounce of prevention is worth a pound of cure.
- An attacker can't execute an attack path if the path doesn't exist.



**John Lambert** ✓


@JohnLaTwC

8/10 Prevention is the guardian of detection. Prevention creates the whitespace to detect and respond to the most important things.

4:05 PM · Dec 30, 2015


# On-Prem AD Domain

# Entra ID Tenant



## On-Prem AD Domain

## Entra ID Tenant





# What should defenders do?



## Identify risky attack paths

- Most synced user relationships are harmless.
- Some synced user relationships create immense risk.



## Eliminate the attack paths that you can

- An ounce of prevention is worth a pound of cure.
- An attacker can't execute an attack path if the path doesn't exist.



## Mitigate the attack paths that remain

- Use preventative tools like Conditional Access and token binding.
- Create high-fidelity, high-importance alerts.

# How to break the token theft cyber-attack chain

By  [Alex Weinert](#)

Published Jun 20 2024 09:00 AM

 41.3K Views



We've written a lot about how attackers try to break passwords. The solution to password attacks—still the most common attack vector for compromising identities—is to [turn on multifactor authentication \(MFA\)](#).

But as more customers do the right thing with MFA, actors are going beyond password-only attacks. So, **we're going to publish a series of articles on how to defeat more advanced attacks, starting with token theft**. In this article, we'll start with some basics on how tokens work, describe a token theft attack, and then explain what you can do to prevent and mitigate token theft now.


## ***Tokens 101***

Before we get too deep into the token theft conversation, let's quickly review the mechanics of tokens.

A token is an authentication artifact that grants you access to resources. You get a token by signing into an identity provider (IDP), such as Microsoft Entra ID, using a set of credentials. The IDP responds to a successful sign-in by issuing a token that describes who you are and what you have permission to do. When you want to access an application or service (we'll just say app from here), you get permission to talk to that resource by presenting a token that's correctly signed by an issuer it trusts. The software on the client device you're using takes care of all token handling behind the scenes.


<https://techcommunity.microsoft.com/t5/microsoft-entra-blog/how-to-o-break-the-token-theft-cyber-attack-chain/ba-p/4062700>

# What's next?




## Host equivalency

Hybrid-joined computers are represented as both “Computer” and “Device” nodes, but control of one guarantees control of the other.



## Group sync/writeback

Permissions delegated to groups will make cross-platform attack paths that traverse group sync/writeback configurations even more difficult to identify without tools like BloodHound.



## More...

We have our eyes on other hybrid and inter-platform attack paths.

# Further Reading/Viewing

- Alex Weinert: [How to break the token theft cyber-attack chain](#)
- Daniel Heinsen: [I'd TAP That Pass](#)
- Adam Chester: [WAM BAM - Recovering Web Tokens From Office](#)
- Melvin Flangvik: [Post-Compromise Session Hijacking with Mythic C2 and RoadTools!](#)

# Further Reading/Viewing

- Dirk-jan Mollema: [Obtaining Domain Admin from Azure AD by abusing Cloud Kerberos Trust](#)
- Fabien Bader: [From on-prem to Global Admin without password reset](#)
- Nestori Syynimaa: [Stealing and faking Azure AD device identities](#)
- Renos Nikolaou: [Abusing Azure Arc for lateral movement](#)



# Thank you!

Get BloodHoundCE: <https://ghst.ly/bh-github>

Get Mythic: <https://github.com/its-a-feature/Mythic>

Join the BloodHound Slack: <https://ghst.ly/BHSlack>

Get the 2024 BloodHound shirt:

<https://ghst.ly/bh-tshirt-24>

All funds go directly to the American Cancer Society

We are HIRING: <https://specterops.io/careers/#careers>

