

CS630 Graduate Algorithms

September 17, 2024

by Dora Erdos and Jeffrey Considine

- Polynomial reductions



Polynomial Reduction to Problems (informal)

Think of the max-flow solving algorithm (in our case FF - there are others) as a call to an **API**.

In the applications we used this API to solve other problems.

- max bipartite matching
- disjoint paths
- baseball elimination
- blood donation, dance competition, spies, etc.

Can we do this API-style trick with other algorithms/solvers too?

Polynomial-time reductions

Suppose there is an algorithm to solve problem Y .

- the algorithm is unknown to us, we treat it as a *black-box* or *API*

Polynomial Reduction. Problem X is **polynomial-time reducible to** problem Y if arbitrary instances of problem X can be solved using:

- Polynomial number of standard computational steps, plus
- Polynomial number of calls to an oracle/black box that solves problem Y .

Notation. $X \leq_p Y$.

Bipartite Matching \leq_p Max Flow

- define flow graph corresponding to the bipartite graph
- find max flow (using FF)
- iterate over middle edges and assign pairs with non-zero flow to the matching

Longest Path and Hamiltonian Path problems

Longest Path: Given a weighted graph G and an integer k , is there a simple path of lengths at least k ?

- if G does have a path of length k , it is easy to “prove” by returning the path itself
 - Proof by example - the path is an easy certificate for Longest Path

Longest Path and Hamiltonian Path problems

Longest Path: Given a weighted graph G and an integer k , is there a simple path of lengths at least k ?

- if G does have a path of length k , it is easy to "prove" by returning the path itself
 - Proof by example - the path is an easy certificate for Longest Path

Hamiltonian-path problem: Given an *unweighted* graph $G(V,E)$ is there a simple path that contains every node exactly once?

- Proof by example - the path is another easy certificate

Hamiltonian Path - TopHat

Hamiltonian path problem: Given an *unweighted* graph G , is there a simple path in G that contains *all* vertices?

Suppose that there is an algorithm $\text{Long}()$ that solves the **Longest path problem**.

Question: we can use $\text{Long}()$ to solve the Ham-path problem. Which of these best describes this approach?

- A. Pick a random source s . Run DFS on G from s to find the “deepest” path. If this contains every node, then we found the Hamiltonian path.
- B. Assign weight 1 to each edge in G then call $\text{Long}(G, n-1)$. If it returns $n-1$ as the longest simple path length, then G contains a Hamiltonian path.
- C. Find whether there is a Hamiltonian path in G . If yes, then return that $\text{Long}(G)$ is $n-1$.

Longest Path and Hamiltonian Path problems

Longest Path: Given a weighted graph G and an integer k , is there a simple path of lengths at least k ?

- we don't know of any polynomial algorithm for it
 - No super-polynomial lower bound either
 - Belongs to a class called NP-Complete → next lecture's topic
- if G does have a path of length k , it is easy to “prove” by returning the path itself

Longest Path and Hamiltonian Path problems

Longest Path: Given a weighted graph G and an integer k , is there a simple path of lengths at least k ?

- we don't know of any polynomial algorithm for it
 - No super-polynomial lower bound either
 - Belongs to a class called NP-Complete \rightarrow next lecture's topic
- if G does have a path of length k , it is easy to "prove" by returning the path itself

Hamiltonian-path problem: Given an unweighted graph $G(V,E)$ is there a simple path that contains every node exactly once?

There is a polynomial-time reduction from Hamiltonian-path to Longest Path. Which means that any algorithm solving LP can also be used to solve Ham-Path with polynomial number of extra steps.

Polynomial-time reductions


Suppose there is an algorithm to solve problem Y .

- the algorithm is unknown to us, we treat it as a *black-box* or *API*

Polynomial Reduction. Problem X is **polynomial-time reducible to** problem Y if arbitrary instances of problem X can be solved using:

- Polynomial number of standard computational steps, plus
- Polynomial number of calls to an oracle/black box that solves problem Y .

Notation. $X \leq_P Y$.



Hamiltonian path \leq_P Longest Path

Same result, new notation.

Circuit Value Problem

Given a description of a Boolean circuit and its input values, calculate the output value of the circuit.

A Boolean circuit is usually describe with a directed acyclic graph with vertices labeled as inputs, outputs, or internal gates (of type NOT/AND/OR...)





Image source: <https://online.visual-paradigm.com/>

Topological Sort


Given a directed acyclic graph, generate an order of the vertices such that if there is an edge $u \rightarrow v$, then u comes before v in the new order.



What are the topological sorts of this graph?

Topological Sort

Given a directed acyclic graph, generate an order of the vertices such that if there is an edge $u \rightarrow v$, then u comes before v in the new order.




What are the topological sorts of this graph?

1. $u \rightarrow s \rightarrow v$
2. $s \rightarrow u \rightarrow v$

Topological Sort

Given a directed acyclic graph, generate an order of the vertices such that if there is an edge $u \rightarrow v$, then u comes before v in the new order.



What are the topological sorts of this graph?

1. $u \rightarrow s \rightarrow v$
2. $s \rightarrow u \rightarrow v$

How does this relate to the previous problem?

Circuit Value Problem \leq_P Topological Sort

Loosely following “left-to-right” evaluation strategy...

Circuit Value Problem \leq_P Topological Sort

Loosely following “left-to-right” evaluation strategy...

- ▶ Perform a topological sort of the circuit DAG.
 - ▶ Input \rightarrow output
- ▶ Traverse this order and calculate all the node values in one pass.
 - ▶ When we get to a node, all its inputs are already calculated.

Circuit Value Problem \leq_P Topological Sort

Loosely following “left-to-right” evaluation strategy...

- ▶ Perform a topological sort of the circuit DAG.
 - ▶ Input \rightarrow output
- ▶ Traverse this order and calculate all the node values in one pass.
 - ▶ When we get to a node, all its inputs are already calculated.


No recursion after topological sort.

(Topological sort usually uses modified DFS.)

Cosine Similarity

Old measure of vector similarity.

$$u \cdot v = u^T v = \cos \theta \|u\| \|v\|$$

$$\frac{u \cdot v}{\|u\| \|v\|} = \cos \theta$$


Cosine Similarity

Old measure of vector similarity.

$$u \cdot v = u^T v = \cos \theta \|u\| \|v\|$$

$$\frac{u \cdot v}{\|u\| \|v\|} = \cos \theta$$

Information Retrieval

- ▶ Map documents of interest to vectors of features.
- ▶ Use cosine similarity to compare document vectors and identify related or similar documents.
- ▶ Higher cosine similarity \rightarrow better match.

Cosine Similarity

Old measure of vector similarity.

$$u \cdot v = u^T v = \cos \theta \|u\| \|v\|$$

$$\frac{u \cdot v}{\|u\| \|v\|} = \cos \theta$$

Information Retrieval

- ▶ Map documents of interest to vectors of features.
- ▶ Use cosine similarity to compare document vectors and identify related or similar documents.
- ▶ Higher cosine similarity → better match.

Popular again with new machine learning developments

- ▶ Turns out many large language model make really good vectors.
- ▶ Revival of cosine similarity to retrieve related documents, and drive Retrieval Augmented Generation (RAG)

Cosine Similarity

How to find vectors with highest cosine similarity to v ?

Cosine Similarity

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

Cosine Similarity \leq_p Nearest Neighbors

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

1. Normalize all unit vectors to be unit vectors.
(Divide by length, so resulting vectors have length 1.)
2. Find the nearest neighbors of v .

Cosine Similarity \leq_p Nearest Neighbors

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

1. Normalize all unit vectors to be unit vectors.
(Divide by length, so resulting vectors have length 1.)
2. Find the nearest neighbors of v .
 - ▶ Now all the vectors are on a unit hypersphere.
 - ▶ Smaller θ corresponds to smaller distance.

Cosine Similarity \leq_p Nearest Neighbors

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

1. Normalize all unit vectors to be unit vectors.
(Divide by length, so resulting vectors have length 1.)
2. Find the nearest neighbors of v .
 - ▶ Now all the vectors are on a unit hypersphere.
 - ▶ Smaller θ corresponds to smaller distance.

Isn't reducing cosine similarity to nearest neighbors reducing to the same problem?

Cosine Similarity \leq_p Nearest Neighbors

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

1. Normalize all unit vectors to be unit vectors.
(Divide by length, so resulting vectors have length 1.)
2. Find the nearest neighbors of v .
 - ▶ Now all the vectors are on a unit hypersphere.
 - ▶ Smaller θ corresponds to smaller distance.

Isn't reducing cosine similarity to nearest neighbors reducing to the same problem?

- ▶ Very similar, but nearest neighbors is an “off the shelf” problem.
- ▶ Vector databases are specialized for this.

Cosine Similarity \leq_p Nearest Neighbors

How to find vectors with highest cosine similarity to v ?

$\theta \rightarrow 0$ to get $\cos \theta \rightarrow 1$ (max)

1. Normalize all unit vectors to be unit vectors.
(Divide by length, so resulting vectors have length 1.)
2. Find the nearest neighbors of v .
 - ▶ Now all the vectors are on a unit hypersphere.
 - ▶ Smaller θ corresponds to smaller distance.

Isn't reducing cosine similarity to nearest neighbors reducing to the same problem?


- ▶ Very similar, but nearest neighbors is an “off the shelf” problem.
- ▶ Vector databases are specialized for this.

TLDR:

- ▶ Reduce cosine similarity to nearest neighbors by normalizing lengths.
- ▶ Then highest cosine similarity is the same as smallest distance.


Vertex Cover

Given a graph $G = (V, E)$, find a minimum subset of V such that each edge is covered. That is, find minimum $V' \subseteq V$ such that $\forall (u, v) \in E (u \in V' \vee v \in V')$.




Vertex Cover

Given a graph $G = (V, E)$, find a minimum subset of V such that each edge is covered. That is, find minimum $V' \subseteq V$ such that $\forall (u, v) \in E (u \in V' \vee v \in V')$.



Vertex Cover

Given a graph $G = (V, E)$, find a minimum subset of V such that each edge is covered. That is, find minimum $V' \subseteq V$ such that $\forall (u, v) \in E (u \in V' \vee v \in V')$.



Set Cover

Finding the minimum set of courses to fulfill your HUB requirements

Algorithm: always pick the course with the largest number of additional HUB units

	CS111	CS112	CS132	AN101	AN103	EE150	BI306	AR307
Quant Reas	X	X	X					X
Crit. think	X	X	X		X			X
Creat/Inno	X	X						
Digi/multi			X					
res and inf				X		X	X	X
Social Inq				X	X			
Indiv in Com					X			
Sci Inq						X	X	X
History						X		

AN101 Intro to Cult Anthropology AN103 Anthropology through Ethnography AS105 EE150 Sustainable Energy BI306 Bio of global change AR307 Archeological Science

Set Cover

Given a set of n items $U = \{u_1, u_2, \dots, u_n\}$ and m subsets of these items S_1, S_2, \dots, S_m find a minimum number of subsets, such that their union contains every element in U .

Vertex Cover \leq_p Set Cover

Reduction:

Vertex Cover \leq_P Set Cover

Reduction:

1. VC edges \rightarrow SC items

Vertex Cover \leq_p Set Cover

Reduction:

1. VC edges \rightarrow SC items
2. VC vertices \rightarrow SC sets of the VC edge SC items

Vertex Cover \leq_p Set Cover

Reduction:

1. VC edges \rightarrow SC items
2. VC vertices \rightarrow SC sets of the VC edge SC items

So,

- ▶ Picking an SC set \leftrightarrow picking a VC vertex

Vertex Cover \leq_P Set Cover

Reduction:

1. VC edges \rightarrow SC items
2. VC vertices \rightarrow SC sets of the VC edge SC items

So,

- ▶ Picking an SC set \leftrightarrow picking a VC vertex
- ▶ Items covered by picked SC set \leftrightarrow VC edges covered by picked VC vertex

Vertex Cover to Set Cover

Reduction:

1. VC edges \rightarrow SC items
2. VC vertices \rightarrow SC sets of the VC edge SC items

So,

- ▶ Picking an SC set \leftrightarrow picking a VC vertex
- ▶ Items covered by picked SC set \leftrightarrow VC edges covered by picked VC vertex

Spoiler for next time: Set Cover \leq_P Vertex Cover too!